

## EE-559 – Deep learning

### 1.6. Tensor internals

François Fleuret

<https://fleuret.org/ee559/>

Wed Aug 29 16:56:57 CEST 2018

A tensor is a view of a storage, which is a low-level 1d vector.

```
>>> x = torch.zeros(2, 4)
>>> x.storage()
0.0
0.0
0.0
0.0
0.0
0.0
0.0
0.0
[torch.FloatTensor of size 8]
>>> q = x.storage()
>>> q[4] = 1.0
>>> x
tensor([[ 0.,  0.,  0.,  0.],
        [ 1.,  0.,  0.,  0.]])
```

Multiple tensors can share the same storage. It happens when using operations such as `view()`, `expand()` or `transpose()`.

```
>>> y = x.view(2, 2, 2)
>>> y
tensor([[[ 0.,  0.],
          [ 0.,  0.]],

        [[ 1.,  0.],
          [ 0.,  0.]])
>>> y[1, 1, 0] = 7.0
>>> x
tensor([ [ 0.,  0.,  0.,  0.],
         [ 1.,  0.,  7.,  0.]])
>>> y.narrow(0, 1, 1).fill_(3.0)
>>> x
tensor([[[ 3.,  3.],
          [ 3.,  3.]])
>>> x
tensor([ [ 0.,  0.,  0.,  0.],
         [ 3.,  3.,  3.,  3.]])
```

The first coefficient of a tensor is the one at `storage_offset()` in `storage()`.

The first coefficient of a tensor is the one at `storage_offset()` in `storage()`. To increment index `k` by 1, you have to move by `stride(k)` elements in the storage.

The first coefficient of a tensor is the one at `storage_offset()` in `storage()`. To increment index `k` by 1, you have to move by `stride(k)` elements in the storage.

```
>>> q = torch.arange(0, 20).storage()
>>> x = torch.empty(0).set_(q, storage_offset = 5, size = (3, 2), stride = (4, 1))
>>> x
tensor([[ 5.,  6.],
        [ 9., 10.],
        [13., 14.]])
```

The first coefficient of a tensor is the one at `storage_offset()` in `storage()`. To increment index `k` by 1, you have to move by `stride(k)` elements in the storage.

```
>>> q = torch.arange(0, 20).storage()
>>> x = torch.empty(0).set_(q, storage_offset = 5, size = (3, 2), stride = (4, 1))
>>> x
tensor([[ 5.,  6.],
        [ 9., 10.],
        [13., 14.]])
```

q =

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
---	---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----

The first coefficient of a tensor is the one at `storage_offset()` in `storage()`. To increment index `k` by 1, you have to move by `stride(k)` elements in the storage.


```
>>> q = torch.arange(0, 20).storage()
>>> x = torch.empty(0).set_(q, storage_offset = 5, size = (3, 2), stride = (4, 1))
>>> x
tensor([[ 5.,  6.],
        [ 9., 10.],
        [13., 14.]])
```






The first coefficient of a tensor is the one at `storage_offset()` in `storage()`. To increment index `k` by 1, you have to move by `stride(k)` elements in the storage.

```
>>> q = torch.arange(0, 20).storage()
>>> x = torch.empty(0).set_(q, storage_offset = 5, size = (3, 2), stride = (4, 1))
>>> x
tensor([[ 5.,  6.],
        [ 9., 10.],
        [13., 14.]])
```




The first coefficient of a tensor is the one at `storage_offset()` in `storage()`. To increment index `k` by 1, you have to move by `stride(k)` elements in the storage.

```
>>> q = torch.arange(0, 20).storage()
>>> x = torch.empty(0).set_(q, storage_offset = 5, size = (3, 2), stride = (4, 1))
>>> x
tensor([[ 5.,  6.],
        [ 9., 10.],
        [13., 14.]])
```



The first coefficient of a tensor is the one at `storage_offset()` in `storage()`. To increment index `k` by 1, you have to move by `stride(k)` elements in the storage.

```
>>> q = torch.arange(0, 20).storage()
>>> x = torch.empty(0).set_(q, storage_offset = 5, size = (3, 2), stride = (4, 1))
>>> x
tensor([[ 5.,  6.],
        [ 9., 10.],
        [13., 14.]])
```



We can explicitly create different “views” of the same storage

```
>>> n = torch.linspace(1, 4, 4)
>>> n
tensor([ 1.,  2.,  3.,  4.])
>>> torch.tensor(0.).set_(n.storage(), 1, (3, 3), (0, 1))
tensor([[ 2.,  3.,  4.],
        [ 2.,  3.,  4.],
        [ 2.,  3.,  4.]])
>>> torch.tensor(0.).set_(n.storage(), 1, (2, 4), (1, 0))
tensor([[ 2.,  2.,  2.,  2.],
        [ 3.,  3.,  3.,  3.]])
```

We can explicitly create different “views” of the same storage

```
>>> n = torch.linspace(1, 4, 4)
>>> n
tensor([ 1.,  2.,  3.,  4.])
>>> torch.tensor(0.).set_(n.storage(), 1, (3, 3), (0, 1))
tensor([[ 2.,  3.,  4.],
        [ 2.,  3.,  4.],
        [ 2.,  3.,  4.]])
>>> torch.tensor(0.).set_(n.storage(), 1, (2, 4), (1, 0))
tensor([[ 2.,  2.,  2.,  2.],
        [ 3.,  3.,  3.,  3.]])
```

This is in particular how transpositions and broadcasting are implemented.

This organization explains the following (maybe surprising) error

```
>>> x = torch.empty(100, 100)
>>> x.stride()
(100, 1)
>>> y = x.t()
>>> y.stride()
(1, 100)
>>> y.view(-1)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
RuntimeError: invalid argument 2: view size is not compatible with
input tensor's size and stride (at least one dimension spans across
two contiguous subspaces).
```

`x.t()` shares `x`'s storage and cannot be “flattened” to a 1d without a memory copy.

This organization explains the following (maybe surprising) error

```
>>> x = torch.empty(100, 100)
>>> x.stride()
(100, 1)
>>> y = x.t()
>>> y.stride()
(1, 100)
>>> y.view(-1)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
RuntimeError: invalid argument 2: view size is not compatible with
input tensor's size and stride (at least one dimension spans across
two contiguous subspaces).
```

`x.t()` shares `x`'s storage and cannot be “flattened” to a 1d without a memory copy.

This can be fixed either by using `contiguous()`, which returns a contiguous version of the tensor, making a copy if needed, or directly with `reshape()` which combines contiguous and view in one operation.

The end