



Em assembly: x10,zero,0x15




Em assembly:x5,zero,0x8




Em assembly:x6,x10,0x8

Info: Quartus II 64-Bit Programmer was successful. 0 errors, 0 warnings
Total logic elements : 1,175 / 22,320 (5 %)
Dedicated logic registers : 504 / 22,320 (2 %)
Total memory bits : 2,048 / 608,256 (< 1 %)
STA Warning: Clock period outside of range of acceptable values.
Info: Running Quartus II 64-Bit SignalTap II
Info: 7 instructions read successfully from inst.101
Info (23030): Evaluation of Tcl script /labaro/util/inst.tcl was successful
Info: Quartus II 64-Bit SignalTap II was successful. 0 errors, 0 warnings
Info: Running Quartus II 64-Bit SignalTap II
Info: Starting JTAG server




Em assembly:x5,x10,x5

STA Warning: Clock period outside of range of acceptable values.
Info: Running Quartus II 64-Bit SignalTap II
Info: 7 instructions read successfully from inst.101
Info (23030): Evaluation of Tcl script /labaro/util/inst.tcl was successful
Info: Quartus II 64-Bit SignalTap II was successful. 0 errors, 0 warnings
Info: Running Quartus II 64-Bit SignalTap II
Info: Starting JTAG server




Em assembly:x7,x10,x6

STA Warning: Clock period outside of range of acceptable values.
 Info: Running Quartus II 64-Bit SignalTap II
[Info: 7 instructions read successfully from inst.101](#)
 Info (23030): Evaluation of Tcl script /labarc/util/inst.tcl was successful
 Info: Quartus II 64-Bit SignalTap II was successful. 0 errors, 0 warnings
 Info: Running Quartus II 64-Bit SignalTap II
 Info: Starting JTAG server




Em assembly:x10,x7,0x08

STA Warning: Clock period outside of range of acceptable values.
 Info: Running Quartus II 64-Bit SignalTap II
[Info: 7 instructions read successfully from inst.101](#)
 Info (23030): Evaluation of Tcl script /labarc/util/inst.tcl was successful
 Info: Quartus II 64-Bit SignalTap II was successful. 0 errors, 0 warnings
 Info: Running Quartus II 64-Bit SignalTap II
 Info: Starting JTAG server



Em assembly:x6,x5,0x08

STA Warning: Clock period outside of range of acceptable values.
Info: Running Quartus II 64-Bit SignalTap II
Info: 7 instructions read successfully from inst.101
Info (23030): Evaluation of Tcl script /labarc/uttl/inst.tcl was successful
Info: Quartus II 64-Bit SignalTap II was successful. 0 errors, 0 warnings
Info: Running Quartus II 64-Bit SignalTap II
Info: Starting JTAG server



Em assembly:é o resultado das instruções.

Total memory bits : 2,048 / 608,256 (< 1 %)
STA Warning: Clock period outside of range of acceptable values.
Info: Running Quartus II 64-Bit SignalTap II
Info: 7 instructions read successfully from inst.101
Info (23030): Evaluation of Tcl script /labarc/uttl/inst.tcl was successful
Info: Quartus II 64-Bit SignalTap II was successful. 0 errors, 0 warnings
Info: Running Quartus II 64-Bit SignalTap II
Info: Starting JTAG server

