



## Index Structures

Records ordered by search key (may not be "key" in DB sense).

- facilitates queries on the search key

Blocks containing records therefore ordered.

- physically contiguous
- chained

On insert: put record in appropriate block if room.

- Good idea: initialize blocks to be less than full; reorganize periodically if file grows.

If no room in proper block:

- 1. Create new block; insert into proper order if possible.
- 2. If not possible, create overflow block, linked from original block.

## What is an Index?

An index is a data structure that allows us to directly locate units of data based on certain values

- Not just used for databases: also books can contain an index

Indexes for databases are used to find records that have a particular value for the indexed attribute (the "search key")

An index has to be created before it can be used

- creation often initiated by the database designer
- cost of maintenance

Different categories exist

- primary / secondary indexes
- dense / sparse indexes

## Indexes

Dense Indexes: Pointer to every record of file, ordered by search key.

- Can make sense because records may be much bigger than key-pointer pairs.
  - If index requires fewer blocks faster search through index than data file
  - Index might fit in memory, even if data file does not
- Test existence of record without going to data file.

Sparse Indexes: Keypointer pairs for only a subset of records, typically first in each block.

## Implementation of DBMS

### Example: Sequential File

Sequential File

10	
20	
30	
40	
50	
60	
70	
80	
90	
100	

WS 25/26  
Frankfurt UAS

Prof. Dr. Justus Klingemann

### Example: Dense Index

Dense Index

10	
20	
30	
40	
50	
60	
70	
80	
90	
100	
110	
120	

Sequential File

10	
20	
30	
40	
50	
60	
70	
80	
90	
100	
110	
120	

Prof. Dr. Justus Klingemann

### Implementation of DBMS

### Example: Sparse Index

Sparse Index

Sequential File

10	
30	
50	
70	
90	
110	
130	
150	
170	
190	
210	
230	

Prof. Dr. Justus Klingemann

### Implementation of DBMS

### Sparse vs. Dense Index

Sparse: Less index space per record can keep more of index in memory

Dense: Can tell if any record exists without accessing file

Prof. Dr. Justus Klingemann

# Multiple Levels of Index

A sparse index on a (sparse or dense) index is an option.

Good chance that 2nd or higher level indexes can be housed in main memory, so no additional disk I/O's.


Dense higher level indexes make no sense;

# DB Modifications

When we insert or delete on the data file, here are the primitive actions we might take:

1. Create or destroy an overflow block.
2. Create or destroy an empty block in the sequence of blocks belonging to the sequential file.
3. Insert a record into a block that has room.
4. Delete a record.
5. Slide a record to an adjacent block.

# Example: Second Level Index



# Effect of Primitive Actions on Index File

Action	Dense	Sparse
Create/destroy empty overflow block	none	none
Create empty seq. block	none	insert
Destroy empty seq. block	none	delete
Insert record	insert	update(?)
Delete record	delete	update(?)
Slide record	update	update(?)