

# Aggregatable Subvector Commitments for Stateless Cryptocurrencies

---

**Alin Tomescu**<sup>1</sup>  
[@alinush407](#)

Justin Drake<sup>2</sup>  
[@drakejustin](#)

Ittai Abraham<sup>1</sup>  
[@ittaia](#)

Dankrad Feist<sup>2</sup>  
[@dankrad](#)

Vitalik Buterin<sup>2</sup>  
[@VitalikButerin](#)

Dmitry Khovratovich<sup>2</sup>  
[@Khovr](#)

<sup>1</sup>VMware Research, <sup>2</sup>Ethereum Foundation

May 13th, 2020

# Motivation

---

# Stateless Cryptocurrencies

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies)

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]
- Each block  $t$  now stores digest  $d_t$  of the latest state



# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]
- Each block  $t$  now stores digest  $d_t$  of the latest state
- Each user has a proof  $\pi_i$ , which is perpetually updated

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]
- Each block  $t$  now stores digest  $d_t$  of the latest state
- Each user has a proof  $\pi_i$ , which is perpetually updated

**Stateless** transaction validation

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]
- Each block  $t$  now stores digest  $d_t$  of the latest state
- Each user has a proof  $\pi_i$ , which is perpetually updated

**Stateless** transaction validation:

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, \text{bal}_i \geq v]$  against digest  $d_t$  in block  $t$

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]
- Each block  $t$  now stores digest  $d_t$  of the latest state
- Each user has a proof  $\pi_i$ , which is perpetually updated

**Stateless** transaction validation:

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, \text{bal}_i \geq v]$  against digest  $d_t$  in block  $t$

## Why go stateless?

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]
- Each block  $t$  now stores digest  $d_t$  of the latest state
- Each user has a proof  $\pi_i$ , which is perpetually updated

**Stateless** transaction validation:

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, \text{bal}_i \geq v]$  against digest  $d_t$  in block  $t$

## Why go stateless?

(1) Faster validation.

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]
- Each block  $t$  now stores digest  $d_t$  of the latest state
- Each user has a proof  $\pi_i$ , which is perpetually updated

**Stateless** transaction validation:

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, \text{bal}_i \geq v]$  against digest  $d_t$  in block  $t$

## Why go stateless?

(1) Faster validation. (2) Less storage  $\Rightarrow$  lower barrier to entry.

# Stateless Cryptocurrencies

**Stateful** transaction validation (for account-based cryptocurrencies):

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v]$  against **state** on disk

State is just a dictionary  $D(PK_i) \rightarrow \text{bal}_i$  (+ counters for replay attacks)

## Observations

- Could “authenticate” state and verify transaction against *digest* [Mil12, Tod16, But17, RMCI17]
- Each block  $t$  now stores digest  $d_t$  of the latest state
- Each user has a proof  $\pi_i$ , which is perpetually updated

**Stateless** transaction validation:

Check  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, \text{bal}_i \geq v]$  against digest  $d_t$  in block  $t$

## Why go stateless?

(1) Faster validation. (2) Less storage  $\Rightarrow$  lower barrier to entry. (3) Easy sharding.

# Stateless Cryptocurrencies from Vector Commitments (VCs)



# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but...

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment** (VC) is sufficient [CPZ18].

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment** (VC) is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a *user-specific update key*, which should be small

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment (VC)** is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a *user-specific update key*, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment (VC)** is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a *user-specific update key*, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment (VC)** is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a user-specific **update key**, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment (VC)** is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a *user-specific update key*, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$ 
  - $vrk$  is a global **verification key**, which should be small

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment (VC)** is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a user-specific **update key**, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$ 
  - $vrk$  is a global **verification key**, which should be small
2. Miners need  $d_{t+1} = VC.UpdateDig(d_t, \delta_i, i, upk_i)$



# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment** (VC) is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a user-specific **update key**, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$ 
  - $vrk$  is a global **verification key**, which should be small
2. Miners need  $d_{t+1} = VC.UpdateDig(d_t, \delta_i, i, upk_i)$ 
  - i.e., update digest with change in balance  $\delta_i$  for each user  $i$

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment** (VC) is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a user-specific **update key**, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$ 
  - $vrk$  is a global **verification key**, which should be small
2. Miners need  $d_{t+1} = VC.UpdateDig(d_t, \delta_i, i, upk_i)$ 
  - i.e., update digest with change in balance  $\delta_i$  for each user  $i$
3. Users need  $\pi'_j = VC.UpdateProof(\pi_i, \delta_j, j, upk_j)$

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment** (VC) is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a user-specific **update key**, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$ 
  - $vrk$  is a global **verification key**, which should be small
2. Miners need  $d_{t+1} = VC.UpdateDig(d_t, \delta_i, i, upk_i)$ 
  - i.e., update digest with change in balance  $\delta_i$  for each user  $i$
3. Users need  $\pi'_j = VC.UpdateProof(\pi_i, \delta_j, j, upk_j)$ 
  - i.e., update  $i$ 's proof with change in balance  $\delta_j$  for each user  $j$

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment** (VC) is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a user-specific **update key**, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$ 
  - $vrk$  is a global **verification key**, which should be small
2. Miners need  $d_{t+1} = VC.UpdateDig(d_t, \delta_i, i, upk_i)$ 
  - i.e., update digest with change in balance  $\delta_i$  for each user  $i$
3. Users need  $\pi'_j = VC.UpdateProof(\pi_i, \delta_j, j, upk_j)$ 
  - i.e., update  $i$ 's proof with change in balance  $\delta_j$  for each user  $j$
4. Miners want  $\pi_l = VC.AggregateProofs(l, (\pi_i)_{i \in l})$ , where  $l$  = set of users sending coins in a block

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment** (VC) is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a user-specific **update key**, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$ 
  - $vrk$  is a global **verification key**, which should be small
2. Miners need  $d_{t+1} = VC.UpdateDig(d_t, \delta_i, i, upk_i)$ 
  - i.e., update digest with change in balance  $\delta_i$  for each user  $i$
3. Users need  $\pi'_j = VC.UpdateProof(\pi_i, \delta_j, j, upk_j)$ 
  - i.e., update  $i$ 's proof with change in balance  $\delta_j$  for each user  $j$
4. Miners want  $\pi_l = VC.AggregateProofs(l, (\pi_i)_{i \in l})$ , where  $l$  = set of users sending coins in a block
  - Would need corresponding  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i)_{i \in l}, l, \pi_l)$

# Stateless Cryptocurrencies from Vector Commitments (VCs)

An *authenticated dictionary* (AD) is ideal, but... a **vector commitment** (VC) is sufficient [CPZ18].

- $v_i = (H(PK_i) || bal_i)$
- $PK_i = (i, tpk_i, upk_i)$  and  $upk_i$  is a user-specific **update key**, which should be small

Consider miners **validating** and **including**  $tx = [TXFER, PK_i \rightarrow PK_j, v, t, \pi_i, bal_i]$  and users **processing** it.

1. Miners need  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i), i, \pi_i)$ 
  - $vrk$  is a global **verification key**, which should be small
2. Miners need  $d_{t+1} = VC.UpdateDig(d_t, \delta_i, i, upk_i)$ 
  - i.e., update digest with change in balance  $\delta_i$  for each user  $i$
3. Users need  $\pi'_j = VC.UpdateProof(\pi_i, \delta_j, j, upk_j)$ 
  - i.e., update  $i$ 's proof with change in balance  $\delta_j$  for each user  $j$
4. Miners want  $\pi_l = VC.AggregateProofs(l, (\pi_i)_{i \in l})$ , where  $l$  = set of users sending coins in a block
  - Would need corresponding  $VC.VerifyPos(vrk, d_t, (H(PK_i) || bal_i)_{i \in l}, l, \pi_l)$
5. **Proof serving nodes** would like to compute all  $\pi_i$ 's fast

# Contributions

---

# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.



# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
---------------	---------	-----------	-----------	-------------------------	-------------------------	--------------------------	--------------

# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
CF/LM [CF13, LM19]	$n$	$n$	1	1	$\times$	$b_{\mathbb{G}}$	$n^2$

# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
CF/LM [CF13, LM19]	$n$	$n$	1	1	$\times$	$b_{\mathbb{G}}$	$n^2$
KZG [KZG10]	$b$	$\times$	1	$\times$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$

# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
CF/LM [CF13, LM19]	$n$	$n$	1	1	$\times$	$b_{\mathbb{G}}$	$n^2$
KZG [KZG10]	$b$	$\times$	1	$\times$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CDHK [CDHK15]	$n$	$n$	1	1	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$

# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
CF/LM [CF13, LM19]	$n$	$n$	1	1	$\times$	$b_{\mathbb{G}}$	$n^2$
KZG [KZG10]	$b$	$\times$	1	$\times$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CDHK [CDHK15]	$n$	$n$	1	1	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CPZ [CPZ18]	$\log n$	$\log n$	$\log n$	$\log n$	$\times$	$\times$	$n \log n$

# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
CF/LM [CF13, LM19]	$n$	$n$	1	1	$\times$	$b_{\mathbb{G}}$	$n^2$
KZG [KZG10]	$b$	$\times$	1	$\times$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CDHK [CDHK15]	$n$	$n$	1	1	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CPZ [CPZ18]	$\log n$	$\log n$	$\log n$	$\log n$	$\times$	$\times$	$n \log n$
TCZ [TCZ <sup>+</sup> 20, Tom20]	$\log n + b$	$\log n$	$\log n$	$\log n$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n \log n$

# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
CF/LM [CF13, LM19]	$n$	$n$	1	1	$\times$	$b_{\mathbb{G}}$	$n^2$
KZG [KZG10]	$b$	$\times$	1	$\times$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CDHK [CDHK15]	$n$	$n$	1	1	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CPZ [CPZ18]	$\log n$	$\log n$	$\log n$	$\log n$	$\times$	$\times$	$n \log n$
TCZ [TCZ <sup>+</sup> 20, Tom20]	$\log n + b$	$\log n$	$\log n$	$\log n$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n \log n$
Pointproofs [GRWZ20]	$n$	$n$	1	1	$b_{\mathbb{G}}$	$b_{\mathbb{G}}$	$n^2$

# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
CF/LM [CF13, LM19]	$n$	$n$	1	1	$\times$	$b_{\mathbb{G}}$	$n^2$
KZG [KZG10]	$b$	$\times$	1	$\times$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CDHK [CDHK15]	$n$	$n$	1	1	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CPZ [CPZ18]	$\log n$	$\log n$	$\log n$	$\log n$	$\times$	$\times$	$n \log n$
TCZ [TCZ <sup>+</sup> 20, Tom20]	$\log n + b$	$\log n$	$\log n$	$\log n$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n \log n$
Pointproofs [GRWZ20]	$n$	$n$	1	1	$b_{\mathbb{G}}$	$b_{\mathbb{G}}$	$n^2$
<b>Our aSVC</b>	$b$	1	1	1	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$		$n \log n$



# Our Contribution: Aggregatable Subvector Commitments with Scalable Updates

**Table 1:** Asymptotic comparison to previous (aS)VCs:  $n$  is the size of  $\vec{v}$  and  $b$  is the # of proofs to aggregate.

(aS)VC scheme	$ vrk $	$ upk_i $	$ \pi_i $	Proof update time	Aggr. proofs time	Verify aggr. proof	Prove all
CF/LM [CF13, LM19]	$n$	$n$	1	1	$\times$	$b_{\mathbb{G}}$	$n^2$
KZG [KZG10]	$b$	$\times$	1	$\times$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CDHK [CDHK15]	$n$	$n$	1	1	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n^2$
CPZ [CPZ18]	$\log n$	$\log n$	$\log n$	$\log n$	$\times$	$\times$	$n \log n$
TCZ [TCZ <sup>+</sup> 20, Tom20]	$\log n + b$	$\log n$	$\log n$	$\log n$	$\times$	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$	$n \log n$
Pointproofs [GRWZ20]	$n$	$n$	1	1	$b_{\mathbb{G}}$	$b_{\mathbb{G}}$	$n^2$
<b>Our aSVC</b>	$b$	1	1	1	$b \lg^2 b_{\mathbb{F}} + b_{\mathbb{G}}$		$n \log n$

\*All schemes can (1) verify a proof  $\pi_i$  in  $O(|\pi_i|)$  time and (2) update digests in  $O(1)$  time.

## **Techniques: VCs from Univariate Polynomial Commitments**

---

Motivation

Contributions

Techniques: VCs from Univariate Polynomial Commitments

Committing to Vectors (and Updating Digests)

Computing and Updating Proofs

Aggregating Proofs into Subvector Proofs

Conclusion

# KZG Constant-sized Polynomial Commitments [KZG10]

## KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

## KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

For any polynomial  $\phi = \sum_{i=0}^n \phi_i X^i = \langle \phi_0, \phi_1, \dots, \phi_n \rangle$  of degree  $\leq n$ :

# KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

For any polynomial  $\phi = \sum_{i=0}^n \phi_i X^i = \langle \phi_0, \phi_1, \dots, \phi_n \rangle$  of degree  $\leq n$ :

$$c = g^{\phi(\tau)} \tag{1}$$

(2)

(3)

(4)

(5)

# KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

For any polynomial  $\phi = \sum_{i=0}^n \phi_i X^i = \langle \phi_0, \phi_1, \dots, \phi_n \rangle$  of degree  $\leq n$ :

$$c = g^{\phi(\tau)} \tag{1}$$

$$= (g^{\tau^n})^{\phi_n} (g^{\tau^{n-1}})^{\phi_{n-1}} \dots (g^{\tau})^{\phi_1} (g)^{\phi_0} \tag{2}$$

(3)

(4)

(5)



# KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

For any polynomial  $\phi = \sum_{i=0}^n \phi_i X^i = \langle \phi_0, \phi_1, \dots, \phi_n \rangle$  of degree  $\leq n$ :

$$c = g^{\phi(\tau)} \tag{1}$$

$$= (g^{\tau^n})^{\phi_n} (g^{\tau^{n-1}})^{\phi_{n-1}} \dots (g^{\tau})^{\phi_1} (g)^{\phi_0} \tag{2}$$

$$= g^{\phi_n \tau^n} g^{\phi_{n-1} \tau^{n-1}} \dots g^{\phi_1 \tau} g^{\phi_0} \tag{3}$$

$$\tag{4}$$

$$\tag{5}$$

# KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

For any polynomial  $\phi = \sum_{i=0}^n \phi_i X^i = \langle \phi_0, \phi_1, \dots, \phi_n \rangle$  of degree  $\leq n$ :

$$c = g^{\phi(\tau)} \tag{1}$$

$$= (g^{\tau^n})^{\phi_n} (g^{\tau^{n-1}})^{\phi_{n-1}} \dots (g^{\tau})^{\phi_1} (g)^{\phi_0} \tag{2}$$

$$= g^{\phi_n \tau^n} g^{\phi_{n-1} \tau^{n-1}} \dots g^{\phi_1 \tau} g^{\phi_0} \tag{3}$$

$$= g^{\phi_n \tau^n + \phi_{n-1} \tau^{n-1} + \dots + \phi_1 \tau + \phi_0} \tag{4}$$

$$\tag{5}$$

# KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

For any polynomial  $\phi = \sum_{i=0}^n \phi_i X^i = \langle \phi_0, \phi_1, \dots, \phi_n \rangle$  of degree  $\leq n$ :

$$c = g^{\phi(\tau)} \tag{1}$$

$$= (g^{\tau^n})^{\phi_n} (g^{\tau^{n-1}})^{\phi_{n-1}} \dots (g^{\tau})^{\phi_1} (g)^{\phi_0} \tag{2}$$

$$= g^{\phi_n \tau^n} g^{\phi_{n-1} \tau^{n-1}} \dots g^{\phi_1 \tau} g^{\phi_0} \tag{3}$$

$$= g^{\phi_n \tau^n + \phi_{n-1} \tau^{n-1} + \dots + \phi_1 \tau + \phi_0} \tag{4}$$

$$= g^{\phi(\tau)} \tag{5}$$

# KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

For any polynomial  $\phi = \sum_{i=0}^n \phi_i X^i = \langle \phi_0, \phi_1, \dots, \phi_n \rangle$  of degree  $\leq n$ :

$$c = g^{\phi(\tau)} \tag{1}$$

$$= (g^{\tau^n})^{\phi_n} (g^{\tau^{n-1}})^{\phi_{n-1}} \dots (g^{\tau})^{\phi_1} (g)^{\phi_0} \tag{2}$$

$$= g^{\phi_n \tau^n} g^{\phi_{n-1} \tau^{n-1}} \dots g^{\phi_1 \tau} g^{\phi_0} \tag{3}$$

$$= g^{\phi_n \tau^n + \phi_{n-1} \tau^{n-1} + \dots + \phi_1 \tau + \phi_0} \tag{4}$$

$$= g^{\phi(\tau)} \tag{5}$$

Can **interpolate** polynomial from  $n$  points  $(x_i, \phi(x_i))_{i \in [n]}$  in  $O(n \log^2 n)$  field operations.

# KZG Constant-sized Polynomial Commitments [KZG10]

Fix  $n$ -SDH public parameters  $(g^{\tau^i})_{0 \leq i \leq n}$  such that **trapdoor**  $\tau$  is unknown.

For any polynomial  $\phi = \sum_{i=0}^n \phi_i X^i = \langle \phi_0, \phi_1, \dots, \phi_n \rangle$  of degree  $\leq n$ :

$$c = g^{\phi(\tau)} \tag{1}$$

$$= (g^{\tau^n})^{\phi_n} (g^{\tau^{n-1}})^{\phi_{n-1}} \dots (g^{\tau})^{\phi_1} (g)^{\phi_0} \tag{2}$$

$$= g^{\phi_n \tau^n} g^{\phi_{n-1} \tau^{n-1}} \dots g^{\phi_1 \tau} g^{\phi_0} \tag{3}$$

$$= g^{\phi_n \tau^n + \phi_{n-1} \tau^{n-1} + \dots + \phi_1 \tau + \phi_0} \tag{4}$$

$$= g^{\phi(\tau)} \tag{5}$$

Can **interpolate** polynomial from  $n$  points  $(x_i, \phi(x_i))_{i \in [n]}$  in  $O(n \log^2 n)$  field operations.  
Time to commit is an  $O(n)$ -sized multi-exponentiation.



## VCs from Lagrange Basis Polynomials [CDHK15]

Compute  $\phi(X)$  s.t.  $\phi(i) = v_i$ :

## VCs from Lagrange Basis Polynomials [CDHK15]

Compute  $\phi(X)$  s.t.  $\phi(i) = v_i$ :

$$\phi(X) = \sum_{i=0}^{n-1} v_i \cdot L_i(X), \text{ where } L_i(X) = \prod_{\substack{j \in [0, n) \\ j \neq i}} \frac{X - j}{i - j} \quad (6)$$



## VCs from Lagrange Basis Polynomials [CDHK15]

Compute  $\phi(X)$  s.t.  $\phi(i) = v_i$ :

$$\phi(X) = \sum_{i=0}^{n-1} v_i \cdot L_i(X), \text{ where } L_i(X) = \prod_{\substack{j \in [0, n) \\ j \neq i}} \frac{X - j}{i - j} \quad (6)$$

Setup Lagrange basis polynomial commitments  $\ell_i = g^{L_i(\tau)}, \forall i \in [0, n)$  (speed?)

## VCs from Lagrange Basis Polynomials [CDHK15]

Compute  $\phi(X)$  s.t.  $\phi(i) = v_i$ :

$$\phi(X) = \sum_{i=0}^{n-1} v_i \cdot L_i(X), \text{ where } L_i(X) = \prod_{\substack{j \in [0, n) \\ j \neq i}} \frac{X - j}{i - j} \quad (6)$$

Setup Lagrange basis polynomial commitments  $\ell_i = g^{L_i(\tau)}$ ,  $\forall i \in [0, n)$  (speed?). Then, commit to  $\vec{v}$  as [CDHK15]:

## VCS from Lagrange Basis Polynomials [CDHK15]

Compute  $\phi(X)$  s.t.  $\phi(i) = v_i$ :

$$\phi(X) = \sum_{i=0}^{n-1} v_i \cdot L_i(X), \text{ where } L_i(X) = \prod_{\substack{j \in [0, n) \\ j \neq i}} \frac{X - j}{i - j} \quad (6)$$

Setup Lagrange basis polynomial commitments  $\ell_i = g^{L_i(\tau)}$ ,  $\forall i \in [0, n)$  (speed?). Then, commit to  $\vec{v}$  as [CDHK15]:

$$c = \prod_{i \in [0, n)} \ell_i^{v_i} \quad (7)$$

$$(8)$$

$$(9)$$

## VCS from Lagrange Basis Polynomials [CDHK15]

Compute  $\phi(X)$  s.t.  $\phi(i) = v_i$ :

$$\phi(X) = \sum_{i=0}^{n-1} v_i \cdot L_i(X), \text{ where } L_i(X) = \prod_{\substack{j \in [0, n) \\ j \neq i}} \frac{X - j}{i - j} \quad (6)$$

Setup Lagrange basis polynomial commitments  $\ell_i = g^{L_i(\tau)}$ ,  $\forall i \in [0, n)$  (speed?). Then, commit to  $\vec{v}$  as [CDHK15]:

$$c = \prod_{i \in [0, n)} \ell_i^{v_i} \quad (7)$$

$$= g^{\sum_{i \in [0, n)} L_i(\tau) v_i} \quad (8)$$

$$(9)$$

## VCS from Lagrange Basis Polynomials [CDHK15]

Compute  $\phi(X)$  s.t.  $\phi(i) = v_i$ :

$$\phi(X) = \sum_{i=0}^{n-1} v_i \cdot L_i(X), \text{ where } L_i(X) = \prod_{\substack{j \in [0, n) \\ j \neq i}} \frac{X - j}{i - j} \quad (6)$$

Setup Lagrange basis polynomial commitments  $\ell_i = g^{L_i(\tau)}$ ,  $\forall i \in [0, n)$  (speed?). Then, commit to  $\vec{v}$  as [CDHK15]:

$$c = \prod_{i \in [0, n)} \ell_i^{v_i} \quad (7)$$

$$= g^{\sum_{i \in [0, n)} L_i(\tau) v_i} \quad (8)$$

$$= g^{\phi(\tau)} \quad (9)$$



Let  $\phi'(X)$  be the updated polynomial after  $v_i$  changes to  $v_i + \delta_i$ :

Let  $\phi'(X)$  be the updated polynomial after  $v_i$  changes to  $v_i + \delta_i$ :

$$\phi'(X) = \phi(X) + \delta_i L_i(X) \tag{10}$$



## Updating the Digest

Let  $\phi'(X)$  be the updated polynomial after  $v_i$  changes to  $v_i + \delta_i$ :

$$\phi'(X) = \phi(X) + \delta_i L_i(X) \quad (10)$$

To update  $c$  via  $VC.UpdateDig(c, \delta_i, i, \text{upk}_i)$ :

## Updating the Digest

Let  $\phi'(X)$  be the updated polynomial after  $v_i$  changes to  $v_i + \delta_i$ :

$$\phi'(X) = \phi(X) + \delta_i L_i(X) \quad (10)$$

To update  $c$  via  $VC.UpdateDig(c, \delta_i, i, upk_i)$ :

$$c' = c \cdot \ell_i^{\delta_i} \quad (11)$$

(12)

(13)

## Updating the Digest

Let  $\phi'(X)$  be the updated polynomial after  $v_i$  changes to  $v_i + \delta_i$ :

$$\phi'(X) = \phi(X) + \delta_i L_i(X) \quad (10)$$

To update  $c$  via  $VC.UpdateDig(c, \delta_i, i, \text{upk}_i)$ :

$$c' = c \cdot \ell_i^{\delta_i} \quad (11)$$

$$= g^{\phi(\tau)} \cdot g^{\delta_i L_i(\tau)} \quad (12)$$

$$(13)$$

## Updating the Digest

Let  $\phi'(X)$  be the updated polynomial after  $v_i$  changes to  $v_i + \delta_i$ :

$$\phi'(X) = \phi(X) + \delta_i L_i(X) \quad (10)$$

To update  $c$  via  $VC.UpdateDig(c, \delta_i, i, \text{upk}_i)$ :

$$c' = c \cdot \ell_i^{\delta_i} \quad (11)$$

$$= g^{\phi(\tau)} \cdot g^{\delta_i L_i(\tau)} \quad (12)$$

$$= g^{\phi'(\tau)} \quad (13)$$

## Updating the Digest

Let  $\phi'(X)$  be the updated polynomial after  $v_i$  changes to  $v_i + \delta_i$ :

$$\phi'(X) = \phi(X) + \delta_i L_i(X) \quad (10)$$

To update  $c$  via  $VC.UpdateDig(c, \delta_i, i, \text{upk}_i)$ :

$$c' = c \cdot \ell_i^{\delta_i} \quad (11)$$

$$= g^{\phi(\tau)} \cdot g^{\delta_i L_i(\tau)} \quad (12)$$

$$= g^{\phi'(\tau)} \quad (13)$$

**Jon done:** Each  $\text{upk}_i$  must include  $\ell_i$ .

Motivation

Contributions

Techniques: VCs from Univariate Polynomial Commitments

Committing to Vectors (and Updating Digests)

Computing and Updating Proofs

Aggregating Proofs into Subvector Proofs

Conclusion

## Proof $\pi_i$ for $v_i$ Refresher

## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a KZG evaluation proof:



## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

**Step 2:** Compute  $q_i(X) = \frac{\phi(X) - v_i}{X - i}$  in  $O(n)$  time.

## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

**Step 2:** Compute  $q_i(X) = \frac{\phi(X) - v_i}{X - i}$  in  $O(n)$  time.

**Step 3:** Compute  $\pi_i = g^{q_i(\tau)}$  using an  $O(n)$ -sized multiexp.

## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

**Step 2:** Compute  $q_i(X) = \frac{\phi(X) - v_i}{X - i}$  in  $O(n)$  time.

**Step 3:** Compute  $\pi_i = g^{q_i(\tau)}$  using an  $O(n)$ -sized multiexp.

To verify, use **pairings** and  $g^\tau$  from **vrk** to check:

## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

**Step 2:** Compute  $q_i(X) = \frac{\phi(X) - v_i}{X - i}$  in  $O(n)$  time.

**Step 3:** Compute  $\pi_i = g^{q_i(\tau)}$  using an  $O(n)$ -sized multiexp.

To verify, use **pairings** and  $g^\tau$  from **vrk** to check:

$$e(c/g^{v_i}, g) = e(\pi_i, g^\tau / g^i) \Leftrightarrow \quad (14)$$

(15)

(16)

(17)

## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

**Step 2:** Compute  $q_i(X) = \frac{\phi(X) - v_i}{X - i}$  in  $O(n)$  time.

**Step 3:** Compute  $\pi_i = g^{q_i(\tau)}$  using an  $O(n)$ -sized multiexp.

To verify, use **pairings** and  $g^\tau$  from **vrk** to check:

$$e(c/g^{v_i}, g) = e(\pi_i, g^\tau / g^i) \Leftrightarrow \quad (14)$$

$$e(g^{\phi(\tau)} / g^{v_i}, g) = e(g^{q_i(\tau)}, g^{\tau-i}) \Leftrightarrow \quad (15)$$

$$(16)$$

$$(17)$$

## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

**Step 2:** Compute  $q_i(X) = \frac{\phi(X) - v_i}{X - i}$  in  $O(n)$  time.

**Step 3:** Compute  $\pi_i = g^{q_i(\tau)}$  using an  $O(n)$ -sized multiexp.

To verify, use **pairings** and  $g^\tau$  from **vrk** to check:

$$e(c/g^{v_i}, g) = e(\pi_i, g^\tau / g^i) \Leftrightarrow \quad (14)$$

$$e(g^{\phi(\tau)} / g^{v_i}, g) = e(g^{q_i(\tau)}, g^{\tau-i}) \Leftrightarrow \quad (15)$$

$$e(g^{\phi(\tau) - v_i}, g) = e(g, g)^{q_i(\tau)(\tau-i)} \Leftrightarrow \quad (16)$$

$$(17)$$

## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

**Step 2:** Compute  $q_i(X) = \frac{\phi(X) - v_i}{X - i}$  in  $O(n)$  time.

**Step 3:** Compute  $\pi_i = g^{q_i(\tau)}$  using an  $O(n)$ -sized multiexp.

To verify, use **pairings** and  $g^\tau$  from **vrk** to check:

$$e(c/g^{v_i}, g) = e(\pi_i, g^\tau / g^i) \Leftrightarrow \quad (14)$$

$$e(g^{\phi(\tau)} / g^{v_i}, g) = e(g^{q_i(\tau)}, g^{\tau-i}) \Leftrightarrow \quad (15)$$

$$e(g^{\phi(\tau) - v_i}, g) = e(g, g)^{q_i(\tau)(\tau-i)} \Leftrightarrow \quad (16)$$

$$\phi(\tau) - v_i = q_i(\tau)(\tau - i) \quad (17)$$



## Proof $\pi_i$ for $v_i$ Refresher

A proof for  $v_i$  is just a **KZG evaluation proof**:

**Step 1:** Interpolate  $\phi(X)$  in  $O(n \log^2 n)$  time.

**Step 2:** Compute  $q_i(X) = \frac{\phi(X) - v_i}{X - i}$  in  $O(n)$  time.

**Step 3:** Compute  $\pi_i = g^{q_i(\tau)}$  using an  $O(n)$ -sized multiexp.

To verify, use **pairings** and  $g^\tau$  from **vrk** to check:

$$e(c/g^{v_i}, g) = e(\pi_i, g^\tau / g^i) \Leftrightarrow \quad (14)$$

$$e(g^{\phi(\tau)} / g^{v_i}, g) = e(g^{q_i(\tau)}, g^{\tau-i}) \Leftrightarrow \quad (15)$$

$$e(g^{\phi(\tau) - v_i}, g) = e(g, g)^{q_i(\tau)(\tau-i)} \Leftrightarrow \quad (16)$$

$$\phi(\tau) - v_i = q_i(\tau)(\tau - i) \quad (17)$$

**New technique:**  $O(n)$  time w/o interpolating  $\phi(X)$  via **upk<sub>i</sub>**'s (see [TAB<sup>+</sup>20, Appendix D.7]).

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

(19)

(20)

(21)

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$(20)$$

$$(21)$$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_i (L_i(X) - 1)}{X - i} \quad (20)$$

$$(21)$$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_i (L_i(X) - 1)}{X - i} \quad (20)$$

$$= q_i(X) + \delta_i \left( \frac{L_i(X) - 1}{X - i} \right) \quad (21)$$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_i (L_i(X) - 1)}{X - i} \quad (20)$$

$$= q_i(X) + \delta_i \left( \frac{L_i(X) - 1}{X - i} \right) \quad (21)$$

Let  $u_i$  be a KZG commitment to  $\frac{L_i(X)-1}{X-i}$ .



## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_i (L_i(X) - 1)}{X - i} \quad (20)$$

$$= q_i(X) + \delta_i \left( \frac{L_i(X) - 1}{X - i} \right) \quad (21)$$

Let  $u_i$  be a KZG commitment to  $\frac{L_i(X)-1}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_i (L_i(X) - 1)}{X - i} \quad (20)$$

$$= q_i(X) + \delta_i \left( \frac{L_i(X) - 1}{X - i} \right) \quad (21)$$

Let  $u_i$  be a KZG commitment to  $\frac{L_i(X)-1}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

$$\pi'_i = \pi_i \cdot (u_i)^{\delta_i} \quad (22)$$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_i (L_i(X) - 1)}{X - i} \quad (20)$$

$$= q_i(X) + \delta_i \left( \frac{L_i(X) - 1}{X - i} \right) \quad (21)$$

Let  $u_i$  be a KZG commitment to  $\frac{L_i(X)-1}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

$$\pi'_i = \pi_i \cdot (u_i)^{\delta_i} \quad (22)$$

**Job done:** Each  $upk_i$  must include  $u_i$ .

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_i (L_i(X) - 1)}{X - i} \quad (20)$$

$$= q_i(X) + \delta_i \left( \frac{L_i(X) - 1}{X - i} \right) \quad (21)$$

Let  $u_i$  be a KZG commitment to  $\frac{L_i(X)-1}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

$$\pi'_i = \pi_i \cdot (u_i)^{\delta_i} \quad (22)$$

**Job done:** Each  $upk_i$  must include  $u_i$ . Wait, what about computing all  $u_i$ 's?

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_i$

Consider new  $q'_i(X)$  when  $v_i$  changed to  $v_i + \delta_i$ :

$$q'_i(X) = \frac{\phi'(X) - (v_i + \delta_i)}{X - i} \quad (18)$$

$$= \frac{(\phi(X) + \delta_i L_i(X)) - v_i - \delta_i}{X - i} \quad (19)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_i (L_i(X) - 1)}{X - i} \quad (20)$$

$$= q_i(X) + \delta_i \left( \frac{L_i(X) - 1}{X - i} \right) \quad (21)$$

Let  $u_i$  be a KZG commitment to  $\frac{L_i(X)-1}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

$$\pi'_i = \pi_i \cdot (u_i)^{\delta_i} \quad (22)$$

**Job done:** Each  $upk_i$  must include  $u_i$ . Wait, what about computing all  $u_i$ 's? Later.

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

(24)

(25)

(26)



## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$(25)$$

$$(26)$$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_j L_j(X)}{X - i} \quad (25)$$

$$(26)$$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_j L_j(X)}{X - i} \quad (25)$$

$$= q_i(X) + \delta_j \left( \frac{L_j(X)}{X - i} \right) \quad (26)$$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_j L_j(X)}{X - i} \quad (25)$$

$$= q_i(X) + \delta_j \left( \frac{L_j(X)}{X - i} \right) \quad (26)$$

Let  $u_{i,j}$  be a KZG commitment to  $U_{i,j}(X) = \frac{L_j(X)}{X - i}$ .

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_j L_j(X)}{X - i} \quad (25)$$

$$= q_i(X) + \delta_j \left( \frac{L_j(X)}{X - i} \right) \quad (26)$$

Let  $u_{i,j}$  be a KZG commitment to  $U_{i,j}(X) = \frac{L_j(X)}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_j L_j(X)}{X - i} \quad (25)$$

$$= q_i(X) + \delta_j \left( \frac{L_j(X)}{X - i} \right) \quad (26)$$

Let  $u_{i,j}$  be a KZG commitment to  $U_{i,j}(X) = \frac{L_j(X)}{X - i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

$$\pi'_i = \pi_i \cdot (u_{i,j})^{\delta_j} \quad (27)$$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_j L_j(X)}{X - i} \quad (25)$$

$$= q_i(X) + \delta_j \left( \frac{L_j(X)}{X - i} \right) \quad (26)$$

Let  $u_{i,j}$  be a KZG commitment to  $U_{i,j}(X) = \frac{L_j(X)}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

$$\pi'_i = \pi_i \cdot (u_{i,j})^{\delta_j} \quad (27)$$

**Big problem:** To update  $\pi_i$  after a change to any  $j$ , need  $\text{upk}_j = \{u_{i,j}, \forall i \neq j\}$

## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_j L_j(X)}{X - i} \quad (25)$$

$$= q_i(X) + \delta_j \left( \frac{L_j(X)}{X - i} \right) \quad (26)$$

Let  $u_{i,j}$  be a KZG commitment to  $U_{i,j}(X) = \frac{L_j(X)}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

$$\pi'_i = \pi_i \cdot (u_{i,j})^{\delta_j} \quad (27)$$

**Big problem:** To update  $\pi_i$  after a change to any  $j$ , need  $\text{upk}_j = \{u_{i,j}, \forall i \neq j\} \Rightarrow |\text{upk}_j| = O(n)$ .



## New Technique: Updating Proofs $\pi_i$ After a Change to $v_j, j \neq i$

Consider new  $q'_i(X)$  when  $v_j$  changed to  $v_j + \delta_j$ :

$$q'_i(X) = \frac{\phi'(X) - v_i}{X - i} \quad (23)$$

$$= \frac{(\phi(X) + \delta_j L_j(X)) - v_i}{X - i} \quad (24)$$

$$= \frac{\phi(X) - v_i}{X - i} - \frac{\delta_j L_j(X)}{X - i} \quad (25)$$

$$= q_i(X) + \delta_j \left( \frac{L_j(X)}{X - i} \right) \quad (26)$$

Let  $u_{i,j}$  be a KZG commitment to  $U_{i,j}(X) = \frac{L_j(X)}{X-i}$ . Then,  $\pi'_i = g^{q'_i(\tau)}$  can be computed as:

$$\pi'_i = \pi_i \cdot (u_{i,j})^{\delta_j} \quad (27)$$

**Big problem:** To update  $\pi_i$  after a change to any  $j$ , need  $\text{upk}_j = \{u_{i,j}, \forall i \neq j\} \Rightarrow |\text{upk}_j| = O(n)$ .

**New technique:** Compute  $u_{i,j}$  in  $O(1)$  time from  $\text{upk}_i$  and  $\text{upk}_j$ .

**New Technique:** Compute  $u_{i,j}$  in  $O(1)$  time

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0,n)} (X - i)$ .

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0, n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2),

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0, n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0,n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

(29)

(30)

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0, n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$(30)$$

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0, n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$= \frac{1}{A'(j)} \cdot W_{i,j}(X) \quad (30)$$



## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0, n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$= \frac{1}{A'(j)} \cdot W_{i,j}(X) \quad (30)$$

Fortunately, it happens that (see Appendix 1):

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0,n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$= \frac{1}{A'(j)} \cdot W_{i,j}(X) \quad (30)$$

Fortunately, it happens that (see Appendix 1):

$$\frac{1}{i-j} \cdot \frac{A(X)}{X-i} + \frac{1}{j-i} \cdot \frac{A(X)}{X-j} = \frac{A(X)}{(X-i)(X-j)} = W_{i,j}(X) \quad (31)$$

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0, n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$= \frac{1}{A'(j)} \cdot W_{i,j}(X) \quad (30)$$

Fortunately, it happens that (see Appendix 1):

$$\frac{1}{i-j} \cdot \frac{A(X)}{X-i} + \frac{1}{j-i} \cdot \frac{A(X)}{X-j} = \frac{A(X)}{(X-i)(X-j)} = W_{i,j}(X) \quad (31)$$

**New technique:** Let  $a_i = g^{A(\tau)/(\tau-i)}$  and compute  $u_{i,j}$  as:

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0,n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$= \frac{1}{A'(j)} \cdot W_{i,j}(X) \quad (30)$$

Fortunately, it happens that (see Appendix 1):

$$\frac{1}{i-j} \cdot \frac{A(X)}{X-i} + \frac{1}{j-i} \cdot \frac{A(X)}{X-j} = \frac{A(X)}{(X-i)(X-j)} = W_{i,j}(X) \quad (31)$$

**New technique:** Let  $a_i = g^{A(\tau)/(\tau-i)}$  and compute  $u_{i,j}$  as:

$$u_{i,j} = \left( a_i^{\frac{1}{i-j}} \cdot a_j^{\frac{1}{j-i}} \right)^{\frac{1}{A'(j)}} \quad (32)$$

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0,n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$= \frac{1}{A'(j)} \cdot W_{i,j}(X) \quad (30)$$

Fortunately, it happens that (see Appendix 1):

$$\frac{1}{i-j} \cdot \frac{A(X)}{X-i} + \frac{1}{j-i} \cdot \frac{A(X)}{X-j} = \frac{A(X)}{(X-i)(X-j)} = W_{i,j}(X) \quad (31)$$

**New technique:** Let  $a_i = g^{A(\tau)/(\tau-i)}$  and compute  $u_{i,j}$  as:

$$u_{i,j} = \left( a_i^{\frac{1}{i-j}} \cdot a_j^{\frac{1}{j-i}} \right)^{\frac{1}{A'(j)}} \quad (32)$$

**Job done:** Each  $upk_i$  must include  $a_i$  and  $A'(i)$ .

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0,n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$= \frac{1}{A'(j)} \cdot W_{i,j}(X) \quad (30)$$

Fortunately, it happens that (see Appendix 1):

$$\frac{1}{i-j} \cdot \frac{A(X)}{X-i} + \frac{1}{j-i} \cdot \frac{A(X)}{X-j} = \frac{A(X)}{(X-i)(X-j)} = W_{i,j}(X) \quad (31)$$

**New technique:** Let  $a_i = g^{A(\tau)/(\tau-i)}$  and compute  $u_{i,j}$  as:

$$u_{i,j} = \left( a_i^{\frac{1}{i-j}} \cdot a_j^{\frac{1}{j-i}} \right)^{\frac{1}{A'(j)}} \quad (32)$$

**Job done:** Each  $upk_i$  must include  $a_i$  and  $A'(i)$ . Wait, what about computing all  $a_i$ 's?

## New Technique: Compute $u_{i,j}$ in $O(1)$ time

Let  $A(X) = \prod_{i \in [0,n)} (X - i)$ . Then,  $L_j(X) = \frac{A(X)}{A'(j)(X-j)}$  (see Appendix 2), and:

$$U_{i,j}(X) = L_j(X)/(X - i) = \left( \frac{A(X)}{A'(j)(X-j)} \right) / (X - i) \quad (28)$$

$$= \frac{1}{A'(j)} \cdot \frac{A(X)}{(X-j)(X-i)} \quad (29)$$

$$= \frac{1}{A'(j)} \cdot W_{i,j}(X) \quad (30)$$

Fortunately, it happens that (see Appendix 1):

$$\frac{1}{i-j} \cdot \frac{A(X)}{X-i} + \frac{1}{j-i} \cdot \frac{A(X)}{X-j} = \frac{A(X)}{(X-i)(X-j)} = W_{i,j}(X) \quad (31)$$

**New technique:** Let  $a_i = g^{A(\tau)/(\tau-i)}$  and compute  $u_{i,j}$  as:

$$u_{i,j} = \left( a_i^{\frac{1}{i-j}} \cdot a_j^{\frac{1}{j-i}} \right)^{\frac{1}{A'(j)}} \quad (32)$$

**Job done:** Each  $upk_i$  must include  $a_i$  and  $A'(i)$ . Wait, what about computing all  $a_i$ 's? Later.

Motivation

Contributions

Techniques: VCs from Univariate Polynomial Commitments

Committing to Vectors (and Updating Digests)

Computing and Updating Proofs

Aggregating Proofs into Subvector Proofs

Conclusion



# Computing $I$ -subvector Proofs From Scratch

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \tag{33}$$

$$\tag{34}$$

$$\tag{35}$$

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in l}$ :

$$A_l(X) = \prod_{i \in l} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in l} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in l, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$(35)$$

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  $l$ -subvector proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in I} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  $l$ -subvector proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in I} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

**Note that**

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in I} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

## Note that

$A_l(i) = 0$  and  $R_l(i) = v_i, \forall i \in I$ .

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in I} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

## Note that

$A_l(i) = 0$  and  $R_l(i) = v_i, \forall i \in I$ .

Can compute  $A_l(X)$  and  $R_l(X)$  in  $O(|I| \log^2 |I|)$  field operations.



# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in I} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

## Note that

$A_l(i) = 0$  and  $R_l(i) = v_i, \forall i \in I$ .

Can compute  $A_l(X)$  and  $R_l(X)$  in  $O(|I| \log^2 |I|)$  field operations.

Can compute  $q_l(X)$  in  $O(n \log n)$  field operations.

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in I} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

## Note that

$A_l(i) = 0$  and  $R_l(i) = v_i, \forall i \in I$ .

Can compute  $A_l(X)$  and  $R_l(X)$  in  $O(|I| \log^2 |I|)$  field operations.

Can compute  $q_l(X)$  in  $O(n \log n)$  field operations.

$l$ -subvector proof is  $\pi_l = g^{q_l(\tau)}$ , computed with  $O(n - |I|)$ -sized multiexp.

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in I} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

## Note that

$A_l(i) = 0$  and  $R_l(i) = v_i, \forall i \in I$ .

Can compute  $A_l(X)$  and  $R_l(X)$  in  $O(|I| \log^2 |I|)$  field operations.

Can compute  $q_l(X)$  in  $O(n \log n)$  field operations.

$l$ -subvector proof is  $\pi_l = g^{q_l(\tau)}$ , computed with  $O(n - |I|)$ -sized multiexp. To verify:

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  $l$ -subvector proof  $\pi_l$  for all  $(v_i)_{i \in I}$ :

$$A_l(X) = \prod_{i \in I} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in I} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

## Note that

$A_l(i) = 0$  and  $R_l(i) = v_i, \forall i \in I$ .

Can compute  $A_l(X)$  and  $R_l(X)$  in  $O(|I| \log^2 |I|)$  field operations.

Can compute  $q_l(X)$  in  $O(n \log n)$  field operations.

$l$ -subvector proof is  $\pi_l = g^{q_l(\tau)}$ , computed with  $O(n - |I|)$ -sized multiexp. To verify:

$$e(c/g^{R_l(\tau)}, g) = e(\pi_l, g^{A_l(\tau)}) \quad (36)$$

# Computing $l$ -subvector Proofs From Scratch

Can use **KZG batch proofs** to compute a constant-sized  **$l$ -subvector** proof  $\pi_l$  for all  $(v_i)_{i \in l}$ :

$$A_l(X) = \prod_{i \in l} (X - i) \quad (33)$$

$$R_l(X) = \sum_{i \in l} v_i \cdot L_i^*(X), \text{ where } L_i^*(X) = \prod_{j \in l, j \neq i} \frac{X - j}{i - j} \quad (34)$$

$$q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)} \quad (35)$$

## Note that

$A_l(i) = 0$  and  $R_l(i) = v_i, \forall i \in l$ .

Can compute  $A_l(X)$  and  $R_l(X)$  in  $O(|l| \log^2 |l|)$  field operations.

Can compute  $q_l(X)$  in  $O(n \log n)$  field operations.

$l$ -subvector proof is  $\pi_l = g^{q_l(\tau)}$ , computed with  $O(n - |l|)$ -sized multiexp. To verify:

$$e(c/g^{R_l(\tau)}, g) = e(\pi_l, g^{A_l(\tau)}) \quad (36)$$

Note: **vrk** contains  $(g^{\tau^i})_{i \in [0, |l|]}$

## Aggregating $l$ -subvector Proof $\pi_l$ From $(\pi_i)_{i \in I}$

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

$$\frac{1}{A_I(X)} = \frac{1}{\prod_{i \in I} (X - i)} = \sum_{i \in I} \frac{1}{A'_I(i)} \cdot \frac{1}{X - i} \quad (37)$$



## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

$$\frac{1}{A_I(X)} = \frac{1}{\prod_{i \in I} (X - i)} = \sum_{i \in I} \frac{1}{A'_I(i)} \cdot \frac{1}{X - i} \quad (37)$$

We “decompose” the quotient  $q_I(X) = \frac{\phi(X) - R_I(X)}{A_I(X)}$  in  $\pi_I$  as:

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

$$\frac{1}{A_I(X)} = \frac{1}{\prod_{i \in I} (X - i)} = \sum_{i \in I} \frac{1}{A'_I(i)} \cdot \frac{1}{X - i} \quad (37)$$

We “decompose” the quotient  $q_I(X) = \frac{\phi(X) - R_I(X)}{A_I(X)}$  in  $\pi_I$  as:

$$q_I(X) = \phi(X) \frac{1}{A_I(X)} - R_I(X) \frac{1}{A_I(X)} \quad (38)$$

(39)

(40)

(41)

(42)

(43)

# Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

$$\frac{1}{A_I(X)} = \frac{1}{\prod_{i \in I} (X - i)} = \sum_{i \in I} \frac{1}{A'_I(i)} \cdot \frac{1}{X - i} \quad (37)$$

We “decompose” the quotient  $q_I(X) = \frac{\phi(X) - R_I(X)}{A_I(X)}$  in  $\pi_I$  as:

$$q_I(X) = \phi(X) \frac{1}{A_I(X)} - R_I(X) \frac{1}{A_I(X)} \quad (38)$$

$$= \phi(X) \frac{1}{A_I(X)} - \left( \sum_{i \in I} v_i \cdot L_i^*(X) \right) \frac{1}{A_I(X)} \quad (39)$$

(40)

(41)

(42)

(43)

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

$$\frac{1}{A_I(X)} = \frac{1}{\prod_{i \in I} (X - i)} = \sum_{i \in I} \frac{1}{A'_I(i)} \cdot \frac{1}{X - i} \quad (37)$$

We “decompose” the quotient  $q_I(X) = \frac{\phi(X) - R_I(X)}{A_I(X)}$  in  $\pi_I$  as:

$$q_I(X) = \phi(X) \frac{1}{A_I(X)} - R_I(X) \frac{1}{A_I(X)} \quad (38)$$

$$= \phi(X) \frac{1}{A_I(X)} - \left( \sum_{i \in I} v_i \cdot L_i^*(X) \right) \frac{1}{A_I(X)} \quad (39)$$

$$= \phi(X) \sum_{i \in I} \frac{1}{A'_I(i)(X - i)} - \left( \sum_{i \in I} v_i \cdot \frac{A_I(X)}{A'_I(i)(X - i)} \right) \cdot \frac{1}{A_I(X)} \quad (40)$$

$$(41)$$

$$(42)$$

$$(43)$$

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

$$\frac{1}{A_I(X)} = \frac{1}{\prod_{i \in I}(X - i)} = \sum_{i \in I} \frac{1}{A'_I(i)} \cdot \frac{1}{X - i} \quad (37)$$

We “decompose” the quotient  $q_I(X) = \frac{\phi(X) - R_I(X)}{A_I(X)}$  in  $\pi_I$  as:

$$q_I(X) = \phi(X) \frac{1}{A_I(X)} - R_I(X) \frac{1}{A_I(X)} \quad (38)$$

$$= \phi(X) \frac{1}{A_I(X)} - \left( \sum_{i \in I} v_i \cdot L_i^*(X) \right) \frac{1}{A_I(X)} \quad (39)$$

$$= \phi(X) \sum_{i \in I} \frac{1}{A'_I(i)(X - i)} - \left( \sum_{i \in I} v_i \cdot \frac{A_I(X)}{A'_I(i)(X - i)} \right) \cdot \frac{1}{A_I(X)} \quad (40)$$

$$= \sum_{i \in I} \frac{\phi(X)}{A'_I(i)(X - i)} - \sum_{i \in I} \frac{v_i}{A'_I(i)(X - i)} \quad (41)$$

$$(42)$$

$$(43)$$

## Aggregating $l$ -subvector Proof $\pi_l$ From $(\pi_i)_{i \in l}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

$$\frac{1}{A_l(X)} = \frac{1}{\prod_{i \in l}(X - i)} = \sum_{i \in l} \frac{1}{A'_l(i)} \cdot \frac{1}{X - i} \quad (37)$$

We “decompose” the quotient  $q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)}$  in  $\pi_l$  as:

$$q_l(X) = \phi(X) \frac{1}{A_l(X)} - R_l(X) \frac{1}{A_l(X)} \quad (38)$$

$$= \phi(X) \frac{1}{A_l(X)} - \left( \sum_{i \in l} v_i \cdot L_i^*(X) \right) \frac{1}{A_l(X)} \quad (39)$$

$$= \phi(X) \sum_{i \in l} \frac{1}{A'_l(i)(X - i)} - \left( \sum_{i \in l} v_i \cdot \frac{A_l(X)}{A'_l(i)(X - i)} \right) \cdot \frac{1}{A_l(X)} \quad (40)$$

$$= \sum_{i \in l} \frac{\phi(X)}{A'_l(i)(X - i)} - \sum_{i \in l} \frac{v_i}{A'_l(i)(X - i)} \quad (41)$$

$$= \sum_{i \in l} \frac{1}{A'_l(i)} \cdot \frac{\phi(X) - v_i}{X - i} \quad (42)$$

$$(43)$$

## Aggregating $l$ -subvector Proof $\pi_l$ From $(\pi_i)_{i \in l}$

We use *partial fraction decomposition*, as proposed by Drake and Buterin [But20] (see Appendix 2):

$$\frac{1}{A_l(X)} = \frac{1}{\prod_{i \in l} (X - i)} = \sum_{i \in l} \frac{1}{A'_l(i)} \cdot \frac{1}{X - i} \quad (37)$$

We “decompose” the quotient  $q_l(X) = \frac{\phi(X) - R_l(X)}{A_l(X)}$  in  $\pi_l$  as:

$$q_l(X) = \phi(X) \frac{1}{A_l(X)} - R_l(X) \frac{1}{A_l(X)} \quad (38)$$

$$= \phi(X) \frac{1}{A_l(X)} - \left( \sum_{i \in l} v_i \cdot L_i^*(X) \right) \frac{1}{A_l(X)} \quad (39)$$

$$= \phi(X) \sum_{i \in l} \frac{1}{A'_l(i)(X - i)} - \left( \sum_{i \in l} v_i \cdot \frac{A_l(X)}{A'_l(i)(X - i)} \right) \cdot \frac{1}{A_l(X)} \quad (40)$$

$$= \sum_{i \in l} \frac{\phi(X)}{A'_l(i)(X - i)} - \sum_{i \in l} \frac{v_i}{A'_l(i)(X - i)} \quad (41)$$

$$= \sum_{i \in l} \frac{1}{A'_l(i)} \cdot \frac{\phi(X) - v_i}{X - i} \quad (42)$$

$$= \sum_{i \in l} \frac{1}{A'_l(i)} \cdot q_i(X) \quad (43)$$

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$ (Continued)



## Aggregating $l$ -subvector Proof $\pi_l$ From $(\pi_i)_{i \in l}$ (Continued)

To aggregate  $\pi_l$ :

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$ (Continued)

To aggregate  $\pi_I$ :

**Step 1:** Interpolate  $A_I(X) = \prod_{i \in I} (X - i)$  in  $O(|I| \log^2 |I|)$  field operations.

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$ (Continued)

To aggregate  $\pi_I$ :

**Step 1:** Interpolate  $A_I(X) = \prod_{i \in I} (X - i)$  in  $O(|I| \log^2 |I|)$  field operations.

**Step 2:** Compute its derivative  $A'_I(X)$  in  $O(|I|)$  field operations.

## Aggregating $l$ -subvector Proof $\pi_l$ From $(\pi_i)_{i \in l}$ (Continued)

To aggregate  $\pi_l$ :

**Step 1:** Interpolate  $A_l(X) = \prod_{i \in l} (X - i)$  in  $O(|l| \log^2 |l|)$  field operations.

**Step 2:** Compute its derivative  $A'_l(X)$  in  $O(|l|)$  field operations.

**Step 3:** Compute all  $A'_l(i)$  in  $O(|l| \log^2 |l|)$  field operations via a *polynomial multipoint evaluation* [vzGG13].

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$ (Continued)

To aggregate  $\pi_I$ :

**Step 1:** Interpolate  $A_I(X) = \prod_{i \in I} (X - i)$  in  $O(|I| \log^2 |I|)$  field operations.

**Step 2:** Compute its derivative  $A'_I(X)$  in  $O(|I|)$  field operations.

**Step 3:** Compute all  $A'_I(i)$  in  $O(|I| \log^2 |I|)$  field operations via a *polynomial multipoint evaluation* [vzGG13].

**Step 4:** Compute  $\pi_I$  using an  $O(|I|)$ -sized multiexp:

## Aggregating $I$ -subvector Proof $\pi_I$ From $(\pi_i)_{i \in I}$ (Continued)

To aggregate  $\pi_I$ :

**Step 1:** Interpolate  $A_I(X) = \prod_{i \in I} (X - i)$  in  $O(|I| \log^2 |I|)$  field operations.

**Step 2:** Compute its derivative  $A'_I(X)$  in  $O(|I|)$  field operations.

**Step 3:** Compute all  $A'_I(i)$  in  $O(|I| \log^2 |I|)$  field operations via a *polynomial multipoint evaluation* [vzGG13].

**Step 4:** Compute  $\pi_I$  using an  $O(|I|)$ -sized multiexp:

$$\pi_I = \prod_{i \in I} \pi_i^{1/A'_I(i)} \quad (44)$$

## Aggregating $l$ -subvector Proof $\pi_l$ From $(\pi_i)_{i \in l}$ (Continued)

To aggregate  $\pi_l$ :

**Step 1:** Interpolate  $A_l(X) = \prod_{i \in l} (X - i)$  in  $O(|l| \log^2 |l|)$  field operations.

**Step 2:** Compute its derivative  $A'_l(X)$  in  $O(|l|)$  field operations.

**Step 3:** Compute all  $A'_l(i)$  in  $O(|l| \log^2 |l|)$  field operations via a *polynomial multipoint evaluation* [vzGG13].

**Step 4:** Compute  $\pi_l$  using an  $O(|l|)$ -sized multiexp:

$$\pi_l = \prod_{i \in l} \pi_i^{1/A'_l(i)} \quad (44)$$

**Job done:** Can aggregate  $\pi_i$ 's for  $(v_i)_{i \in l}$  into constant-sized  $\pi_l$ .

# Conclusion

---





# Summary

**Main contributions:**

# Summary

## Main contributions:

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys

# Summary

## Main contributions:

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof

# Summary

## Main contributions:

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof
- Proofs can be updated efficiently

# Summary

## Main contributions:

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof
- Proofs can be updated efficiently
- Can be used to build highly-efficient, account-based stateless cryptocurrencies

# Summary

## **Main contributions:**

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof
- Proofs can be updated efficiently
- Can be used to build highly-efficient, account-based stateless cryptocurrencies

## **Other goodies (not in this talk):**

# Summary

## **Main contributions:**

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof
- Proofs can be updated efficiently
- Can be used to build highly-efficient, account-based stateless cryptocurrencies

## **Other goodies (not in this talk):**

- aSVC formalization that accounts for update keys



# Summary

## Main contributions:

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof
- Proofs can be updated efficiently
- Can be used to build highly-efficient, account-based stateless cryptocurrencies

## Other goodies (not in this talk):

- aSVC formalization that accounts for update keys
- Each update key  $upk_i$  is verifiable against  $vrk$

# Summary

## Main contributions:

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof
- Proofs can be updated efficiently
- Can be used to build highly-efficient, account-based stateless cryptocurrencies

## Other goodies (not in this talk):

- aSVC formalization that accounts for update keys
- Each update key  $upk_i$  is verifiable against  $vrk$
- New security definition for KZG batch proofs, which reduces to  $n$ -SBDH

# Summary

## Main contributions:

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof
- Proofs can be updated efficiently
- Can be used to build highly-efficient, account-based stateless cryptocurrencies

## Other goodies (not in this talk):

- aSVC formalization that accounts for update keys
- Each update key  $upk_i$  is verifiable against  $vrk$
- New security definition for KZG batch proofs, which reduces to  $n$ -SBDH
- Subtleties of VC-based stateless cryptocurrencies

# Summary

## Main contributions:

- New aSVC with constant-sized (subvector) proofs and constant-sized update keys
- Proofs can be aggregated efficiently into subvector proof
- Proofs can be updated efficiently
- Can be used to build highly-efficient, account-based stateless cryptocurrencies

## Other goodies (not in this talk):

- aSVC formalization that accounts for update keys
- Each update key  $upk_i$  is verifiable against  $vrk$
- New security definition for KZG batch proofs, which reduces to  $n$ -SBDH
- Subtleties of VC-based stateless cryptocurrencies
- Aggregating multiple  $l$ -subvector proofs across different commitments [GRWZ20].

## Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th root of unity.

## Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th root of unity. This has several advantages:

# Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th root of unity. This has several advantages:

- Our public parameters can be *efficiently* derived from “powers-of-tau”  $g^{\tau^i}$ ’s:

# Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th root of unity. This has several advantages:

- Our public parameters can be *efficiently* derived from “powers-of-tau”  $g^{\tau^i}$ ’s:
  - $\ell_i$ ’s via an inverse FFT [Vir17]



# Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th root of unity. This has several advantages:

- Our public parameters can be *efficiently* derived from “powers-of-tau”  $g^{\tau^i}$ ’s:
  - $\ell_i$ ’s via an inverse FFT [Vir17]
  - $a_i$ ’s via the Feist-Khovratovich (FK) technique [FK20]

# Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th root of unity. This has several advantages:

- Our public parameters can be *efficiently* derived from “powers-of-tau”  $g^{\tau^i}$ ’s:
  - $\ell_i$ ’s via an inverse FFT [Vir17]
  - $a_i$ ’s via the Feist-Khovratovich (FK) technique [FK20]
  - $u_i$ ’s via **our new, FK-like, technique** (see [TAB<sup>+</sup>20, Sec 3.4.5])

# Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th **root of unity**. This has several advantages:

- Our public parameters can be *efficiently* derived from “powers-of-tau”  $g^{\tau^i}$ ’s:
  - $\ell_i$ ’s via an inverse FFT [Vir17]
  - $a_i$ ’s via the Feist-Khovratovich (FK) technique [FK20]
  - $u_i$ ’s via **our new, FK-like, technique** (see [TAB<sup>+</sup>20, Sec 3.4.5])
- Since  $g^{\tau^i}$ ’s are updatable, our public parameters are *updatable*.

# Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th **root of unity**. This has several advantages:

- Our public parameters can be *efficiently* derived from “powers-of-tau”  $g^{\tau^i}$ ’s:
  - $\ell_i$ ’s via an inverse FFT [Vir17]
  - $a_i$ ’s via the Feist-Khovratovich (FK) technique [FK20]
  - $u_i$ ’s via **our new, FK-like, technique** (see [TAB<sup>+</sup>20, Sec 3.4.5])
- Since  $g^{\tau^i}$ ’s are updatable, our public parameters are *updatable*.
- Can precompute all  $n$  proofs in  $O(n \log n)$  time via FK technique [FK20].

# Roots of Unity Benefits

Our scheme actually uses  $\phi(\omega_i) = v_i$ , where  $\omega$  is a primitive  $n$ th root of unity. This has several advantages:

- Our public parameters can be *efficiently* derived from “powers-of-tau”  $g^{\tau^i}$ ’s:
  - $\ell_i$ ’s via an inverse FFT [Vir17]
  - $a_i$ ’s via the Feist-Khovratovich (FK) technique [FK20]
  - $u_i$ ’s via *our new, FK-like, technique* (see [TAB<sup>+</sup>20, Sec 3.4.5])
- Since  $g^{\tau^i}$ ’s are updatable, our public parameters are *updatable*.
- Can precompute all  $n$  proofs in  $O(n \log n)$  time via FK technique [FK20].
- Can remove  $A'(i)$  from *upk<sub>i</sub>*.

**Questions?**

# Outline

Decomposition of  $1/((X - i)(X - j))$

Decomposition of  $1/A_l(X)$

## Decomposition of $A(X) / ((X - i)(X - j))$

Note that:

$$\frac{1}{i-j} \cdot \frac{A(X)}{X-i} + \frac{1}{j-i} \cdot \frac{A(X)}{X-j} = \frac{1}{i-j} \cdot \frac{A(X)(X-j)}{(X-i)(X-j)} + \frac{1}{j-i} \cdot \frac{A(X)(X-i)}{(X-j)(X-i)} \quad (45)$$

$$= \frac{\frac{1}{i-j}A(X)(X-j) - \frac{1}{i-j}A(X)(X-i)}{(X-i)(X-j)} \quad (46)$$

$$= \frac{\frac{1}{i-j}A(X)[(X-j) - (X-i)]}{(X-i)(X-j)} \quad (47)$$

$$= \frac{\frac{1}{i-j}A(X)(-j+i)}{(X-i)(X-j)} \quad (48)$$

$$= \frac{A(X)}{(X-i)(X-j)} \quad (49)$$



Decomposition of  $1 / ((X - i)(X - j))$

Decomposition of  $1 / A_l(X)$

# Partial Fraction Decomposition From Lagrange Interpolation

It is well-known that Lagrange coefficients can be *rewritten* as [BT04, vzGG13]:

$$L_i(X) = \prod_{j \in I, j \neq i} \frac{X - j}{i - j} = \frac{A_i(X)}{A_i'(i)(X - i)}, \text{ where } A_i(X) = \prod_{i \in I} (X - i) \quad (50)$$

Here,  $A_i'(X)$  is the derivative of  $A_i(X)$  and has the (non-obvious) property that  $A_i'(i) = \prod_{j \in I, j \neq i} (i - j)$ .

Next, consider the Lagrange interpolation of  $\phi(X) = 1$ :

$$\phi(X) = \sum_{i \in I} v_i L_i(X) \Leftrightarrow \quad (51)$$




$$1 = A_i(X) \sum_{i \in [0, n)} \frac{v_i}{A_i'(i)(X - i)} \Leftrightarrow \quad (52)$$

$$\frac{1}{A_i(X)} = \sum_{i \in I} \frac{1}{A_i'(i)(X - i)} \Leftrightarrow \quad (53)$$

$$\frac{1}{A_i(X)} = \sum_{i \in I} \frac{1}{A_i'(i)} \cdot \frac{1}{(X - i)} \Rightarrow \quad (54)$$




$$c_i = \frac{1}{A_i'(i)} \quad (55)$$




## References i

-  J. Berrut and L. Trefethen.  
**Barycentric Lagrange Interpolation.**  
*SIAM Review*, 46(3):501–517, 2004.
-  Vitalik Buterin.  
**The stateless client concept.**  
ethresear.ch, 2017.  
<https://ethresear.ch/t/the-stateless-client-concept/172>.
-  Vitalik Buterin.  
**Using polynomial commitments to replace state roots.**  
<https://ethresear.ch/t/using-polynomial-commitments-to-replace-state-roots/7095>, 2020.

## References ii

-  Jan Camenisch, Maria Dubovitskaya, Kristiyan Haralambiev, and Markulf Kohlweiss.  
**Composable and Modular Anonymous Credentials: Definitions and Practical Constructions.**  
In Tetsu Iwata and Jung Hee Cheon, editors, *Advances in Cryptology – ASIACRYPT 2015*, pages 262–288, Berlin, Heidelberg, 2015. Springer Berlin Heidelberg.
-  Dario Catalano and Dario Fiore.  
**Vector Commitments and Their Applications.**  
In Kaoru Kurosawa and Goichiro Hanaoka, editors, *Public-Key Cryptography – PKC 2013*, pages 55–72, Berlin, Heidelberg, 2013. Springer Berlin Heidelberg.
-  Alexander Chepur, Charalampos Papamanthou, and Yupeng Zhang.  
**Edrax: A Cryptocurrency with Stateless Transaction Validation.**  
Cryptology ePrint Archive, Report 2018/968, 2018.  
<https://eprint.iacr.org/2018/968>.

-  Dankrad Feist and Dmitry Khovratovich.  
**Fast amortized Kate proofs, 2020.**  
<https://github.com/khovratovich/Kate>.
-  Sergey Gorbunov, Leonid Reyzin, Hoeteck Wee, and Zhenfei Zhang.  
**Pointproofs: Aggregating Proofs for Multiple Vector Commitments.**  
Cryptology ePrint Archive, Report 2020/419, 2020.  
<https://eprint.iacr.org/2020/419>.
-  Aniket Kate, Gregory M. Zaverucha, and Ian Goldberg.  
**Constant-Size Commitments to Polynomials and Their Applications.**  
In Masayuki Abe, editor, *ASIACRYPT '10*, pages 177–194, Berlin, Heidelberg, 2010.  
Springer Berlin Heidelberg.

-  Russell W. F. Lai and Giulio Malavolta.  
**Subvector Commitments with Application to Succinct Arguments.**  
In Alexandra Boldyreva and Daniele Micciancio, editors, *Advances in Cryptology – CRYPTO 2019*, pages 530–560, Cham, 2019. Springer International Publishing.
-  Andrew Miller.  
**Storing UTXOs in a balanced Merkle tree (zero-trust nodes with  $O(1)$ -storage).**  
BitcoinTalk Forums, 2012.  
<https://bitcointalk.org/index.php?topic=101734.msg1117428>.
-  Leonid Reyzin, Dmitry Meshkov, Alexander Chepurnoy, and Sasha Ivanov.  
**Improving Authenticated Dynamic Dictionaries, with Applications to Cryptocurrencies.**  
In Aggelos Kiayias, editor, *Financial Cryptography and Data Security*, pages 376–392, Cham, 2017. Springer International Publishing.


## References v

 Alin Tomescu, Ittai Abraham, Vitalik Buterin, Justin Drake, Dankrad Feist, and Dmitry Khovratovich.

**Aggregatable Subvector Commitments for Stateless Cryptocurrencies.**

Cryptology ePrint Archive, Report 2020/527, 2020.

<https://eprint.iacr.org/2020/527>.

 Alin Tomescu, Robert Chen, Yiming Zheng, Ittai Abraham, Benny Pinkas, Guy Golan Gueta, and Srinivas Devadas.



**Towards Scalable Threshold Cryptosystems.**

In *2020 IEEE Symposium on Security and Privacy (SP)*, May 2020.

 Peter Todd.

**Making utxo set growth irrelevant with low-latency delayed txo commitments, 2016.**

<https://peterertodd.org/2016/delayed-txo-commitments>.

-  Alin Tomescu.  
***How to Keep a Secret and Share a Public Key (Using Polynomial Commitments).***  
PhD thesis, Massachusetts Institute of Technology, Cambridge, MA, USA, 2020.
-  Madars Virza.  
***On Deploying Succinct Zero-Knowledge Proofs.***  
PhD thesis, Massachusetts Institute of Technology, Cambridge, MA, USA, 2017.
-  Joachim von zur Gathen and Jurgen Gerhard.  
**Fast polynomial evaluation and interpolation.**  
In *Modern Computer Algebra*, chapter 10, pages 295–310. Cambridge University Press, New York, NY, USA, 3rd edition, 2013.