Is a 6D Representation of Meaning Possible? Exploring the Challenges and Possibilities of Semantic Modeling: A Concise Note.

Alireza Dehbozorgi

4 min read · Just now



Preamble

Representation of meaning has long been a challenging problem in the field of computational linguistics. How can we capture the nuances of meaning and context in a way that is useful for natural language processing (NLP) algorithms? One approach that has gained traction in recent years is distributional semantics, which represents words as vectors in high-dimensional space based on their co-occurrence patterns in large corpora of text. However, the question remains: is a 6D representation of meaning possible?

In this article, I will explore the challenges and possibilities of semantic modeling in higher dimensions.

. . .

Challenges to 6D Representation of Meaning

One of the main challenges to the idea of a 6D representation of meaning is that meaning is often context-dependent. Words can have different meanings depending on the context in which they are used. For example, the word "bank" can refer to a financial institution or the edge of a river, depending on the context. This variability in meaning makes it difficult to capture meaning in a fixed-dimensional space.



Affine Spaces (https://en.wikipedia.org/wiki/Affine_space)

Another challenge to the idea of a 6D representation of meaning is that meaning is inherently complex. Words can have multiple meanings, and the relationships between words can be intricate and difficult to capture in a simple model. In fact, some researchers have proposed models with more than six dimensions to better capture the complexity of meaning. For example, in the book "The Geometry of Meaning (2014)" by Peter Gärdenfors, the author proposes a 13-dimensional model of meaning. (See also A. M. Young (1976) & D. Widdows (2004))

https://www.penguin.com.au/books/the-geometry-of-meaning-9780262533751



https://www.amazon.com/Geometry-Meaning-Arthur-Young-1976-12-31/dp/B01K90MCG0



https://press.uchicago.edu/ucp/books/book/distributed/G/bo3632677.html

...

Possibilities for 6D Representation of Meaning

Despite these challenges, some researchers have continued to explore the idea of a 6D representation of meaning. For example, in a recent paper published in the journal "Nature" researchers have proposed a six-dimensional model of semantic space for abstract concepts. The authors of the paper argue that their six-dimensional model provides a better fit for human judgments of semantic similarity than other models with fewer dimensions.

One possible solution to the challenge of context-dependent meaning is to incorporate context into the model. For example, instead of representing words as fixed vectors in space, researchers could use contextualized word embeddings, which take into account the context in which a word is used. This approach has shown promise in recent research, although it is still in its early stages.

...

Conclusion

In conclusion, the question of whether a 6D representation of meaning is possible remains an open one. While some researchers have proposed such models, others have suggested that more dimensions may be necessary to fully capture the nuances of meaning. Contextualized word embeddings may be a promising solution to the challenge of context-dependent meaning, but more research is needed to determine their effectiveness. As NLP algorithms continue to advance, the representation of meaning will remain an important area of research and development in the field of computational linguistics.

...

Selected References:

- Gärdenfors, Peter. (2014). The Geometry of Meaning: Semantics based on Conceptual Spaces. The MIT Press.

- — — — — — — — — — (2000). Conceptual Spaces: The Geometry of Thought. MIT Press.
- Li, J., Jurafsky, D. (2015). Do Multi-Sense Embeddings Improve Natural Language Understanding? In Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing.
- Lenci, A. (2008). Distributional Semantics in Linguistics and Cognitive Science. Rivista di Linguistica 20.1 (2008), pp. 1–31.
- Murphy, B. (2012). Machine Learning: A Probabilistic Perspective. MIT Press.
- Schnabel, T., Labutov, I., Mimno, D., Joachims, T. (2015). Evaluation Methods for Unsupervised Word Embeddings. Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing.
- A Survey on Contextual Embeddings (2020).
- Wang, S., Zhang, Y., Shi, W. *et al.* (2023). A large dataset of semantic ratings and its computational extension. *Sci Data* **10**, 106. https://doi.org/10.1038/s41597-023-01995-6
- Blanco, J. L. (2019). A Modular Optimization Framework for Localization and Mapping.
- Widdows, D. (2004). Geometry and Meaning. Chicago University Press.
- Oloff, R. (2023). The Geometry of Spacetime: A Mathematical Introduction to Relativity Theory. Berlin: Springer.

. . .

Thank you so much for your attention! Stay tuned for many more!!

Alireza Dehbozorgi

https://www.linkedin.com/in/alireza-dehbozorgi-80557702a/

Twitter: https://twitter.com/BDehbozorgi83

Email: alirezadehbozorgi83@yahoo.com

Linguistics Semantics Physics Geometry Computational Linguistics

Edit profile

Written by Alireza Dehbozorgi

60 Followers

I'm a linguist and AI researcher interested in mathematical/computational approaches to both human and formal languages. Twitter: @BDehbozorgi83

More from Alireza Dehbozorgi

 Alireza Dehbozorgi

Unraveling the Mystery of Prolog: Why it's More Relevant than Ever

Prolog, the Programming in Logic language, is a powerful tool for solving complex problems using a declarative approach. Prolog is a logic…

3 min read · May 19

4 1



Alireza Dehbozorgi

Some Thoughts on Integrating Acoustic Speech Data into Formal Ontologies and Knowledge Management…

Acoustic analysis can be used to integrate speech cues and data into formal ontologies (1) by identifying and extracting acoustic features…

6 min read · 4 days ago

101 2



Alireza Dehbozorgi

Relational Calculus & Algebra (RCA) and Actionable Knowledge (Part I: Theoretical and Ethical…

Introduction

11 min read · May 11

1

Alireza Dehbozorgi

Computational Theories of Cognition- Part II: Logic-Based Models of Cognition.

This article explains the approach to reaching the overarching scientific goal of capturing the cognition of persons in computational formal…

18 min read · May 11

2

See all from Alireza Dehbozorgi

Recommended from Medium

Douglas Giles, PhD in Ellemeno

The Memeocene: Humanity's New Epoch

Slouching toward mediocrity?

· 8 min read · 4 days ago

1.2K 17

Benjamin Cain in God's Funeral

How the Youthful Universe Conjures its Structure

Reconciling science and religion with pantheism

· 7 min read · 5 days ago

Lists

Staff Picks

323 stories · 81 saves

Neel Dozome in UX Collective

Times New Roman: can we make serifs great again?

Matthew Carter and the re-invention of type design for screens and desktop printing

· 30 min read · 1 day ago



Ethan Siegel in Starts With A Bang!

We can’t avoid a singularity inside every black hole

Yes, “the laws of physics break down” at singularities. But something really weird must have happened for black holes to not possess them.

· 10 min read · 4 days ago

Greg Satell

Change Is Never Simple Or Linear—You Need To Tap Into Networks And Ecosystems

It is networks of unseen connections that lead to transformation and change.

· 6 min read · May 20

Marc Barham in Counter Arts

Our Real Multiverse Of Death

God, Videogames, and War.

· 6 min read · 6 days ago

See more recommendations