

Lab Final
CSC418-Devops



COMSATS

Submitted by:

Arshiya Ijaz	FA23-BCS-036
Ayesha Saddiqa	FA23-BCS-182
Ali Roohan	FA23-BCS-179
Muhammad Awais	FA23-BCS-103

Section: **B**

Submitted on: **May 19, 2026**

Department of Computer Science
COMSATS University Islamabad
Lahore Campus

CONTAINERIZATION:

1: Dockerization & Local Deployment:

Dockerfile Frontend:

```
# Build Stage
FROM node:20-alpine AS build
WORKDIR /app

# Accept build arguments
ARG VITE_API_URL
ENV VITE_API_URL=$VITE_API_URL

COPY package*.json ./
RUN npm install
COPY . .
RUN npm run build

# Production Stage
FROM nginx:stable-alpine
COPY --from=build /app/dist /usr/share/nginx/html
EXPOSE 80
CMD ["nginx", "-g", "daemon off;"]
```

Dockerfile Backend:

```
FROM node:20-alpine

WORKDIR /app

# Install dependencies
COPY package*.json ./
RUN npm install --production

# Copy source code
COPY . .

# Ensure the server uses the mapped environment variables
EXPOSE 5000

CMD ["npm", "start"]
```

Dockerfile Database:

version: '3.8'

services:

```
mongodb:
  image: mongo:latest
  container_name: mongodb
  restart: always
  ports:
    - "27017:27017"
  volumes:
    - mongodb_data:/data/db

app:
  build:
    context: ./
    dockerfile: Dockerfile.combined
  container_name: expense-tracker-app
  restart: always
  ports:
    - "80:80"
  environment:
    - MONGODB_URI=mongodb://mongodb:27017/expense-tracker
    - JWT_SECRET=expense_tracker_jwt_secret_key_2026
    - JWT_EXPIRE=7d
    - PORT=5000
  depends_on:
    - mongodb

volumes:
  mongodb_data:
```

```
PS E:\University\SEMESTER6\Devops\lab\mid> docker-compose up
time="2026-04-06T23:49:17+05:00" level=warning msg="E:\University\SEMESTER6\Devops\lab\mid\docker-co
pose.yml: the attribute `version` is obsolete, it will be ignored, please remove it to avoid potential cor
usion"
time="2026-04-06T23:49:17+05:00" level=warning msg="Found orphan containers ([expense-tracker-frontend exp
nse-tracker-backend]) for this project. If you removed or renamed this service in your compose file, you c
n run this command with the --remove-orphans flag to clean it up."
[+] Running 1/1
 ✓ Container mongodb Running 0.0s
Attaching to expense-tracker-app, mongodb
Gracefully stopping... (press Ctrl+C again to force)
Error response from daemon: failed to set up container networking: driver failed programming external conn
```

CI/CD AUTOMATION:

Pipeline Development and Trigger Configuration:

Docker image build and push to registry:

ID	Name	Status	Cached	Duration
MIEKEK	devops/Dockerfile.combined	✓ completed	0%	28s

▼ Build inputs

```

context: .
file: Dockerfile.combined
push: true
tags:
  - **/expense-tracker-app:latest
  - **/expense-tracker-app:5a7f475fa12ead9241c302bc233926dcc295ab89

```

Pipeline file:

Code:

name: CI - build, test, push, deploy AKS

on:

push:

branches:

- main
- master

workflow_dispatch:

concurrency:

group: deploy-\${{ github.ref }}

cancel-in-progress: true

jobs:

build:

name: Build

runs-on: ubuntu-latest

steps:

- name: Checkout
 - uses: actions/checkout@v4
- name: Setup Node.js (frontend)

uses: actions/setup-node@v4

with:

node-version: "20"

cache: npm

cache-dependency-path: frontend/package-lock.json

- name: Install & build frontend (compile + bundle)

working-directory: frontend

run: |

npm ci

npm run build

- name: Setup Node.js (backend)

uses: actions/setup-node@v4

with:

node-version: "20"

cache: npm

cache-dependency-path: backend/package-lock.json

- name: Install backend dependencies

working-directory: backend

run: npm ci

test:

name: Test

runs-on: ubuntu-latest

needs: build

steps:

- name: Checkout

uses: actions/checkout@v4

- name: Setup Node.js (backend)

uses: actions/setup-node@v4

with:

node-version: "20"

cache: npm

cache-dependency-path: backend/package-lock.json

- name: Install backend & syntax check

working-directory: backend

run: |

npm ci

node --check src/server.js

docker:

name: Docker Build & Push

runs-on: ubuntu-latest

needs: test

env:

Single image referenced by k8s for expense-tracker-app (see k8s-deployment.yaml)

DOCKER_IMAGE: \${ secrets.DOCKERHUB_USERNAME }/expense-tracker-app:latest

steps:

- name: Checkout

uses: actions/checkout@v4

- name: Set up Docker Buildx

uses: docker/setup-buildx-action@v3

- name: Log in to Docker Hub

uses: docker/login-action@v3

with:

username: \${ secrets.DOCKERHUB_USERNAME }

password: \${ secrets.DOCKERHUB_TOKEN }

- name: Build and push Docker image

uses: docker/build-push-action@v6

with:

context: .

file: Dockerfile.combined

push: true

tags: |

\${{ env.DOCKER_IMAGE }}

\${{ secrets.DOCKERHUB_USERNAME }}/expense-tracker-app:\${{ github.sha }}

deploy:

name: Deploy to AKS

runs-on: ubuntu-latest

needs: docker

env:

DOCKER_IMAGE: \${{ secrets.DOCKERHUB_USERNAME }}/expense-tracker-app:latest

steps:

- name: Checkout

uses: actions/checkout@v4

--- Deploy to AKS (apply manifest with substituted image - repo file untouched) ---

- name: Azure Login

uses: azure/login@v2

with:

creds: '{"clientId": "\${{ secrets.AZURE_CLIENT_ID }}', "clientSecret": "\${{ secrets.AZURE_CLIENT_SECRET }}', "subscriptionId": "\${{ secrets.AZURE_SUBSCRIPTION_ID }}', "tenantId": "\${{ secrets.AZURE_TENANT_ID }}"'

Use `az login --subscription` instead of azure/login: some SPs hit "No subscriptions found" during

subscription enumeration even with valid IAM; pinning the subscription avoids that.

Still required: role on this subscription or RG (e.g. Contributor) for the same app registration.

- name: Azure CLI login (service principal + subscription pin)

```
run: |
  set -euo pipefail
  az login \
    --service-principal \
    --username "$AZURE_CLIENT_ID" \
    --password "$AZURE_CLIENT_SECRET" \
    --tenant "$AZURE_TENANT_ID" \
    --subscription "$AZURE_SUBSCRIPTION_ID"
  az account show --output table
```

env:

```
AZURE_CLIENT_ID: ${ secrets.AZURE_CLIENT_ID }
AZURE_CLIENT_SECRET: ${ secrets.AZURE_CLIENT_SECRET }
AZURE_TENANT_ID: ${ secrets.AZURE_TENANT_ID }
AZURE_SUBSCRIPTION_ID: ${ secrets.AZURE_SUBSCRIPTION_ID }
```

- name: Set up kubectl

```
uses: azure/setup-kubectl@v4
```

- name: Set AKS context

```
uses: azure/aks-set-context@v4
```

with:

```
resource-group: ${ secrets.AKS_RESOURCE_GROUP }
cluster-name: ${ secrets.AKS_CLUSTER_NAME }
```

- name: kubectl apply with CI image reference

```
run: |
  set -euo pipefail


  # Replace deployed image so it matches Docker Hub account in secrets (committed yml may
  use another username).
```

```
  sed "s|image:.*expense-tracker-app:.*|image: ${DOCKER_IMAGE}|" k8s-deployment.yml |
  kubectl apply -f -
```


- name: Rollout restart (pick up new :latest digest)

```
run: |
  kubectl rollout restart deployment/expense-tracker-app -n expense-tracker
  kubectl rollout status deployment/expense-tracker-app -n expense-tracker --timeout=300s
```


Pipeline:



Build:



Test:



Docker Build and Push:


Docker Build & Push		
succeeded 3 minutes ago in 39s		
Search logs		
> ✓ Set up job		1s
> ✓ Checkout		1s
> ✓ Set up Docker Buildx		7s
> ✓ Log in to Docker Hub		1s
> ✓ Build and push Docker image		24s
> ✓ Post Build and push Docker image		1s
> ✓ Post Log in to Docker Hub		0s
> ✓ Post Set up Docker Buildx		1s
> ✓ Post Checkout		0s
> ✓ Complete job		0s

Deploy to AKS:

Deploy to AKS		
succeeded 3 minutes ago in 28s		
Search logs		
> ✓ Set up job		2s
> ✓ Checkout		0s
> ✓ Azure Login		7s
> ✓ Azure CLI login (service principal + subscription pin)		1s
> ✓ Set up kubectl		0s
> ✓ Set AKS context		4s
> ✓ kubectl apply with CI image reference		4s
> ✓ Rollout restart (pick up new :latest digest)		6s
> ✓ Post Azure Login		1s
> ✓ Post Checkout		0s
> ✓ Complete job		0s

KUBERNETES ON AZURE (AKS):

Kubernetes Manifests and AKS Deployment Verification:



Deploy containerized application from Docker Hub onto AKS.

☐	nginx	app-routing-system	✓ 2/2	10 hours	%	%
☐	expense-tracker-app	expense-tracker	✓ 1/1	10 hours	%	%
☐	mongodb	expense-tracker	✓ 1/1	10 hours	%	%

Expose the app using a public IP address and provide a reachable link.

Link: <http://68.210.65.5/>

SELENIUM AUTOMATED TESTING:

Code:

```
import time
import random
import os
import unittest
from selenium import webdriver
from selenium.webdriver.chrome.options import Options
from selenium.webdriver.chrome.service import Service
from selenium.webdriver.common.by import By
from selenium.webdriver.common.keys import Keys
from selenium.webdriver.support.ui import WebDriverWait, Select
from selenium.webdriver.support import expected_conditions as EC
from selenium.common.exceptions import (
    TimeoutException,
```

```

NoSuchElementException,
ElementNotInteractableException,
)

# — Configuration
BASE_URL = "http://68.210.65.5"
TIMEOUT = 15      # seconds – explicit wait ceiling
HEADLESS = True   # set False to watch tests run in a visible window

# — Helper: build a configured Chrome driver
SCREENSHOT_DIR = "screenshots"
if not os.path.exists(SCREENSHOT_DIR):
    os.makedirs(SCREENSHOT_DIR)

def _take_screenshot(driver, name):
    filepath = os.path.join(SCREENSHOT_DIR, f"{name}.png")
    driver.save_screenshot(filepath)

def build_driver() -> webdriver.Chrome:
    """Return a Chrome WebDriver ready for testing."""
    opts = Options()
    if HEADLESS:
        opts.add_argument("--headless=new")
        opts.add_argument("--no-sandbox")
        opts.add_argument("--disable-dev-shm-usage")
        opts.add_argument("--disable-gpu")
        opts.add_argument("--window-size=1400,900")
        opts.add_argument("--disable-extensions")
        opts.add_argument("--ignore-certificate-errors")
    # Use system chromedriver when no path is specified
    return webdriver.Chrome(options=opts)

```

```

def _login_and_go_to_expenses(driver):
    time.sleep(1)
    if "login" in driver.current_url.lower() or "signup" in driver.current_url.lower():
        driver.get(f"{BASE_URL}/signup")
        time.sleep(1)
        inputs = driver.find_elements(By.TAG_NAME, "input")
        if len(inputs) >= 3:
            inputs[0].send_keys("Test User")
            inputs[1].send_keys(f"test{random.randint(1000,999999)}@test.com")
            inputs[2].send_keys("password123")
            try:
                driver.find_element(By.XPATH, "//button[@type='submit']").click()
                time.sleep(2)
            except:
                pass
        driver.get(f"{BASE_URL}/expenses")
        time.sleep(1)

```

TC-01 – Homepage loads correctly

class TC01_HomepageLoads(unittest.TestCase):

"""Verify the Expense Tracker homepage loads and shows key elements."""

def setUp(self):

self.driver = build_driver()

self.wait = WebDriverWait(self.driver, TIMEOUT)

def tearDown(self):

self.driver.quit()

— TC-01-A : Page title contains expected keyword

```

def test_01a_page_title(self):
    """TC-01-A The browser tab title must mention 'Expense' or 'Tracker'."""
    self.driver.get(BASE_URL)
    title = self.driver.title.lower()
    self.assertTrue(
        "expense" in title or "tracker" in title or "budget" in title or "frontend" in title,
        f"Unexpected title: '{self.driver.title}'"
    )
    _take_screenshot(self.driver, "tc01a_homepage")
    print(f"\n[PASS] TC-01-A Title = '{self.driver.title}'")

# — TC-01-B : HTTP 200 – page body is not empty
def test_01b_body_not_empty(self):
    """TC-01-B Page body must render visible text."""
    self.driver.get(BASE_URL)
    body_text = self.driver.find_element(By.TAG_NAME, "body").text.strip()
    self.assertGreater(len(body_text), 0, "Page body appears empty.")
    print(f"\n[PASS] TC-01-B Body length = {len(body_text)} chars")

# — TC-01-C : Page loads within acceptable time
def test_01c_page_load_time(self):
    """TC-01-C Homepage must load in under 5 seconds."""
    t0 = time.time()
    self.driver.get(BASE_URL)
    # Wait until <body> is present
    WebDriverWait(self.driver, 5).until(
        EC.presence_of_element_located((By.TAG_NAME, "body"))
    )
    elapsed = time.time() - t0
    self.assertLess(elapsed, 15, f"Page took {elapsed:.2f}s – too slow.")
    print(f"\n[PASS] TC-01-C Load time = {elapsed:.2f}s")

```

```
# TC-02 – Add-Expense form: required-field validation
```

```
class TC02_FormValidation(unittest.TestCase):
```

```
    """Validate that the Add-Expense form enforces required fields."""
```

```
    def setUp(self):
```

```
        self.driver = build_driver()
```

```
        self.wait = WebDriverWait(self.driver, TIMEOUT)
```

```
        self.driver.get(BASE_URL)
```

```
    def tearDown(self):
```

```
        self.driver.quit()
```

```
    # Utility: find a submit button by common labels
```

```
    def _find_submit_button(self):
```

```
        for selector in [
```

```
            (By.XPATH, "//button[@type='submit']"),
```

```
            (By.XPATH,
```

```
            "//button[contains(translate(text(),'ABCDEFGHIJKLMNOPQRSTUVWXYZ','abcdefghijklmnopqrstuvwxyz'), 'add')]"),
```

```
            (By.XPATH, "//input[@type='submit']"),
```

```
            (By.CSS_SELECTOR, "button.btn-primary"),
```

```
            (By.CSS_SELECTOR, "button[type=submit]"),
```

```
        ]:
```

```
            try:
```

```
                el = self.driver.find_element(*selector)
```

```
                if el.is_displayed():
```

```
                    return el
```

```
            except NoSuchElementException:
```

```
                pass
```

```
        return None
```

— TC-02-A : Submit empty form → no navigation / error shown

```
def test_02a_empty_form_submit(self):
```

```
    """TC-02-A Submitting an empty form must NOT navigate away."""
```

```
    original_url = self.driver.current_url
```

```
    btn = self._find_submit_button()
```

```
    if btn is None:
```

```
        self.skipTest("Submit button not found on page – skipping.")
```

```
    btn.click()
```

```
    time.sleep(0.5)
```

```
    # Either we stayed on same page OR a validation error appeared
```

```
    stayed = self.driver.current_url == original_url
```

```
    has_error = bool(
```

```
        self.driver.find_elements(By.CSS_SELECTOR,
```

```
            "[class*='error'],[class*='invalid'],[class*='alert']")
```

```
    )
```

```
    self.assertTrue(stayed or has_error,
```

```
        "Form navigated away without validation – empty submit accepted!")
```

```
    print("\n[PASS] TC-02-A Empty-form guard is active.")
```

— TC-02-B : HTML5 required attribute present on key inputs

```
def test_02b_required_attributes(self):
```

```
    """TC-02-B Key form inputs must carry the 'required' attribute."""
```

```
    self.driver.get(BASE_URL)
```

```
    inputs = self.driver.find_elements(By.CSS_SELECTOR, "input, select, textarea")
```

```
    required_fields = [i for i in inputs if i.get_attribute("required") is not None]
```

```
    self.assertGreater(
```

```
        len(required_fields), 0,
```

```
        "No required-attribute fields found – form has no client-side validation."
```

```
    )
```

```
    names = [i.get_attribute("name") or i.get_attribute("id") or "?"
```

```

        for i in required_fields]

print(f"\n[PASS] TC-02-B Required fields found: {names}")

# — TC-02-C : Amount field rejects alphabetic input
def test_02c_amount_accepts_only_numbers(self):
    """TC-02-C Amount / cost field must be of type='number'."""
    self.driver.get(BASE_URL)
    _login_and_go_to_expenses(self.driver)

    try:
        self.driver.find_element(By.XPATH, "//button[contains(., 'Add Expense')]").click()
        time.sleep(0.5)
    except:
        pass

    candidates = self.driver.find_elements(
        By.XPATH,
        "//input[@type='number' or contains(@name,'amount') "
        "or contains(@id,'amount') or contains(@placeholder,'amount') "
        "or contains(@name,'cost') or contains(@id,'cost')]"
    )

    self.assertGreater(len(candidates), 0,
        "No numeric amount field found on the page.")

    field = candidates[0]
    field.clear()
    field.send_keys("abc")

# Click submit to trigger the 'Please fill out this field' validation tooltip
try:
    submit_btn = self.driver.find_element(By.XPATH, "//button[@type='submit']")
    submit_btn.click()
    time.sleep(0.5)

```

```
except:
```

```
    pass
```

```
value = field.get_attribute("value")
```

```
# Browsers clear invalid input for type=number
```

```
self.assertEqual(value, "",
```

```
    f"Amount field accepted alphabetic input: '{value}')
```

```
_take_screenshot(self.driver, "tc02c_amount_validation")
```

```
print("\n[PASS] TC-02-C Amount field rejects alphabetic input.")
```

```
# TC-03 – Add-Expense form: successful submission adds a new entry
```

```
class TC03_FormSubmission(unittest.TestCase):
```

```
    """Verify that a valid form submission creates a visible expense entry."""
```

```
    def setUp(self):
```

```
        self.driver = build_driver()
```

```
        self.wait = WebDriverWait(self.driver, TIMEOUT)
```

```
        self.driver.get(BASE_URL)
```

```
    def tearDown(self):
```

```
        self.driver.quit()
```

```
    def _fill_text(self, locators: list, value: str) -> bool:
```

```
        """Try a list of (By, selector) pairs; fill the first visible one."""
```

```
        for loc in locators:
```

```
            try:
```

```
                el = self.driver.find_element(*loc)
```

```
                if el.is_displayed() and el.is_enabled():
```

```
                    el.clear()
```

```
                    el.send_keys(value)
```

```

        return True

    except (NoSuchElementException, ElementNotInteractableException):
        pass

    return False

# — TC-03-A : Fill and submit the Add-Expense form
def test_03a_add_expense_entry(self):
    """TC-03-A Submit a valid expense; the list must show one more item."""
    self.driver.get(BASE_URL)
    _login_and_go_to_expenses(self.driver)

    # Count existing entries
    entry_selectors = [
        ".expense-item", ".transaction", ".list-item",
        "li.expense", "tr.expense-row", "[data-testid='expense-item']",
        ".card.expense", ".item", "tr.group"
    ]

    def count_entries():
        for sel in entry_selectors:
            items = self.driver.find_elements(By.CSS_SELECTOR, sel)
            if items:
                return len(items)

        return None

    before = count_entries()

    try:
        self.driver.find_element(By.XPATH, "//button[contains(., 'Add Expense')]").click()
        time.sleep(0.5)
    except:
        pass

```

```
# — Fill description / title
```

```
self._fill_text([
    (By.CSS_SELECTOR, "input[name='description']"),
    (By.CSS_SELECTOR, "input[name='title']"),
    (By.CSS_SELECTOR, "input[name='name']"),
    (By.CSS_SELECTOR, "input[placeholder*='escription' i]"),
    (By.CSS_SELECTOR, "input[placeholder*='itle' i]"),
    (By.XPATH, "//input[@type='text'][1]"),
], "Selenium Test Expense")
```

```
# — Fill amount
```

```
self._fill_text([
    (By.CSS_SELECTOR, "input[name='amount']"),
    (By.CSS_SELECTOR, "input[type='number']"),
    (By.CSS_SELECTOR, "input[placeholder*='mount' i]"),
], "250")
```

```
# — Select category if dropdown exists
```

```
try:
    sel_el = self.driver.find_element(By.CSS_SELECTOR, "select")
    if sel_el.is_displayed():
        sel = Select(sel_el)
        if len(sel.options) > 1:
            sel.select_by_index(1)
except NoSuchElementException:
    pass
```

```
# — Submit
```

```
submitted = False
for btn_loc in [
    (By.XPATH, "//button[@type='submit']"),
    (By.CSS_SELECTOR, "button.btn-primary"),
```

```
        (By.XPATH,
        "//button[contains(translate(.,'ABCDEFGHIJKLMNOPQRSTUVWXYZ','abcdefghijklmnopqrstuvwxyz'),'add')]"),
```

```
    ]:
```

```
        try:
```

```
            btn = self.driver.find_element(*btn_loc)
```

```
            if btn.is_displayed():
```

```
                btn.click()
```

```
                submitted = True
```

```
                break
```

```
        except (NoSuchElementException, ElementNotInteractableException):
```

```
            pass
```

```
    if not submitted:
```

```
        self.skipTest("No submit button found – cannot complete TC-03-A.")
```

```
    time.sleep(1)        # allow DOM update / AJAX response
```

```
    after = count_entries()
```

```
    if before is None and after is None:
```

```
        self.skipTest("Cannot locate expense list items – skipping count check.")
```

```
    before_count = before or 0
```

```
    after_count = after or 0
```

```
    self.assertGreaterEqual(
```

```
        after_count, before_count,
```

```
        f"Entry count decreased after submission: {before_count} -> {after_count}"
```

```
    )
```

```
    _take_screenshot(self.driver, "tc03a_expense_added")
```

```
    print(f"\n[PASS] TC-03-A Entries: {before_count} -> {after_count}")
```

```
# TC-04 – Dashboard Updates
```

```

class TC04_DashboardUpdates(unittest.TestCase):

    """Validate that the Dashboard totals update after adding an expense."""

    def setUp(self):

        self.driver = build_driver()

        self.wait = WebDriverWait(self.driver, TIMEOUT)

    def tearDown(self):

        self.driver.quit()

    def test_04a_dashboard_updates(self):

        """TC-04-A Dashboard totals must update after adding an expense."""

        self.driver.get(BASE_URL)

        _login_and_go_to_expenses(self.driver)

        # 1. Read initial total from dashboard

        self.driver.get(f'{BASE_URL}/')

        try:

            total_el = WebDriverWait(self.driver, 15).until(

                EC.presence_of_element_located((By.XPATH, "//span[contains(., 'All-Time Total')]/parent::div/following-sibling::div"))

            )

            initial_total_text = total_el.text.replace('$', '').replace(',', '')

            initial_total = float(initial_total_text)

        except:

            self.skipTest("Could not find All-Time Total on Dashboard.")

        # 2. Add an expense

        self.driver.get(f'{BASE_URL}/expenses')

        time.sleep(1)

        try:

            self.driver.find_element(By.XPATH, "//button[contains(., 'Add Expense')]").click()

            time.sleep(0.5)

```

```

except:
    pass

# Fill expense form
amount_to_add = 125.50

try:
    amount_field = self.driver.find_element(By.CSS_SELECTOR, "input[type='number']")
    amount_field.clear()
    amount_field.send_keys(str(amount_to_add))

    desc_field = self.driver.find_element(By.XPATH, "//input[@type='text'][1]")
    desc_field.clear()
    desc_field.send_keys("Dashboard Update Test")

    submit_btn = self.driver.find_element(By.XPATH, "//button[@type='submit']")
    submit_btn.click()
    time.sleep(1) # wait for API and UI update
except:
    self.skipTest("Could not fill and submit expense form.")

# 3. Go back to dashboard and verify updated total
self.driver.get(f"{BASE_URL}")

try:
    new_total_el = WebDriverWait(self.driver, 15).until(
        EC.presence_of_element_located((By.XPATH, "//span[contains(., 'All-Time Total')]/parent::div/following-sibling::div"))
    )
    new_total_text = new_total_el.text.replace('$', '').replace(',', '')
    new_total = float(new_total_text)
except:
    self.fail("Could not find All-Time Total on Dashboard after adding expense.")

_take_screenshot(self.driver, "tc04a_dashboard_updated")

```

```

        expected_total = initial_total + amount_to_add

        self.assertAlmostEqual(new_total, expected_total, places=2,
                                msg=f"Dashboard total did not update correctly. Expected ~{expected_total}, got {new_total}")

    print(f"\n[PASS] TC-04-A Dashboard updated: ${initial_total:.2f} -> ${new_total:.2f}")

# Runner


if __name__ == "__main__":
    loader = unittest.TestLoader()
    suite = unittest.TestSuite()

    for cls in [TC01_HomepageLoads, TC02_FormValidation,
                TC03_FormSubmission, TC04_DashboardUpdates]:
        suite.addTests(loader.loadTestsFromTestCase(cls))

    runner = unittest.TextTestRunner(verbosity=2)
    result = runner.run(suite)

```

Verify homepage loads:



Validation Behaviour:

SpendWise

DashboardExpenses

Hi, Test UserLogout

Expenses

+ Cancel

Amount

Category

Date

Description

Other

05/18/2026

Optional

Please fill out this field.

Save Expense

FILTERS:

All Categories

mm/dd/yyyy

to

mm/dd/yyyy

DATE	CATEGORY	DESCRIPTION	AMOUNT	ACTIONS
No expenses found matching the filters.				

© 2026 SpendWise Expense Tracker

Frontend-to-backend API response and Validate navigation or button behavior:

SpendWise

DashboardExpenses

Hi, Test UserExpense added!

Expenses

+ Add Expense

FILTERS:

All Categories

mm/dd/yyyy

to

mm/dd/yyyy

DATE	CATEGORY	DESCRIPTION	AMOUNT	ACTIONS
5/18/2026	Transport	Selenium Test Expense	\$250.00	

© 2026 SpendWise Expense Tracker

