

Code

The goal of this assignment is two fold:

a) Smooth the noisy image attached by using a mean (average) filter in 3x3 window iteratively until satisfactory results are obtained. Show the results for 1 5 10 iterations.

b) Do some research on median filters and advantage of median filter over mean filter. Apply median filtering in 3x3 window to smooth the noisy image given below and, iterate 1, 5, 10 times and show the results. Write your conclusions after you compare the results from average filter and median filter


Part a): Smooth the noisy image attached by using a mean (average) (Convolve)

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
```

```
In [2]: lena_noisy = plt.imread('lena_noisy.jpg')
m,n = lena_noisy.shape
print(m,n)
plt.imshow(lena_noisy, cmap = 'gray')
```

256 256

```
Out[2]: <matplotlib.image.AxesImage at 0x230d3e4c5b0>
```




```
In [3]: def padpixels(x):
        m,n = x.shape
        x1 = np.zeros((m,n+2),dtype = 'uint8')
        x1[:,1:n+1] = x
        x1[:,0] = x[:,0]
        x1[:,n+1] = x[:,n-1]
        x2 = np.zeros((m+2,n+2), dtype = 'uint8')
        x2[1:m+1,1:n+1] = x1[0:m,0:n]
        x2[0,:] = x1[0,:]
        x2[m+1,:] = x1[m-1,:]
        return x2
```

Padded Image

```
In [4]: lpad = padpixels(lena_noisy)
        print(lpad.shape)
        plt.imshow(lpad, cmap = 'gray')
```

(258, 258)

```
Out[4]: <matplotlib.image.AxesImage at 0x230d4145d00>
```



Implementing the mean spatial filter

```
In [5]: def convolve(x,h):
```

```

m,n = x.shape
x1 = padpixels(x)
x2 = np.zeros(x1.shape, dtype = 'float')
for i in range(1,m):
    for j in range(1,n):
        for ii in range(-1,2):
            for jj in range(-1,2):
                x2[i,j] += x1[i+ii, j+jj]*h[1+ii, 1+jj]
return x2[1:m+1, 1:n+1]

```

Filter h definition

```

In [6]: h = np.ones((3,3), dtype = 'float')
        h = h/9

```


1 iterations

```

In [7]: x = lena_noisy
        for i in range(1):
            x = np.uint8(convolve(x,h))
        plt.imshow(x, cmap = 'gray')
        print(x.shape)

```

(256, 256)




5 iterations

```

In [8]: x = lena_noisy
        for i in range(5):
            x = np.uint8(convolve(x,h))
        plt.imshow(x, cmap = 'gray')
        print(x.shape)

```


(256, 256)



10 iterations

```
In [9]: x = lena_noisy
        for i in range(10):
            x = np.uint8(convolve(x,h))
        plt.imshow(x, cmap = 'gray')
        print(x.shape)
```

(256, 256)




Part b) Implementing median filtering in 3x3 window to smooth the noisy image given below and, iterate 1, 5, 10 times and show the results.

```
In [10]: def convolveMedian(x):
        m,n = x.shape
        x1 = padpixels(x)
        x2 = np.zeros(x1.shape, dtype = 'float')
        for i in range(1,m):
            for j in range (1,n):
                x2[i,j] = np.median(x1[i:i+3,j:j+3])
        return x2[1:m+1, 1:n+1]
```

1 iteration

```
In [11]: x = lena_noisy
for i in range(1):
    x = np.uint8(convolveMedian(x))
plt.imshow(x, cmap = 'gray')
print(x.shape)
```


(256, 256)



5 iterations

```
In [12]: x = lena_noisy
for i in range(5):
    x = np.uint8(convolveMedian(x))
plt.imshow(x, cmap = 'gray')
print(x.shape)
```

(256, 256)



10 iterations

```
In [13]: x = lena_noisy
for i in range(10):
    x = np.uint8(convolveMedian(x))
```

```
plt.imshow(x, cmap = 'gray')  
print(x.shape)
```

(256, 256)

