

Title: Security Enhanced linux (SE linux)

A. Check current linux

Command : – sestatus or getenforce

```
root@localhost:~# sestatus
SELinux status:                enabled
SELinuxfs mount:              /sys/fs/selinux
SELinux root directory:      /etc/selinux
Loaded policy name:           targeted
Current mode:                 enforcing
Mode from config file:       enforcing
Policy MLS status:           enabled
Policy deny_unknown status:   allowed
Memory protection checking:   actual (secure)
Max kernel policy version:    33
root@localhost:~#
```

B. Configure the server to enable (enforcing) SE linux

Command : – setenforce 1

– nano /etc/selinux/config_d

– find the SELINUX=disable or SELINUX=permissive and change it to
SELINUX = enforcing

– Sudo reboot

```
root@localhost:~ -- -bash
root@localhost:~# sudo setenforce 1
root@localhost:~# getenforce
Enforcing
root@localhost:~#
```

```
root@localhost:~# sudo vi /etc/selinux/config
root@localhost:~#
```

```
root@localhost:~ – sudo vi /etc/selinux/config

#
# NOTE: In earlier Fedora kernel builds, SELINUX=disabled would also
# fully disable SELinux during boot. If you need a system with SELinux
# fully disabled instead of SELinux running with no policy loaded, you
# need to pass selinux=0 to the kernel command line. You can use grubby
# to persistently set the bootloader to boot with selinux=0:
#
#   grubby --update-kernel ALL --args selinux=0
#
# To revert back to SELinux enabled:
#
#   grubby --update-kernel ALL --remove-args selinux
#
SELINUX=enforcing
# SELINUXTYPE= can take one of these three values:
#   targeted - Targeted processes are protected,
#   minimum - Modification of targeted policy. Only selected processes are protected.
#   mls - Multi Level Security protection.
SELINUXTYPE=targeted
```

```
root@localhost:~# sudo reboot
```