

# Lab 3: Nonnegative Matrix Factorization

Ting Lin, 1700010644

May 27, 2020

## Contents

<b>1 Problem Setting</b>	<b>2</b>
<b>2 Methods based on MU</b>	<b>2</b>
2.1 MU and its convergence analysis . . . . .	2
2.2 Modified and Accelerated MU . . . . .	3
2.3 Accelerated MU . . . . .	4
<b>3 Methods based on ALS</b>	<b>5</b>
3.1 Naive ALS . . . . .	5
3.2 Projected BB method based ALS . . . . .	6
3.3 Projected Gradient Descent based ALS . . . . .	7
3.4 Hierarchical ALS and its acceleration . . . . .	7
<b>4 Methods based on ADMM</b>	<b>7</b>
4.1 a short introduction to ADMM framework . . . . .	8
4.2 Naive ADMM . . . . .	8
4.3 Alternating Optimizing ADMM . . . . .	8
<b>5 A new method: LMF-ADMM</b>	<b>9</b>
5.1 Trust region method . . . . .	9
5.2 ADMM solving subproblem . . . . .	10
<b>6 Numerical Experiment (I): Synthesis Data</b>	<b>11</b>
<b>7 Numerical Experiment (II): ORL and YALE data</b>	<b>16</b>

In this lab, we surveyed several methods on non-negative matrix factorization (NMF). Most of introduced algorithms are concerning NMF under the Euclidean(Frobenius) metric, however, some of them can be naturally extended to KL divergence. We introduce methods based on Multiplicative Update, Alternative Least Square, Alternative Non-negative Least Square, Alternative Direction of Multiplier Methods. Moreover, a new algorithm based on Nonlinear Least Square while subproblem is solved by ADMM is proposed. In the sections, we will analyze the convergence and test their performance, and finally test them in the popular ORL and Yale database.

# 1 Problem Setting

Nonnegative matrix factorization(NMF) considers the following optimization problem,

$$\begin{aligned} \min & \|V - WH\|_F^2 \\ \text{s.t. } & 0 < W \in \mathbb{R}^{m \times r}, \\ & 0 < H \in \mathbb{R}^{r \times n} \end{aligned} \quad (1)$$

or based on KL divergence alternatively,

$$\begin{aligned} \min & D(V||WH) \\ \text{s.t. } & 0 < W \in \mathbb{R}^{m \times r}, \\ & 0 < H \in \mathbb{R}^{r \times n} \end{aligned} \quad (2)$$

Here

$$D(A||B) = \sum_{i,j} A_{ij} \log \frac{A_{ij}}{B_{ij}} - A_{ij} + B_{ij},$$

which might behaves singular when the entry of  $A$  or  $B$  is near zero.

We always assume that  $V$  is nonnegative otherwise we can consider  $\mathcal{P}(V)$ . Here and throughout this paper we denote  $\mathcal{P}(V)$  by the projection:  $[\mathcal{P}(V)]_{ij} = \max(V_{ij}, 0)$ .

We recall some basic properties according to [1]:

1. NMF does not in general have a unique solution (up to scaling and permutation).
2. NMF is not identifiable, in the sense that the task is challenging even in the clear artificial low rank data.
3. Clearly, it is smooth but non-convex.
4. The gradient of  $W$  is  $\nabla W = W(HH') - VH'$ , and  $\nabla H = W'WH - W'V$

## 2 Methods based on MU

In this section we introduce MU method and its variants, like [2, 4, 3, 5].

### 2.1 MU and its convergence analysis

The basic idea of MU is simple, we choose a suitable stepsize and do gradient descent. Concretely, consider the gradient descent:

$$H_{ij} = H_{ij} + \eta_{ij} [\nabla H]_{ij}$$

Set  $\eta_{ij} = H_{ij} / [W'WH]_{ij}$  we obtain the update rule of  $H$ ,

$$H_{ij} = H_{ij} \frac{[W'V]_{ij}}{[W'WH]_{ij}}$$

Similar for  $W$ 's update,

$$W_{ij} = W_{ij} \frac{[V'H]_{ij}}{[WHH']_{ij}}$$

Here we introduce a more compact notation, let  $\otimes$  and  $\oslash$  be the element-wise multiplication and division operator, we can rewrite it as

$$H = H \otimes (W'V) \oslash (W'WH), \quad W = W \otimes (V'H) \oslash (WHH')$$

The implementation please see **nmf\_mu.m**.

The implementation is a little complex in the KL version:

$$H_{ij} = H_{ij} \frac{\sum_k W_{ki} V_{kj} / [WH]_{kj}}{\sum_k W_{ki}}$$

$$H_{ij} = H_{ij} \frac{\sum_k H_{jk} V_{ik} / [WH]_{ik}}{\sum_k H_{jk}}$$

also, see **nmf\_mu.m**

The update factor is chosen such that the residual  $\|V - WH\|$  ( $D(V||WH)$  resp) is nonincreasing. The advantage of MU method is that no explicit projection operation is needed.

**Proposition 1.**  $\|V - WH\|$  ( $D(V||WH)$  resp) is nonincreasing after each update.

We summarize it into the following algorithm [2].

---

**Algorithm 1** MU

---

**Require:**  $V, k$

- 1: Initialize  $W$  and  $H$
- 2: **while** not convergence **do**
- 3:

$$W_{ij} = W_{ij} \frac{[V'H]_{ij}}{[WHH']_{ij}}$$

4:

$$H_{ij} = H_{ij} \frac{[W'V]_{ij}}{[W'WH]_{ij}}$$

5: **end while**

6: **return**  $W, H$ .

---

In practice, we set stop criterion as max iteration, and initialization step we use  $W = \text{rand}(m, r); H = \text{rand}(r, n)$ .

## 2.2 Modified and Accelerated MU

However, the original MU method is not efficient, and faced various problem. We introduce some techniques to alleviate them and make mu more powerful.

**Modified MU** In [3], two main difficulties of MU is declared:

1. The denominator of the step size may be zero.
2. If the numerator is zero, and the gradient is negative, then  $H_{ij}^k$  will not be changed. Hence the convergence analysis fails, and it often occurs in numerical results.

Therefore, the authors proposed the modified step size to

$$\bar{H} \oslash (W'WH + \delta)$$

where

$$\bar{H} = H \otimes [\nabla H \geq 0] + \max(H, \sigma) \otimes [\nabla H < 0].$$

The detailed algorithm is shown below.

---

**Algorithm 2** Modified MU

---

**Require:**  $V, k$

1: Initialize  $W$  and  $H$

2: **while** not convergence **do**

3:

$$\bar{H} = H \otimes [\nabla H \geq 0] + \max(H, \sigma) \otimes [\nabla H < 0].$$

4:

$$\bar{W} = W \otimes [\nabla W \geq 0] + \max(W, \sigma) \otimes [\nabla W < 0].$$

5:

$$H = H - \bar{H} \oslash (W'W\bar{H} + \delta) \otimes \nabla H$$

6:

$$W = W - \bar{W} \oslash (\bar{W}HH' + \delta) \otimes \nabla W$$

7:   normalize  $W$  and  $H$ , such that the column sum of  $W$  is one.

8: **end while**

9: **return**  $W, H$ .

---

In [3], several properties about this method is discussed.

**Proposition 2.** *If the initial value is nonnegative (strictly positive), then nonnegativity and strict positivity will be preserved after each update.*

**Proposition 3.** *The loss  $\|V - WH\|$  is nonincreasing after each modified MU update. The sequence  $W^k, H^k$  is pre-compact, and each of its accumulated point satisfies KKT condition.*

### 2.3 Accelerated MU

The acceleration techniques is introduced and analyzed in [4, 5]. We mainly focus on the work in [4].

For any given  $\rho_W$  and  $\rho_H$ , we introduce the following algorithm:

**Algorithm 3** Accelerated MU**Require:**  $V, k, \delta$ 

```

1: Initialize  $W$  and  $H$ 
2: while not convergence do
3:    $\varepsilon = 1, \gamma = 1$ 
4:   while iter $\leq [1 + \rho_W \alpha]$  and  $\gamma > \delta \varepsilon$  do
5:      $W^- = W$ 
6:      $W = W \otimes (V'H) \oslash (WHH')$ 
7:     if iter==1 then
8:        $\varepsilon = \|W - W^-\|_F$ 
9:     end if
10:     $\gamma = \|W - W^-\|_F$ 
11:   end while
12:    $\varepsilon = 1, \gamma = 1$ 
13:   while iter $\leq [1 + \rho_H \alpha]$  and  $\gamma > \delta \varepsilon$  do
14:      $H^- = H$ 
15:      $H = H \otimes (W'V) \oslash (W'WH)$ 
16:     if iter==1 then
17:        $\varepsilon = \|H - H^-\|_F$ 
18:     end if
19:      $\gamma = \|H - H^-\|_F$ 
20:   end while
21: end while
22: return  $W, H$ .

```

Here  $\rho_W = 1 + \frac{mn+nr}{mr+m}$ ,  $\rho_H = 1 + \frac{mn+mr}{nr+n}$ .  $\delta$  is chosen to control the stop criterion and is chosen as 0.1 in our code (see `mnf_muacc.m`). Notice that the method is just replace an alternative update to a new update strategy with condition, hence all the convergence analysis makes sense in the accelerated version.

### 3 Methods based on ALS

The idea of Alternative (Nonnegative) Least Square is instead of solving the original problem, we optimize two linear problem alternatively.

$$\min_{W>0} \|V - WH^*\| \quad (3)$$

$$\min_{H>0} \|V - W^*H\| \quad (4)$$

clearly, if we can solve the linear problem correctly, then the series  $W^k, H^k$  must be non-increasing. Two ways was attempted in the literature. We will discuss the methods based on solving subproblem with or without constraints. In this section we introduce solve ALS plus a suitable projection step, and more general algorithms in constraint linear programming is explored in

#### 3.1 Naive ALS

In Naive ALS, we only need to compute the least square solution and project it into positive cone.

---

**Algorithm 4** MU

---

**Require:**  $V, k$ 

```

1: Initialize  $W$  and  $H$ 
2: while not convergence do
3:    $H = (W'W)^{-1}(W'V)$ 
4:    $H = \mathcal{P}(H)$ 
5:    $W = VH'(HH')^{-1}$ 
6:    $W = \mathcal{P}(W)$ 
7: end while
8: return  $W, H$ .

```

---

**3.2 Projected BB method based ALS**

We solve the subproblem by a projected BB, which is first introduced in [7]. Which is slightly different from global BB method, since we have to project our result into positive cone after each line search.

---

**Algorithm 5** PBBNLS

---

**Require:**  $A, B, X, \nabla X, \rho$ 

```

1: Set  $\gamma, M, \lambda_{max}, \lambda_{min}$ 
2: Set  $Q(X) - (A'B, X) + 0.5(X, A'AX)$ 
3:  $\lambda = 1/\|\nabla X\|_\infty$ 
4: for  $i = 1:\text{iter}$  do
5:    $\alpha = 1$ 
6:    $X^+ = X - \lambda \nabla X$ 
7:    $X^+ = \mathcal{P}(X^+)$ 
8:    $Q^+ = Q(X^+)$ 
9:   while  $\lambda > \lambda_{min}$  and  $Q^+ < \max_{i-M < k < i} Q(X_i) + \gamma\alpha(\nabla X, D)$  do
10:     $\alpha = \alpha/4$ 
11:     $X^+ = X - \alpha\lambda \nabla X$ 
12:     $X^+ = \mathcal{P}(X^+)$ 
13:     $Q^+ = Q(X^+)$ 
14:   end while
15:    $s = X^+ - X$ 
16:    $\nabla X^+ = A'AX - A'B$ 
17:    $y = \nabla X^+ - \nabla X$ 
18:   if  $(s, y) < \varepsilon$  then
19:      $\lambda = \lambda_{max}$ 
20:   else
21:      $\lambda = \min(\lambda_{max}, \max(\lambda_{min}, (s, s)/(s, y)))$ 
22:   end if
23:    $\nabla X = \nabla X^+, X_i = X = X^+$ 
24: end for
25: return  $X, \nabla X$ 

```

---

The whole algorithm uses PBBNLS to update each steps.

---

**Algorithm 6** APBB

---

**Require:**  $V, k$ 

```

1: Initialize  $W$  and  $H$ 
2: while not convergence do
3:    $[W, \nabla W] = PBBNLS(H', V', W', \nabla W')$ 
4:    $W = W'$ 
5:    $\nabla W = \nabla W'$ 
6:    $[H, \nabla H] = PBBNLS(W, V, H, \nabla H)$ 
7: end while
8: return  $W, H$ .

```

---

### 3.3 Projected Gradient Descent based ALS

[6] proposed a projected gradient descent method to solve the subproblem.

### 3.4 Hierarchical ALS and its acceleration

Hierarchical ALS [8] solves subproblem by LS with rank one modification. More precisely, we solve the linear problem column by column in  $W$ , and row by row in  $H$  in one epoch's update. Here is the algorithm, written in MATLAB format in order to make the idea of row/column by row/column more clear.

---

**Algorithm 7** HALS

---

**Require:**  $V, k$ 

```

1: Initialize  $W$  and  $H$ 
2: while not convergence do
3:    $VtW = V'W, WtW = W'W$ 
4:   for  $k = 1 : r$  do
5:      $tmp = VtW(:, k)' - (WtW(:, k) * H) + WtW(k, k) * H(k, :)$ 
6:      $H(k, :) = \mathcal{P}(tmp / WtW(k, k))$ 
7:   end for
8:    $VHt = VH', HHt = HH'$ 
9:   for  $k = 1 : r$  do
10:     $tmp = (VHt(:, k) - (W * HHt(:, k)) + (W(:, k) * HHt(k, k)))$ 
11:     $W(:, k) = \mathcal{P}(tmp / HHt(k, k))$ 
12:   end for
13: end while
14: return  $W, H$ .

```

---

Also, an accelerated version is provided in [4] and implemented in this lab, see `nmf_halsacc.m`

## 4 Methods based on ADMM

In this section we introduce Alternative Direction of Multiplier Method, which is powerful in handling constraint problem and non-smooth problem.

## 4.1 a short introduction to ADMM framework

Suppose we aim to solve a function

$$\min_X f(X)$$

where  $X$  is subjected to some constraints. We introduce an auxiliary variable  $Z$ , and consider the following augmented Lagrangian

$$L(X, Z, \alpha) = g(X, Z) + (\alpha, X - Z) + \frac{\rho}{2} \|X - Z\|^2.$$

Here  $g(X, Z)$  is a splitting of  $f(X)$ , i.e.  $g(X, X) = f(X)$ .

The ADMM provides the following framework: Usually two arg min problem does not have the closed form solution,

---

### Algorithm 8 General ADMM

---

**Require:**  $f, X$

- 1: Set  $L$  be the augmented Lagrangian.
  - 2:  $Z = X, \alpha = 0$ .
  - 3: **while** not converge **do**
  - 4:    $Z = \arg \min L(X, Z, \alpha)$
  - 5:    $X = \arg \min L(X, Z, \alpha)$
  - 6:    $\alpha = \alpha + \rho(X - Z)$
  - 7: **end while**
- 

however, if there is a splitting such that both subproblem is easy to solve, then the algorithm might be very effective, at least in convex optimization. In practice, especially in nonconvex problem, such algorithm is also widely used while some rigorous convergence analysis is lacked.

## 4.2 Naive ADMM

We first apply ADMM naively, the algorithm is introduced in [?] and we use the form shown in [9], yielding the following algorithm.

The augmented Lagrangian function is denoted as

$$L(W, H, S, T, \Lambda, \Pi) = \frac{1}{2} \|X - WH\|_F^2 + (\Lambda, W - S) + (\Pi, V - T) + \frac{\rho}{2} \|U - S\|_F^2 + \frac{\rho}{2} \|V - T\|_F^2$$

## 4.3 Alternating Optimizing ADMM

AO-ADMM is use ADMM to solve the subproblem in ALS, introduced in [10]. We only introduce how to solve the subproblem by ADMM, in the following algorithm.



---

**Algorithm 9** Naive ADMM

---

**Require:**  $f, X$ 

```

1: Set  $L$  be the augmented Lagrangian.
2:  $Z = X, \alpha = 0$ .
3: while not converge do
4:    $W = (VH' + \rho S - \Lambda)(HH' + \rho I)^{-1}$ 
5:    $H = (W'W + \rho I)^{-1}(W'V + \rho T - \Pi)$ 
6:    $S = \mathcal{P}(W + \Lambda/\rho)$ 
7:    $T = \mathcal{P}(H + \Pi/\rho)$ 
8:    $\Lambda = \Lambda + \rho(W - S)$ 
9:    $\Pi = \Pi + \rho(H - T)$ 
10: end while

```

---



---

**Algorithm 10** ADMM-LS-UPDATE

---

**Require:**  $Y, W, H, r$ 

```

1:  $G = W'W$ 
2:  $Haux = H, \alpha = 0$ 
3:  $\rho = \text{tr}(G)/k$ 
4: for  $i = 1 : \text{iter}$  do
5:    $Haux = (G + \rho I)^{-1}(W'Y + \rho(H + \alpha))$ 
6:    $H = Haux - \alpha$ 
7:    $\alpha = \alpha + H - Haux$ 
8: end for

```

---

## 5 A new method: LMF-ADMM

In this section we propose a new method based on LMF method of Nonlinear Least Square, and use ADMM to solve the subproblem.

### 5.1 Trust region method

We first recall LMF method, regarding NMF into a nonlinear least square problem: Suppose we have  $x_k$  and  $J_k = \nabla r(x_k)$ . Here  $r(x) : \mathbb{R}^m \rightarrow \mathbb{R}^n$  is the residual function and our goal is to minimize  $r'r$

Then we solve the following question to obtain the next point:

$$\min \|J_k(x - x_k) - r_k\|_F^2 + \nu \|x - x_k\|_F^2$$

Without constraint, the minimizer has a closed form:

$$x_k + (J_k'J_k + \nu I)^{-1}(J_k'r_k)$$

That is equivalent to LMF method. Inspired by this, we proposed an ANLS approach of LMF method.

**Algorithm 11** LMF1

---

```

1:  $R = V - WH$ 
2: for  $i = 1 : iter$  do
3:    $[W^+, H^+] = \text{admm\_update}(W, H)$ 
4:    $R^+ = V - W^+ H^+$ 
5:    $dW = W^+ - W, dH = H^+ - H$ 
6:    $\Delta f = \|R\|_F^2 - \|R^+\|_F^2$ 
7:   if  $\Delta f > 0$  then
8:      $W = W^+, H = H^+, R = R^+, \mu = \mu/2$ 
9:      $\nabla W = WHH' - VH', \nabla H = W'WH - W'V$ 
10:  else
11:     $\mu = 2\mu$ 
12:  end if
13: end for

```

---

or a more complicated trust region update method

**Algorithm 12** LMF2

---

```

1:  $R = V - WH$ 
2: for  $i = 1 : iter$  do
3:    $[W^+, H^+] = \text{admm\_update}(W, H)$ 
4:    $R^+ = V - W^+ H^+$ 
5:    $dW = W^+ - W, dH = H^+ - H$ 
6:    $\Delta g = \frac{1}{2}[(dW, \nu dW - \nabla W) + (dH, \nu dH - \nabla H)]$ 
7:   if  $\Delta g < 0$  then
8:      $\nu = 4\nu$ 
9:   end if
10:   $\Delta f = \|R\|_F^2 - \|R^+\|_F^2$ 
11:  if  $\Delta f > 0$  then
12:     $W = W^+, H = H^+, R = R^+, \mu = \mu/2$ 
13:     $\nabla W = WHH' - VH', \nabla H = W'WH - W'V$ 
14:  else
15:     $\mu = 2\mu$ 
16:  end if
17: end for

```

---

**5.2 ADMM solving subproblem**

We introduce ADMM for solving the subproblem, since direct projection based solver will behave bad in numeric. Consider the following Augmented Lagrangian.

$$L(x, z, \alpha, \rho) = \frac{1}{2} \|J(z - u) - d\|^2 + \frac{\nu u}{2} \|x - u\|^2 + (\alpha, x - z) + \frac{\rho}{2} \|x - z\|^2$$

Here  $x = \text{vec}(W, H)$ , transforming the ensemble of  $W$  and  $H$  into a global vector,  $z = \text{vec}(W_{aux}, H_{aux})$  is the vectorized auxiliary variable,  $\alpha = \text{vec}(\alpha_W, \alpha_H)$  is vectorized multiplier.  $u = \text{vec}(W_0, H_0)$  is the starting point.

**Algorithm 13** LMF-ADMM

- 
- 1:  $\min z : u + (J'J + rho)^{-1}(J'd + \rho(x - u) + \alpha)$
  - 2:  $\min x : (\nu u + \rho z - \alpha)/(\nu + \rho)$
  - 3:  $x = \mathcal{P}(x)$
  - 4: update  $\alpha = \alpha + \mu(x - z)$
- 

However, this form is not computable, since we do not know the form of  $J$ . We first try to understand the mechanism of  $J, J', J'J$  at point  $W, H$

Notice that

$$\begin{aligned} J(\tilde{W}, \tilde{H}) &= W\tilde{H} + \tilde{W}H \\ J'(\tilde{V}) &= [\tilde{V}H', W'\tilde{V}] \\ (J'J)(\tilde{W}, \tilde{H}) &= [\tilde{W}HH' + W\tilde{H}H', W'\tilde{W}H + W'W\tilde{H}] \end{aligned}$$

Hence we can use the mapping  $[\tilde{W}, \tilde{H}] = (J'J)[\tilde{W}, \tilde{H}]$  and apply krylov subspace method to solve the problem.

## 6 Numerical Experiment (I): Synthesis Data

In this section we test aforementioned algorithms in the  $m = n = 100, r = 5$ , the initial is random given and we run 1000 iterations. We test the following case:

1. actually low rank:  $V_1$  is a non-negative low rank matrix, generated by  $rand(m, r) * rand(r, n)$
2. multiplicative noise:  $V_2 = V_1 * (1 + 0.01 * rand(100))$
3. additive noise :  $V_3 = V_1 + (0.01) * max(V_1) * rand(100)$
4. intermediate rank  $V_4 = rand(100, 10) * rand(10, 100)$
5. totally full rank  $V_5 = rand(100)$

The following algorithm will be tested: MU, MUmod, MUacc, ALS, HALS, HALSacc, ALSPGD, APBB, ANLSBPP, ANLSas, ANLSgroup, ADMM, AO-ADMM, and our LMF-ADMM. Here ANLS does not appear in this report, and the solver of subproblem is written by Jingu Kim.

Rank 5 result

	10	50	100	300	CPUTIME	
MU	1.82E+01	1.20E+01	4.74E+00	1.65E+00	0.11	
MUmod	1.86E+01	1.31E+01	6.94E+00	1.77E+00	0.30	
MUacc	2.31E+00	1.32E+00	7.68E-01	2.74E-01	1.44	
ALS	6.23E+00	1.50E+00	7.46E-01	1.52E-01	0.33	
HALS	1.05E+01	1.89E+00	1.38E+00	6.82E-01	0.30	
HALSacc	1.02E+01	2.13E+00	1.26E+00	3.41E-01	0.53	
APBB	2.81E+00	1.41E+00	7.96E-01	1.25E-01	6.19	
ALSPGD	2.55E+00	9.35E-01	6.03E-01	1.45E-01	0.58	
ANLSas	2.67E+00	1.02E+00	2.41E-01	9.08E-03	1.56	
ANLSgp	2.67E+00	1.02E+00	2.41E-01	9.08E-03	7.97	
ANLSbpp	2.67E+00	1.02E+00	2.41E-01	9.08E-03	1.00	
ADMM	1.99E+00	9.44E-01	7.75E-01	5.06E-02	0.22	
AO-ADMM	1.89E+00	9.22E-01	6.94E-01	5.60E-01	0.77	
LMF-ADMM	4.92E+00	1.08E+00	2.56E-01	2.49E-03	58.95	

2

	10	50	100	300	CPUTIME	
MU	11.73354	9.43582	6.46684	4.90432	0.18750	
MUmod	19.63202	13.88192	8.24987	3.82733	0.21875	
MUacc	4.63789	3.74934	3.59990	3.52362	1.28125	
ALS	4.96628	3.98324	3.71764	3.52806	0.35938	
HALS	7.04732	3.76370	3.61449	3.52758	0.29688	
HALSacc	5.59787	3.72378	3.61851	3.52389	0.42188	
APBB	4.35276	3.83743	3.66441	3.52452	5.82813	
ALSPGD	3.72733	3.52501	3.51194	3.50714	1.60938	
ANLSas	3.78897	3.55926	3.52209	3.50764	1.14063	
ANLSgp	3.78897	3.55926	3.52209	3.50764	7.42188	
ANLSbpp	3.78897	3.55926	3.52209	3.50764	1.12500	
ADMM	3.60405	3.58949	3.52744	3.50635	0.23438	
AO-ADMM	3.90334	3.59783	3.53715	3.50812	1.10938	
LMF-ADMM	5.05952	3.52288	3.50702	3.50629	52.53125	

3

	10	50	100	300	CPUTIME
MU	13.52824	8.02069	6.19232	4.38261	0.21875
MU <sub>mod</sub>	18.39742	12.46458	8.33057	3.76292	0.34375
MU <sub>acc</sub>	3.87478	1.48928	1.11853	0.96705	1.40625
ALS	NaN	NaN	NaN	NaN	f
HALS	3.47972	1.74977	1.63396	1.30570	0.32813
HALS <sub>acc</sub>	3.47727	1.74606	1.58582	1.25207	0.51563
APBB	2.70701	1.82558	1.60890	0.96966	6.37500
ALSPGD	2.15294	1.41451	1.01194	0.93130	1.40625
ANLS <sub>as</sub>	1.69059	0.96913	0.93201	0.92897	1.14063
ANLS <sub>gp</sub>	1.69059	0.96913	0.93201	0.92897	7.96875
ANLS <sub>bpp</sub>	1.69059	0.96913	0.93201	0.92897	0.85938
ADMM	1.40970	1.31235	1.35918	0.93221	0.21875
AO-ADMM	1.66494	1.02083	0.93671	0.92899	0.78125
LMF-ADMM	3.55281	0.93506	0.92922	0.92889	50.93750

4

	10	50	100	300	CPUTIME
MU	13.57983	9.57117	7.88564	5.40414	0.20313
MU <sub>mod</sub>	18.43720	14.24323	9.12457	1.97093	0.21875
MU <sub>acc</sub>	4.85143	1.21040	1.01626	0.95890	1.23438
ALS	4.08123	1.89589	1.86719	1.47343	0.23438
HALS	7.83307	1.66307	1.39283	1.01988	0.34375
HALS <sub>acc</sub>	7.62153	2.06372	1.52949	0.97912	0.43750
APBB	2.60248	1.60447	1.52344	1.11161	6.23438
ALSPGD	1.53281	0.97816	0.93703	0.92972	1.01563
ANLS <sub>as</sub>	1.74547	1.05425	0.97569	0.93301	1.45313
ANLS <sub>gp</sub>	1.74547	1.05425	0.97569	0.93301	7.57813
ANLS <sub>bpp</sub>	1.74547	1.05425	0.97569	0.93301	0.87500
ADMM	1.33932	1.02559	0.95570	0.92964	0.21875
AO-ADMM	2.00599	1.12812	0.99042	0.94364	0.98438
LMF-ADMM	3.35264	0.93401	0.93020	0.92893	56.48438

5

	10	50	100	300	CPUTIME
MU	27.19286	26.90420	26.86254	26.74390	0.21875
MU <sub>mod</sub>	27.88722	26.83411	26.56678	26.40138	0.31250
MU <sub>acc</sub>	26.79257	26.41016	26.37401	26.36624	1.15625
ALS	26.43794	26.40644	26.40803	26.42186	0.35938
HALS	26.59060	26.37620	26.36408	26.36200	0.28125
HALS <sub>acc</sub>	26.61683	26.38218	26.36590	26.36232	0.42188
APBB	26.45687	26.37201	26.36953	26.36495	6.31250
ALSPGD	26.44448	26.36726	26.36561	26.36330	1.93750
ANLS <sub>as</sub>	26.39062	26.36580	26.36292	26.36125	1.79688
ANLS <sub>gp</sub>	26.39062	26.36580	26.36292	26.36125	8.10938
ANLS <sub>bpp</sub>	26.39062	26.36580	26.36292	26.36125	1.15625
ADMM	26.37509	26.34614	26.35163	26.35347	0.42188
AO-ADMM	26.39926	26.36603	26.36315	26.36128	0.93750
LMF-ADMM	26.65626	26.46923	26.46770	26.46701	53.78125

1000 raknk 5

	10	50	100	300	CPUTIME
MU	196.78	161.34	81.09	17.78	18.67
MU <sub>mod</sub>	197.61	159.68	77.02	22.46	17.78
MU <sub>acc</sub>	23.69	4.97	2.52	0.90	29.33
ALS	47.72	30.63	8.05	0.71	18.36
HALS	131.97	24.24	23.58	22.11	16.78
HALS <sub>acc</sub>	112.31	24.58	22.61	7.67	17.64
APBB	23.26	17.19	15.42	1.27	50.92
ALSPGD	26.72	12.06	3.30	2.22	12.66
ANLS <sub>as</sub>	16.97	2.41	1.06	0.28	21.64
ANLS <sub>gp</sub>	27.85	12.22	2.61	0.38	102.27
ANLS <sub>bpp</sub>	24.41	10.53	2.51	0.44	22.02
ADMM	19.45	4.32	4.90	2.89	18.17
AO-ADMM	24.28	9.01	2.38	0.41	32.05
LMF-ADMM	31.84	1.58	0.37	0.05	211.63

	10	50	100	300	CPUTIME
MU	198.49	151.31	74.80	24.82	18.84
MUmod	198.40	157.87	71.48	24.54	20.20
MUacc	27.19	12.39	11.35	11.07	29.23
ALS	33.36	12.50	11.25	11.04	18.03
HALS	135.15	20.84	16.39	11.35	16.92
HALSacc	74.15	22.08	14.91	11.14	19.11
APBB	26.71	23.76	20.40	11.10	50.92
ALSPGD	28.41	20.70	11.65	11.07	19.56
ANLSas	29.68	20.59	16.80	11.04	22.63
ANLSgp	27.52	19.78	13.97	11.04	98.25
ANLSbpp	27.58	19.04	17.65	11.07	21.95
ADMM	21.61	11.87	12.03	11.51	17.95
AO-ADMM	26.57	19.03	12.59	11.04	28.13
LMF-ADMM	34.14	11.10	11.03	11.03	246.45

1000 rank 10

	10	50	100	300	CPUTIME
MU	325.47	258.97	236.80	184.70	18.63
MUmod	325.04	260.14	244.43	184.05	18.89
MUacc	182.82	177.82	177.63	177.54	31.23
ALS	186.42	178.40	178.13	177.84	20.52
HALS	234.62	191.31	179.44	177.89	16.86
HALSacc	201.10	178.53	177.80	177.59	19.66
APBB	202.02	179.42	178.73	177.57	54.25
ALSPGD	184.14	177.68	177.53	177.52	36.44
ANLSas	179.91	177.54	177.52	177.51	22.28
ANLSgp	180.40	177.57	177.53	177.51	97.50
ANLSbpp	181.41	177.67	177.61	177.57	19.83
ADMM	180.44	177.84	177.50	177.50	18.28
AO-ADMM	183.68	178.96	177.72	177.59	30.63
LMF-ADMM	186.29	180.38	178.41	177.64	206.25

1000 rand

	10	50	100	300	CPUTIME
MU	290.52	287.66	287.04	286.37	17.05
MU <sub>mod</sub>	290.45	287.62	287.00	286.37	17.86
MU <sub>acc</sub>	286.23	286.09	286.07	286.07	29.88
ALS	286.27	286.08	286.07	286.07	16.22
HALS	287.37	286.53	286.27	286.12	14.34
HALS <sub>acc</sub>	287.03	286.27	286.15	286.09	14.27
APBB	286.47	286.13	286.09	286.07	49.22
ALSPGD	286.33	286.09	286.08	286.08	9.86
ANLS <sub>as</sub>	286.21	286.09	286.07	286.07	20.73
ANLS <sub>gp</sub>	286.21	286.08	286.07	286.07	104.97
ANLS <sub>bpp</sub>	286.19	286.08	286.08	286.07	20.61
ADMM	286.22	286.08	286.07	286.07	16.61
AO-ADMM	286.35	286.09	286.07	286.07	26.75
LMF-ADMM	286.78	286.14	286.09	286.08	225.22

## 7 Numerical Experiment (II): ORL and YALE data

ORL  $r = 25$

	10	50	100	300	CPUTIME
MU	19440.65	15744.82	12926.04	10678.80	9.03
MU <sub>mod</sub>	19416.06	15847.19	13029.62	10643.24	8.73
MU <sub>acc</sub>	10580.54	10151.85	10093.71	10019.69	26.20
ALS	16430.72	17949.73	20445.01	15497.98	7.80
HALS	11498.96	10401.59	10192.43	10043.15	6.80
HALS <sub>acc</sub>	11129.77	10229.99	10114.94	10029.77	10.36
APBB	10742.71	10176.37	10083.67	10022.82	166.30
ALSPGD	10323.89	10080.27	10042.24	10003.47	91.63
ANLS <sub>as</sub>	10356.45	10103.21	10035.58	9990.92	31.11
ANLS <sub>gp</sub>	10325.57	10115.27	10062.05	10000.40	93.67
ANLS <sub>bpp</sub>	10314.33	10047.80	9999.50	9971.23	28.20
ADMM	9762.95	9753.69	9753.68	9753.72	9.02
AO-ADMM	10370.99	10102.02	10036.93	9983.37	22.52
LMF-ADMM	17030.63	11659.28	11389.58	11384.44	1057.09

orl rank = 5



	10	50	100	300	CPUTIME
MU	20085.40	17308.75	15413.77	14732.42	8.23
MU <sub>mod</sub>	20067.81	17406.64	15562.47	14787.19	6.98
MU <sub>acc</sub>	14960.11	14661.48	14647.24	14643.68	10.19
ALS	14955.29	15206.21	14928.43	14756.34	6.16
HALS	15583.35	14757.70	14691.18	14672.70	5.59
HALS <sub>acc</sub>	15888.10	14778.31	14682.50	14641.19	6.16
APBB	14881.16	14669.87	14647.22	14639.27	40.44
ALSPGD	14837.19	14756.62	14667.70	14638.19	29.34
ANLS <sub>as</sub>	14699.73	14655.41	14639.05	14634.60	9.98
ANLS <sub>sgp</sub>	14801.67	14649.31	14641.85	14632.81	55.14
ANLS <sub>sbpp</sub>	14774.92	14651.12	14639.58	14634.50	9.67
ADMM	14611.43	14611.36	14611.36	14611.37	6.55
AO-ADMM	14822.87	14667.14	14644.08	14634.95	12.64
LMF-ADMM	17450.14	14745.60	14702.23	14695.00	130.97

## References

- [1] Gillis N. Nonnegative matrix factorization: Complexity, algorithms and applications[J]. Unpublished doctoral dissertation, Universit catholique de Louvain. Louvain-La-Neuve: CORE, 2011.
- [2] Lee D D, Seung H S. Algorithms for non-negative matrix factorization[C]//Advances in neural information processing systems. 2001: 556-562.
- [3] Lin C J. On the convergence of multiplicative update algorithms for nonnegative matrix factorization[J]. IEEE Transactions on Neural Networks, 2007, 18(6): 1589-1596.
- [4] N. Gillis and F. Glineur, "Accelerated Multiplicative Updates and hierarchical ALS Algorithms for Nonnegative Matrix Factorization"
- [5] Gonzalez E F, Zhang Y. Accelerating the Lee-Seung algorithm for nonnegative matrix factorization[R]. 2005.
- [6] Lin C J. Projected gradient methods for nonnegative matrix factorization[J]. Neural computation, 2007, 19(10): 2756-2779.
- [7] Han, Lixing Neumann, Michael Prasad, Upendra. (2010). Alternating projected Barzilai-Borwein methods for Nonnegative Matrix Factorization. Electronic transactions on numerical analysis ETNA. 36. 54-82.
- [8] Cichocki A, Phan A H. Fast local algorithms for large scale nonnegative matrix and tensor factorizations[J]. IEICE transactions on fundamentals of electronics, communications and computer sciences, 2009, 92(3): 708-721.
- [9] Song D, Meyer D A, Min M R. Fast nonnegative matrix factorization with rank-one admm[C]//NIPS 2014 Workshop on Optimization for Machine Learning (OPT2014). 2014.
- [10] Huang K, Sidiropoulos N D, Liavas A P. A flexible and efficient algorithmic framework for constrained matrix and tensor factorization[J]. IEEE Transactions on Signal Processing, 2016, 64(19): 5052-5065.