

Redesigning Yield Map Plots for Comprehension and Usability

2023 SDSS

Alison Kleffner

Department of Statistics, University of Nebraska - Lincoln

✉ akleffner@huskers.unl.edu

🏠 <https://alison-kleffner.netlify.app/>

🐙 [alisonkleffner](#)

Slides: https://alisonkleffner.github.io/presentations/SDSS_2023/index.html#1

Outline

📊 Data Intensive Farm Management

📖 Perceptual Issues with Current Maps

📋 Redesign Process

🔮 Future Work

Data Intensive Farm Management

Background

- With a projected increase in future crop demand, researchers are conducting studies on crop input application to increase yield, focusing on sustainability (Tilman, Balzer, Hill, and Befort, 2011)
- Crop Input Example: Nitrogen Fertilizer
 - Nitrogen is an essential component of food production as allows plants to photosynthesize efficiently (Maheswari, Murthy, and Shanker, 2017)
 - Nearly half of the nitrogen fertilizer supplied to the field is not used by the crops (Billen, Garnier, and Lassaletta, 2013)
 - This excess nitrogen can be harmful
- Hence, research needs to be conducted on determining input rates that increase crop yield, and are also more sustainable.



Data Intensive Farm Management (DIFM)

Problem: Address inefficient application of crop inputs to farm fields worldwide

Methods: On-Farm Precision Experimentation

- Conduct experiments using site-specific inputs
- GPS-reliant technology

Goals

- Develop infrastructure to develop and analyze these experiments
- Find economically optimal application rate to increase profit while reducing environmental impacts.


Project Website



Trial Design

Step 1: Develop infrastructure to develop experiments using site-specific inputs


Trial Design Tool



Output: shape files that can be put into a farmer's tractor that allows them to carry out the experiments

Data Collection

Step 2: Conduct experiments and collect data



Examples of Data Collected:

- As-applied
- Yield
- Location of measurements

Explain the Results

Step 3: Explain the optimal management decisions, accounting for various factors

How: create a user interface, designed around explaining machine learning output to non-experts


- Build trust in models
- Learn how crop yield responds to different input application rates, field characteristics, and weather to hopefully increase profits.

One way to do this: Visually explore the relationship between input application and yield through a graph

- Show the spatial correlations between the application/treatment and yield in a way that is understandable to farmers and consultants.
- Develop perceptually optimal plots that communicate this relationship.

Current Maps




Yield Maps Currently Used by DIFM




Examples of two versions of this plot currently given to farmers/crop consultants in DIFM reports

Other Maps in the Literature

Plenty of other iterations of trial design/yield maps used in the literature. Here's some examples



Juxtaposed vs Superimposed Graphs




- **Juxtaposed graphs:** side by side (Gleicher, Albers, Walker, Jusufi, Hansen, and Roberts, 2011)
 - Benefits: less issues with visual clutter and easier to create
 - Drawbacks: comparative burden is placed on the user
- **Superimposed graphs:** multiple objects in same coordinate system (Gleicher, Albers, Walker, et al., 2011)
 - Benefits: Easier to compare as users can use perception rather than memory
 - Drawbacks: clutter
 - Useful when spatial location is a key component of the comparison (Wang, Haleem, Shi, Wu, Zhao, Fu, and Qu, 2018)

Data Clutter with Superimposed Graphs

Drawback: clutter


- General principle of graphical design: show data clearly (Cleveland, 1984; Gordon and Finch, 2015)
- Overlap - multiple dots on top of one another
 - Obscures true number of dots, harder to find patterns
 - Visual cues, like color, becomes partially obstructed, thereby reducing search efficiency (Bravo and Farid, 2004a; Bravo and Farid, 2004b)
 - Can overburden human perception, causing errors in performing tasks (Huang, Eades, and Hong, 2009)



Comparative Burden with Superimposed

Drawback: Most of the comparative burden placed on users' memory

- A mental image is relied on for comparison in these scenarios, as the user moves their eyes between images (shifting focus).
 - The plot contents may not be accurately formed in working memory, leading to potential errors when deriving patterns (Vanderplas, Cook, and Hofmann, 2020; LYi, Jo, and Seo, 2021)
- Lack of visual cues for locations



Color


- Red-green color blindness is experienced by approximately 8% of men and 0.5% of women of Northern European ancestry.
 - Difficult to discriminate between these colors (Wong, 2011)
- Stop-Light Color Scheme
 - Yellow has a highlighting effect
 - Univariate Scale more appropriate (magnitude only)
- Same Color scheme for multiple variables
 - May cause confusion
- Rainbow Color Scheme
 - No inherent ordering of magnitude (Light and Bartlein, 2004)
 - Extremes are visually close (red and violet) (Silva, Sousa Santos, and Madeira, 2011)

Number of Categories

Number of categorical scales should be limited to **5-7 categories** (Miller, 1956)

- Due to working memory limits (Macdonald, 1999)
 - Harder for the user to distinguish between colors and remember the meaning of colors.
- The load on the user's working memory leads to an increase in the time it takes for the user to comprehend the plot (Huang, Eades, and Hong, 2009)


Yield (bu/ac)



Next: Redesign Process

Redesign

Redesign: Color Blending Part 1



Focus: Superimpose the treatment and yield plots, while reducing the clutter


- Use of transparency to show both at same time
- Interactive plot with *leaflet* (Cheng, Karambelkar, and Xie, 2022)
 - Can add and remove trial plot layer

Work that still needs to be done:


- Color needs some work
 - different color schemes

Redesign: Color Blending Part 2


Focus: Color/Scales



Targeted
Nitrogen Rate
(lbs)





Yield (bu/ac)



- Working on blending using transparency
- Categorical Groups for both variables
 - Trial Design treatment is a factor
 - Reduce number of colors for yield
 - Use quantiles to determine categories for yield (Brewer and Pickle, 2002)

Redesign: Bivariate Color Plot

Alternative to color blending



- **Benefit:** relationship between the variables is most important (Elmer, 2013)
- Recommendation: 3x3 scale (Leonowicz, 2003)
 - ■ Quantiles (Biesecker, Zahnd, Brandt, Adams, and J.M, 2020)
- **Focus:** diagonal
 - Diagonal: grayscale color scheme.
 - Upper left and lower right: complementary color scheme (Strode, Morgan, Thornton, Mesev, Rau, Shortes, and Johnson, 2020)
- **Drawback:** Lose more detailed information


Redesign: Correlation

Directly encode correlations between As Applied treatments and Yield

Benefit: Direct statement of correlation while maintaining some spatial orientation


- Explicit Encoding Layout (Gleicher, Albers, Walker, et al., 2011)
 - Bivariate color scale
 - Maintain some spatial information.
- Correlations may be impacted by field location

Drawback: complicated to connect the displayed relationship back to the data (Gleicher, Albers, Walker, et al., 2011)



Redesign: Correlation with Scatterplot

Add some context back



- A standard practice to overcome weakness of decontextualization is utilizing a hybrid comparative layout (LYi et al., 2021).
 - Juxtaposed scatterplot to the correlation plot (combining the layouts of juxtaposition and explicit encoding).
- Interactivity connects the juxtaposed plots, where hovering over a trial plot in the correlation map highlights the corresponding points in the scatterplot used in the correlation calculation.

[Link](#)

Future Work

Conclusion/Future Work

Next Step: Obtain Feedback from those using the plots (farmers, crop consultants)

- Eventually do some testing between the layouts to see which farmers are reading more accurately.

Eventually: Develop a R Shiny app to explaining machine learning output to non-experts

- Build trust in the model predictions without requiring farmers to learn the details of statistical modeling.
- Will utilize these plots, among others
 - For example, accuracy of as applied treatment compared to trial design

References

- Biesecker, C., W. Zahnd, H. M. Brandt, et al. (2020). “A Bivariate Mapping Tutorial for Cancer Control Resource Allocation Decisions and Interventions”. In: *Preventing chronic disease* 17 (E01). DOI: 10.5888/pcd17.190254.
- Billen, G., J. Garnier, and L. Lassaletta (2013). “The nitrogen cascade from agricultural soils to the sea: modelling nitrogen transfers at regional watershed and global scales”. In: *Philosophical Transactions of the Royal Society B: Biological Sciences* 368.1621, p. 20130123. DOI: 10.1098/rstb.2013.0123.
- Bravo, M. and H. Farid (2004a). “Recognizing and segmenting objects in clutter”. In: *Vision Research* 44.4, pp. 385–396.
- (2004b). “Search for a category target in clutter”. In: *Perception* 33.5, pp. 643–652.
- Brewer, C. A. and L. Pickle (2002). “Evaluation of Methods for Classifying Epidemiological Data on Choropleth Maps in Series”. In: *Annals of the Association of American Geographers* 92.4, pp. 662–681.
- Cheng, J., B. Karambelkar, and Y. Xie (2022). *leaflet: Create Interactive Web Maps with the JavaScript 'Leaflet' Library*. R package version 2.1.1. URL: <https://CRAN.R-project.org/package=leaflet>.
- Cleveland, W. S. and R. McGill (1984). “Graphical Perception: Theory, Experimentation, and Application to the Development of Graphical Methods”. In: *Journal of the American Statistical Association* 79.387, pp. 531–554.
- Elmer, M. E. (2013). “Symbol considerations for bivariate thematic maps”. In: *Proceedings of 26th International Cartographic Conference*.
- Gleicher, M., D. Albers, R. Walker, et al. (2011). “Visual Comparison for Information Visualization”. In: *Information Visualization* 10.4, pp. 289–309.
- Gordon, I. and S. Finch (2015). “Statistician Heal Thyself: Have We Lost the Plot?” In: *Journal of Computational and Graphical Statistics* 24.4, pp. 1210–1229. DOI: 10.1080/10618600.2014.989324.
- Huang, W., P. Eades, and S. Hong (2009). “Measuring Effectiveness of Graph Visualizations: A Cognitive Load Perspective”. In: *Information Visualization* 8.3, pp. 139–152.
- Leonowicz, A. (2003). “RESEARCH ON TWO-VARIABLE CHOROPLETH MAPS AS A METHOD FOR PORTRAYING GEOGRAPHICAL RELATIONSHIPS”. In: *Proceedings of the 21st International Cartographic Conference*. The International Cartographic Association.
- Light, A. and P. Bartlein (2004). “The End of the Rainbow? Color Schemes for Improved Data Graphics”. In: *Eos, Transactions American Geophysical Union* 85.40, pp. 385–391. DOI: 10.1029/2004EO400002.
- LYi, S., J. Jo, and J. Seo (2021). “Comparative Layouts Revisited: Design Space, Guidelines, and Future Directions”. In: *IEEE Transactions on Visualization and Computer Graphics* 27.2, pp. 1525–1535.
- Macdonald, L. (1999). “Using color effectively in computer graphics”. In: *Computer Graphics and Applications, IEEE* 19, pp. 20–35. DOI: 10.1109/38.773961.
- Maheswari, M., A. Murthy, and A. Shanker (2017). “12 - Nitrogen Nutrition in Crops and Its Importance in Crop Quality”. In: *The Indian Nitrogen Assessment*. Ed. by Y. P. Abrol, T. K. Adhya, V. P. Aneja, N. Raghuram, H. Pathak, U. Kulshrestha, C. Sharma and B. Singh. Elsevier, pp. 175–186. DOI: <https://doi.org/10.1016/B978-0-12-811836-8.00012-4>.
- Maxwell, B., P. Hegedus, P. Davis, et al. (2018). “Can Optimization Associated with On-Farm Experimentation Using Site-Specific Technologies Improve Producer Management Decisions?” In: *14th International Conference on Precision Agriculture*.

References

- Miller, G. A. (1956). "The magical number seven plus or minus two: some limits on our capacity for processing information." In: *Psychological review* 63 (2), pp. 81–97.
- Peerlinck, A., J. W. Sheppard, and B. D. Maxwell (2018). "Using Deep Learning in Yield and Protein Prediction of Winter Wheat Based on Fertilization Prescriptions in Precision Agriculture". In: *14th International Conference on Precision Agriculture*.
- Searcy, S. W. (1997). "Precision Farming: A New Approach to Crop Management, Texas Agricultural Extension Service". In: *The Texas A&M University System, College Station, TX, USA*.
- Silva, S., B. Sousa Santos, and J. Madeira (2011). "Using color in visualization: A survey". In: *Computers & Graphics* 35.2, pp. 320–333. DOI: <https://doi.org/10.1016/j.cag.2010.11.015>.
- Strode, G., J. Morgan, B. Thornton, et al. (2020). "Operationalizing Trumbo's Principles of Bivariate Choropleth Map Design". In: *Cartographic Perspectives* 94, pp. 5–24. DOI: [10.14714/CP94.1538](https://doi.org/10.14714/CP94.1538).
- Tilman, D., C. Balzer, J. Hill, et al. (2011). "Global food demand and the sustainable intensification of agriculture". In: *Proceedings of the National Academy of Sciences* 108.50, pp. 20260–20264. DOI: [10.1073/pnas.1116437108](https://doi.org/10.1073/pnas.1116437108).
- Trevisan, R., D. Bullock, and N. Martin (2021). "Spatial Variability of Crop Responses to Agronomic Inputs in On-Farm Precision Experimentation". In: *Precision Agriculture* 22.2, pp. 342–363. DOI: [10.1007/s11119-020-09720-8](https://doi.org/10.1007/s11119-020-09720-8).
- Vanderplas, S., D. Cook, and H. Hofmann (2020). "Testing Statistical Charts: What Makes a Good Graph?" In: *Annual Review of Statistics and Its Application* 7.1, pp. 61–88.
- Wang, Y., H. Haleem, C. Shi, et al. (2018). "Towards Easy Comparison of Local Businesses Using Online Reviews". In: *Computer Graphics Forum* 37.
- Wong, B. (2011). "Color blindness". In: *nature methods* 8.6, p. 441.

Questions?

✉ akleffner@huskers.unl.edu

🔄 [alisonkleffner](#)