

**PREPRINT August 7, 2013**

## **LSSC**

Yohann Salaun<sup>1</sup> & Marc Lebrun<sup>2</sup>

<sup>1</sup> Polytechnique, France ([yohann.salaun@polytechnique.org](mailto:yohann.salaun@polytechnique.org))

<sup>2</sup> CMLA, ENS Cachan, France ([marc.lebrun@cmla.ens-cachan.fr](mailto:marc.lebrun@cmla.ens-cachan.fr))

### **Abstract**

## **1 Overview**

## **2 Theoretical Description**

### **2.1 Notations**

In order to keep coherence with [3], the notations used are the same. A picture of  $n$  pixels is seen as a column vector in  $\mathbb{R}^n$ . The noisy picture is noted  $\mathbf{y}$  and the denoised one  $\mathbf{x}$ . The  $i$ -th pixel of  $\mathbf{x}$  is noted  $\mathbf{x}[i]$  and the patch centered in  $\mathbf{x}[i]$  and of size  $m$  is noted  $\mathbf{x}_i$ .

### **2.2 Learned Sparse Coding**

The idea behind this method is to assume that the denoised picture is a signal that can be approximated by a sparse linear combinations of elements from a basis set. The basis set is called a dictionary  $\mathbf{D} \in \mathbb{R}^{m \times k}$  and is composed of  $k$  elements. The denoised patches are then computed from  $\mathbf{D}$  with:

$$\min_{\boldsymbol{\alpha} \in \mathbb{R}^k} \|\boldsymbol{\alpha}\|_p \quad s.t. \quad \|\mathbf{y}_i - \mathbf{D}\boldsymbol{\alpha}\|_2^2 \leq \epsilon \quad (1)$$

$\mathbf{D}\boldsymbol{\alpha}$  is the estimate of the denoised patch and  $\|\boldsymbol{\alpha}\|_p$  is a regularization term that impose sparsity for  $\boldsymbol{\alpha}$ .

$p$  is usually 0 or 1. Eq. 1 becomes NP-hard to solve when  $p = 0$  and a greedy algorithm such as Orthogonal Matching Pursuit [5] can give an approximation. With  $p = 1$ , the problem is convex and solved efficiently with the LARS algorithm [6]. Experimental observations [7] have shown that the learning part is better with  $p = 1$  and the recomposition part with  $p = 0$ .

$\epsilon$  can be chosen according to the value of the estimated standard deviation of the noise.

## 2.3 Simultaneous Sparse Coding

# 3 Algorithm Description

## 3.1 Algorithm Overview

The first part consists in initializing a dictionary that will denoise roughly the picture.

Once the picture is denoised a first time, a clustering is made in order to regroup similar patches for further treatment.

Then, iteratively for each clusters, the dictionary is updated using simultaneous sparse coding and the cluster is denoised.

## 3.2 Dictionnary Initialization

The initial dictionnary is first learned offline on the 10 000 images of the PASCAL VOC'07 database using the online dictionary learning procedure of [2]. This procedure is then used on the noisy picture in order to improve the dictionary efficiency.

In fact, only a fixed number  $T$  of patches in the picture are used to update the dictionary. However they are chosen so that they are independently and identically distributed in the picture.

The algorithm corresponds then to the minimization of eq.1 on the  $T$  patches with the  $l_1$  norm using the LARS [6] algorithm.

**Input** : number of iterations  $T$ , i.i.d. sampling of  $T$  patches of the noisy picture  $\mathbf{Y}_T$ , initial dictionary  $\mathbf{D}^0 \in \mathbb{R}^{m \times k}$ , regularization parameter  $\lambda$

**Output** : learned dictionary  $\mathbf{D}$

**Initialization** :  $\mathbf{A}^0 \in \mathbb{R}^{k \times k} \leftarrow 0$ ,  $\mathbf{B}^0 \in \mathbb{R}^{m \times k} \leftarrow 0$

**for**  $t = 1..T$  **do**

$\mathbf{y}_t = \mathbf{Y}_T[t]$

    Sparse coding: compute with LARS algorithm:

$$\boldsymbol{\alpha}^t = \operatorname{argmin}_{\boldsymbol{\alpha} \in \mathbb{R}^k} \|\boldsymbol{\alpha}\|_1 \text{ s.t. } \|\mathbf{y} - \mathbf{D}^{t-1} \boldsymbol{\alpha}\|_2^2 \leq \lambda$$

$$\mathbf{A}^t \leftarrow \mathbf{A}^{t-1} + \boldsymbol{\alpha}^t \boldsymbol{\alpha}^{tT}$$

$$\mathbf{B}^t \leftarrow \mathbf{B}^{t-1} + \mathbf{y}^t \boldsymbol{\alpha}^{tT}$$

    Update dictionary from  $\mathbf{D}^{t-1}$  to  $\mathbf{D}^t$  so that:

$$\mathbf{D}^t = \operatorname{argmin}_{\mathbf{D} \in \mathbb{R}^{m \times k}} \frac{1}{t} \sum_{i=1}^t \left( \frac{1}{2} \|\mathbf{y}^i - \mathbf{D} \boldsymbol{\alpha}^i\|_2^2 + \lambda \|\boldsymbol{\alpha}^i\|_1 \right)$$

**end**

**return**  $\mathbf{D}^T$

#### Algorithm 1: Online Dictionary Learning

**Input** :input dictionary  $\mathbf{D} = [\mathbf{d}^1, \dots, \mathbf{d}^k] \in \mathbb{R}^{m \times k}$ ,

$\mathbf{A} = [\mathbf{a}^1, \dots, \mathbf{a}^k] \in \mathbb{R}^{k \times k}$ ,  $\mathbf{B} = [\mathbf{b}^1, \dots, \mathbf{b}^k] \in \mathbb{R}^{m \times k}$

**Output** : updated dictionary  $\mathbf{D}$

**repeat**

**for**  $j = 1..k$  **do**

        update the  $j^{th}$  column:

**if**  $\mathbf{A}(j,j) = 0$  **then**

$$\mathbf{d}^j \leftarrow 0$$

**end**

**else**

$$\mathbf{u}^j \leftarrow \frac{1}{\mathbf{A}(j,j)} (\mathbf{b}^j - \mathbf{D} \mathbf{a}^j) + \mathbf{d}^j$$

$$\mathbf{d}^j \leftarrow \frac{1}{\max(\|\mathbf{u}^j\|_2, 1)} \mathbf{u}^j$$

**end**

**end**

**until** *convergence* ;

**return**  $\mathbf{D}$

#### Algorithm 2: Dictionary Update



**Input** : Gram matrix of the dictionary  $G = \mathbf{D}^T \mathbf{D} \in \mathbb{R}^{k \times k}$  where  $\mathbf{D} = [\mathbf{d}^1, \dots, \mathbf{d}^k] \in \mathbb{R}^{m \times k}$ ,  
noisy patch  $\mathbf{y}$ , constraint  $\lambda$

**Output** : sparse vector  $\boldsymbol{\alpha} \in \mathbb{R}^k$

—INITIALIZATION—

normX  $\in \mathbb{R} \leftarrow \|\mathbf{y}\|_2^2$   
coeffs  $\in \mathbb{R}^k \leftarrow \mathbf{0}$   
*Most correlated element*  
 $\hat{\mathbf{c}} \in \mathbb{R}^k \leftarrow \mathbf{D}^T \mathbf{y}$   
 $C \in \mathbb{R}^+ \leftarrow \max_{j=1..m} (|\hat{\mathbf{c}}_j|)$   
currentInd  $\leftarrow j$  s.t.  $\hat{\mathbf{c}}_j = C$   
**if** normX  $> \lambda$  **then**  
| **return**  $\mathbf{0}$   
**end**  
newAtom  $\leftarrow \mathbf{True}$   
**for**  $i = 1..k$  **do**  
| —NEW ATOM—  
| **if** newAtom **then**  
| |  $\mathcal{A}[i] \leftarrow \text{currentInd}$   
| |  $G_A[i^{th} \text{ line}] \leftarrow G[\mathcal{A}[i]^{th} \text{ line}]$   
| |  $G_S \leftarrow \mathbf{D}_{\mathcal{A}}^T \mathbf{D}_{\mathcal{A}}$   
| | UPDATE  $G_S^{-1}$   
| **end**  
| —VARIABLES UPDATES—  
|  $\mathbf{u} \leftarrow G_S^{-1}(\text{sgn}(\hat{\mathbf{c}}_j))_{j \in \mathcal{A}}$   
| ratio  $\leftarrow \left( -\frac{\text{coeffs}[j]}{u_j} \right)_{j \in [1;i]}$   
| stepMAX  $\leftarrow \min^+(\text{ratio})$  ( $\min^+$  means its the minimum between positive values)  
| criticalInd  $\leftarrow j$  s.t. ratio[j] = stepMAX  
|  $C \leftarrow \hat{\mathbf{c}}[0]$   
|  $\gamma \leftarrow \min^+ \left( \frac{C \pm \hat{\mathbf{c}}_j}{1 \pm (G_A u)[j]} \right)_{j \notin \mathcal{A}}$   
| —POLYNOMIAL RESOLUTION—  
|  $a \leftarrow \sum_{j \in \mathcal{A}} \text{sgn}(\hat{\mathbf{c}}[\mathcal{A}[j]]) u[j]$   
|  $b \leftarrow \sum_{j \in \mathcal{A}} \hat{\mathbf{c}}[\mathcal{A}[j]] u[j]$   
|  $c \leftarrow \text{normX} - \lambda$   
|  $\Delta \leftarrow b^2 - ac$   
| stepMAX2  $\leftarrow \min(\frac{b - \sqrt{\Delta}}{a}, C)$   
| —FINAL STEP & BREAK—  
|  $\gamma \leftarrow \min(\gamma, \text{stepMAX}, \text{stepMAX2})$   
| coeffs  $\leftarrow \text{coeffs} + \gamma \mathbf{u}$   
|  $\hat{\mathbf{c}} \leftarrow \hat{\mathbf{c}} - \gamma G_A \mathbf{u}$   
| normX  $\leftarrow \text{normX} + a\gamma^2 - 2b\gamma$   
| **if**  $|\gamma| < 1e^{-15} \parallel \gamma = \text{stepMAX2} \parallel \text{normX} < 1e^{-15} \parallel \text{normX} - \lambda < 1e^{-15}$  **then**  
| | **break**  
| **end**  
| **if**  $\gamma = \text{stepMAX}$  **then**  
| | DOWNDATA  $G_S^{-1}$   
| | newAtom  $\leftarrow \mathbf{False}$   
| |  $i \leftarrow i-2$   
| **end**  
| **else**  
| | newAtom  $\leftarrow \mathbf{True}$   
| **end**  
**end**

**return**  $\boldsymbol{\alpha} = \text{sort}(\text{coeffs}, \mathcal{A})$  (sorted coefficient with respect to the increasing order of  $\mathcal{A}$  indexes and filled with 0 if necessary)

**Algorithm 3:** LARS algorithm - Mairal Version

**Input** : Gram matrix  $G_S \in \mathbb{R}^{i \times i}$ , and its former inverse to update  $G_S^{-1} \in \mathbb{R}^{i-1 \times i-1}$

**Output** : updated  $G_S^{-1} \in \mathbb{R}^{i \times i}$

**if**  $i = 1$  **then**

**return**  $\frac{1}{G_S}$

**end**

$u \leftarrow G_S^{-1} G_S[i^{th} \text{ line}]$

$\sigma \leftarrow \frac{1}{G_S(i,i) - u \cdot G_S[i^{th} \text{ line}]}$

$G_S^{-1}(i, i) \leftarrow \sigma$

$G_S^{-1}[i^{th} \text{ line}] \leftarrow -\sigma u$

**return**  $G_S^{-1} \leftarrow G_S^{-1} + \sigma u u^T$

**Algorithm 4:** Update invert algorithm

**Input** : pseudo-Gram matrix  $G_A \in \mathbb{R}^{i \times i}$  Gram matrix  $G_S \in \mathbb{R}^{i \times i}$ , and its inverse  $G_S^{-1} \in \mathbb{R}^{i \times i}$ , active indexes list  $\mathcal{A} \in \mathbb{R}^i$ , sparse coefficient list coeffs  $\in \mathbb{R}^k$ , criticalInd  $\in [1; k]$ , current iteration  $i$

**Output** : downdated matrices  $G_S, G_S^{-1}, G_A \in \mathbb{R}^{i-1 \times i-1}$ , downdated lists  $\mathcal{A} \in \mathbb{R}^{i-1}$ , coeffs  $\in \mathbb{R}^k$

$\sigma \leftarrow \frac{1}{G_S^{-1}(\text{criticalInd}, \text{criticalInd})}$

$u \leftarrow G_S^{-1}[\text{criticalInd}^{th} \text{ line}]$  without its criticalInd<sup>th</sup> coefficient

**for**  $j = \text{criticalInd} : i$  **do**

$G_A[j^{th} \text{ line}] \leftarrow G_A[(j+1)^{th} \text{ line}]$

**for**  $k = 1 : \text{criticalInd} - 1$  **do**

$G_S(j, k) \leftarrow G_S(j+1, k)$

$G_S^{-1}(j, k) \leftarrow G_S^{-1}(j+1, k)$

**end**

**for**  $k = \text{criticalInd} : i$  **do**

$G_S(j, k) \leftarrow G_S(j+1, k+1)$

$G_S^{-1}(j, k) \leftarrow G_S^{-1}(j+1, k+1)$

**end**

$\mathcal{A}[j] \leftarrow \mathcal{A}[j+1]$

    coeffs[j]  $\leftarrow$  coeffs[j+1]

**end**

coeffs[i]  $\leftarrow$  0

$G_S^{-1} \leftarrow G_S^{-1} - \sigma u u^T$

**Algorithm 5:** Downdate invert algorithm

## Glossary

## Image Credits



© IPOL (there's no need to credit this image, here is used as an example.)

## 4 References

### References

- [1] B. Efron, T. Hastie, I. Johnstone, and R. Tibshirani *Least angle regression*. Ann. Statist., 32(2):407-499, 2004.

- [2] J. Mairal, F. Bach, J. Ponce, and G. Sapiro *Online dictionary learning for sparse coding*. ICML, 2009.
- [3] J. Mairal, F. Bach, J. Ponce, G. Sapiro and A. Zisserman *Non-local Sparse Models for Image Restoration*. International Conference on Computer Vision, 2009.
- [4] J. Mairal *Représentations parcimonieuses en apprentissage statistique, traitement d'image et vision par ordinateur*. PhD thesis, 2010.
- [5] S. Mallat and Z. Zhang *Matching pursuit in a timefrequency dictionary*. IEEE T. SP, 41(12):3397-3415, 1993.
- [6] B. Efron, T. Hastie, I. Johnstone, and R. Tibshirani *Least angle regression*. Ann. Statist., 32(2):407-499, 2004.
- [7] M. Elad and M. Aharon *Image denoising via sparse and redundant representations over learned dictionaries*. IEEE T. IP, 54(12):3736-3745, 2006.