

Cooler Service Company Inc.

P.O. Box 581928 Tulsa, OK 74158-1928
Phone (918) 834-0002 Fax (918) 834-0128

AIR COOLED EXCHANGER

SPECIFICATION SHEET

CSCI

Date: 10/16/2014
Prop/Job #: 41914 Rev 1

Customer: Compressor Systems Inc
Reference: Hess - Hawkeye (CAT G3612 3550HP @ 1000RPM)
Model: H156-3-60 Forced Location:
CSC Contact: Jason Herrel
Qty per Spec Sheet: 3

TUBE SIDE PERFORMANCE

Service	EJW	TAW/CLO	IC-1	IC-2	IC-3	AC
Fluid	50% E.Gly	50% E.Gly	Nat. Gas	Nat. Gas	Nat. Gas	Nat. Gas
GPM/MMSCFD	575.0	500.0	16.3	15.9	13.0	13.4
SG (Gas MW)	1.02	1.02	0.872 (25.29)	0.874 (25.34)	0.873 (25.33)	0.874 (25.34)
Temperature In	190.	149.8	253.	227.	257.	271.
Temperature Out	179.26	130.	120.	120.	120.	120.
Pressure In-psia	35.	35.	115.	240.	584.	1,427.
Pressure Drop	9.16	6.95	1.93	2.43	2.57	6.07
Duty-1000 BTU/HR	2,654.0	4,139.3	3,050.0	2,516.0	2,958.0	4,103.0
MTD	47.62	22.48	51.69	43.04	47.32	50.59
Overall Rate	3.3	6.8	2.5	2.9	3.3	4.2
Fouling Factor	0.0005	0.0005	0.002	0.002	0.002	0.002
External Surface (Bare), ft^2	17038(915)	26939(1371)	23590(1270)	20396(1035)	18785(1006)	19303(904)
Sections-Qty	1	1	1	1	1	1
No. passes	2	2	1	1	2	2
Crossflow	YES	YES	YES	YES	YES	YES
No. rows	6	4	4	5	5	5
Design Temp.	300	300	350	350	350	350
Design Press.	150	150	215	645	645	1650
Test Pres.	195	195	280	839	839	2145
Nozzles (In/Out)	1-6."/1-6."-150#RF	1-6."/1-6."-150#RF-10."/1-10."-150#RF	1-8."/1-8."-300#RF	1-6."/1-6."-300#RF	1-6."/1-6."-900#RF	
Tubes, OD	1.5	1.25	1.5	1.25	1.5	1
Wall	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW MW
Material	SA-214	SA-214	SA-179	SA-179	SA-179	SA-179
Qty/Section	39	70	54	53	43	58
Length-ft	60					
Fins	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum
Turbulators						
Header Type	Plug Box					
Material	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N
Corrosion	0.125	0.125	0.125	0.125	0.125	0.125
ASME stamp	Yes	Yes	Yes	Yes	Yes	Yes
Plug Type	SHLD	SHLD	SHLD	SHLD	SHLD	SHLD

AIR SIDE PERFORMANCE

Air Side	Ambient	100	Elevation	2350
Temp-in	100			
Total SCFM	476,468			
Temp-out	138			

MECHANICAL EQUIPMENT

Mechanical Equipment	No. Fans/Motors/Drives	3
Fan dia.	13	Motor Siemens or Equal Reducer
Blades	8	Type 460/3/60 IEEE-841
RPM	242	Speed 1750
HP/Fan	26.6	HP 40 Min. Shaft Diameter, in. 2.4375

Notes:

Coil Volumes: EJW=185 gal. TAW/CLO=217 gal. IC-1=273 gal. IC-2=175 gal. IC-3=204 gal. AC=107 gal.
Header Volumes: EJW=12.1 gal. TAW/CLO=16.5 gal. IC-1=19.8 gal. IC-2=20.9 gal. IC-3=12.1 gal. AC=11 gal.

Estimated Plot size Length, ft.: 62.5 Width, ft.: 15.8 Height, ft.: 18.2 Weight: 103620

Cooler Service Company Inc.

P.O. Box 581928 Tulsa, OK 74158-1928
Phone (918) 834-0002 Fax (918) 834-0128

AIR COOLED EXCHANGER

SPECIFICATION SHEET

CSCI

Date: 10/16/2014
Prop/Job #: 41914 Rev 1

Customer: Compressor Systems Inc
Reference: Hess - Hawkeye (CAT G3612 3550HP @ 1000RPM)
Model: H156-3-60 Forced Location:
CSC Contact: Jason Herrel
Qty per Spec Sheet: 3

TUBE SIDE PERFORMANCE

Service	EJW	TAW/CLO	IC-1	IC-2	IC-3	AC
Fluid	50% E.Gly	50% E.Gly	Nat. Gas	Nat. Gas	Nat. Gas	Nat. Gas
GPM/MMSCFD	575.0	500.0	16.3	15.9	13.0	13.4
SG (Gas MW)	1.02	1.02	0.872 (25.29)	0.874 (25.34)	0.873 (25.33)	0.874 (25.34)
Temperature In	190.	149.8	253.	227.	257.	271.
Temperature Out	179.26	130.	120.	120.	120.	120.
Pressure In-psia	35.	35.	115.	240.	584.	1,427.
Pressure Drop	9.16	6.95	1.93	2.43	2.57	6.07
Duty-1000 BTU/HR	2,654.0	4,139.3	3,050.0	2,516.0	2,958.0	4,103.0
MTD	47.62	22.48	51.69	43.04	47.32	50.59
Overall Rate	3.3	6.8	2.5	2.9	3.3	4.2
Fouling Factor	0.0005	0.0005	0.002	0.002	0.002	0.002
External Surface (Bare), ft^2	17038(915)	26939(1371)	23590(1270)	20396(1035)	18785(1006)	19303(904)
Sections-Qty	1	1	1	1	1	1
No. passes	2	2	1	1	2	2
Crossflow	YES	YES	YES	YES	YES	YES
No. rows	6	4	4	5	5	5
Design Temp.	300	300	350	350	350	350
Design Press.	150	150	215	645	645	1650
Test Pres.	195	195	280	839	839	2145
Nozzles (In/Out)	1-6."/1-6."-150#RF	1-6."/1-6."-150#RF-10."/1-10."-150#RF	1-8."/1-8."-300#RF	1-6."/1-6."-300#RF	1-6."/1-6."-900#RF	
Tubes, OD	1.5	1.25	1.5	1.25	1.5	1
Wall	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW MW
Material	SA-214	SA-214	SA-179	SA-179	SA-179	SA-179
Qty/Section	39	70	54	53	43	58
Length-ft	60					
Fins	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum
Turbulators						
Header Type	Plug Box					
Material	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N
Corrosion	0.125	0.125	0.125	0.125	0.125	0.125
ASME stamp	Yes	Yes	Yes	Yes	Yes	Yes
Plug Type	SHLD	SHLD	SHLD	SHLD	SHLD	SHLD

AIR SIDE PERFORMANCE

Air Side	Ambient	100	Elevation	2350
Temp-in	100			
Total SCFM	476,468			
Temp-out	138			

MECHANICAL EQUIPMENT

Mechanical Equipment	No. Fans/Motors/Drives	3
Fan dia.	13	Motor Siemens or Equal Reducer
Blades	8	Type 460/3/60 IEEE-841
RPM	242	Speed 1750
HP/Fan	26.6	HP 40
		Min. Shaft Diameter, in.
		2.4375

Notes:

Coil Volumes: EJW=185 gal. TAW/CLO=217 gal. IC-1=273 gal. IC-2=175 gal. IC-3=204 gal. AC=107 gal.
Header Volumes: EJW=12.1 gal. TAW/CLO=16.5 gal. IC-1=19.8 gal. IC-2=20.9 gal. IC-3=12.1 gal. AC=11 gal.

Estimated Plot size Length, ft.: 62.5 Width, ft.: 15.8 Height, ft.: 18.2 Weight: 103620

Cooler Service Company Inc.

P.O. Box 581928 Tulsa, OK 74158-1928
Phone (918) 834-0002 Fax (918) 834-0128

AIR COOLED EXCHANGER

SPECIFICATION SHEET

CSCI

Date: 10/16/2014
Prop/Job #: 41914 Rev 1

Customer: Compressor Systems Inc
Reference: Hess - Hawkeye (CAT G3612 3550HP @ 1000RPM)
Model: H156-3-60 Forced Location:
CSC Contact: Jason Herrel
Qty per Spec Sheet: 3

TUBE SIDE PERFORMANCE

Service	EJW	TAW/CLO	IC-1	IC-2	IC-3	AC
Fluid	50% E.Gly	50% E.Gly	Nat. Gas	Nat. Gas	Nat. Gas	Nat. Gas
GPM/MMSCFD	575.0	500.0	16.3	15.9	13.0	13.4
SG (Gas MW)	1.02	1.02	0.872 (25.29)	0.874 (25.34)	0.873 (25.33)	0.874 (25.34)
Temperature In	190.	149.8	253.	227.	257.	271.
Temperature Out	179.26	130.	120.	120.	120.	120.
Pressure In-psia	35.	35.	115.	240.	584.	1,427.
Pressure Drop	9.16	6.95	1.93	2.43	2.57	6.07
Duty-1000 BTU/HR	2,654.0	4,139.3	3,050.0	2,516.0	2,958.0	4,103.0
MTD	47.62	22.48	51.69	43.04	47.32	50.59
Overall Rate	3.3	6.8	2.5	2.9	3.3	4.2
Fouling Factor	0.0005	0.0005	0.002	0.002	0.002	0.002
External Surface (Bare), ft^2	17038(915)	26939(1371)	23590(1270)	20396(1035)	18785(1006)	19303(904)
Sections-Qty	1	1	1	1	1	1
No. passes	2	2	1	1	2	2
Crossflow	YES	YES	YES	YES	YES	YES
No. rows	6	4	4	5	5	5
Design Temp.	300	300	350	350	350	350
Design Press.	150	150	215	645	645	1650
Test Pres.	195	195	280	839	839	2145
Nozzles (In/Out)	1-6."/1-6."-150#RF	1-6."/1-6."-150#RF-10."/1-10."-150#RF	1-8."/1-8."-300#RF	1-6."/1-6."-300#RF	1-6."/1-6."-900#RF	
Tubes, OD	1.5	1.25	1.5	1.25	1.5	1
Wall	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW MW
Material	SA-214	SA-214	SA-179	SA-179	SA-179	SA-179
Qty/Section	39	70	54	53	43	58
Length-ft	60					
Fins	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum
Turbulators						
Header Type	Plug Box					
Material	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N
Corrosion	0.125	0.125	0.125	0.125	0.125	0.125
ASME stamp	Yes	Yes	Yes	Yes	Yes	Yes Yes
Plug Type	SHLD	SHLD	SHLD	SHLD	SHLD	SHLD

AIR SIDE PERFORMANCE

Air Side	Ambient	100	Elevation	2350
Temp-in	100			
Total SCFM	476,468			
Temp-out	138			

MECHANICAL EQUIPMENT

Mechanical Equipment	No. Fans/Motors/Drives	3
Fan dia.	13	Motor Siemens or Equal Reducer HTD
Blades	8	Type 460/3/60 IEEE-841
RPM	242	Speed 1750
HP/Fan	26.6	HP 40 Min. Shaft Diameter, in. 2.4375

Notes:

Coil Volumes: EJW=185 gal. TAW/CLO=217 gal. IC-1=273 gal. IC-2=175 gal. IC-3=204 gal. AC=107 gal.
Header Volumes: EJW=12.1 gal. TAW/CLO=16.5 gal. IC-1=19.8 gal. IC-2=20.9 gal. IC-3=12.1 gal. AC=11 gal.

Estimated Plot size Length, ft.: 62.5 Width, ft.: 15.8 Height, ft.: 18.2 Weight: 103620

Cooler Service Company Inc.

P.O. Box 581928 Tulsa, OK 74158-1928
Phone (918) 834-0002 Fax (918) 834-0128

AIR COOLED EXCHANGER

SPECIFICATION SHEET

CSCI

Date: 10/16/2014
Prop/Job #: 42014

Customer: Compressor Systems inc
Reference: Hess - Hawkeye (CAT G3606 1775HP @ 1000RPM)
Model: H156-2-44 Forced Location:
CSC Contact: Jason Herrel
Qty per Spec Sheet: 2

TUBE SIDE PERFORMANCE

Service	EJW	TAW/CLO	IC-1	IC-2	IC-3	AC
Fluid	50% E.Gly	50% E.Gly	Nat. Gas	Nat. Gas	Nat. Gas	Nat. Gas
GPM/MMSCFD	340.0	280.0	8.3	8.3	8.0	7.0
SG (Gas MW)	1.02	1.02	0.872 (25.29)	0.872 (25.29)	0.874 (25.34)	0.874 (25.33)
Temperature In	190.	147.96	210.	224.	238.	291.
Temperature Out	181.06	130.	120.	120.	120.	120.
Pressure In-psia	35.	35.	78.	164.	378.	1,427.
Pressure Drop	5.5	8.08	1.28	3.73	3.91	3.23
Duty-1000 BTU/HR	1,305.8	2,101.6	1,050.1	1,270.6	1,561.0	2,433.5
MTD	66.91	25.	42.18	42.22	47.43	61.16
Overall Rate	2.3	5.6	2.0	2.5	3.1	4.3
Fouling Factor	0.0005	0.0005	0.002	0.002	0.002	0.002
External Surface (Bare), ft^2	8329(448)	15132(712)	12174(653)	12174(650)	10724(544)	9274(435)
Sections-Qty	1	1	1	1	1	1
No. passes	2	2	1	2	2	2
Crossflow	YES	YES	YES	YES	YES	YES
No. rows	4	4	4	5	4	3
Design Temp.	300	300	350	350	350	350
Design Press.	150	150	215	645	645	1650
Test Pres.	195	195	280	839	839	2145
Nozzles (In/Out)	1-6."/1-6."-150#RF	1-6."/1-6."-150#RF	1-8."/1-8."-150#RF	1-6."/1-6."-300#RF	1-6."/1-6."-300#RF	1-4."/1-4."-900#RF
Tubes, OD	1.5	1	1.5	1.5	1.25	1
Wall	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW
Material	SA-214	SA-214	SA-179	SA-179	SA-179	SA-179
Qty/Section	26	62	38	38	38	38
Length-ft	44					
Fins	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum
Turbulators						
Header Type	Plug Box					
Material	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N
Corrosion	0.125	0.125	0.125	0.125	0.125	0.125
ASME stamp	Yes	Yes	Yes	Yes	Yes	Yes
Plug Type	SHLD	SHLD	SHLD	SHLD	SHLD	SHLD

AIR SIDE PERFORMANCE

Air Side	Ambient	100	Elevation	2350
Temp-in	100			
Total SCFM	332,377			
Temp-out	127			

MECHANICAL EQUIPMENT

Mechanical Equipment	No. Fans/Motors/Drives	2
Fan dia.	13	Motor Siemens or Equal
Blades	6	Type 460/3/60 IEEE-841
RPM	271	Speed 1750
HP/Fan	27.7	HP 40
		Min. Shaft Diameter, in.
		2.4375

Notes:

Coil Volumes: EJW=93 gal. TAW/CLO=87 gal. IC-1=143 gal. IC-2=135 gal. IC-3=90 gal. AC=52 gal.

Header Volumes: EJW=7.7 gal. TAW/CLO=12.1 gal. IC-1=18.7 IC-2=11 IC-3=8.8 gal. AC=5.5 gal.

Estimated Plot size Length, ft.: 46 Width, ft.: 13.8 Height, ft.: 14.7 Weight: 55110

Cooler Service Company Inc.

P.O. Box 581928 Tulsa, OK 74158-1928
Phone (918) 834-0002 Fax (918) 834-0128

AIR COOLED EXCHANGER

SPECIFICATION SHEET

CSCI

Date: 10/16/2014
Prop/Job #: 42014

Customer: Compressor Systems inc
Reference: Hess - Hawkeye (CAT G3606 1775HP @ 1000RPM)
Model: H156-2-44 Forced Location:
CSC Contact: Jason Herrel
Qty per Spec Sheet: 2

TUBE SIDE PERFORMANCE

Service	EJW	TAW/CLO	IC-1	IC-2	IC-3	AC
Fluid	50% E.Gly	50% E.Gly	Nat. Gas	Nat. Gas	Nat. Gas	Nat. Gas
GPM/MMSCFD	340.0	280.0	8.3	8.3	8.0	7.0
SG (Gas MW)	1.02	1.02	0.872 (25.29)	0.872 (25.29)	0.874 (25.34)	0.874 (25.33)
Temperature In	190.	147.96	210.	224.	238.	291.
Temperature Out	181.06	130.	120.	120.	120.	120.
Pressure In-psia	35.	35.	78.	164.	378.	1,427.
Pressure Drop	5.5	8.08	1.28	3.73	3.91	3.23
Duty-1000 BTU/HR	1,305.8	2,101.6	1,050.1	1,270.6	1,561.0	2,433.5
MTD	66.91	25.	42.18	42.22	47.43	61.16
Overall Rate	2.3	5.6	2.0	2.5	3.1	4.3
Fouling Factor	0.0005	0.0005	0.002	0.002	0.002	0.002
External Surface (Bare), ft^2	8329(448)	15132(712)	12174(653)	12174(650)	10724(544)	9274(435)
Sections-Qty	1	1	1	1	1	1
No. passes	2	2	1	2	2	2
Crossflow	YES	YES	YES	YES	YES	YES
No. rows	4	4	4	5	4	3
Design Temp.	300	300	350	350	350	350
Design Press.	150	150	215	645	645	1650
Test Pres.	195	195	280	839	839	2145
Nozzles (In/Out)	1-6."/1-6."-150#RF	1-6."/1-6."-150#RF	1-8."/1-8."-150#RF	1-6."/1-6."-300#RF	1-6."/1-6."-300#RF	1-4."/1-4."-900#RF
Tubes, OD	1.5	1	1.5	1.5	1.25	1
Wall	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW MW
Material	SA-214	SA-214	SA-179	SA-179	SA-179	SA-179
Qty/Section	26	62	38	38	38	38
Length-ft	44					
Fins	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum
Turbulators						
Header Type	Plug Box					
Material	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N
Corrosion	0.125	0.125	0.125	0.125	0.125	0.125
ASME stamp	Yes	Yes	Yes	Yes	Yes	Yes
Plug Type	SHLD	SHLD	SHLD	SHLD	SHLD	SHLD

AIR SIDE PERFORMANCE

Air Side	Ambient	100	Elevation	2350
Temp-in	100			
Total SCFM	332,377			
Temp-out	127			

MECHANICAL EQUIPMENT

Mechanical Equipment	No. Fans/Motors/Drives	2
Fan dia.	13	Motor Siemens or Equal Reducer
Blades	6	Type 460/3/60 IEEE-841
RPM	271	Speed 1750
HP/Fan	27.7	HP 40 Min. Shaft Diameter, in. 2.4375

Notes:

Coil Volumes: EJW=93 gal. TAW/CLO=87 gal. IC-1=143 gal. IC-2=135 gal. IC-3=90 gal. AC=52 gal.

Header Volumes: EJW=7.7 gal. TAW/CLO=12.1 gal. IC-1=18.7 IC-2=11 IC-3=8.8 gal. AC=5.5 gal.

Estimated Plot size Length, ft.: 46 Width, ft.: 13.8 Height, ft.: 14.7 Weight: 55110

Cooler Service Company Inc.

P.O. Box 581928 Tulsa, OK 74158-1928
Phone (918) 834-0002 Fax (918) 834-0128

AIR COOLED EXCHANGER

SPECIFICATION SHEET

CSCI

Date: 10/16/2014
Prop/Job #: 42014

Customer: Compressor Systems inc
Reference: Hess - Hawkeye (CAT G3606 1775HP @ 1000RPM)
Model: H156-2-44 Forced Location:
CSC Contact: Jason Herrel
Qty per Spec Sheet: 2

TUBE SIDE PERFORMANCE

Service	EJW	TAW/CLO	IC-1	IC-2	IC-3	AC
Fluid	50% E.Gly	50% E.Gly	Nat. Gas	Nat. Gas	Nat. Gas	Nat. Gas
GPM/MMSCFD	340.0	280.0	8.3	8.3	8.0	7.0
SG (Gas MW)	1.02	1.02	0.872 (25.29)	0.872 (25.29)	0.874 (25.34)	0.874 (25.33)
Temperature In	190.	147.96	210.	224.	238.	291.
Temperature Out	181.06	130.	120.	120.	120.	120.
Pressure In-psia	35.	35.	78.	164.	378.	1,427.
Pressure Drop	5.5	8.08	1.28	3.73	3.91	3.23
Duty-1000 BTU/HR	1,305.8	2,101.6	1,050.1	1,270.6	1,561.0	2,433.5
MTD	66.91	25.	42.18	42.22	47.43	61.16
Overall Rate	2.3	5.6	2.0	2.5	3.1	4.3
Fouling Factor	0.0005	0.0005	0.002	0.002	0.002	0.002
External Surface (Bare), ft^2	8329(448)	15132(712)	12174(653)	12174(650)	10724(544)	9274(435)
Sections-Qty	1	1	1	1	1	1
No. passes	2	2	1	2	2	2
Crossflow	YES	YES	YES	YES	YES	YES
No. rows	4	4	4	5	4	3
Design Temp.	300	300	350	350	350	350
Design Press.	150	150	215	645	645	1650
Test Pres.	195	195	280	839	839	2145
Nozzles (In/Out)	1-6."/1-6."-150#RF	1-6."/1-6."-150#RF	1-8."/1-8."-150#RF	1-6."/1-6."-300#RF	1-6."/1-6."-300#RF	1-4."/1-4."-900#RF
Tubes, OD	1.5	1	1.5	1.5	1.25	1
Wall	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW	0.109 MW
Material	SA-214	SA-214	SA-179	SA-179	SA-179	SA-179
Qty/Section	26	62	38	38	38	38
Length-ft	44					
Fins	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum	L-Tension wrapped Aluminum
Turbulators						
Header Type	Plug Box					
Material	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N	SA-516 70N
Corrosion	0.125	0.125	0.125	0.125	0.125	0.125
ASME stamp	Yes	Yes	Yes	Yes	Yes	Yes
Plug Type	SHLD	SHLD	SHLD	SHLD	SHLD	SHLD

AIR SIDE PERFORMANCE

Air Side	Ambient	100	Elevation	2350
Temp-in	100			
Total SCFM	332,377			
Temp-out	127			

MECHANICAL EQUIPMENT

Mechanical Equipment	No. Fans/Motors/Drives	2
Fan dia.	13	Motor Siemens or Equal
Blades	6	Type 460/3/60 IEEE-841
RPM	271	Speed 1750
HP/Fan	27.7	HP 40
		Min. Shaft Diameter, in.
		2.4375

Notes:

Coil Volumes: EJW=93 gal. TAW/CLO=87 gal. IC-1=143 gal. IC-2=135 gal. IC-3=90 gal. AC=52 gal.

Header Volumes: EJW=7.7 gal. TAW/CLO=12.1 gal. IC-1=18.7 IC-2=11 IC-3=8.8 gal. AC=5.5 gal.

Estimated Plot size Length, ft.: 46 Width, ft.: 13.8 Height, ft.: 14.7 Weight: 55110