

**NAME**

**sc\_pinger** — scamper driver to run ping with different probe methods on a list of addresses.

**SYNOPSIS**

```
sc_pinger [-?D] [-a infile] [-c probe-count] [-l limit] [-m method]  
          [-M move-dir] [-o outfile] [-p port] [-R unix-remote] [-t logfile]  
          [-U unix-socket]
```

**DESCRIPTION**

The **sc\_pinger** utility provides the ability to connect to a running *scamper*(1) instance and run ping on a set of IPv4 and IPv6 addresses. For each address in the file, **sc\_pinger** will try ICMP, UDP, and TCP-ack probe methods to solicit responses from the address. **sc\_pinger** will not try all methods if one method obtains responses. The output of **sc\_pinger** is written to a *warts*(5) file, which can then be processed to extract details of responses. The options are as follows:

- ? prints a list of command line options and a synopsis of each.
- D causes **sc\_pinger** to detach and become a daemon.
- a *infile*  
specifies the name of the input file which consists of a sequence of IPv4 and IPv6 addresses, one per line.
- c *probe-count*  
specifies the number of probes to send for each method. **sc\_pinger** accepts two formats: a single integer that specifies the number of probes (and responses) desired; or, two integers, separated by /, that specify the number of responses desired and maximum number of probes to send. By default, **sc\_pinger** seeks three responses from up to five probes.
- l *limit*  
specifies the number of objects to write to an output file, before closing it and opening the next file. The output file must contain a %u format specifier, which **sc\_pinger** uses to embed a counter value that increments with each new output file. If the user uses the move option, **sc\_pinger** moves the file when it closes the file.
- m *method*  
specifies a single probe method to try. The available probe methods are the same as *scamper*'s ping implementation, listed in *scamper*(1) manual page. By default, **sc\_pinger** uses ICMP-echo, UDP-dport, and TCP-ack-sport to destination port 80.
- M *move-dir*  
specifies the name of the directory to move completed files to. By default, **sc\_pinger** leaves completed files in place.
- o *outfile*  
specifies the name of the output file to be written. The output file will use the *warts*(5) format.
- p *port*  
specifies the port on the local host where *scamper*(1) is accepting control socket connections.
- R *unix-remote*  
specifies the name of a unix domain socket on the local host where a remote *scamper*(1) instance is accepting commands.
- t *logfile*  
specifies the name of a file to log output from **sc\_pinger** generated at run time.

**-U** *unix-local*

specifies the name of a unix domain socket on the local host where a local `scamper(1)` instance is accepting commands.

## EXAMPLES

Given a set of IPv4 and IPv6 address sets in a file named `infile.txt`:

```
192.0.2.1
192.0.32.10
192.0.31.60
2001:db8::1
```

and a `scamper(1)` daemon listening on port 31337, then these addresses can be probed using

```
sc_pinger -a infile.txt -o outfile.warts -p 31337
```

To send 4 probes, and stop after receiving two responses:

```
sc_pinger -a infile.txt -o outfile.warts -p 31337 -c 2/4
```

To use ICMP-echo and TCP-syn probes to destination port 443

```
sc_pinger -a infile.txt -o outfile.warts -p 31337 -m icmp-echo -m
'tcp-syn -d 443'
```

The following command writes a series of gzip-compressed `warts(5)` files, each of which have up to 1000 objects in them, with names such as `outfile_0000.warts.gz`, `outfile_0001.warts.gz`, moving them to the finished directory:

```
sc_pinger -a infile.txt -o outfile_%04u.warts.gz -p 31337 -l 1000 -m
finished
```

A user can concatenate these files into a final bzip2-compressed `warts(5)` file with `sc_wartscat(1)`:

```
sc_wartscat -o outfile_final.warts.bz2 outfile_0000.warts.gz
outfile_0001.warts.gz
```

## SEE ALSO

`scamper(1)`, `sc_wartscat(1)`, `sc_wartsdump(1)`, `sc_warts2json(1)`, `sc_warts2text(1)`

## AUTHORS

**sc\_pinger** was written by Matthew Luckie <mjl@luckie.org.nz>.