

Module 04 — Structural Patterns I: Wrappers

Contents

1	Learning outcomes	2
2	Motivation	2
3	Adapter	2
3.1	Problem	2
3.2	Intent	2
3.3	Structure	3
3.4	Classic Java	3
3.5	Modern Java 27	4
3.6	Real-world usage	5
3.7	Pitfalls and when NOT to use it	5
3.8	Related patterns	6
4	Decorator	6
4.1	Problem	6
4.2	Intent	6
4.3	Structure	6
4.4	Classic Java	6
4.5	Modern Java 27	7
4.6	Stacking order matters	8
4.7	Real-world usage	9
4.8	Pitfalls and when NOT to use it	10
4.9	Related patterns	10
5	Proxy	10
5.1	Problem	10
5.2	Intent	10
5.3	Structure	11
5.4	Classic Java	11
5.5	Modern Java 27	12
5.6	Real-world usage	15
5.7	Pitfalls and when NOT to use it	15
5.8	Related patterns	15
6	Adapter vs. Decorator vs. Proxy	15
7	Summary	16
8	Quiz	16
9	Assignments	17
10	Further reading	17

Week 5 · Prerequisites: m01 (composition over inheritance, DIP), m03 (injected `Clock`, composition root), m00 (records, sealed types, lambdas) · Estimated study time: 5 h

Run every example without a
 build: `java modules/m04-structural-wrappers/src/main/java/io/github/aliturgutbozkurt/patterns/m04/examples/<path>/<Demo>.java`
 (JDK 27)

1 Learning outcomes

By the end of this module you can:

1. **Implement** an object adapter and a class adapter for a legacy API, **explain** why the object adapter is usually preferred, and **write** an adapter as a lambda when the target is a functional interface.
2. **Implement** Decorator in its classic form (abstract decorator base) and its modern form (records, Function composition), and **predict** how the order of stacked decorators changes the result.
3. **Read and build** `java.io` decorator chains and **write** a custom `FilterInputStream`.
4. **Implement** virtual, protection and caching proxies, and a dynamic proxy with `java.lang.reflect.Proxy` that handles default methods and exceptions correctly.
5. **Distinguish** Adapter, Decorator and Proxy by intent, and **decide** when a wrapper is the wrong tool.

2 Motivation

m02 and m03 were about *creating* objects. Structural patterns are about *combining* them. This module covers the three that look identical in a class diagram — one object wraps another and forwards calls to it — but exist for different reasons:

- **Adapter** *changes* an interface, so code written against one interface can use an object that has another.
- **Decorator** *adds* behaviour and keeps the interface, so features can be stacked like layers.
- **Proxy** *controls access* to an object and keeps the interface: it creates it late, checks permissions, caches answers — or does all of that generically at run time.

Learn to ask "*why* is this object wrapped?" and you will recognise all three in the JDK, in frameworks and in your own code.

3 Adapter


3.1 Problem

Our smart-home code reads temperatures through a `CelsiusThermometer`. The sensor driver we bought only has `double readFahrenheit()`, and we cannot change it. In the online shop, a legacy payment SDK takes the amount as a decimal *string* and answers with numeric status codes (0, 51, 54, ...), while our checkout works with amounts in minor units (kuruş, cents) and a `PaymentResult` type. Rewriting either side is not an option.

3.2 Intent

Convert the interface of a class into another interface clients expect, so classes with incompatible interfaces can work together.

3.3 Structure



The **target** is the interface the client wants, the **adaptee** is the class that does the work, the **adapter** implements the target and translates each call into the adaptee's language.

3.4 Classic Java

An **object adapter** holds the adaptee and delegates to it:

```

// file: adapter/thermometer/FahrenheitAdapter.java
public final class FahrenheitAdapter implements CelsiusThermometer {

    private final FahrenheitSensor sensor;           // the adaptee, held by
    composition

    public FahrenheitAdapter(FahrenheitSensor sensor) {
        this.sensor = Objects.requireNonNull(sensor, "sensor");
    }

    @Override
    public double readCelsius() {
        return toCelsius(sensor.readFahrenheit()); // translate the call and
    the unit
    }
}
  
```

A **class adapter** *inherits* from the adaptee instead and implements the target. Java has single inheritance, so this works only when the adaptee is a class you may extend and the target is an interface:

```

// file: adapter/payment/LegacyPaymentClassAdapter.java
public class LegacyPaymentClassAdapter extends LegacyPaymentGateway implements
PaymentProcessor {

    @Override
    public PaymentResult pay(PaymentRequest request) {
        String amount = LegacyPaymentMapping.toLegacyAmount(request.amountMinor());
        int status = makePayment(request.cardNumber(), amount, request.currency()); //
    }
}
  
```

```

inherited, not delegated
    return LegacyPaymentMapping.toResult(status, lastTransactionId());
}
}

```

The price: a class adapter is a `LegacyPayGateway`, so every legacy method leaks to its clients. A test in `PaymentAdapterTest` casts it and calls `makePayment(..., "-5.00", ...)` directly — bypassing the validation the adapter was written to add. Prefer the object adapter: it can adapt any subclass of the adaptee, it can be swapped in tests, and it exposes only the target interface.

3.5 Modern Java 27

A **lambda is an adapter** when the target is a functional interface — no class needed:

```

// file: adapter/thermometer/ThermometerAdapterDemo.java
FahrenheitSensor sensor = new FahrenheitSensor(212.0, 32.0, -40.0);
CelsiusThermometer lambda = () ->
FahrenheitAdapter.toCelsius(sensor.readFahrenheit());

```

```

adapter class: 100.0 °C, 0.0 °C, -40.0 °C
lambda adapter: 100.0 °C, 0.0 °C, -40.0 °C

```

A **record is an object adapter** with a free constructor, `equals` and `toString`:

```

// file: adapter/payment/LegacyPaymentAdapter.java
public record LegacyPaymentAdapter(LegacyPayGateway gateway) implements PaymentProcessor
{
    public LegacyPaymentAdapter {
        Objects.requireNonNull(gateway, "gateway");
    }

    @Override
    public PaymentResult pay(PaymentRequest request) {
        String amount = LegacyPaymentMapping.toLegacyAmount(request.amountMinor()); //
        validates first
        int status = gateway.makePayment(request.cardNumber(), amount,
        request.currency());
        return LegacyPaymentMapping.toResult(status, gateway.lastTransactionId());
    }
}

```

The real work of an adapter is often the *translation of values*. Legacy status codes become a **sealed** result, so that from here on the compiler checks that every outcome is handled:

```

// file: adapter/payment/LegacyPaymentMapping.java
static PaymentResult toResult(int status, String transactionId) {
    return switch (status) {
        case LegacyPayGateway.OK -> new Approved(transactionId);
        case LegacyPayGateway.INSUFFICIENT_FUNDS ->
            new Declined(DeclineReason.INSUFFICIENT_FUNDS, "insufficient
            funds");
        case LegacyPayGateway.CARD_EXPIRED -> new
            Declined(DeclineReason.CARD_EXPIRED, "card expired");
        default -> new Declined(DeclineReason.UNKNOWN, "legacy status " + status);
    }
}

```

```
};
}
```

An `int` has no end, so that `switch` needs a default. The client's `switch` over the sealed `PaymentResult` does not — record patterns take it apart and the switch is exhaustive:

```
// file: adapter/payment/PaymentAdapterDemo.java
String outcome = switch (processor.pay(order)) {
exhaustive: no default needed
    case Approved(String transactionId) -> "approved, transaction " +
transactionId;
    case Declined(DeclineReason reason, String message) -> "declined (" +
reason + "): " + message;
};
```

```
object adapter (record LegacyPaymentAdapter)
  12.50 TRY on card ending 1111: approved, transaction TX-1001
  7.00 TRY on card ending 0051: declined (INSUFFICIENT_FUNDS): insufficient funds
  99.90 EUR on card ending 0054: declined (CARD_EXPIRED): card expired
  1.00 USD on card ending 0096: declined (UNKNOWN): legacy status 96
class adapter (LegacyPaymentClassAdapter extends LegacyPayGateway)
  12.50 TRY on card ending 1111: approved, transaction TX-1001
  7.00 TRY on card ending 0051: declined (INSUFFICIENT_FUNDS): insufficient funds
  99.90 EUR on card ending 0054: declined (CARD_EXPIRED): card expired
  1.00 USD on card ending 0096: declined (UNKNOWN): legacy status 96
rejected before the gateway: amount must be positive: 0
```

3.6 Real-world usage

The JDK is full of adapters (`adapter/jdk/JdkAdaptersDemo.java`): `InputStreamReader` adapts a byte stream to a character stream, `Arrays.asList` adapts an array to the `List` interface (a fixed-size *view*, not a copy), `Enumeration.asIterator()` and `Collections.enumeration(...)` bridge the legacy and the modern iteration interfaces.

```
InputStreamReader: 14 bytes -> 7 chars: çğİİöşü
Arrays.asList: set(1) wrote through -> array is [1A, taken, 1C]
Arrays.asList: add -> UnsupportedOperationException (fixed-size view)
Enumeration.asIterator: alpha, beta, gamma
```

Beyond the JDK: SLF4J bridges adapt one logging API to another, Spring's `HandlerAdapter` lets one dispatcher call very different controller types, and "Ports and Adapters" (m11) scales the idea up to whole architectures.

3.7 Pitfalls and when NOT to use it

- An adapter that grows business rules is no longer an adapter — keep it a thin translation layer.
- Translations lose information: an unknown legacy code must not silently become "approved". Map it to an explicit `UNKNOWN` case and test it.
- If you own both sides, change one of them instead of adapting.
- A record adapter's accessor (`gateway()`) exposes the adaptee; that is fine for tests, but clients should depend on the target interface only.

3.8 Related patterns

Decorator keeps the interface, Adapter changes it. **Facade** (m05) also wraps, but it *simplifies* a whole subsystem behind a new interface. **Bridge** (m05) separates abstraction and implementation *by design*; Adapter repairs a mismatch *after the fact*.

4 Decorator


4.1 Problem

A coffee shop sells espresso and house blend, with milk, syrup and extra shots in any combination and quantity. One subclass per combination (`EspressoWithMilkAndTwoShots`) explodes. The same happens with cross-cutting concerns: a stock service needs logging in one place, retries in another, both in a third – without changing the service.

4.2 Intent

Attach additional responsibilities to an object dynamically. Decorators provide a flexible alternative to subclassing for extending functionality.

4.3 Structure



A decorator **is a Beverage** (so it can be used, and wrapped, wherever a beverage is expected) and **has a Beverage** (the one it decorates).

4.4 Classic Java

The abstract decorator holds the wrapped component:

```
// file: coffee/classic/CondimentDecorator.java
public abstract class CondimentDecorator implements Beverage {

    protected final Beverage beverage; // the wrapped component

    protected CondimentDecorator(Beverage beverage) {
```

```

        this.beverage = Objects.requireNonNull(beverage, "beverage");
    }
}

```

Each concrete decorator delegates and then adds its part:

```

// file: coffee/classic/Milk.java
@Override
public String description() {
    return beverage.description() + ", Milk";           // delegate, then add
}

@Override
public long priceInKurus() {
    return beverage.priceInKurus() + 500;
}

```

```

// file: coffee/classic/CoffeeDemo.java
print(new Espresso());
print(new Syrup(new Milk(new Espresso())));           // innermost
first: Espresso, Milk, Syrup
print(new Milk(new ExtraShot(new ExtraShot(new HouseBlend()))));

```

```

Espresso: 45.00 TL
Espresso, Milk, Syrup: 57.50 TL
House Blend, Extra Shot, Extra Shot, Milk: 75.00 TL

```

4.5 Modern Java 27

Records as decorators. The wrapped component becomes a record component, there is no abstract base, and the compact constructor rejects `null`:

```

// file: coffee/modern/Milk.java
public record Milk(Beverage inner) implements Beverage {

    public Milk {
        Objects.requireNonNull(inner, "inner");
    }

    @Override
    public String description() {
        return inner.description() + ", Milk";
    }
}

```

Records also bring value equality and a `toString` that shows the wrapping structure:

```

Espresso: 45.00 TL
Espresso, Milk, Syrup: 57.50 TL
House Blend, Extra Shot, Extra Shot, Milk: 75.00 TL
same order twice is equal: true
Syrup[inner=Milk[inner=ESPRESSO]]

```

Functional decoration. When the "component" is a single function, decorators need no classes at all: `Function.andThen` and `compose` stack behaviour. The comment-moderation pipeline is built once from small `UnaryOperator<String>` filters and reused for every comment:

```
// file: decorator/functional/CommentPipeline.java
/** A new pipeline that runs this one and then {@code filter}; this pipeline is
unchanged. */
public CommentPipeline then(UnaryOperator<String> filter) {
    return new CommentPipeline(steps.andThen(Objects.requireNonNull(filter,
"filter"))));
}
```

```
// file: decorator/functional/FunctionalDecoratorDemo.java
Function<String, String> censorThenTruncate =
censor(banned).andThen(truncate(10));
Function<String, String> truncateThenCensor =
truncate(10).andThen(censor(banned));
```

```
before: [ This darn product is GREAT, darn it! ]
after: [This **** product is GREAT, **]
censor, then truncate(10): [this is **]
truncate(10), then censor: [this is da]
```

Truncating first cut the banned word in half, so the censor no longer recognised it.

4.6 Stacking order matters

Cross-cutting decorators for a warehouse `StockService`: one logs each call, one retries failures immediately (no back-off — that is out of scope). When all attempts fail, the last exception is rethrown with the earlier ones attached as *suppressed*, so nothing is lost:

```
// file: decorator/resilience/RetryingStockService.java
@Override
public int available(String sku) {
    List<RuntimeException> failures = new ArrayList<>();
    for (int attempt = 1; attempt <= maxAttempts; attempt++) {
        try {
            return target.available(sku);
        } catch (RuntimeException e) {
            failures.add(e);
            // no sleeping: back-off is out of scope
        }
    }
    RuntimeException last = failures.removeLast();
    failures.forEach(last::addSuppressed);
    // keep the history, throw the latest
    throw last;
}
```

The composition root stacks the same three pieces in two orders:

```
// file: decorator/resilience/ResilienceDemo.java
StockService loggingOutside =
    new LoggingStockService(new RetryingStockService(new
FlakyStockService(2, stock), 3), log);
```

```
// ...
StockService retryingOutside =
    new RetryingStockService(new LoggingStockService(new
    FlakyStockService(2, stock), log), 3);
```

```
logging(retrying(flaky)):
  log: available(A-42) = 7
retrying(logging(flaky)):
  log: available(A-42) failed: warehouse timeout #1
  log: available(A-42) failed: warehouse timeout #2
  log: available(A-42) = 7
retrying(flaky) that never recovers:
  gave up: warehouse timeout #3 (suppressed: warehouse timeout #1, warehouse timeout #2)
```

Logging *outside* retry sees one logical call; logging *inside* sees every attempt. Neither is wrong — they answer different questions ("what did the caller experience?" vs. "how flaky is the warehouse?"). The outermost decorator acts first on the way in and last on the way out.

4.7 Real-world usage

java.io is built from decorators. `ByteArrayInputStream` and `FileInputStream` are real sources; `BufferedReader`, `InputStreamReader`, `GZIPInputStream` and every `FilterInputStream` wrap another stream. (`InputStreamReader` is strictly an *adapter*: bytes in, chars out.)

```
// file: decorator/jdk/JdkDecoratorsDemo.java
var counting = new CountingInputStream(new ByteArrayInputStream(gzip));
List<String> lines;
try (var reader = new BufferedReader(
lines
    new InputStreamReader(
chars
        new GZIPInputStream(counting),
bytes
        StandardCharsets.UTF_8))) {
    lines = reader.lines().toList();
}
```

Writing your own is a matter of extending `FilterInputStream`. One trap: `FilterInputStream.read(byte[])` goes through `read(byte[], int, int)`, but `skip` goes *straight* to the wrapped stream — a counting decorator must override it too:

```
// file: decorator/jdk/CountingInputStream.java
@Override
public long skip(long n) throws IOException { // FilterInputStream.skip
    bypasses the read overrides
    long skipped = super.skip(n);
    count += skipped;
    return skipped;
}
```

Closing the outermost reader closes every stream down to the source. `Collections.unmodifiableList` is a read-only *view* (it shows later changes to the backing list), while `List.copyOf` is a *copy*:

```
wrote 4 lines -> 92 gzip bytes
read back 4 lines, errors: [ERROR payment timeout]
CountingInputStream saw 92 of 92 bytes
after backing.add("c"): view [a, b, c], copy [a, b]
view.add -> UnsupportedOperationException
```

Outside the JDK: servlet filters and Spring's `HandlerInterceptors`, `Collections.synchronizedList`, and resilience libraries whose `retry` / `circuit-breaker` wrappers are decorators around a call.

4.8 Pitfalls and when NOT to use it

- **Identity:** a decorated object is a *different* object. `==`, `getClass()` and classic `equals` no longer match the original (`new Milk(new Espresso())` is not equal to another one); records restore value equality.
- **Order:** stacking order changes behaviour — document it and build stacks in one place (the composition root).
- **Deep stacks** are hard to debug: stack traces and `toString` show layer after layer.
- **Sealed interfaces cannot be decorated by others:** if `Beverage` were sealed ... `permits Espresso, HouseBlend`, no one outside could write a `Milk`. Sealing and decorating are opposite design choices.
- If a feature is always on, just put it in the class; decorators pay off when combinations vary.

4.9 Related patterns

Adapter changes the interface, **Decorator** keeps it. **Proxy** has the same shape but controls access rather than adding features. **Composite** (m05) also wraps components, but many of them in a tree. **Chain of Responsibility** (m07) is a stack of handlers that may *stop* the call.

5 Proxy

5.1 Problem


A photo gallery shows hundreds of thumbnails; loading each full-size image up front takes seconds and memory. A document store must refuse writes from viewers. A currency service charges per request although rates change only every few minutes. And in a large application, *every* repository should be timed — without writing a timing class for each one.

5.2 Intent

Provide a surrogate or placeholder for another object to control access to it.

Common kinds: a **virtual proxy** creates the real object lazily; a **protection proxy** checks permissions; a **caching proxy** remembers answers; a **remote proxy** stands in for an object in another process (RMI stubs, gRPC clients). A **dynamic proxy** is not a kind but a *mechanism*: the proxy class is generated at run time.

5.3 Structure



5.4 Classic Java

Virtual proxy. `LazyImage` answers the cheap question itself and creates the expensive `HighResImage` only when the image is really rendered:

```
// file: proxy/virtual/LazyImage.java
@Override
public String fileName() {
    return fileName;
}
// cheap question:
// answered without loading

@Override
public String render() {
    return real.get().render();
}
// first call loads,
// later calls reuse
```

A naive `if (real == null) real = new HighResImage(...)` is a race: two threads can both see `null` and load twice. `Lazy` memoizes with double-checked locking on a `volatile` field:

```
// file: proxy/virtual/Lazy.java
@Override
public T get() {
    T result = value;
    if (result == null) {
        // fast path: no lock
        synchronized (this) {
            result = value;
            if (result == null) {
                // re-check: another
                // thread may have won
                result = Objects.requireNonNull(factory.get(), "factory returned
                null");
            }
        }
    }
    return result;
}
```

```

        value = result;
    }
}
return result;
}

```

```

gallery of 3 created, loads: 0
thumbnails: [beach.jpg, bosphorus.jpg, cappadocia.jpg], loads: 0
open: bosphorus.jpg [6000x4000 pixels]
open again: bosphorus.jpg [6000x4000 pixels]
loads after viewing one image twice: 1
1000 virtual threads rendered one proxy, loads: 1

```

Sidebar — Lazy Constants (JEP 531, preview in JDK 27). The JDK is getting a built-in *lazy constant*: a holder whose value is computed at most once, on first access, and then treated by the JVM like a `final` field. It would replace hand-written memoizers like `Lazy`. It is a preview API, so this course does not use it in graded code.

Protection proxy. The rule is an exhaustive `switch` over the role enum — adding a role will not compile until someone decides what it may do — and a forbidden call never reaches the real store:

```

// file: proxy/protection/ProtectedDocumentStore.java
static boolean allowed(Role role, Operation operation) {
    return switch (role) {
        case VIEWER -> operation == Operation.READ;
        case EDITOR -> operation != Operation.DELETE;
        case ADMIN -> true;
    };
}
// ...
@Override
public void delete(String id) {
    check(Operation.DELETE, id);
    target.delete(id);
}

```

```

deniz (VIEWER):
  read -> draft
  denied: deniz (VIEWER) may not WRITE contract-7
  denied: deniz (VIEWER) may not DELETE draft-1
ece (EDITOR):
  read -> draft
  write -> ok
  denied: ece (EDITOR) may not DELETE draft-1
mert (ADMIN):
  read -> revised by ece
  write -> ok
  delete -> ok

```

5.5 Modern Java 27

Caching proxy with an injected clock. Time comes from a `java.time.Clock` (m03), so the demo and the tests move it by hand instead of sleeping. An entry is fresh while `now` is *before* `storedAt + ttl`:

```
// file: proxy/caching/CachingExchangeRateService.java
@Override
public BigDecimal rate(String from, String to) {
    String key = from + "/" + to;
    Instant now = clock.instant();
    Entry entry = cache.get(key);
    if (entry != null && now.isBefore(entry.storedAt().plus(ttl))) {    // fresh
until storedAt + ttl
        return entry.rate();
    }
    BigDecimal rate = target.rate(from, to);
    cache.put(key, new Entry(rate, now));
    return rate;
}
```

```
2026-09-29T09:00:00Z EUR/TRY = 48.10  (remote calls: 1)
2026-09-29T09:09:00Z EUR/TRY = 48.10  (remote calls: 1)
2026-09-29T09:09:00Z USD/TRY = 41.25  (remote calls: 2)
2026-09-29T09:10:00Z EUR/TRY = 48.10  (remote calls: 3)
2026-09-29T09:10:00Z USD/TRY = 41.25  (remote calls: 3)
```

Dynamic proxies. Writing `TimedOrderRepository`, `TimedPricelist`, ... by hand does not scale. `java.lang.reflect.Proxy` generates a class at run time that implements the given interfaces and sends every call to one `InvocationHandler`:

```
// file: proxy/dynamic/Proxies.java
private static <T> T create(Class<T> iface, InvocationHandler handler) {
    if (!iface.isInterface()) {
        throw new IllegalArgumentException(iface.getName() + " is not an
interface");
    }
    Object proxy = Proxy.newProxyInstance(iface.getClassLoader(), new Class<?>[]
{iface}, handler);
    return iface.cast(proxy);
}
```

The handler receives the proxy, the `Method` and the arguments. Three details make it correct:


```
// file: proxy/dynamic/TimingHandler.java
@Override
public Object invoke(Object proxy, Method method, Object[] args) throws Throwable {
    if (method.getDeclaringClass() == Object.class) {
        return Proxies.objectMethod(proxy, method, args, "timed " + target);    //
not timed
    }
    long start = nanoTicker.getAsLong();
    try {
        return method.isDefault()
            ? InvocationHandler.invokeDefault(proxy, method, args)    // its
inner calls come back here
            : method.invoke(target, args);
    } catch (InvocationTargetException e) {
        throw e.getCause();    // the target's own
exception, unchanged
    } finally {
```

```

        long millis = (nanoTicker.getAsLong() - start) / 1_000_000;
        log.accept(method.getDeclaringClass().getSimpleName() + "." +
method.getName() + " took " + millis + " ms");
    }
}

```

1. `toString`, `equals` and `hashCode` are dispatched to the handler too; answer them without timing.
2. `Method.invoke` wraps the target's exception in `InvocationTargetException`. Rethrow the **cause** — otherwise the caller receives an `UndeclaredThrowableException` instead of its own exception.
3. `default` methods are run with `InvocationHandler.invokeDefault`; the calls they make go through the proxy again:



The time comes from a fake ticker that advances 3 ms per reading, so the output is deterministic. The read-only proxy (`ReadOnlyHandler`) blocks every method annotated `@Mutator`:

```

timing proxy:
log: OrderRepository.findById took 3 ms
findById -> 2 x keyboard
log: OrderRepository.findById took 3 ms
log: OrderRepository.describe took 9 ms
describe -> A-2: 1 x monitor
log: OrderRepository.findById took 3 ms
findById -> NoSuchElementException: no order Z-9
log: PriceList.priceOf took 3 ms
priceOf -> 49.90
read-only proxy:
findAllIds -> [A-1, A-2]
save -> OrderRepository.save is read-only
ids after the blocked save: [A-1, A-2]
Proxy.isProxyClass: true

```

JDK dynamic proxies work **only for interfaces** (`Proxies` rejects a class with `IllegalArgumentException`). Libraries such as `ByteBuddy` and `CGLIB` generate *subclasses* instead, which is how frameworks proxy classes.

5.6 Real-world usage

`Collections.unmodifiableList` is a protection proxy. Spring AOP wraps beans in JDK dynamic proxies (or generated subclasses) for `@Transactional`, `@Cacheable` and security; Hibernate returns lazy-loading proxies for associations; Mockito's mocks are generated proxies; RMI and gRPC stubs are remote proxies.

5.7 Pitfalls and when NOT to use it


- **Identity again:** `proxy.getClass()` is `jdk.proxy1.$Proxy...`, and Hibernate proxies make `getClass()`-based `equals` fail — compare with `instanceof` on the interface.
- **Self-invocation:** a method of the real object that calls another of its methods does not go through the proxy (this is why a `@Transactional` method called from the same class is not transactional). Default methods are the exception — `invokeDefault` routes their calls through the proxy.
- **Lazy + concurrency:** a virtual proxy must be thread-safe or it may create the object twice.
- **Stale caches:** a caching proxy needs an expiry rule, and failures must not be cached.
- **Hidden cost:** a call that looks local may be remote, slow, or throw. Make that visible in names and docs.

5.8 Related patterns

Decorator has the same structure but adds behaviour chosen by the client; a proxy usually controls access and is often created *for* the client (by a factory or framework). **Adapter** changes the interface. **Flyweight** (m05) and **Object Pool** (m03) share objects; a proxy can hand them out.

6 Adapter vs. Decorator vs. Proxy

All three have the same shape — a wrapper implements an interface and delegates to the object it holds:



	Adapter	Decorator	Proxy
Intent	change the interface	add behaviour	control access
Interface of the wrapper vs. the wrapped object	different	same	same

	Adapter	Decorator	Proxy
Who chooses the wrapper?	the integrator	the client, often stacking several	usually a factory or framework
Typical number of layers	one	several, order matters	one
Example in this module	<code>LegacyPaymentAdapter</code>	<code>RetryingStockService</code>	<code>ProtectedDocumentStore</code>
JDK example	<code>InputStreamReader</code>	<code>BufferedReader</code>	<code>Collections.unmodifiableList</code>

7 Summary

Pattern	Use when	Avoid when	Java 27 shortcut
Adapter	An existing class has the wrong interface	You own both sides	Lambda for a functional target; record object adapter; sealed result + exhaustive <code>switch</code>
Decorator	Features combine freely or cross-cut many classes	A feature is always on; the interface is sealed	Records as decorators; <code>Function.andThen / compose</code>
Virtual proxy	Creating the object is expensive and often unnecessary	It is cheap, or always needed	Thread-safe memoizer (Lazy Constants, preview)
Protection proxy	Access depends on who calls	Rules belong in the domain model	Exhaustive <code>switch</code> on a role enum
Caching proxy	Answers are expensive and change slowly	Data must always be fresh	Injected <code>Clock</code> , record entries
Dynamic proxy	The same behaviour for many interfaces	One or two interfaces — write the class	<code>Proxy.newProxyInstance</code> , <code>InvocationHandler.invokeDefault</code>

8 Quiz

1. A class wraps a `Reader` and exposes it as an `Iterator<String>` of lines. Adapter, Decorator or Proxy? And a class that wraps a `Reader` and counts the characters read?
2. Why is the object adapter usually preferred over the class adapter in Java? What did the class adapter test show?
3. When is a lambda enough to implement an adapter?
4. `logging(retrying(x))` logs one line, `retrying(logging(x))` logs three. Explain. Which order would you use to measure how flaky the warehouse is?
5. In `JdkDecoratorsDemo`, which classes are "real" sources and which are decorators? Why did `CountingInputStream` have to override `skip`?
6. Why is `new Milk(new Espresso())` not equal to another `new Milk(new Espresso())` in the classic version, and why are the record versions equal?
7. Why can no one outside your module decorate a sealed interface?
8. Name the four kinds of proxy in this module and one real-world use of each.

9. What does an `InvocationHandler` receive, why must `InvocationTargetException` be unwrapped, and why do JDK dynamic proxies need interfaces?

Answers

1. The first is an **Adapter** (the interface changes: `Reader` → `Iterator<String>`). The second is a **Decorator** (still a `Reader`, with added counting).
2. Java has single inheritance: a class adapter uses up the superclass, works only with one concrete adaptee class, and exposes all adaptee methods. The test cast the class adapter to `LegacyPayGateway` and called `makePayment` with a negative amount, bypassing the adapter's validation.
3. When the target is a functional interface (one abstract method) and the translation fits in an expression.
4. The outermost decorator sees the call first. Logging outside sees one logical call; logging inside retry sees every attempt, including the two failures. To measure flakiness, put logging inside: `retrying(logging(x))`.
5. `ByteArrayInputStream` is a real source; `CountingInputStream`, `GZIPInputStream`, `InputStreamReader` (an adapter) and `BufferedReader` wrap other streams. `FilterInputStream.skip` calls the wrapped stream's `skip` directly, bypassing the overridden `read` methods, so skipped bytes would not be counted.
6. Classic decorators inherit `Object.equals` — identity. Records generate `equals` from their components, and the innermost component `Coffee.ESPRESSO` is an enum constant, so two equal orders compare equal.
7. A sealed interface lists all its implementations in `permits`; a decorator is a new implementation, which the compiler rejects outside the permitted set.
8. Virtual (Hibernate lazy associations), protection (`Collections.unmodifiableList`, Spring Security method security), caching (Spring `@Cacheable`), remote (RMI or gRPC stubs). Dynamic proxies are the mechanism behind many of them.
9. The proxy, the `Method` being called and the arguments. `Method.invoke` wraps the target's exception in `InvocationTargetException`; rethrowing that (or any undeclared checked exception) makes the caller receive `UndeclaredThrowableException`. `java.lang.reflect.Proxy` generates a class that *implements* interfaces — it cannot extend an arbitrary class; `ByteBuddy`/`CGLIB` generate subclasses for that.

9 Assignments

- 01 — Data-source decorators (compression + Base64) ★★☆
- 02 — Caching proxy with TTL for a slow weather service ★★★

10 Further reading

- Gamma, Helm, Johnson, Vlissides, *Design Patterns* (1994) — Adapter, Decorator, Proxy.
- Joshua Bloch, *Effective Java*, 3rd ed. (2018), item 18 (favour composition over inheritance — the forwarding class and wrapper).
- JDK API: `java.lang.reflect.Proxy`, `InvocationHandler.invokeDefault`, `java.io.FilterInputStream`
- JEP 531 — [Lazy Constants \(preview\)](#) · JEP 444 — [Virtual Threads](#)
- Terms in Turkish: [docs/glossary.md](#)