

Module 03 – Creational Patterns II: Construction

Contents

1	Learning outcomes	2
2	Motivation	2
3	Builder	2
3.1	Problem	2
3.2	Intent	2
3.3	Structure	3
3.4	Classic Java	3
3.5	Modern Java 27	4
3.6	Real-world usage	5
3.7	Pitfalls and when NOT to use it	5
3.8	Related patterns	5
4	Prototype	6
4.1	Problem	6
4.2	Intent	6
4.3	Structure	6
4.4	Classic Java	6
4.5	Modern Java 27	7
4.6	Real-world usage	7
4.7	Pitfalls and when NOT to use it	8
4.8	Related patterns	8
5	Object Pool	8
5.1	Problem	8
5.2	Intent	8
5.3	Structure	8
5.4	Classic Java	8
5.5	Modern Java 27	9
5.6	Real-world usage	10
5.7	Pitfalls and when NOT to use it	10
5.8	Related patterns	10
6	Dependency injection as creation	10
6.1	Problem	10
6.2	Intent	10
6.3	Structure	10
6.4	Classic Java	10
6.5	Modern Java 27	11
6.6	Real-world usage	11
6.7	Pitfalls and when NOT to use it	11
6.8	Related patterns	11
7	Choosing a construction technique	12
8	Summary	12
9	Quiz	12
10	Assignments	13

11 Further reading 13

Week 4 · Prerequisites: m02 (factories), m01 (DIP, composition root) · Estimated study time: 5 h

Run every example without a build:
`java modules/m03-creational-construction/src/main/java/io/github/aliturgutbozkurt/patterns/m03/examples/<path>/<Demo>.java`
 (JDK 27)

1 Learning outcomes

By the end of this module you can:

1. **Implement** a classic Builder with validation in `build()`, a record with a nested builder, and `with` copies.
2. **Design** a step builder whose types make an incomplete object impossible to build.
3. **Explain** shallow vs. deep copy and **implement** Prototype with copy constructors and a registry.
4. **Implement** a bounded Object Pool and **decide** when pooling helps — and why virtual threads are never pooled.
5. **Wire** an application in a composition root and swap collaborators for fakes in tests.

2 Motivation

m02 decided *which* class to create. This module is about *how* to assemble an object: when it has many optional parts (Builder), when a ready-made one should be copied (Prototype), when creating it is so expensive that it should be reused (Object Pool), and when a whole graph of objects has to be put together (dependency injection).

3 Builder


3.1 Problem

A pizza has a size, a crust, up to five toppings and optional extra cheese. A constructor with every combination — `Pizza(Size)`, `Pizza(Size, Crust)`, `Pizza(Size, Crust, List<String>, boolean)` — is a *telescoping constructor*: hard to read (`new Pizza(LARGE, null, List.of(), true)`?) and it cannot check rules that involve several parts.

3.2 Intent

Separate the construction of a complex object from its representation, so it can be built **step by step** and validated **as a whole**.

3.3 Structure



3.4 Classic Java

The required part goes into `builder(size)`; optional parts read like sentences:

```
// file: examples/builder/PizzaDemo.java
Pizza deluxe = Pizza.builder(Size.LARGE)
    .topping("mushroom")
    .topping("olives")
    .crust(Crust.STUFFED)
    .extraCheese()
    .build();
```

`build()` checks the rules that involve several parts before an immutable `Pizza` exists:

```
// file: examples/builder/classic/Pizza.java
/** Validates the combination and creates the pizza. */
public Pizza build() {
    if (toppings.size() > MAX_TOPPINGS) {
        throw new IllegalStateException("at most " + MAX_TOPPINGS + " toppings, got " + toppings.size());
    }
}
```

`Pizza` extends `MenuItem(name, price)`, and its price depends on the builder's choices. Before Java 25 that calculation had to hide in a static helper, because nothing could run before `super(...)`. With **flexible constructor bodies** (JEP 513) it can be written in place — and the compiler enforces the rule of this early phase: fields may be **assigned** but not **read** before `super(...)`:

```
// file: examples/builder/classic/Pizza.java
private Pizza(Builder builder) {
    // Flexible constructor body (JEP 513): before super(...) we may compute with
    // locals and *assign* our fields,
    // but not *read* them — so the price is computed from the builder's values.
```

```

List<String> chosenToppings = List.copyOf(builder.toppings);
BigDecimal price = builder.size.basePrice
    .add(TOPPING_PRICE.multiply(BigDecimal.valueOf(chosenToppings.size())))
    .add(builder.extraCheese ? EXTRA_CHEESE_PRICE : BigDecimal.ZERO)
    .add(builder.crust == Crust.STUFFED ? STUFFED_CRUST_PRICE :
BigDecimal.ZERO);
size = builder.size;
crust = builder.crust;
toppings = chosenToppings;
extraCheese = builder.extraCheese;
super(builder.size.name().toLowerCase(Locale.ROOT) + " pizza", price);
}

```

A second classic builder mirrors the JDK's own `java.net.http.HttpRequest.newBuilder()`. Each part is checked when it is added (a header name, a timeout); the rules that combine parts are checked in `build()`:

```

// file: examples/builder/classic/HttpRequest.java
/** Checks the rules that involve several parts, then creates the request. */
public HttpRequest build() {
    boolean hasBody = body != null;
    switch (method) {
        case GET, DELETE -> {
            if (hasBody) {
                throw new IllegalStateException(method + " request must not have
a body");
            }
        }
        case POST, PUT -> {
            if (!hasBody) {
                throw new IllegalStateException(method + " request needs a
body");
            }
        }
    }
    return new HttpRequest(this);
}

```

3.5 Modern Java 27

Records with a builder. A record already gives immutability, equality and one canonical constructor. Put all validation in its compact constructor — the *one* place every path goes through — and let the builder hold only defaults. `withX` methods create modified copies:

```

// file: examples/builder/record/ServerConfig.java
public record ServerConfig(String host, int port, Duration timeout, boolean tls, int
maxConnections) {
    // ...
    public ServerConfig withPort(int newPort) {
        return new ServerConfig(host, newPort, timeout, tls, maxConnections);
    }
    // ...
    private final String host;
    private int port = 8080;
    private Duration timeout = Duration.ofSeconds(30);
    private boolean tls;
    private int maxConnections = 100;
}

```

```
defaults: ServerConfig[host=localhost, port=8080, timeout=PT30S, tls=false,
maxConnections=100]
production: ServerConfig[host=api.example.com, port=443, timeout=PT10S, tls=true,
maxConnections=500]
staging copy: ServerConfig[host=api.example.com, port=8443, timeout=PT10S, tls=true,
maxConnections=500]
```

Step builders. A normal builder lets you call `build()` too early and fails at run time. A *step builder* returns a different interface after each call, so only the legal next calls exist:

```
// file: examples/builder/step/Query.java
/** Step 1: choose columns. */
public interface SelectStep {
    FromStep select(String... columns);

    FromStep selectAll();
}

/** Step 2: choose the table. */
public interface FromStep {
    QueryStep from(String table);
}
```

```
// file: examples/builder/QueryDemo.java
// Query.builder().select("name").build(); // does not compile: FromStep has
no build()
```

```
SELECT name, email FROM users WHERE active = true ORDER BY name LIMIT 20
SELECT * FROM orders WHERE total > 100 AND status = 'PAID' ORDER BY total DESC
```

3.6 Real-world usage

`java.net.http.HttpRequest.newBuilder()`, `HttpClient.newBuilder()`, `StringBuilder`, `Stream.builder()`, `Locale.Builder`, `ProcessBuilder` and `Thread.ofVirtual().name(...).start(...)` are all builders.

3.7 Pitfalls and when NOT to use it

- A record with two or three components does not need a builder — the canonical constructor is readable enough.
- Validate in **one** place. With records, that place is the compact constructor; the builder only fills defaults.
- A builder is mutable and not thread-safe; the object it builds should be immutable.
- The query example concatenates text: fine for teaching, **not** safe against SQL injection — real code binds parameters.

3.8 Related patterns

Abstract Factory (m02) returns a finished product in one call; a builder assembles one in steps. **Composite** (m05) structures are often assembled by builders.

4 Prototype


4.1 Problem

A document template with sections and metadata took effort to configure; users want to start new documents from it. Constructing each one from scratch repeats that work — copying the template is simpler. But *how* you copy matters.

4.2 Intent

Create new objects by **copying a prototypical instance**.

4.3 Structure



4.4 Classic Java

Java's built-in mechanism is `Cloneable` + `Object.clone()`. It copies fields one by one — a **shallow** copy: the clone and the original share every object their fields refer to. A **copy constructor** says explicitly what to copy:

```
// file: examples/prototype/documents/DocumentTemplate.java
/** Copy constructor: a deep copy – new lists and maps with the same (immutable)
strings. */
public DocumentTemplate(DocumentTemplate other) {
    this(other.title, other.sections, other.metadata);
}

/** Shallow copy: the clone shares {@code sections} and {@code metadata} with this
template. */
@Override
public DocumentTemplate clone() {
    try {
        return (DocumentTemplate) super.clone();
    } catch (CloneNotSupportedException e) {
        throw new AssertionError("Cloneable is implemented", e);
    }
}
```

```
    }
}
```

```
template: Invoice [Header, Lines, Totals] {lang=en}
== clone() then edit the copy ==
copy:      Receipt [Header, Lines, Totals, Signature] {lang=tr}
template: Invoice [Header, Lines, Totals, Signature] {lang=tr}    <- changed too!
== copy constructor then edit the copy ==
copy:      Receipt [Header, Lines, Totals, Signature] {lang=tr}
template: Invoice [Header, Lines, Totals] {lang=en}
```

Why `clone()` is considered broken: it creates objects **without calling a constructor**, so invariants are not checked; it cannot re-assign `final` fields, so deep copies need non-final fields; `Cloneable` has no methods, and `Object.clone()` is `protected` and throws a checked exception. Recent JDKs are also closing the reflective back door for mutating `final` fields (JEP 500). Prefer copy constructors or a `copy()` method.

4.5 Modern Java 27

Immutable values need no copying — share them. In the game-unit registry, `Stats` and `Position` are records: a copy may simply reuse them. Only the *mutable* state (the field holding the position, the arrow count) is per-copy:

```
// file: examples/prototype/registry/Archer.java
private Archer(Archer other) {
    this.stats = other.stats;
    this.position = other.position;
    this.arrows = other.arrows;
}
```

A **prototype registry** stores configured units under a name and hands out copies — and it copies on the way *in* as well, so a caller cannot change the stored prototype later:

```
// file: examples/prototype/registry/UnitRegistry.java
/** Stores a <em>copy</em>, so later changes to {@code prototype} do not leak into
the registry. */
public void register(String name, Unit prototype) {
    prototypes.put(name, prototype.copy());
}

public Unit spawn(String name) {
    Unit prototype = prototypes.get(name);
    if (prototype == null) {
        throw new IllegalArgumentException("unknown unit: " + name + " (known: " +
names() + ")");
    }
    return prototype.copy();
}
```

4.6 Real-world usage

`ArrayList` has a copy constructor (`new ArrayList<>(other)`), `List.copyOf`, `Map.copyOf` and `EnumSet.copyOf` create copies; `Object.clone()` still exists on arrays, where `array.clone()` is the idiomatic shallow copy.

4.7 Pitfalls and when NOT to use it

- Shallow vs. deep: decide field by field — immutable objects may be shared, mutable ones must be copied.
- Deep copies of object graphs with cycles need care (a map of already-copied objects).
- With immutable records, "copying" is usually just reusing the object or calling a `withX` method.

4.8 Related patterns

A **Composite** (m05) must copy its children recursively — as in assignment 02. **Memento** (m07) stores copies of state.

5 Object Pool


5.1 Problem

Opening a database connection costs a TCP handshake, TLS and authentication — milliseconds each time — and the database only accepts a limited number of connections. Creating one per request is slow and can overload the server.

5.2 Intent

Keep a set of **initialised, reusable objects** and lend them out instead of creating and destroying them.

5.3 Structure



5.4 Classic Java

A `Semaphore` bounds the number of leases; idle connections wait in a deque; new ones are created lazily up to the limit; a timeout prevents waiting forever:

```
// file: examples/pool/ConnectionPool.java
public PooledConnection acquire(Duration timeout) throws InterruptedException {
    if (!permits.tryAcquire(timeout.toNanos(), TimeUnit.NANOSECONDS)) {
        throw new IllegalStateException("no connection available within " +
```

```

timeout);
    }
    Connection connection;
    synchronized (this) {
        connection = idle.pollFirst();
        if (connection == null) {
            connection = factory.apply(++created);
        }
        inUse++;
        maxInUse = Math.max(maxInUse, inUse);
    }
    return new PooledConnection(this, connection);
}

```

The lease is `AutoCloseable`, so `try-with-resources` always gives the connection back — even when the query throws:

```

// file: examples/pool/ConnectionPoolDemo.java
try (PooledConnection connection =
sequential.acquire(Duration.ofSeconds(1))) {
    System.out.println(connection.query("SELECT " + i));
}

```

```

conn-1: SELECT 1
conn-1: SELECT 2
conn-1: SELECT 3
sequential use created 1 connection(s)
200 virtual threads, pool of 2: max in use <= 2? true, created <= 2? true
exhausted: no connection available within PT0.05S

```

5.5 Modern Java 27

For years the most famous pool was the **thread pool**. Virtual threads (JEP 444) change that: they are cheap to create, so every task gets its own and **virtual threads are never pooled**. What remains scarce is the resource the tasks use — so bound *that*, with a `Semaphore`, and pool nothing at all:

```

// file: examples/pool/throttle/ThrottledClient.java
public String call(String request) throws InterruptedException {
    permits.acquire();
    try {
        peak.accumulateAndGet(current.incrementAndGet(), Math::max);
        return service.apply(request);
    } finally {
        current.decrementAndGet();
        permits.release();
    }
}

```

```

1000 calls on 1000 virtual threads completed: true
peak concurrent calls <= 5? true

```

Connection pools are still worth it (the connection is expensive, not the thread); pools of cheap objects are not — modern garbage collectors allocate short-lived objects almost for free.

5.6 Real-world usage

JDBC connection pools (HikariCP and others) behind `javax.sql.DataSource`; `ThreadPoolExecutor` for platform threads; `Executors.newVirtualThreadPerTaskExecutor()` deliberately does **not** pool.

5.7 Pitfalls and when NOT to use it

- A returned object may carry **stale state** (an open transaction, a changed setting) into the next lease — reset it on release.
- Leaks: a lease that is never returned shrinks the pool forever; try-with-resources prevents it.
- Pooling cheap objects makes code slower and more complex.

5.8 Related patterns

Flyweight (m05) also shares objects, but immutable ones, and nobody "returns" them. **Proxy** (m04) can wrap a pooled object so that `close()` returns it.

6 Dependency injection as creation


6.1 Problem

If every class creates its collaborators, nobody can replace them — not in tests, not in production. If they fetch them from Singletons, the dependencies are hidden (m02). Someone still has to call `new`.

6.2 Intent

Create and wire the whole object graph in **one place** — the composition root — and pass every collaborator in through constructors.

6.3 Structure



6.4 Classic Java

The business class creates nothing, not even the clock:

```
// file: examples/di/CheckoutService.java
/** Prices, charges and stores the order; an unknown item fails before anything is
charged. */
public OrderRecord checkout(String customer, String item, int quantity) {
    BigDecimal total = prices.priceOf(item, quantity);
    String receipt = payments.charge(customer, total);
    var order = new OrderRecord(customer, item, quantity, total, receipt,
clock.instant());
    orders.save(order);
    return order;
}
```

6.5 Modern Java 27

The composition root is plain code — no framework. Each collaborator is created once and shared: "singleton" by wiring, not by a static field. Tests call the same wiring with a fake gateway and a fixed clock:

```
// file: examples/di/CompositionRoot.java
private static ShopApp wire(PaymentGateway gateway, Clock clock) {
    var orders = new InMemoryOrderRepository();
    var checkout = new CheckoutService(new CatalogPriceCalculator(CATALOG), gateway,
orders, clock);
    return new ShopApp(checkout, orders);
}
```

```
ada bought 2 x keyboard for 99.80 (receipt PAY-1)
alan bought 1 x monitor for 229.00 (receipt PAY-2)
orders stored: 2
```

6.6 Real-world usage

Every DI framework (Spring, Guice, Dagger, CDI) automates a composition root; `main` methods of small applications are composition roots written by hand. Module `m11` builds on this.

6.7 Pitfalls and when NOT to use it

- A composition root that grows to hundreds of lines is a sign to split it by feature — or to adopt a framework.
- Do not pass the root (or a "service locator") into business classes; pass only what each class needs.

6.8 Related patterns

It replaces most **Singletons** (m02) and uses **factories** for the collaborators it cannot create up front.

7 Choosing a construction technique

Situation	Use
Few parts, all required	Constructor or record
Many optional parts, rules across parts	Builder (record + builder when possible)
Order of steps matters, forgetting one must not compile	Step builder
New objects are variations of a configured one	Prototype (copy constructor / <code>copy()</code>), registry
Objects are expensive and limited (connections)	Object Pool
Threads for blocking tasks	Virtual thread per task + <code>Semaphore</code> , never a pool
Wiring a whole application	Composition root

8 Summary

Pattern	Use when	Avoid when	Java 27 shortcut
Builder	Many optional parts; cross-part validation	Two or three required parts	Record + nested builder, <code>withX</code> copies
Step builder	Mandatory order of steps	Parts are all optional	One interface per step
Prototype	Copying is simpler than configuring	The object is immutable — just share it	Copy constructor, <code>copy()</code>
Object Pool	Creation is expensive and capacity limited	Objects are cheap; threads (use virtual threads)	<code>Semaphore</code> + <code>AutoCloseable</code> lease
Composition root	Building an application's object graph	—	Plain constructors, <code>Clock</code> injected

9 Quiz

1. What is a telescoping constructor and which two problems does a builder solve?
2. In `ServerConfig`, why does the compact constructor — not the builder — validate the port?
3. What does a step builder guarantee that a normal builder cannot?
4. In JEP 513's early construction phase, what may a constructor do with its own fields, and what may it not?
5. Why did `clone()` change the original template's sections but not its title?
6. Give three reasons why `Cloneable` / `clone()` is considered broken.
7. Why may a prototype copy share its `Stats` record but not the field holding its position?
8. Why should virtual threads not be pooled, and what should you bound instead?
9. How does a composition root differ from a Singleton?

Answers

1. A chain of constructors with ever more parameters. A builder makes calls readable (named steps, defaults) and can validate the combination of parts in `build()`.
2. Because every path — the builder, `withPort`, a direct constructor call — goes through the canonical constructor; validating there keeps the rule in exactly one place.
3. That `build()` (and every step) can only be called in the right order — mistakes are compile errors, not run-time exceptions.

4. It may assign its fields, but it may not read them (or otherwise use `this`) before `super(...)`.
5. The clone got its own `title` field (strings are immutable, re-assigning it affects only the clone), but both objects' `sections` fields refer to the same `ArrayList`.
6. It bypasses constructors (and their validation); it cannot re-assign `final` fields; `Cloneable` has no methods and `Object.clone()` is `protected`, returns `Object` and throws a checked exception.
7. `Stats` is immutable, so sharing it is invisible; the position changes per unit, so each copy needs its own field.
8. They are cheap to create, one per task is the intended model; bound the scarce resource (connections, a remote service) with a `Semaphore`.
9. A composition root creates one instance and *passes* it to those who need it; a Singleton is fetched through a global access point, which hides the dependency.

10 Assignments

- [01 — Travel booking builder](#) ★★☆
- [02 — Shape editor with prototypes](#) ★★☆

11 Further reading

- Gamma, Helm, Johnson, Vlissides, *Design Patterns* (1994) — Builder, Prototype.
- Joshua Bloch, *Effective Java*, 3rd ed. (2018), items 2 (builders) and 13 (override `clone` judiciously).
- JEP 513 — [Flexible Constructor Bodies](#) · JEP 444 — [Virtual Threads](#) · JEP 500 — [Prepare to Make Final Mean Final](#)
- Mark Seemann, "Composition Root" — the term used in this module.
- Terms in Turkish: [docs/glossary.md](#)