

Group 15 - LAB 2

Einar Lennelöv | Mustafa Al-Janabi



3.1


Batch mode training using least squares



Analysis of absolute error


RBF units linearly spaced.

Decay of mean absolute error on sin2.
Average over 10 trials.



0.1: 22 units
0.01 31 units
0.001 42 units

Decay of mean absolute error on square2.
Average over 10 trials.




0.1: 27 units
0.01 60 units
0.001 70 units



Step transformed RBF output on square

Linearly spaced RBFs:


Residual error over the number of RBFs, #data-points=64, RBF-variance=0.1





Step transformed RBF output on square

4 intelligently spaced RBFs:
0 MSE for step transformed
output.
Useful for classification.



3.2


Regression with noise




Linspaced vs random RBF placement

MSE plotted against number of RBF nodes

Centering comparison for sin2 with data noise of 10%



Centering comparison for square with data noise of 10%







Comparison of different RBF widths

MSE plotted against number of RBF nodes

Variance comparison for sin2 with data noise of 10%



Variance comparison for square with data noise of 10%




3.3

Competitive learning (CL) to initialise RBF units




Ordinary CL vs Leaky CL

4 RBFs on sin2 data





Ordinary CL





Leaky CL

2d competitive learning



RBF network on 2d data

Highly sensitive to RBF width and number of nodes




4.1

Topological ordering of animal species



Animal Ordering




4.2

Cyclic tour





Travelling Salesperson Problem



4.3


Data clustering: votes of MPs







Votes of MPs

By party, gender, and district



Parties

Genders



Districts