

Index

- ABS braking 395,400
- Adhesion 82
- Aerodynamic drag 525
- Aligning torque, definition 3
- Aligning torque, steady state 4,96,113,177,183,188,190,208
- Aligning stiffness, definition 5
- Aligning stiffness 97,159,234
- Axes system 4,64
- Axle characteristics 7,12,37,43
- Axle cornering stiffness 9,11
- Axle side force 11
- Badalamenti and Doyle 484
- Bakker 172,176,179
- Bandel 472,486,487
- Bayer 518
- Bayle 172,182
- Belt distortion 78,134
- Belt dynamics 277,413,452
- Bernard 86,92
- Berritta 518
- Berzeri 435
- Besselink 218,261,295,312,318,320,322,360,631
- Biral 518
- Böhm 90,92
- Brake lever arm 466,468
- Braking 51,148,395,505,557
- Breuer 518
- Brockman and Braisted 466
- Bruni 462
- Brush model 86,90,94,124,413
- Calspan flat track test stand 209
- Camber angle 71,73,78,81,118,124,163,176,206,261,342,353,452,505
- Camber stiffness 80,162
- Camber reduction factor 80,119,146
- Capsize mode 542
- Carcass compliance 88,134,341,360,413,417,452,462,634
- Carcass distortion 78
- Caster length (trail) 8,312,320,544
- Centre of gravity 24,312,544,546,551
- Cheli 462
- Characteristic equation 30,298,331
- Characteristic speed 26
- Characteristics, cf. tyre characteristics
- Clark 388,465
- Cleat 484
- Coefficient of friction 5,6,83,134,186
- Combined slip 104,134,164,181,434
- Combined slip with F_x as input 170
- Composite slip 183,434,438
- Conicity 81,137,198
- Constitutive relations 461
- Contact centre 64,206
- Contact length 99,161,291,461,632
- Contact patch mass 359,396,452
- Contact patch slip model 414,422,427
- Contact width 461
- Cornering force, cf. side force
- Cornering on uneven road 293,367
- Cornering stiffness, definition 5
- Cornering stiffness 6,97,234
- vs normal load 5,159,176,270,368
- loss (side force) 293,367,372,374
- Cornering stiffness string model 270
- Cossalter 518
- Critical speed 26,29,58,151,542,559
- Cross section 78,100,206,521
- Curvature factor 174
- Cut-off frequency 238,241,242,416
- Damping:
 - vehicle handling 31
 - shimmy 299,301,315
 - tyre 328,346,375,407,462,474,636
 - motorcycle steer 546
- Davis 486

- Deflections (tyre) 76,147
- Delft-Tyre 172,512,514
- Delft dyn. brake and cleat rig 470,591
- Delft flat plank 236,350,497,499,590
- Delft pendulum test stand 472,592
- Delft tyre test trailer 209,587
- Delft University of Technology
 - vi,172,412,470,592
- Delft yaw oscillation test rig 472,593
- Differential equations:
 - string approximations 253,255
 - single contact point 341,360
 - contact patch 420,427,430,459
 - with carcass compliance 436
- Dijks 186
- Discrete Element Model 514,515
- Dugoff 85,92
- Effective inputs 413,483
- Eff. road pl. height/slope 486,494,506
- Effective rolling radius, definition 3,65
- Effective rolling radius
 - 101,208,376,466,468,495,499,632
- Eigenvalues:
 - vehicle handling 30
 - motorcycle 540,577
- Eldik Thieme, van vi,587,590,592
- Empirical model 85,156
- Energy flow 321,324,327,467
- Enveloping power 413,483,512
- Equations of motion:
 - vehicle handling 20,21,23,148,364
 - car-trailer 56
 - shimmy 296,304
 - steering vibrations 392
 - braked wheel system 398
 - contact patch mass 432,456
 - rigid belt 454
 - motorcycle 537
- Fancher 85
- Fiala 86,90,92
- Finite Element Model 515
- Forissier 179
- Four wheel steer 36
- Frank 91
- Frequency response:
 - vehicle handling 33,365
 - string model 237,239,272
 - and approximations 257,258
 - string with approx. dynamics 281
 - longitud. force (single point) 383
 - long. force (SWIFT) 416,417,477
 - lateral force (SWIFT) 419,478
 - aligning torque (SWIFT) 426,478
 - steering vibrations 393,394
 - SWIFT (zero belt mass) 441-446
 - braked wheel 400
- Freudenstein 92,146
- Fritz 218
- Fromm 90,92,295
- FTire 414,512,514
- Geometric filtering 505
- Gillespie 16
- Gipser 88,414,484,514
- Goncharenko 261
- Gong 484,486
- Gough 100,483
- Green function 87
- Growth (centrifugal) 464,632
- Guan, Dihua 88
- Guntur 400
- Guo 88,92
- Gyroscopic couple
 - 275,302,306,313,358,544
- Handling curve 37
- Handling diagram 37,43,569,572
- Hasegawa 518
- Higuchi 146,219,236,350,373
- Ho and Hall 218
- HSRI (UMTRI) 85
- Human rider model 518,539,548
- Hurwitz stability criterium 57,298,308
- Hysteresis 375
- Iffelsberger 518
- Inclination angle, cf. camber angle
- Influence function 87

- Instability:
 divergent 29,58,152,300,560
 oscillatory 58,300,388
 Jagt, van der 205,207,211,360,395,448
 Jianmin 375
 Julien 90
 Karlsruhe University of Techn. 590
 Katayama 518
 Keldysh 218,261
 Kluiters 218,250
 Kobiki 476
 Koenen 518,577
 Kortüm 16
 Laerman 219
 Lafon 179
 Lagrange's equations 17,56,512,532
 Lateral acceleration response 35
 Lateral force, cf. side force
 Lateral slip 73
 Lateral slip stiffness, cf. cornering stiffness
 Lateral stiffness
 standing tyre 234
 suspension 305,310
 Lateral c.g. offset (motorcycle) 562
 Lee 199
 Limit-cycle 295,330,334
 Lippmann 483
 Load transfer 9,14,526
 Load variations 284,446
 Loaded radius 207,377,465,468,631
 Longitudinal force, definition 3
 Longitudinal force 4,187,189,375
 Longitud. slip, def. 3,65,67,68,73,103
 Longitudinal slip 101,414
 Longitudinal slip stiffness, def. 3
 Longitudinal slip stiffness 6,104
 Lugner 16
 Magic Formula 6,44,156,160,169,345,397,412,413,436,437,513
 Magic Formula, cosine version 178
 Magic Formula Tyre Model 172,184
 Magic Formula with turn slip 191
 Magic Formula motorcycle 528,578
 Manoeuvring 54,518
 Mastinu 88
 Maurice 219,412,421,435,473,477
 Meier-Dörnberg 218
 MF-Tyre 513
 Michelin 172,179
 Milliken 16,53,55,157
 Milliken Research Associates 53
 Mitschke 16,466
 Modes of vibration 319,323,389,474
 Moment method 53
 Moreland 218,262
 Motorcycle dynamics 517
 Motorcycle tyre force/ and moment 527,579,583
 Mousseau 484
 MTS Flat Trac III 209
 MTS Flat Trac Roadway Simulator 55
 Natural frequencies:
 vehicle handling 31
 tyre out-of-plane 277,280,476,512
 tyre in-plane 462,474,476,512
 shimmy 301,319
 steering vibration 389,393
 Neutral steer 25
 Neutral steer point 24
 Nishimi 518
 Non-dimensionalisation 157
 Non-holonomic constraint 305
 Non-lagging part 355,360
 Non-linear system 46,330,333
 Non-steady state 217,414
 Non-uniformity 375,379
 Normal force, load 62,190,358,463,632
 Normal deflection 207,358,464,507,631
 Nyquist plot:
 tyre measurements 274,275,282
 string model 243,244
 and approximations 259,260
 - with gyroscopic couple 277
 string with approx. dynamics 282

- | | | | |
|--------------------------------|------------------------|---|-----------------------------|
| SWIFT (zero belt mass) | 442 | Response successive steps | 362,481,482 |
| Obstacle | 412,483,484 | Rider robot | 518,547 |
| Oertel | 414,484,515 | Rigid ring | 413,452 |
| Olley | 295 | Rigid wheel | 305,492 |
| Oosten, van | 176,631 | Rise time | 32 |
| Out of roundness | 379 | RMOD-K | 414,512,515 |
| Oversteer | 25,37 | Road camber | 505 |
| Overturning couple | | Road unevenness | 375,403,412,483 |
| 63,64,190,203,206,211,554 | | Rogers | 218,248 |
| Parameter assessment | | Roll angle motorcycle | 553 |
| 176,370,470,477,631,512 | | Roll axis | 8 |
| Parameters Mag.Form./SWIFT | 629,631 | Roll steer/camber | 10,22 |
| Parking manoeuvre | 447,451 | Rolling resistance | 375,455,465,631 |
| Path curvature | 25,118,146,191,448,553 | Rolling resist. moment | 62,64,190,469 |
| Pevsner | 16 | Rotation transformation | 523 |
| Phase plane | 46 | Ruijs | 518,547 |
| Physical model | 85,90,134,429,432 | Sakai | 92,93 |
| Ply-steer | 81,137,198 | Savkoor | 90 |
| Pneumatic trail, definition | 5 | Scaling factors | 186 |
| Pneumatic trail | | Schlippe, von | |
| 6,28,45,98,108,139,161,177,421 | | 217,226,246,247,281,295,299 | |
| Point of intersection | 64 | Schmeitz | 487,491,493,500,502,509 |
| Pothole response (SWIFT) | 505 | Segel | 6,16,85,217,219,226,246,355 |
| Pressure distribution | 83,97,134 | Self aligning torque, cf. aligning torque | |
| Pure slip | 4 | Self-excited oscillations | 295 |
| Radial stiffness | 464,632 | Separatrix | 48,334 |
| Radt | 16,157 | Shang, Jin | 88 |
| Regression technique | 176 | Shape factor | 174 |
| Reimpell | 186,206,464 | Sharp | 88,517,518 |
| Relaxation length: | | Sharpness factor | 176 |
| single point model | 341,348,361 | Shimmy | 295,337 |
| string model | 222,238,242,260 | Side force, definition | 3 |
| string with tread elements | 270,291 | Side force | 4,96,187,189,527 |
| vehicle handling | 22,472 | Side force steer | 9,10 |
| vs normal load | 270 | Side slip, definition | 3 |
| contact patch model | 416 | Side walls | 100,462 |
| - with carcass compl. | 417,424,634 | Sign convention | 3,65,612 |
| motorcycle tyre | 527,542 | Similarity modelling method | 157,397 |
| Residual stiffness | 413,452,456,463 | Single point approximations | |
| Residual torque | 162,177,199 | linear | 251,297,340 |
| Response to cleats (SWIFT) | 483,501 | semi-non-linear | 345,404 |
| Response to load var. | 284,350,371,374 | fully non-linear | 346,405 |
| | | restr. fully non-linear | 348,406,411 |
| | | enhanced model | 359,396,406,411 |

- Single track vehicle 517
- Singular point 41,48
- Sliding region 97,122
- Sliding velocity 77,82
- Slip angle, definition 3,4,69
- Slip angle 23,96,525
- Slip components 69,106
- Slip point 65,101,356,378
- Slip radius 65
- Slip ratio, cf. longitudinal slip
- Smiley 217,246,248
- Speed of revolution 68
- Speed of rolling, angular 67,72
- Speed of rolling, linear 67,72,102
- Spin (slip) 69,191,342,448
- Stability:
 - vehicle handling 16,29,41,47,48
 - car-trailer 57,59
 - motorcycle 540
- Stability boundary 42,58,300,314,322
- Standing waves 466
- Standstill (stop, start) 344,404,447
- State space 333
- Steady-state cornering 29,37,550,568
- Steady-state response:
 - string model 230
 - vehicle handling 29,37
- Steer angle 25,553,556
- Steer compliance 9,10,11
- Steer stiffness 302
- Steer torque 451,547,563,573
- Steering vibrations 389
- Step response (tyre):
 - measured 236,351,354
 - string model 230,233
 - and approximations 256,257
 - single point model 351,355
 - SWIFT (zero belt mass) 440
 - vehicle handling 366,518
 - motorcycle 547,549
- Stepan 299
- Strackerjan 218,276
- Straight tangent approx. 246,250,296
- String model 217,220,222
- String with tread elements 263,284
- Suspension compliance 305,310,389
- SWIFT model 412-516,513,629,631
- Synchronous oscillation 336,337
- System of axes, cf. axes system
- Takahashi 219,348,369,373,518
- Tandem 'cam' technique 493,501
- Tandem rear axle 44
- Test facilities 470,586
- TNO-Automotive 172,412,587,631
- Toe angle 10
- Torsional stiffness:
 - standing tyre 234,242
 - motorcycle 542
- Trailer 55
- Trajectory 47
- Transfer function:
 - string model 227
 - string with tread elements 268
- Transient slip values 345,396,538
- Transient tyre behaviour 344
- Tread compliance 413
- Tread simulation model 134,613
- Tread width effect
 - 131,134,242,252,301
- Truck 44,146,212,337
- TU-Delft 172
- Turn slip 71,73,139,145,
 - 185,191,236,342,353,430
- Turn-slip stiffness 235,243
- Turning 118,124,146,447
- TYDEX 631
- Tyre characteristics (steady-state):
 - example 4,5
 - brush model 99,109,110,112,116
 - brush model, spin 125,132
 - brush model, camber 127
 - Magic Formula 181,182,183,210
 - Mag. Form. mot.cycle 530,569,584
 - Magic Form. with turn slip 197,439
 - measured 114,169,210,583
 - non-dimensionalised 157

- | | | | |
|----------------------------------|---------------|-----------------------|---|
| similarity method | 168,169 | Vries, de | 472,474,529,578 |
| spin, turn slip | 144,145,192 | Wavelength | 216,371,396,413,483,510 |
| string with tread elements | 266 | Weave mode | 542 |
| tread simulation model | 141-145 | Weighting function | 179,181,191 |
| Tyre dynamics | 277,452 | Weir | 518 |
| Tyre inertia | 277,452,636 | Wet road | 6,186 |
| Tyre models | 84 | Wheel lock | 148,166,349,408 |
| Tyre pull | 202 | Whipple | 517 |
| UMTRI | 85 | Willumeit | 88 |
| Unbalance | 336,337 | Wind-up oscillations | 408 |
| Understeer | 25,37,553,556 | Winkler | 45 |
| Understeer at braking | 51 | Wisselman | 518 |
| Vehicle handling | 16 | Wobble mode | 542 |
| Vehicle model | 8,16 | Yaw velocity response | 35 |
| Vehicle slip angle response | 35 | Zegelaar | 219,412,461,468,471,
477,484,487,491,497,500,505 |
| Vehicle stability, cf. stability | | | |
| Volvo | 172 | | |