

## ■ FEATURES OF 2UZ-FE ENGINE

The 2UZ-FE engine has been able to achieve the following performance through the adoption of the items listed below.

- (1) High performance and reliability
- (2) Low noise and vibration
- (3) Lightweight and compact design
- (4) Good serviceability
- (5) Clean emission and fuel economy

| Item                         |                                                                                        | (1) | (2) | (3) | (4) | (5) |
|------------------------------|----------------------------------------------------------------------------------------|-----|-----|-----|-----|-----|
| Engine Proper                | An upright intake port is used.                                                        | ○   |     | ○   |     |     |
|                              | A taper squish shape is used for combustion chamber.                                   | ○   |     |     |     | ○   |
|                              | The piston skirt is coated with resin.                                                 | ○   | ○   |     |     |     |
|                              | No.1oil pan sub-assembly made of aluminum alloy is used.                               |     | ○   | ○   |     |     |
| Lubrication System           | A water-cooled type engine oil cooler is used.                                         | ○   |     |     |     |     |
| Cooling System               | TOYOTA Genuine SLLC (Super Long Life Coolant) is used as the engine coolant.           |     |     |     | ○   |     |
| Intake and Exhaust System    | A long port intake manifold made of plastic is used.                                   | ○   |     | ○   |     |     |
|                              | The link-less type throttle body is used.                                              |     |     | ○   | ○   |     |
|                              | Stainless steel exhaust manifolds are used.                                            |     |     | ○   |     |     |
|                              | Ceramic type TWCs (Three Way catalytic Converters) are used.                           |     |     |     |     | ○   |
| Fuel System                  | 4-hole type fuel injectors are used to improve the atomization of fuel.                | ○   |     |     |     | ○   |
| Ignition System              | The DIS (Direct Ignition System) makes ignition timing adjustment unnecessary.         | ○   |     |     | ○   | ○   |
| Charging System              | Segment Conductor type generator is used.                                              | ○   |     | ○   |     |     |
| Serpentine Belt Drive System | A serpentine belt drive system is used.                                                |     |     | ○   | ○   |     |
| Engine Control System        | MRE (Magnetic Resistance Element) type camshaft position sensor is used.               | ○   |     |     |     |     |
|                              | The ETCS-i (Electronic Throttle Control System- intelligent) is used.                  | ○   |     |     |     | ○   |
|                              | The VVT-i (Variable Valve Timing-intelligent) system is used.                          | ○   |     |     |     | ○   |
|                              | The ACIS (Acoustic Control Induction System) is used.                                  | ○   |     |     |     | ○   |
|                              | An air injection system is used.<br>(Only for European, Australian and Chinese models) |     |     |     |     | ○   |
|                              | The cranking hold function is used.                                                    | ○   |     |     |     |     |