

MAJOR TECHNICAL SPECIFICATIONS

Item			Area				Europe			
Body Type			Station Wagon (5-Seater)				Station Wagon (7-Seater)			
Vehicle Grade			VX							
Model Code			UZI200L-GMAEKW		VDJ200L-GMTEZW		UZI200L-GNAEKW		UZI200R-GNAEKW	
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	5
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	
		Height	mm (in.)	1910 (75.2)	1910 (75.2)	1910 (75.2)	1910 (75.2)	1910 (75.2)	1910 (75.2)	
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	
	Tread	Front	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	
		Rear	mm (in.)	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)	10
	Room	Length	mm (in.)	1965 (77.4)	1965 (77.4)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)	
		Width	mm (in.)	1615 (63.6)	1615 (63.6)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	15
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	
	Angle of Approach		degrees	30	30	30	30	30	30	
	Angle of Departure		degrees	20	20	20	20	20	20	
	Curb Weight	Front	kg (lb)	1320 to 1380 (2909 to 3042)	1430 to 1480 (3152 to 3263)	1320 to 1380 (2911 to 3042)	1320 to 1380 (2911 to 3042)	1320 to 1380 (2911 to 3042)	1320 to 1380 (2911 to 3042)	20
		Rear	kg (lb)	1190 to 1270 (2623 to 2800)	1165 to 1240 (2567 to 2734)	1230 to 1310 (2711 to 2888)	1230 to 1310 (2711 to 2888)	1230 to 1310 (2711 to 2888)	1230 to 1310 (2711 to 2888)	
		Total	kg (lb)	2510 to 2650 (5533 to 5842)	2595 to 2720 (5719 to 5997)	2550 to 2690 (5622 to 5930)	2550 to 2690 (5622 to 5930)	2550 to 2690 (5622 to 5930)	2550 to 2690 (5622 to 5930)	
Performance	Gross Vehicle Weight	Front	kg (lb)	1435 (3163)	1545 (3405)	1435 (3163)	1435 (3163)	1435 (3163)	1435 (3163)	
		Rear	kg (lb)	1865 (4110)	1755 (3868)	1865 (4110)	1865 (4110)	1865 (4110)	1865 (4110)	
		Total	kg (lb)	3300 (7275)	3300 (7275)	3300 (7275)	3300 (7275)	3300 (7275)	3300 (7275)	
	Fuel Tank Capacity		ℓ (US. gal, Imp. gal)	93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)	25
	Luggage Capacity (VDA)		m ³ (cu.ft.)	0.909 (32.1)	0.909 (32.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	
	Max. Speed		km/h	200	210	200	200	200	200	
	Max. Cruising Speed		km/h	200	210	200	200	200	200	
	Acceleration	0 to 100 km/h	sec.	9.5	8.6	9.5	9.5	9.5	9.5	30
		0 to 400 m	sec.	16.9	16.2	16.9	16.9	16.9	16.9	
	Max. Permissible Speed	1st Gear	km/h	57	51	57	57	57	57	
		2nd Gear	km/h	98	86	98	98	98	98	
		3rd Gear	km/h	143	125	143	143	143	143	
		4th Gear	km/h	200	169	200	200	200	200	35
		5th Gear	km/h	200	210	200	200	200	200	
		6th Gear	km/h	—	210	—	—	—	—	
	Min. Turning Radius	Tyre	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	
		Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	
Engine	Engine Type			2UZ-FE	1VD-FTV	2UZ-FE	2UZ-FE	2UZ-FE	2UZ-FE	40
	No. of Cyls. & Arrangement			8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	
	Valve Mechanism			32-Valve, DOHC with VVT-i	32-Valve, DOHC	32-Valve, DOHC with VVT-i	32-Valve, DOHC with VVT-i	32-Valve, DOHC with VVT-i	32-Valve, DOHC with VVT-i	
	Bore × Stroke		mm (in.)	94.0 × 84.0 (3.70 × 3.31)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	
	Displacement		cm ³ (cu.in.)	4664 (284.5)	4461 (272.2)	4664 (284.5)	4664 (284.5)	4664 (284.5)	4664 (284.5)	
	Compression Ratio			10.0 : 1	16.8 : 1	10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1	
	Fuel System			EFI	Common-rail Type	EFI	EFI	EFI	EFI	45
	Research Octane No. or Cetane No. (Diesel)			95 or higher	48 or higher	95 or higher	95 or higher	95 or higher	95 or higher	
	Max. Output (SAE)		kW@rpm	212@5400	210@3600*2	212@5400	212@5400	212@5400	212@5400	
	Max. Torque (SAE)		N·m@rpm	445@3400	650@1600 to 2800*2	445@3400	445@3400	445@3400	445@3400	
Engine Electrical	Battery Capacity (SHR)		Voltage & Amp. hr.	12-55 (12-64)*3	12-110 (12-128)*4	12-55 (12-64)*3	12-55 (12-64)*3	12-55 (12-64)*3	12-55 (12-64)*3	50
	Alternator Output		Watts	1560, 1800*5	1800, 2160*5	1560, 1800*5	1560, 1800*5	1560, 1800*5	1560, 1800*5	
	Starter Output		kW	2.0	2.7	2.0	2.0	2.0	2.0	
Chassis	Clutch Type			—	—	—	—	—	—	
	Transaxle Type			A750F	AB60F	A750F	A750F	A750F	A750F	
	Gear Ratio	In First		3.520	3.333	3.520	3.520	3.520	3.520	55
		In Second		2.042	1.960	2.042	2.042	2.042	2.042	
		In Third		1.400	1.353	1.400	1.400	1.400	1.400	
		In Fourth		1.000	1.000	1.000	1.000	1.000	1.000	
		In Fifth		0.716	0.728	0.716	0.716	0.716	0.716	
		In Sixth		—	0.588	—	—	—	—	
	Transfer Gear Ratio		H4 / L4	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	60
	Differential Gear Ratio (Front/Rear)			4.100 / 4.100	3.909 / 3.909	4.100 / 4.100	4.100 / 4.100	4.100 / 4.100	4.100 / 4.100	
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	65
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	
	Proportioning Valve Type			—	—	—	—	—	—	
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	70
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard	Standard	Standard	
		Rear		Standard	Standard	Standard	Standard	Standard	Standard	
	Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	
	Steering Gear Ratio			16.7, 14.2 to 17.6*6	16.7, 14.2 to 17.6*6	16.7, 14.2 to 17.6*6	16.7, 14.2 to 17.6*6	16.7, 14.2 to 17.6*6	16.7, 14.2 to 17.6*6	75
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	

*1: 8J Disc Wheel

*2: ECE

*3: Cold area specification models with gasoline engine

*4: Cold area specification models with diesel engine

*5: Models with towing package

*6: Models with VGRS

	Europe		G.C.C. Countries		
	Station Wagon (7-Seater)		Station Wagon (8-Seater)		
	VX		VX	GX	
	VDJ200L-GNTEZW	VDJ200R-GNTEZW	UZJ200L-GNAEKV	GRJ200L-GNANKV	GRJ200L-GNMNKKV
5	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
	1910 (75.2)	1910 (75.2)	1890 (74.3)	1890 (74.3)	1890 (74.3)
	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	1640 (64.5)	1640 (64.5)	1640 (64.5)	1680 (66.1)	1680 (66.1)
10	1635 (64.3)	1635 (64.3)	1635 (64.3)	1675 (65.9)	1675 (65.9)
	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)
	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
15	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
	30	30	30	30	30
	20	20	20	20	20
	1430 to 1480 (3152 to 3263)	1430 to 1480 (3152 to 3263)	1295 to 1320 (2855 to 2910)	1215 to 1305 (2678 to 2876)	1210 to 1300 (2668 to 2866)
20	1205 to 1250 (2657 to 2756)	1205 to 1250 (2657 to 2756)	1270 to 1390 (2800 to 3064)	1220 to 1320 (2690 to 2911)	1215 to 1315 (2678 to 2899)
	2635 to 2730 (5809 to 6019)	2635 to 2730 (5809 to 6019)	2565 to 2710 (5655 to 5974)	2435 to 2625 (5368 to 5787)	2425 to 2615 (5346 to 5765)
	1545 (3406)	1545 (3406)	1390 (3064)	1350 (2976)	1350 (2976)
	1755 (3869)	1755 (3869)	1910 (4211)	1910 (4211)	1910 (4211)
	3300 (7275)	3300 (7275)	3300 (7275)	3260 (7187)	3260 (7187)
25	93 (24.6, 20.5)	93 (24.6, 20.5)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)
	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)
	210	210	200	190	200
	210	210	200	190	200
	8.6	8.6	9.5	10.7	11.0
30	16.2	16.2	16.9	17.6	17.6
	51	51	57	56	56
	86	86	98	96	96
	125	125	143	140	140
	169	169	200	190	200
35	210	210	200	190	200
	210	210	—	—	—
	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
	1VD-FTV	1VD-FTV	2UZ-FE	1GR-FE	1GR-FE
40	8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	6-Cylinder, V Type	6-Cylinder, V Type
	32-Valve, DOHC	32-Valve, DOHC	32-Valve, DOHC with VVT-i	24-Valve, DOHC with VVT-i	24-Valve, DOHC with VVT-i
	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)
	4461 (272.2)	4461 (272.2)	4664 (284.5)	3956 (241.4)	3956 (241.4)
	16.8 : 1	16.8 : 1	10.0 : 1	10.0 : 1	10.0 : 1
45	Common-rail Type	Common-rail Type	EFI	EFI	EFI
	48 or higher	48 or higher	91 or higher	95 or higher	95 or higher
	210@3600*2	210@3600*2	202@5400	179@5200*2	179@5200*2
	650@1600 to 2800*2	650@1600 to 2800*2	410@3400	376@3800*2	376@3800*2
	12-110 (12-128)*4	12-110 (12-128)*4	12-55	12-55	12-55
50	1800, 2160*5	1800, 2160*5	1800	1200	1200
	2.7	2.7	1.4	1.6	1.6
	—	—	—	—	Dry, Single Plate, Diaphragm
	AB60F	AB60F	A750F	A750F	H150F
	3.333	3.333	3.520	3.520	4.529
55	1.960	1.960	2.042	2.042	2.464
	1.353	1.353	1.400	1.400	1.490
	1.000	1.000	1.000	1.000	1.000
	0.728	0.728	0.716	0.716	0.881
	0.588	0.588	—	—	—
60	3.061	3.061	3.224	3.224	4.313
	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618
	3.909 / 3.909	3.909 / 3.909	4.100 / 4.100	4.100 / 4.100	4.100 / 4.100
	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
65	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
	—	—	—	—	—
	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
70	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Standard	Standard	Standard	Standard	Standard
	Standard	Standard	Standard	Standard	Standard
	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	16.7, 14.2 to 17.6*6	16.7, 14.2 to 17.6*6	16.7	16.7	16.7
75	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item			Area				G.C.C. Countries			
Body Type			Station Wagon (8-Seater)				Station Wagon (9-Seater)			
Vehicle Grade			GX							
Model Code			UZI200L-GNANKV		VDJ200L-GNTNZV		VDJ200L-GNMNZV		GRJ200L-GPANKV	
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	5
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	
		Height	mm (in.)	1890 (74.3)	1890 (74.3)	1890 (74.3)	1890 (74.3)	1890 (74.3)	1890 (74.3)	
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	
	Tread	Front	mm (in.)	1680 (66.1)	1680 (66.1)	1680 (66.1)	1680 (66.1)	1680 (66.1)	1680 (66.1)	10
		Rear	mm (in.)	1675 (65.9)	1675 (65.9)	1675 (65.9)	1675 (65.9)	1675 (65.9)	1675 (65.9)	
	Room	Length	mm (in.)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2905 (114.4)	2905 (114.4)	
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	15
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	
	Angle of Approach		degrees	30	30	30	30	30	30	
	Angle of Departure		degrees	20	20	20	20	20	20	
	Curb Weight	Front	kg (lb)	1285 to 1370 (2833 to 3020)	1400 to 1490 (3087 to 3285)	1390 to 1480 (3065 to 3263)	1225 to 1305 (2701 to 2877)	1225 to 1305 (2701 to 2877)	1225 to 1305 (2701 to 2877)	20
		Rear	kg (lb)	1245 to 1345 (2745 to 2965)	1215 to 1260 (2678 to 2778)	1215 to 1260 (2678 to 2778)	1200 to 1285 (2645 to 2833)	1200 to 1285 (2645 to 2833)	1200 to 1285 (2645 to 2833)	
		Total	kg (lb)	2530 to 2715 (5578 to 5985)	2615 to 2750 (5765 to 6063)	2605 to 2740 (5743 to 6041)	2425 to 2590 (5346 to 5710)	2425 to 2590 (5346 to 5710)	2425 to 2590 (5346 to 5710)	
Performance	Gross Vehicle Weight	Front	kg (lb)	1440 (3175)	1570 (3461)	1550 (3417)	1350 (2976)	1350 (2976)	1350 (2976)	
		Rear	kg (lb)	1860 (4100)	1730 (3814)	1750 (3858)	1910 (4211)	1910 (4211)	1910 (4211)	
		Total	kg (lb)	3300 (7275)	3300 (7275)	3300 (7275)	3260 (7187)	3260 (7187)	3260 (7187)	
	Fuel Tank Capacity		ℓ (US. gal, Imp. gal)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	25
	Luggage Capacity (VDA)		m ³ (cu.ft.)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.06 (2.1)	0.06 (2.1)	0.06 (2.1)	
	Max. Speed		km/h	200	210	170	190	190	190	
	Max. Cruising Speed		km/h	200	210	170	190	190	190	
	Acceleration	0 to 100 km/h	sec.	9.5	8.6	12.0	10.7	10.7	10.7	30
		0 to 400 m	sec.	16.9	16.2	18.2	17.6	17.6	17.6	
	Max. Permissible Speed	1st Gear	km/h	57	51	35	56	56	56	
		2nd Gear	km/h	98	86	64	96	96	96	
		3rd Gear	km/h	143	125	106	140	140	140	
		4th Gear	km/h	200	169	158	190	190	190	35
		5th Gear	km/h	200	210	170	190	190	190	
		6th Gear	km/h	—	210	—	—	—	—	
	Min. Turning Radius	Tyre	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	
		Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	
Engine	Engine Type			2UZ-FE	1VD-FTV	1VD-FTV	1GR-FE	1GR-FE	1GR-FE	40
	No. of Cyls. & Arrangement			8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	6-Cylinder, V Type	6-Cylinder, V Type	6-Cylinder, V Type	
	Valve Mechanism			32-Valve, DOHC with VVT-i	32-Valve, DOHC	32-Valve, DOHC	24-Valve, DOHC with VVT-i	24-Valve, DOHC with VVT-i	24-Valve, DOHC with VVT-i	
	Bore × Stroke		mm (in.)	94.0 × 84.0 (3.70 × 3.31)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	
	Displacement		cm ³ (cu.in.)	4664 (284.5)	4461 (272.2)	4461 (272.2)	3956 (241.4)	3956 (241.4)	3956 (241.4)	
	Compression Ratio			10.0 : 1	16.8 : 1	16.8 : 1	10.0 : 1	10.0 : 1	10.0 : 1	45
	Fuel System			EFI	Common-rail Type	Common-rail Type	EFI	EFI	EFI	
	Research Octane No. or Cetane No. (Diesel)			91 or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	95 or higher	95 or higher	95 or higher	
	Max. Output (SAE)		kW@rpm	202@5400	173@3200* ³	162@3600* ³	179@5200* ³	179@5200* ³	179@5200* ³	
	Max. Torque (SAE)		N·m@rpm	410@3400	615@1800 to 2200* ³	430@1200 to 3600* ³	376@3800* ³	376@3800* ³	376@3800* ³	
Engine Electrical	Battery Capacity (SHR)		Voltage & Amp. hr.	12-55	12-110	12-110	12-55	12-55	12-55	50
	Alternator Output		Watts	1800	1560	1560	1200	1200	1200	
	Starter Output		kW	1.4	2.7	2.7	1.6	1.6	1.6	
Chassis	Clutch Type			—	—	Dry, Single Plate, Diaphragm	—	—	—	
	Transaxle Type			A750F	AB60F	H150F	A750F	A750F	A750F	
	Gear Ratio	In First		3.520	3.333	4.529	3.520	3.520	3.520	55
		In Second		2.042	1.960	2.464	2.042	2.042	2.042	
		In Third		1.400	1.353	1.490	1.400	1.400	1.400	
		In Fourth		1.000	1.000	1.000	1.000	1.000	1.000	
		In Fifth		0.716	0.728	0.881	0.716	0.716	0.716	
		In Sixth		—	0.588	—	—	—	—	
	Transfer Gear Ratio		H4 / L4	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	60
	Differential Gear Ratio (Front/Rear)			4.100 / 4.100	3.909 / 3.909	3.909 / 3.909	4.100 / 4.100	4.100 / 4.100	4.100 / 4.100	
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	65
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	
	Proportioning Valve Type			—	—	—	—	—	—	
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	70
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard	Standard	Standard	
		Rear		Standard	Standard	Standard	Standard	Standard	Standard	
	Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	
	Steering Gear Ratio			16.7	16.7	16.7	16.7	16.7	16.7	75
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	

*1: 8J Disc Wheel

*2: Option

*3: ECE

*4: Models with multi-display

	G.C.C. Countries		Australia		
	Station Wagon (9-Seater)		Station Wagon (8-Seater)		
	GX		VX		GX
	GRJ200L-GPMNKV	VDJ200L-GPMNZV	UJZ200R-GNAEKQ	VDJ200R-GNTEZQ	UJZ200R-GNANKQ
5	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
	1890 (74.3)	1890 (74.3)	1905 (74.9)	1905 (74.9)	1905 (74.9)
	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
10	1680 (66.1)	1680 (66.1)	1640 (64.5)	1640 (64.5)	1680 (66.1)
	1675 (65.9)	1675 (65.9)	1635 (64.3)	1635 (64.3)	1675 (65.9)
	2905 (114.4)	2905 (114.4)	2715 (106.8)	2715 (106.8)	2715 (106.8)
	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
15	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
20	30	30	30	30	30
	20	20	20	20	20
	1220 to 1300 (2690 to 2866)	1400 to 1405 (3087 to 3097)	1320 to 1340 (2910 to 2954)	1430 to 1450 (3153 to 3197)	1300 to 1340 (2866 to 2954)
	1195 to 1280 (2634 to 2822)	1200 to 1255 (2645 to 2767)	1290 to 1325 (2844 to 2921)	1245 to 1270 (2745 to 2800)	1255 to 1295 (2767 to 2855)
25	2415 to 2580 (5324 to 5688)	2600 to 2660 (5732 to 5864)	2610 to 2665 (5754 to 5875)	2675 to 2720 (5898 to 5997)	2555 to 2635 (5633 to 5809)
	1350 (2976)	1460 (3219)	1390 (3064)	1520 (3351)	1390 (3064)
	1910 (4211)	1840 (4056)	1910 (4211)	1780 (3924)	1910 (4211)
	3260 (7187)	3300 (7275)	3300 (7275)	3300 (7275)	3300 (7275)
30	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)* ²	138 (36.5, 30.4)
	0.06 (2.1)	0.06 (2.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)
	200	170	200	210	200
	200	170	200	210	200
35	11.0	12.0	9.5	8.6	9.5
	17.8	18.2	16.9	16.2	16.9
	43	35	57	51	57
	78	64	98	86	98
40	130	106	143	125	143
	193	158	200	169	200
	200	170	200	210	200
	—	—	—	210	—
45	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
	1GR-FE	1VD-FTV	2UZ-FE	1VD-FTV	2UZ-FE
	6-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type
50	24-Valve, DOHC with VVT-i	32-Valve, DOHC	32-Valve, DOHC with VVT-i	32-Valve, DOHC	32-Valve, DOHC with VVT-i
	94.0 × 95.0 (3.70 × 3.74)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 84.0 (3.70 × 3.31)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 84.0 (3.70 × 3.31)
	3956 (241.4)	4461 (272.2)	4664 (284.5)	4461 (272.2)	4664 (284.5)
	10.0 : 1	16.8 : 1	10.0 : 1	16.8 : 1	10.0 : 1
55	EFI	Common-rail Type	EFI	Common-rail Type	EFI
	95 or higher	50 (Cetane Index 45) or higher	91 or higher	50 or higher	91 or higher
	179@5200* ³	162@3600* ³	202@5400	195@3400* ³	202@5400
	376@3800* ³	430@1200 to 3600* ³	410@3400	650@1600 to 2600* ³	410@3400
60	12-55	12-110	12-55	12-110	12-55
	1200	1560	1560, 1800* ⁴	1800	1560
	1.6	2.7	1.4	2.7	1.4
	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	—	—
65	H150F	H150F	A750F	AB60F	A750F
	4.529	4.529	3.520	3.333	3.520
	2.464	2.464	2.042	1.960	2.042
	1.490	1.490	1.400	1.353	1.400
70	1.000	1.000	1.000	1.000	1.000
	0.881	0.881	0.716	0.728	0.716
	—	—	—	0.588	—
	4.313	4.313	3.224	3.061	3.224
75	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618
	4.100 / 4.100	3.909 / 3.909	4.100 / 4.100	3.909 / 3.909	4.100 / 4.100
	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
75	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
	—	—	—	—	—
75	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Standard	Standard	Standard	Standard	Standard
	Standard	Standard	Standard	Standard	Standard
75	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	16.7	16.7	16.7	16.7	16.7
	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item			Area	Australia	China			
Body Type				Station Wagon (8-Seater)	Station Wagon (8-Seater)			
Vehicle Grade				GX	VX	GX		
Model Code				VDJ200R-GNTNZQ	UZJ200L-GNAEKC	GRJ200L-GNANKC	GRJ200L-GNMNKC	
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	5100 (200.6)	5100 (200.6)	5100 (200.6)	
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	
		Height	mm (in.)	1965 (77.3)	1945 (76.5)	1945 (76.5)	1945 (76.5)	
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	
	Tread	Front	mm (in.)	1680 (66.1)	1640 (64.5)	1640 (64.5)	1640 (64.5)	
		Rear	mm (in.)	1675 (65.9)	1635 (64.3)	1635 (64.3)	1635 (64.3)	
	Room	Length	mm (in.)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)	
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	
	Overhang	Front	mm (in.)	930 (36.6)	920 (36.2)	920 (36.2)	920 (36.2)	
		Rear	mm (in.)	1170 (46.1)	1180 (46.4)	1180 (46.4)	1180 (46.4)	
	Min. Running Ground Clearance			mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)	
	Angle of Approach			degrees	30	30	30	
	Angle of Departure			degrees	20	20	20	
	Curb Weight	Front	kg (lb)	1410 to 1450 (3108 to 3197)	1355 to 1360 (2987 to 2999)	1245 to 1335 (2745 to 2943)	1240 to 1330 (2734 to 2933)	
		Rear	kg (lb)	1220 to 1250 (2690 to 2756)	1295 (2855)	1285 to 1270 (2833 to 2800)	1280 to 1265 (2821 to 2788)	
		Total	kg (lb)	2630 to 2700 (5798 to 5953)	2650 to 2655 (5842 to 5854)	2530 to 2605 (5578 to 5743)	2520 to 2595 (5555 to 5721)	
	Gross Vehicle Weight	Front	kg (lb)	1515 (3340)	1425 (3141)	1385 (3053)	1385 (3053)	
		Rear	kg (lb)	1785 (3935)	1875 (4134)	1875 (4134)	1875 (4134)	
		Total	kg (lb)	3300 (7275)	3300 (7275)	3260 (7187)	3260 (7187)	
Performance	Fuel Tank Capacity			ℓ (US. gal, Imp. gal)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	
	Luggage Capacity (VDA)			m ³ (cu.ft.)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	
	Max. Speed			km/h	210	200	190	
	Max. Cruising Speed			km/h	210	200	190	
	Acceleration	0 to 100 km/h	sec.	8.6	9.5	10.7	11.0	
		0 to 400 m	sec.	16.2	16.9	17.6	17.8	
	Max. Permissible Speed	1st Gear	km/h	51	57	56	43	
		2nd Gear	km/h	86	98	96	78	
		3rd Gear	km/h	125	143	140	130	
		4th Gear	km/h	169	200	190	193	
		5th Gear	km/h	210	200	190	200	
		6th Gear	km/h	210	—	—	—	
	Min. Turning Radius	Tyre	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	
		Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	
Engine	Engine Type			1VD-FTV	2UZ-FE	1GR-FE	1GR-FE	
	No. of Cyls. & Arrangement			8-Cylinder, V Type	8-Cylinder, V Type	6-Cylinder, V Type	6-Cylinder, V Type	
	Valve Mechanism			32-Valve, DOHC	32-Valve, DOHC with VVT-i	24-Valve, DOHC with VVT-i	24-Valve, DOHC with VVT-i	
	Bore × Stroke			mm (in.)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 95.0 (3.70 × 3.74)	
	Displacement			cm ³ (cu.in.)	4461 (272.2)	4664 (284.5)	3956 (241.4)	
	Compression Ratio			16.8 : 1	10.0 : 1	10.0 : 1	10.0 : 1	
	Fuel System			Common-rail Type	EFI	EFI	EFI	
	Research Octane No. or Cetane No. (Diesel)			50 (Cetane Index 45) or higher	91 or higher	95 or higher	95 or higher	
	Max. Output (SAE)			kW@rpm	195@3400*4	202@5400	179@5200*4	
	Max. Torque (SAE)			N·m@rpm	650@1600 to 2600*4	410@3400	376@3800*4	
Engine Interf. Unit	Battery Capacity (SHR)			Voltage & Amp. hr.	12-110	12-64	12-64	
	Alternator Output			Watts	1800	1800	1200	
	Starter Output			kW	2.7	2.0	2.0	
Chassis	Clutch Type			—	—	—	Dry, Single Plate, Diaphragm	
	Transaxle Type			AB60F	A750F	A750F	H150F	
	Gear Ratio	In First		3.333	3.520	3.520	4.529	
		In Second		1.960	2.042	2.042	2.464	
		In Third		1.353	1.400	1.400	1.490	
		In Fourth		1.000	1.000	1.000	1.000	
		In Fifth		0.728	0.716	0.716	0.881	
		In Sixth		0.588	—	—	—	
	Transfer Gear Ratio			H4 / L4	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	
	Differential Gear Ratio (Front/Rear)				3.909 / 3.909	4.100 / 4.100	4.100 / 4.100	
	Differential Gear Size (Front/Rear)			mm (in.)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	
	Proportioning Valve Type			—	—	—	—	
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard	
		Rear		Standard	Standard	Standard	Standard	
	Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	
	Steering Gear Ratio				16.7	16.7	16.7	
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	

*1: 8J Disc Wheel

*2: Option

*3: Option except South African package models

*4: ECE

*5: Cold area specification models

	China	General Countries			
	Station Wagon (8-Seater)	Station Wagon (5-Seater)			
	GX	GX			
	UZJ200L-GNANKC	GRJ200L-GMMNK	GRJ200R-GMMNK	VDJ200L-GMMNZ	VDJ200R-GMMNZ
5	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
	1840 (72.4)	1905 (74.9)	1905 (74.9)	1905 (74.9)	1905 (74.9)
	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	1640 (64.5)	1680 (66.1)	1680 (66.1)	1680 (66.1)	1680 (66.1)
10	1635 (64.3)	1675 (65.9)	1675 (65.9)	1675 (65.9)	1675 (65.9)
	2715 (106.8)	1965 (77.4)	1965 (77.4)	1965 (77.4)	2715 (106.8)
	1640 (64.5)	1615 (63.6)	1615 (63.6)	1615 (63.6)	1640 (64.5)
	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	920 (36.2)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
15	1180 (46.2)	1175 (46.2)	1175 (46.2)	1170 (46.1)	1170 (46.1)
	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
	30	30	30	30	30
	20	20	20	20	20
	1340 to 1430 (2954 to 3153)	1230 to 1300 (2711 to 2866)	1235 to 1300 (2722 to 2866)	1410 to 1495 (3108 to 3295)	1410 to 1480 (3108 to 3263)
20	1280 to 1265 (2821 to 2788)	1120 to 1215 (2469 to 2678)	1120 to 1215 (2469 to 2678)	1140 to 1220 (2514 to 2690)	1140 to 1255 (2514 to 2767)
	2620 to 2695 (5775 to 5941)	2350 to 2515 (5180 to 5544)	2355 to 2515 (5191 to 5544)	2550 to 2715 (5622 to 5985)	2550 to 2735 (5622 to 6030)
	1495 (3296)	1340 (2954)	1340 (2954)	1520 (3351)	1520 (3351)
	1805 (3979)	1920 (4233)	1920 (4233)	1780 (3924)	1780 (3924)
	3300 (7275)	3260 (7187)	3260 (7187)	3300 (7275)	3300 (7275)
25	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)* ²	93 (24.6, 20.5), 138 (36.5, 30.4)* ³	93 (24.6, 20.5), 138 (36.5, 30.4)* ²	93 (24.6, 20.5), 138 (36.5, 30.4)* ²
	0.259 (9.1)	0.909 (32.1)	0.909 (32.1)	0.909 (32.1)	0.909 (32.1)
	200	200	200	170	170
	200	200	200	170	170
	9.5	11.0	11.0	12.0	12.0
30	16.9	17.8	17.8	18.2	18.2
	57	43	43	35	35
	98	78	78	64	64
	143	130	130	106	106
	200	193	193	158	158
35	200	200	200	170	170
	—	—	—	—	—
	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
	2UZ-FE	1GR-FE	1GR-FE	1VD-FTV	1VD-FTV
40	8-Cylinder, V Type	6-Cylinder, V Type	6-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type
	32-Valve, DOHC with VVT-i	24-Valve, DOHC with VVT-i	24-Valve, DOHC with VVT-i	32-Valve, DOHC	32-Valve, DOHC
	94.0 × 84.0 (3.70 × 3.31)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
	4664 (284.5)	3956 (241.4)	3956 (241.4)	4461 (272.2)	4461 (272.2)
	10.0 : 1	10.0 : 1	10.0 : 1	16.8 : 1	16.8 : 1
45	EFI	EFI	EFI	Common-rail Type	Common-rail Type
	91 or higher	95 or higher	95 or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher
	202@5400	179@5200* ⁴	179@5200* ⁴	162@3600* ⁴	162@3600* ⁴
	410@3400	376@3800* ⁴	376@3800* ⁴	430@1200 to 3600* ⁴	430@1200 to 3600* ⁴
	12-64	12-55	12-55	12-110	12-110
50	1800	1200	1200	1560	1560
	2.0	1.6, 2.0* ⁵	1.6, 2.0* ⁵	2.7	2.7
	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	A750F	H150F	H150F	H150F	H150F
	3.520	4.529	4.529	4.529	4.529
55	2.042	2.464	2.464	2.464	2.464
	1.400	1.490	1.490	1.490	1.490
	1.000	1.000	1.000	1.000	1.000
	0.716	0.881	0.881	0.881	0.881
	—	—	—	—	—
60	3.224	4.313	4.313	4.313	4.313
	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618
	4.100 / 4.100	4.100 / 4.100	4.100 / 4.100	3.909 / 3.909	3.909 / 3.909
	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
65	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
	—	—	—	—	—
	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
70	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Standard	Standard	Standard	Standard	Standard
	Standard	Standard	Standard	Standard	Standard
	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	16.7	16.7	16.7	16.7	16.7
75	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item			Area	General Countries			
Body Type				Station Wagon (8-Seater)			
Vehicle Grade				VX		GX	
Model Code				UZI200L-GNAEK	VDJ200L-GNTEZ	VDJ200R-GNTEZ	GRJ200L-GNMNK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
		Height	mm (in.)	1905 (74.9)	1905 (74.9)	1905 (74.9)	1905 (74.9)
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	Tread	Front	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1680 (66.1)
		Rear	mm (in.)	1635 (64.3)	1635 (64.3)	1635 (64.3)	1675 (65.9)
	Room	Length	mm (in.)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1175 (46.2)
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	20	20	20	20
	Curb Weight	Front	kg (lb)	1310 to 1335 (2888 to 2944)	1425 to 1460 (3141 to 3219)	1425 to 1455 (3141 to 3208)	1225 to 1300 (2701 to 2866)
		Rear	kg (lb)	1290 to 1415 (2844 to 3119)	1195 to 1310 (2634 to 2888)	1195 to 1310 (2634 to 2888)	1165 to 1285 (2568 to 2833)
	Gross Vehicle Weight	Total	kg (lb)	2600 to 2750 (5732 to 6023)	2620 to 2770 (5775 to 6107)	2620 to 2765 (5775 to 6096)	2390 to 2585 (5269 to 5699)
Front		kg (lb)	1415 (3119)	1490 (3285)	1490 (3285)	1340 (2954)	
Rear		kg (lb)	1885 (4156)	1810 (3990)	1810 (3990)	1920 (4233)	
Total		kg (lb)	3300 (7275)	3300 (7275)	3300 (7275)	3260 (7187)	
Fuel Tank Capacity		ℓ (US. gal, Imp. gal)	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*2	93 (24.6, 20.5), 138 (36.5, 30.4)*2	93 (24.6, 20.5), 138 (36.5, 30.4)*2	
Luggage Capacity (VDA)		m³ (cu.ft.)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	
Performance	Max. Speed		km/h	200	210	210	200
	Max. Cruising Speed		km/h	200	210	210	200
	Acceleration	0 to 100 km/h	sec.	9.5	8.6	8.6	11.0
		0 to 400 m	sec.	16.9	16.2	16.2	17.8
	Max. Permissible Speed	1st Gear	km/h	57	51	51	43
		2nd Gear	km/h	98	86	86	78
		3rd Gear	km/h	143	125	125	130
		4th Gear	km/h	200	169	169	193
		5th Gear	km/h	200	210	210	200
		6th Gear	km/h	—	210	210	—
Min. Turning Radius	Tyre	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	
	Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	
Engine	Engine Type		2UZ-FE	1VD-FTV	1VD-FTV	1GR-FE	
	No. of Cyls. & Arrangement		8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	6-Cylinder, V Type	
	Valve Mechanism		32-Valve, DOHC with VVT-i	32-Valve, DOHC	32-Valve, DOHC	24-Valve, DOHC with VVT-i	
	Bore × Stroke		mm (in.)	94.0 × 84.0 (3.70 × 3.31)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 95.0 (3.70 × 3.74)
	Displacement		cm³ (cu.in.)	4664 (284.5)	4461 (272.2)	4461 (272.2)	3956 (241.4)
	Compression Ratio		10.0 : 1	16.8 : 1	16.8 : 1	10.0 : 1	
	Fuel System		EFI	Common-rail Type	Common-rail Type	EFI	
	Research Octane No. or Cetane No. (Diesel)		91 or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	95 or higher	
	Max. Output (SAE)		kW@rpm	202@5400	173@3200*4	173@3200*4	179@5200*4
Engine Electrical	Max. Torque (SAE)		N·m@rpm	410@3400	615@1800 to 2200*4	615@1800 to 2200*4	376@3800*4
	Battery Capacity (5HR)		Voltage & Amp. hr.	12-55	12-110	12-110	12-55
	Alternator Output		Watts	1560, 1800*5	1800	1800	1200
Starter Output		kW	1.4	2.7	2.7	1.6, 2.0*6	
Chassis	Clutch Type		—	—	—	—	Dry, Single Plate, Diaphragm
	Transaxle Type		A750F	AB60F	AB60F	H150F	
	Gear Ratio	In First		3.520	3.333	3.333	4.529
		In Second		2.042	1.960	1.960	2.464
		In Third		1.400	1.353	1.353	1.490
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.716	0.728	0.728	0.881
		In Sixth		—	0.588	0.588	—
		In Reverse		3.224	3.061	3.061	4.313
	Transfer Gear Ratio		H4 / L4	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618
	Differential Gear Ratio (Front/Rear)			4.100 / 4.100	3.909 / 3.909	3.909 / 3.909	4.100 / 4.100
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Stabilizer Bar	Front		Standard	Standard	Standard	Standard	
	Rear		Standard	Standard	Standard	Standard	
Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	
Steering Gear Ratio			16.7	16.7	16.7	16.7	
Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	

*1: 8J Disc Wheel

*2: Option

*3: Option except South African package models

*4: ECE

*5: Models with towing package

*6: Cold area specification models

General Countries				
Station Wagon (8-Seater)				
GX				
	GRJ200R-GNMNK	VDJ200L-GNTNZ	VDJ200R-GNTNZ	VDJ200L-GNMNZ
5	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
	1905 (74.9)	1905 (74.9)	1905 (74.9)	1905 (74.9)
	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
10	1680 (66.1)	1680 (66.1)	1680 (66.1)	1680 (66.1)
	1675 (65.9)	1675 (65.9)	1675 (65.9)	1675 (65.9)
	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)
	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
15	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
	1175 (46.2)	1170 (46.1)	1170 (46.1)	1170 (46.1)
	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
20	30	30	30	30
	20	20	20	20
	1220 to 1300 (2690 to 2866)	1430 to 1505 (3152 to 3318)	1430 to 1505 (3152 to 3318)	1400 to 1490 (3087 to 3285)
	1155 to 1285 (2546 to 2833)	1200 to 1295 (2645 to 2855)	1200 to 1295 (2645 to 2855)	1175 to 1260 (2590 to 2778)
25	2375 to 2585 (5236 to 5699)	2630 to 2800 (5797 to 6273)	2630 to 2800 (5797 to 6273)	2575 to 2750 (5677 to 6063)
	1340 (2954)	1550 (3417)	1550 (3417)	1520 (3351)
	1920 (4233)	1750 (3858)	1750 (3858)	1780 (3924)
	3260 (7187)	3300 (7275)	3300 (7275)	3300 (7275)
30	93 (24.6, 20.5), 138 (36.5, 30.4)* ³	93 (24.6, 20.5), 138 (36.5, 30.4)* ²	93 (24.6, 20.5), 138 (36.5, 30.4)* ²	93 (24.6, 20.5), 138 (36.5, 30.4)* ²
	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)
	200	210	210	170
	200	210	210	170
35	11.0	8.6	8.6	12.0
	17.8	16.2	16.2	18.2
	43	51	51	35
	78	86	86	64
40	130	125	125	106
	193	169	169	158
	200	210	210	170
	—	210	210	—
45	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
	1GR-FE	1VD-FTV	1VD-FTV	1VD-FTV
	6-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type
50	24-Valve, DOHC with VVT-i	32-Valve, DOHC	32-Valve, DOHC	32-Valve, DOHC
	94.0 × 95.0 (3.70 × 3.74)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
	3956 (241.4)	4461 (272.2)	4461 (272.2)	4461 (272.2)
	10.0 : 1	16.8 : 1	16.8 : 1	16.8 : 1
55	EFI	Common-rail Type	Common-rail Type	Common-rail Type
	95 or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher
	179@5200* ⁴	173@3200* ⁴	173@3200* ⁴	162@3600* ⁴
	376@3800* ⁴	615@1800 to 2200* ⁴	615@1800 to 2200* ⁴	430@1200 to 3600* ⁴
60	12-55	12-110	12-110	12-110
	1200	1560	1560	1560
	1.6, 2.0* ⁶	2.7	2.7	2.7
	Dry, Single Plate, Diaphragm	—	—	Dry, Single Plate, Diaphragm
65	H150F	AB60F	AB60F	H150F
	4.529	3.333	3.333	4.529
	2.464	1.960	1.960	2.464
	1.490	1.353	1.353	1.490
70	1.000	1.000	1.000	1.000
	0.881	0.728	0.728	0.881
	—	0.588	0.588	—
	4.313	3.061	3.061	4.313
75	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618	1.000 / 2.618
	4.100 / 4.100	3.909 / 3.909	3.909 / 3.909	3.909 / 3.909
	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
75	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Hydraulic	Hydraulic	Hydraulic	Hydraulic
	—	—	—	—
75	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Standard	Standard	Standard	Standard
	Standard	Standard	Standard	Standard
75	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	16.7	16.7	16.7	16.7
	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item			Area	General Countries		
Body Type				Station Wagon (9-Seater)		
Vehicle Grade				GX		
Model Code				GRJ200L-GPMNK	VDJ200L-GPMNZ	VDJ200R-GPMNZ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	4950 (194.9)	4950 (194.9)
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)
		Height	mm (in.)	1905 (74.9)	1905 (74.9)	1905 (74.9)
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	Tread	Front	mm (in.)	1680 (66.1)	1680 (66.1)	1680 (66.1)
		Rear	mm (in.)	1675 (65.9)	1675 (65.9)	1675 (65.9)
	Room	Length	mm (in.)	2715 (106.8)	2715 (106.8)	2715 (106.8)
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)
	Angle of Approach		degrees	30	30	30
	Angle of Departure		degrees	20	20	20
	Curb Weight	Front	kg (lb)	1230 to 1290 (2711 to 2844)	1410 to 1480 (3108 to 3263)	1410 to 1475 (3108 to 3252)
		Rear	kg (lb)	1140 to 1230 (2513 to 2711)	1160 to 1250 (2558 to 2756)	1160 to 1250 (2558 to 2756)
	Gross Vehicle Weight	Total	kg (lb)	2370 to 2520 (5224 to 5555)	2570 to 2730 (5666 to 6019)	2570 to 2725 (5666 to 6008)
		Front	kg (lb)	1340 (2954)	1520 (3351)	1520 (3351)
		Rear	kg (lb)	1920 (4233)	1780 (3924)	1780 (3924)
		Total	kg (lb)	3260 (7187)	3300 (7275)	3300 (7275)
	Fuel Tank Capacity		ℓ (US. gal, Imp. gal)	93 (24.6, 20.5), 138 (36.5, 30.4)* ²	93 (24.6, 20.5), 138 (36.5, 30.4)* ²	93 (24.6, 20.5), 138 (36.5, 30.4)* ²
	Luggage Capacity (VDA)		m ³ (cu.ft.)	0.06 (2.1)	0.06 (2.1)	0.06 (2.1)
Performance	Max. Speed		km/h	200	170	170
	Max. Cruising Speed		km/h	200	170	170
	Acceleration	0 to 100 km/h	sec.	11.0	12.0	12.0
		0 to 400 m	sec.	17.8	18.2	18.2
	Max. Permissible Speed	1st Gear	km/h	43	35	35
		2nd Gear	km/h	78	64	64
		3rd Gear	km/h	130	106	106
		4th Gear	km/h	193	158	158
		5th Gear	km/h	200	170	170
	Min. Turning Radius	Tyre	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
Body		m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	
Engine	Engine Type		1GR-FE	1VD-FTV	1VD-FTV	
	No. of Cyls. & Arrangement		6-Cylinder, V Type	8-Cylinder, V Type	8-Cylinder, V Type	
	Valve Mechanism		24-Valve, DOHC with VVT-i	32-Valve, DOHC	32-Valve, DOHC	
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	86.0 × 96.0 (3.39 × 3.78)	
	Displacement		cm ³ (cu.in.)	3956 (241.4)	4461 (272.2)	
	Compression Ratio		10.0 : 1	16.8 : 1	16.8 : 1	
	Fuel System		EFI	Common-rail Type	Common-rail Type	
	Research Octane No. or Cetane No. (Diesel)		95 or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	
	Max. Output (SAE)		kW@rpm	179@5200* ³	162@3600* ³	
Engine Electrical	Max. Torque (SAE)		N·m@rpm	376@3800* ³	430@1200 to 3600* ³	
	Battery Capacity (5HR)		Voltage & Amp. hr.	12-55	12-110	
	Alternator Output		Watts	1200	1560	
Starter Output		kW	1.6	2.7		
Chassis	Clutch Type		Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	
	Transaxle Type		H150F	H150F	H150F	
	Gear Ratio	In First	4.529	4.529	4.529	
		In Second	2.464	2.464	2.464	
		In Third	1.490	1.490	1.490	
		In Fourth	1.000	1.000	1.000	
		In Fifth	0.881	0.881	0.881	
		In Sixth	—	—	—	
	Transfer Gear Ratio		H4 / L4	1.000 / 2.618	1.000 / 2.618	
	Differential Gear Ratio (Front/Rear)		4.100 / 4.100	3.909 / 3.909	3.909 / 3.909	
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7) / 241 (9.5)	220 (8.7) / 241 (9.5)	
	Brake Type	Front	Ventilated Disc	Ventilated Disc	Ventilated Disc	
		Rear	Ventilated Disc	Ventilated Disc	Ventilated Disc	
	Parking Brake Type		Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	
	Brake Booster Type		Hydraulic	Hydraulic	Hydraulic	
	Proportioning Valve Type		—	—	—	
	Suspension Type	Front	Double-wishbone	Double-wishbone	Double-wishbone	
		Rear	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	
	Stabilizer Bar	Front	Standard	Standard	Standard	
		Rear	Standard	Standard	Standard	
	Steering Gear Type		Rack & Pinion	Rack & Pinion	Rack & Pinion	
	Steering Gear Ratio		16.7	16.7	16.7	
	Power Steering Type		Hydraulic	Hydraulic	Hydraulic	

*1: 8J Disc Wheel

*2: Option

*3: ECE