

■ PERFORMANCE AND SPECIFICATION

1. Performance

► Front Air Conditioning Unit ◀

Heater	Heat Output	W	5890
	Air Flow Volume	m ³ /h	360
	Power Consumption	W	250
Air Conditioning	Cooling Capacity	W	5450
	Air Flow Volume	m ³ /h	600
	Power Consumption	W	300

► Rear Cooler / Rear Air Conditioning Unit ◀

Heater*	Heat Output	W	3750
	Air Flow Volume	m ³ /h	240
	Power Consumption	W	180
Air Conditioning	Cooling Capacity	W	3300
	Air Flow Volume	m ³ /h	320
	Power Consumption	W	200

*: Models with the rear air conditioning unit

2. Specifications

Destinations				G.C.C. Countries	Europe
Ventilation and Heater Core	Heater Radiator Unit	Front	Type	SFA (Straight Flow-Aluminum)-II	←
			Size W × H × L mm (in.)	295 × 120 × 27 (11.6 × 4.8 × 1.1)	←
			Fin Pitch mm (in.)	1.5 (0.06)	←
		Rear	Type	SFA (Straight Flow-Aluminum)-II	←
			Size W × H × L mm (in.)	191.1 × 130 × 21 (7.5 × 5.1 × 0.8)	←
			Fin Pitch mm (in.)	1.8 (0.07)	←
Ventilation and Heater Core	Blower	Front	Motor Type	Brushless Step-IV	←
			Fan Type	Semi Sirocco	←
			Fan Size Dia. × H mm (in.)	165 × 70 (6.5 × 2.8)	←
		Rear	Motor Type	K62	←
			Fan Type	High Pressure Drop Type	←
			Fan Size Dia. × H mm (in.)	140 × 70 (5.5 × 2.8)	←
Air Conditioning	Condenser		Type	MF (Multi-Flow)-IV	←
			Size W × H × L mm (in.)	626 × 524 × 22 (24.6 × 20.6 × 0.9)	640 × 524 × 16 (25.2 × 20.6 × 0.6)
			Fin Pitch mm (in.)	3.1 (0.12)	3.15 (0.12)
	Evaporator	Front	Type	RS (Revolutionary super-slim Structure)	←
			Size W × H × L mm (in.)	293 × 235 × 50 (11.5 × 9.3 × 2)	←
			Fin Pitch mm (in.)	3.0 (0.1)	←
		Rear	Type	RS (Revolutionary super-slim Structure)	←
			Size W × H × L mm (in.)	146 × 255 × 50 (5.7 × 10 × 2)	←
			Fin Pitch mm (in.)	3.4 (0.13)	←
	Compressor		Type	10SR19	←
			Pulley	Steel with Magnetic Clutch	←
	Refrigerant		Type	HFC 134a	←
			Charge Volume g	870±30*1 1010±30*2 970±30*3	770±30*1 970±30*2 920±30*3

*1: Models with the automatic air conditioning using left/right independent temperature control and without the rear cooler unit

*2: Models with the rear cooler unit or rear air conditioning unit, and cooling box

*3: Models with the rear cooler unit or the rear air conditioning unit, and without cooling box

Destinations				Australia	General Countries and China
Ventilation and Heater Core	Heater Radiator Unit	Front	Type	SFA (Straight Flow-Aluminum)-II	←
			Size W × H × L mm (in.)	295 × 120 × 27 (11.6 × 4.8 × 1.1)	←
			Fin Pitch mm (in.)	1.5 (0.06)	←
		Rear	Type	SFA (Straight Flow-Aluminum)-II	←
			Size W × H × L mm (in.)	191.1 × 130 × 21 (7.5 × 5.1 × 0.8)	←
			Fin Pitch mm (in.)	1.8 (0.07)	←
Ventilation and Heater Core	Blower	Front	Motor Type	Brushless Step-IV	←
			Fan Type	Semi Sirocco	←
			Fan Size Dia. × H mm (in.)	165 × 70 (6.5 × 2.8)	←
		Rear	Motor Type	K62	←
			Fan Type	High pressure drop type	←
			Fan Size Dia. × H mm (in.)	140 × 70 (5.5 × 2.8)	←
Air Conditioning	Condenser		Type	MF (Multi-Flow)-IV	←
			Size W × H × L mm (in.)	640 × 524 × 16 (25.2 × 20.6 × 0.6)	←
			Fin Pitch mm (in.)	3.15 (0.12)	←
	Evaporator	Front	Type	RS (Revolutionary super-slim Structure)	←
			Size W × H × L mm (in.)	293 × 235 × 50 (11.5 × 9.3 × 2)	←
			Fin Pitch mm (in.)	3.0 (0.1)	←
		Rear	Type	RS (Revolutionary super-slim Structure)	←
			Size W × H × L mm (in.)	146 × 255 × 50 (5.7 × 10 × 2)	←
			Fin Pitch mm (in.)	3.4 (0.13)	←
	Compressor		Type	10SR19	←
			Pulley	Steel with Magnetic Clutch	←
	Refrigerant		Type	HFC 134a	←
			Charge Volume g	770±30* ¹ 970±30* ² 920±30* ³	770±30* ¹ 970±30* ² 920±30* ³

*1: Models with the automatic air conditioning using left/right independent temperature control and without the rear cooler unit

*2: Models with the rear cooler unit or rear air conditioning unit, and cooling box

*3: Models with the rear cooler unit or the rear air conditioning unit, and without cooling box