

Nano cryptocurrency C library with P2PoW/DPoW support for Embedded
1.0.0

Generated by Doxygen 1.8.13

Contents

1	Overview	1
2	Data Structure Index	3
2.1	Data Structures	3
3	File Index	5
3.1	Files	5
4	Data Structure Documentation	7
4.1	f_block_transfer_t Struct Reference	7
4.1.1	Detailed Description	7
4.1.2	Field Documentation	7
4.1.2.1	account	7
4.1.2.2	balance	8
4.1.2.3	link	8
4.1.2.4	preamble	8
4.1.2.5	prefixes	8
4.1.2.6	previous	8
4.1.2.7	representative	9
4.1.2.8	signature	9
4.1.2.9	work	9
4.2	f_file_info_err_t Struct Reference	9
4.2.1	Detailed Description	9
4.3	f_nano_crypto_wallet_t Struct Reference	9
4.3.1	Detailed Description	10

4.3.2	Field Documentation	10
4.3.2.1	description	10
4.3.2.2	iv	10
4.3.2.3	nano_hdr	10
4.3.2.4	salt	11
4.3.2.5	seed_block	11
4.3.2.6	ver	11
4.4	f_nano_encrypted_wallet_t Struct Reference	11
4.4.1	Detailed Description	11
4.4.2	Field Documentation	12
4.4.2.1	hash_sk_unencrypted	12
4.4.2.2	iv	12
4.4.2.3	reserved	12
4.4.2.4	sk_encrypted	12
4.4.2.5	sub_salt	13
4.5	f_nano_wallet_info_bdy_t Struct Reference	13
4.5.1	Detailed Description	13
4.5.2	Field Documentation	13
4.5.2.1	last_used_wallet_number	13
4.5.2.2	max_fee	14
4.5.2.3	reserved	14
4.5.2.4	wallet_prefix	14
4.5.2.5	wallet_representative	14
4.6	f_nano_wallet_info_t Struct Reference	14
4.6.1	Detailed Description	15
4.6.2	Field Documentation	15
4.6.2.1	body	15
4.6.2.2	desc	15
4.6.2.3	file_info_integrity	15
4.6.2.4	header	16
4.6.2.5	nanoseed_hash	16
4.6.2.6	version	16

5 File Documentation	17
5.1 f_add_bn_288_le.h File Reference	17
5.1.1 Detailed Description	17
5.1.2 Typedef Documentation	17
5.1.2.1 F_ADD_288	17
5.2 f_add_bn_288_le.h	18
5.3 f_nano_crypto_util.h File Reference	18
5.3.1 Detailed Description	21
5.3.2 Macro Definition Documentation	21
5.3.2.1 DEST_XRB	22
5.3.2.2 F_BRAIN_WALLET_BAD	22
5.3.2.3 F_BRAIN_WALLET_GOOD	22
5.3.2.4 F_BRAIN_WALLET_MAYBE_GOOD	22
5.3.2.5 F_BRAIN_WALLET_NICE	22
5.3.2.6 F_BRAIN_WALLET_PERFECT	23
5.3.2.7 F_BRAIN_WALLET_POOR	23
5.3.2.8 F_BRAIN_WALLET_STILL_WEAK	23
5.3.2.9 F_BRAIN_WALLET_VERY_BAD	23
5.3.2.10 F_BRAIN_WALLET_VERY_GOOD	24
5.3.2.11 F_BRAIN_WALLET_VERY_POOR	24
5.3.2.12 F_BRAIN_WALLET_VERY_WEAK	24
5.3.2.13 F_BRAIN_WALLET_WEAK	24
5.3.2.14 F_DEFAULT_THRESHOLD	25
5.3.2.15 F_IS_SIGNATURE_RAW_HEX_STRING	25
5.3.2.16 F_MESSAGE_IS_HASH_STRING	25
5.3.2.17 F_NANO_POW_MAX_THREAD	25
5.3.2.18 F_SIGNATURE_OUTPUT_NANO_PK	26
5.3.2.19 F_SIGNATURE_OUTPUT_RAW_PK	26
5.3.2.20 F_SIGNATURE_OUTPUT_STRING_PK	26
5.3.2.21 F_SIGNATURE_OUTPUT_XRB_PK	26

5.3.2.22	F_SIGNATURE_RAW	27
5.3.2.23	F_SIGNATURE_STRING	27
5.3.2.24	F_VERIFY_SIG_ASCII_HEX	27
5.3.2.25	F_VERIFY_SIG_NANO_WALLET	27
5.3.2.26	F_VERIFY_SIG_RAW_HEX	28
5.3.2.27	MAX_STR_NANO_CHAR	28
5.3.2.28	NANO_ENCRYPTED_SEED_FILE	28
5.3.2.29	NANO_FILE_WALLETS_INFO	28
5.3.2.30	NANO_PASSWD_MAX_LEN	29
5.3.2.31	NANO_PREFIX	29
5.3.2.32	PUB_KEY_EXTENDED_MAX_LEN	29
5.3.2.33	REP_XRB	29
5.3.2.34	SENDER_XRB	29
5.3.2.35	STR_NANO_SZ	30
5.3.2.36	XRB_PREFIX	30
5.3.3	Typedef Documentation	30
5.3.3.1	F_FILE_INFO_ERR	30
5.3.3.2	f_nano_err	30
5.3.3.3	F_TOKEN	30
5.3.3.4	f_uint128_t	31
5.3.3.5	f_write_seed_err	31
5.3.3.6	NANO_PRIVATE_KEY	31
5.3.3.7	NANO_PRIVATE_KEY_EXTENDED	31
5.3.3.8	NANO_PUBLIC_KEY	31
5.3.3.9	NANO_PUBLIC_KEY_EXTENDED	32
5.3.3.10	NANO_SEED	32
5.3.4	Enumeration Type Documentation	32
5.3.4.1	f_file_info_err_t	32
5.3.4.2	f_nano_err_t	33
5.3.4.3	f_write_seed_err_t	33

5.3.5	Function Documentation	34
5.3.5.1	__attribute__()	34
5.3.5.2	f_bip39_to_nano_seed()	34
5.3.5.3	f_cloud_crypto_wallet_nano_create_seed()	35
5.3.5.4	f_extract_seed_from_brainwallet()	35
5.3.5.5	f_generate_nano_seed()	36
5.3.5.6	f_generate_token()	37
5.3.5.7	f_get_dictionary_path()	37
5.3.5.8	f_get_nano_file_info()	38
5.3.5.9	f_nano_add_sub()	38
5.3.5.10	f_nano_balance_to_str()	39
5.3.5.11	f_nano_block_to_json()	40
5.3.5.12	f_nano_get_block_hash()	40
5.3.5.13	f_nano_get_p2pow_block_hash()	41
5.3.5.14	f_nano_is_valid_block()	41
5.3.5.15	f_nano_key_to_str()	41
5.3.5.16	f_nano_p2pow_to_JSON()	42
5.3.5.17	f_nano_parse_raw_str_to_raw128_t()	42
5.3.5.18	f_nano_parse_real_str_to_raw128_t()	43
5.3.5.19	f_nano_pow()	43
5.3.5.20	f_nano_raw_to_string()	44
5.3.5.21	f_nano_seed_to_bip39()	44
5.3.5.22	f_nano_sign_block()	45
5.3.5.23	f_nano_transaction_to_JSON()	46
5.3.5.24	f_nano_valid_nano_str_value()	46
5.3.5.25	f_nano_value_compare_value()	47
5.3.5.26	f_nano_verify_nano_funds()	48
5.3.5.27	f_parse_nano_seed_and_bip39_to_JSON()	48
5.3.5.28	f_read_seed()	49
5.3.5.29	f_seed_to_nano_wallet()	50

5.3.5.30	f_set_dictionary_path()	51
5.3.5.31	f_set_nano_file_info()	51
5.3.5.32	f_sign_data()	52
5.3.5.33	f_verify_signed_data()	53
5.3.5.34	f_verify_token()	53
5.3.5.35	f_verify_work()	54
5.3.5.36	f_write_seed()	54
5.3.5.37	from_multiplier()	55
5.3.5.38	is_nano_prefix()	56
5.3.5.39	is_null_hash()	56
5.3.5.40	nano_base_32_2_hex()	56
5.3.5.41	pk_to_wallet()	57
5.3.5.42	to_multiplier()	58
5.3.5.43	valid_nano_wallet()	58
5.3.5.44	valid_raw_balance()	58
5.3.6	Variable Documentation	59
5.3.6.1	account	59
5.3.6.2	balance	59
5.3.6.3	body	59
5.3.6.4	desc	60
5.3.6.5	description	60
5.3.6.6	file_info_integrity	60
5.3.6.7	hash_sk_unencrypted	60
5.3.6.8	header	60
5.3.6.9	iv	61
5.3.6.10	last_used_wallet_number	61
5.3.6.11	link	61
5.3.6.12	max_fee	61
5.3.6.13	nano_hdr	61
5.3.6.14	nanoseed_hash	62

5.3.6.15	preamble	62
5.3.6.16	prefixes	62
5.3.6.17	previous	62
5.3.6.18	representative	62
5.3.6.19	reserved	63
5.3.6.20	salt	63
5.3.6.21	seed_block	63
5.3.6.22	signature	63
5.3.6.23	sk_encrypted	63
5.3.6.24	sub_salt	64
5.3.6.25	ver	64
5.3.6.26	version	64
5.3.6.27	wallet_prefix	64
5.3.6.28	wallet_representative	64
5.3.6.29	work	65
5.4	f_nano_crypto_util.h	65
5.5	f_util.h File Reference	70
5.5.1	Detailed Description	71
5.5.2	Macro Definition Documentation	71
5.5.2.1	ENTROPY_BEGIN	71
5.5.2.2	ENTROPY_END	72
5.5.2.3	F_ENTROPY_TYPE_EXCELENT	72
5.5.2.4	F_ENTROPY_TYPE_GOOD	72
5.5.2.5	F_ENTROPY_TYPE_NOT_ENOUGH	72
5.5.2.6	F_ENTROPY_TYPE_NOT_RECOMENDED	73
5.5.2.7	F_ENTROPY_TYPE_PARANOIC	73
5.5.2.8	F_GET_CH_MODE_ANY_KEY	73
5.5.2.9	F_GET_CH_MODE_NO_ECHO	73
5.5.2.10	F_PASS_IS_OUT_OVF	74
5.5.2.11	F_PASS_IS_TOO_LONG	74

5.5.2.12	F_PASS_IS_TOO_SHORT	74
5.5.2.13	F_PASS_MUST_HAVE_AT_LEAST_NONE	74
5.5.2.14	F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE	74
5.5.2.15	F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER	75
5.5.2.16	F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL	75
5.5.2.17	F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE	75
5.5.3	Typedef Documentation	75
5.5.3.1	rnd_fn	75
5.5.4	Function Documentation	75
5.5.4.1	crc32_init()	75
5.5.4.2	f_convert_to_double()	76
5.5.4.3	f_convert_to_long_int()	76
5.5.4.4	f_convert_to_long_int0()	77
5.5.4.5	f_convert_to_long_int0x()	77
5.5.4.6	f_convert_to_long_int_std()	78
5.5.4.7	f_convert_to_unsigned_int()	78
5.5.4.8	f_convert_to_unsigned_int0()	79
5.5.4.9	f_convert_to_unsigned_int0x()	79
5.5.4.10	f_convert_to_unsigned_int_std()	80
5.5.4.11	f_get_char_no_block()	81
5.5.4.12	f_get_entropy_name()	81
5.5.4.13	f_is_random_attached()	82
5.5.4.14	f_pass_must_have_at_least()	82
5.5.4.15	f_passwd_comp_safe()	83
5.5.4.16	f_random()	83
5.5.4.17	f_random_attach()	85
5.5.4.18	f_random_detach()	85
5.5.4.19	f_sel_to_entropy_level()	85
5.5.4.20	f_str_to_hex()	86
5.5.4.21	f_verify_system_entropy()	86
5.5.4.22	get_console_passwd()	87
5.6	f_util.h	88
5.7	sodium.h File Reference	90
5.7.1	Detailed Description	91
5.8	sodium.h	91

Chapter 1

Overview

myNanoEmbedded is a lightweight C library of source files that integrates Nano Cryptocurrency to low complexity computational devices to send/receive digital money to anywhere in the world with fast transaction and with a small fee by delegating a Proof of Work with your choice:

- DPoW (Distributed Proof of Work)
- P2PoW (a Decentralized P2P Proof of Work)

API features

- Attaches a random function to TRNG hardware (if available)
- Self entropy verifier to ensure excellent TRNG or PRNG entropy
- Creates an encrypted by password your stream or file to store your Nano SEED
- Bip39 and Brainwallet support
- Convert raw data to Base32
- Parse SEED and Bip39 to JSON
- Sign a block using Blake2b hash with Ed25519 algorithm
- ARM-A, ARM-M, Thumb, Xtensa-LX6 and IA64 compatible
- Linux desktop, Raspberry PI, ESP32 and Olimex A20 tested platforms
- Communication over Fenix protocol bridge over TLS
- Libsodium and mbedTLS libraries with smaller resources and best performance
- Optimized for size and speed
- Non static functions (all data is cleared before processed for security)
- Fully written in C for maximum performance and portability

To add this API in your project you must first:

1. Download the latest version.

```
git clone https://github.com/devfabiosilva/myNanoEmbedded.git --recurse-submodules
```

2. Include the main library files in the client application.

```
#include "f_nano_crypto_util.h"
```

Initialize API

Function	Description
<code>f_random_attach()</code> (p. ??)	Initializes the PRNG or TRNG to be used in this API

Transmit/Receive transactions

To transmit/receive your transaction you must use `Fenix` protocol to stabilish a DPoW/P2PoW support

Examples using platforms

The repository has some examples with most common embedded and Linux systems

- Native Linux
- Raspberry Pi
- ESP32
- Olimex A20
- STM

Credits

Author

Fábio Pereira da Silva

Date

Feb 2020

Version

1.0

Copyright

License MIT [see here](#)

References:

[1] - Colin LeMahieu - *Nano: A Feeless Distributed Cryptocurrency Network* - (2015)

[2] - Z. S. Spakovszky - *7.3 A Statistical Definition of Entropy* - (2005) - NOTE: Entropy function for cryptography is implemented based on `Definition (7.12)` of this amazing topic

[3] - Kaique Anarkrypto - *Delegated Proof of Work* - (2019)

[4] - `docs.nano.org` - *Node RPCs documentation*

Chapter 2

Data Structure Index

2.1 Data Structures

Here are the data structures with brief descriptions:

f_block_transfer_t	
Nano signed block raw data defined in this reference	7
f_file_info_err_t	
Error enumerator for info file functions	9
f_nano_crypto_wallet_t	
struct of the block of encrypted file to store Nano SEED	9
f_nano_encrypted_wallet_t	
struct of the block of encrypted file to store Nano SEED	11
f_nano_wallet_info_bdy_t	
struct of the body block of the info file	13
f_nano_wallet_info_t	
struct of the body block of the info file	14

Chapter 3

File Index

3.1 Files

Here is a list of all files with brief descriptions:

f_add_bn_288_le.h	
Low level implementation of Nano Cryptocurrency C library	17
f_nano_crypto_util.h	
This API Integrates Nano Cryptocurrency to low computational devices	18
f_util.h	
This ABI is a utility for myNanoEmbedded library and sub routines are implemented here . . .	70
sodium.h	
This header file is an implementation of Libsodium library	90

Chapter 4

Data Structure Documentation

4.1 `f_block_transfer_t` Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- `uint8_t` **preamble** [32]
- `uint8_t` **account** [32]
- `uint8_t` **previous** [32]
- `uint8_t` **representative** [32]
- `f_uint128_t` **balance**
- `uint8_t` **link** [32]
- `uint8_t` **signature** [64]
- `uint8_t` **prefixes**
- `uint64_t` **work**

4.1.1 Detailed Description

Nano signed block raw data defined in this [reference](#)

Definition at line **264** of file **f_nano_crypto_util.h**.

4.1.2 Field Documentation

4.1.2.1 `account`

```
uint8_t account[32]
```

Account in raw binary data.

Definition at line **268** of file **f_nano_crypto_util.h**.

4.1.2.2 balance

`f_uint128_t balance`

Big number 128 bit raw balance.

See also

`f_uint128_t` (p. ??)

Definition at line 276 of file `f_nano_crypto_util.h`.

4.1.2.3 link

`uint8_t link[32]`

link or destination account

Definition at line 278 of file `f_nano_crypto_util.h`.

4.1.2.4 preamble

`uint8_t preamble[32]`

Block preamble.

Definition at line 266 of file `f_nano_crypto_util.h`.

4.1.2.5 prefixes

`uint8_t prefixes`

Internal use for this API.

Definition at line 282 of file `f_nano_crypto_util.h`.

4.1.2.6 previous

`uint8_t previous[32]`

Previous block.

Definition at line 270 of file `f_nano_crypto_util.h`.

4.1.2.7 `representative`

```
uint8_t representative[32]
```

Representative for current account.

Definition at line **272** of file **`f_nano_crypto_util.h`**.

4.1.2.8 `signature`

```
uint8_t signature[64]
```

Signature of the block.

Definition at line **280** of file **`f_nano_crypto_util.h`**.

4.1.2.9 `work`

```
uint64_t work
```

Internal use for this API.

Definition at line **284** of file **`f_nano_crypto_util.h`**.

The documentation for this struct was generated from the following file:

- **`f_nano_crypto_util.h`**

4.2 `f_file_info_err_t` Struct Reference

```
#include <f_nano_crypto_util.h>
```

4.2.1 Detailed Description

Error enumerator for info file functions.

The documentation for this struct was generated from the following file:

- **`f_nano_crypto_util.h`**

4.3 `f_nano_crypto_wallet_t` Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- `uint8_t nano_hdr` [`sizeof(NANO_WALLET_MAGIC)`]
- `uint32_t ver`
- `uint8_t description` [`F_DESC_SZ`]
- `uint8_t salt` [32]
- `uint8_t iv` [16]
- `F_ENCRYPTED_BLOCK seed_block`

4.3.1 Detailed Description

struct of the block of encrypted file to store Nano SEED

Definition at line **395** of file **f_nano_crypto_util.h**.

4.3.2 Field Documentation

4.3.2.1 description

```
uint8_t description[F_DESC_SZ]
```

File description.

Definition at line **401** of file **f_nano_crypto_util.h**.

4.3.2.2 iv

```
uint8_t iv[16]
```

Initial vector of first encryption layer.

Definition at line **405** of file **f_nano_crypto_util.h**.

4.3.2.3 nano_hdr

```
uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)]
```

Header of the file.

Definition at line **397** of file **f_nano_crypto_util.h**.

4.3.2.4 salt

```
uint8_t salt[32]
```

Salt of the first encryption layer.

Definition at line 403 of file `f_nano_crypto_util.h`.

4.3.2.5 seed_block

```
F_ENCRYPTED_BLOCK seed_block
```

Second encrypted block for Nano SEED.

Definition at line 407 of file `f_nano_crypto_util.h`.

4.3.2.6 ver

```
uint32_t ver
```

Version of the file.

Definition at line 399 of file `f_nano_crypto_util.h`.

The documentation for this struct was generated from the following file:

- `f_nano_crypto_util.h`

4.4 f_nano_encrypted_wallet_t Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- `uint8_t sub_salt` [32]
- `uint8_t iv` [16]
- `uint8_t reserved` [16]
- `uint8_t hash_sk_unencrypted` [32]
- `uint8_t sk_encrypted` [32]

4.4.1 Detailed Description

struct of the block of encrypted file to store Nano SEED

Definition at line 367 of file `f_nano_crypto_util.h`.

4.4.2 Field Documentation

4.4.2.1 hash_sk_unencrypted

```
uint8_t hash_sk_unencrypted[32]
```

hash of Nano SEED when unencrypted

Definition at line **375** of file **f_nano_crypto_util.h**.

4.4.2.2 iv

```
uint8_t iv[16]
```

Initial sub vector.

Definition at line **371** of file **f_nano_crypto_util.h**.

4.4.2.3 reserved

```
uint8_t reserved[16]
```

Reserved (not used)

Definition at line **373** of file **f_nano_crypto_util.h**.

4.4.2.4 sk_encrypted

```
uint8_t sk_encrypted[32]
```

Secret.

SEED encrypted (second layer)

Definition at line **377** of file **f_nano_crypto_util.h**.

4.4.2.5 sub_salt

```
uint8_t sub_salt[32]
```

Salt of the sub block to be stored.

Definition at line **369** of file **f_nano_crypto_util.h**.

The documentation for this struct was generated from the following file:

- **f_nano_crypto_util.h**

4.5 f_nano_wallet_info_bdy_t Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- uint8_t **wallet_prefix**
- uint32_t **last_used_wallet_number**
- char **wallet_representative** [MAX_STR_NANO_CHAR]
- char **max_fee** [F_RAW_STR_MAX_SZ]
- uint8_t **reserved** [44]

4.5.1 Detailed Description

struct of the body block of the info file

Definition at line **479** of file **f_nano_crypto_util.h**.

4.5.2 Field Documentation

4.5.2.1 last_used_wallet_number

```
uint32_t last_used_wallet_number
```

Last used wallet number.

Definition at line **483** of file **f_nano_crypto_util.h**.

4.5.2.2 max_fee

```
char max_fee[F_RAW_STR_MAX_SZ]
```

Custom preferred max fee of Proof of Work.

Definition at line 487 of file **f_nano_crypto_util.h**.

4.5.2.3 reserved

```
uint8_t reserved[44]
```

Reserved.

Definition at line 489 of file **f_nano_crypto_util.h**.

4.5.2.4 wallet_prefix

```
uint8_t wallet_prefix
```

Wallet prefix: 0 for NANO; 1 for XRB.

Definition at line 481 of file **f_nano_crypto_util.h**.

4.5.2.5 wallet_representative

```
char wallet_representative[ MAX_STR_NANO_CHAR]
```

Wallet representative.

Definition at line 485 of file **f_nano_crypto_util.h**.

The documentation for this struct was generated from the following file:

- **f_nano_crypto_util.h**

4.6 f_nano_wallet_info_t Struct Reference

```
#include <f_nano_crypto_util.h>
```


Data Fields

- `uint8_t header` [`sizeof(F_NANO_WALLET_INFO_MAGIC)`]
- `uint16_t version`
- `char desc` [`F_NANO_DESC_SZ`]
- `uint8_t nanoseed_hash` [`32`]
- `uint8_t file_info_integrity` [`32`]
- `F_NANO_WALLET_INFO_BODY body`

4.6.1 Detailed Description

struct of the body block of the info file

Definition at line **511** of file `f_nano_crypto_util.h`.

4.6.2 Field Documentation

4.6.2.1 `body`

```
F_NANO_WALLET_INFO_BODY body
```

Body of the file info.

Definition at line **523** of file `f_nano_crypto_util.h`.

4.6.2.2 `desc`

```
char desc[F_NANO_DESC_SZ]
```

Description.

Definition at line **517** of file `f_nano_crypto_util.h`.

4.6.2.3 `file_info_integrity`

```
uint8_t file_info_integrity[32]
```

File info integrity of the body block.

Definition at line **521** of file `f_nano_crypto_util.h`.

4.6.2.4 header

```
uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)]
```

Header magic.

Definition at line **513** of file **f_nano_crypto_util.h**.

4.6.2.5 nanoseed_hash

```
uint8_t nanoseed_hash[32]
```

Nano SEED hash file.

Definition at line **519** of file **f_nano_crypto_util.h**.

4.6.2.6 version

```
uint16_t version
```

Version.

Definition at line **515** of file **f_nano_crypto_util.h**.

The documentation for this struct was generated from the following file:

- **f_nano_crypto_util.h**

Chapter 5

File Documentation

5.1 `f_add_bn_288_le.h` File Reference

```
#include <stdint.h>
```

Typedefs

- typedef uint8_t **F_ADD_288**[36]

5.1.1 Detailed Description

Low level implementation of Nano Cryptocurrency C library.

Definition in file `f_add_bn_288_le.h`.

5.1.2 Typedef Documentation

5.1.2.1 `F_ADD_288`

`F_ADD_288`

288 bit big number

Definition at line **19** of file `f_add_bn_288_le.h`.

5.2 f_add_bn_288_le.h

```

00001  /*
00002      AUTHOR: Fábio Pereira da Silva
00003      YEAR: 2019-20
00004      LICENSE: MIT
00005      EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006  */
00007
00008  #include <stdint.h>
00009
00019  typedef uint8_t F_ADD_288[36];
00020
00021
00022  #ifndef F_DOC_SKIP
00023
00033  void f_add_bn_288_le(F_ADD_288, F_ADD_288, F_ADD_288, int *, int);
00034  void f_sl_elv_add_le(F_ADD_288, int);
00035
00036  #endif
00037

```

5.3 f_nano_crypto_util.h File Reference

```

#include <stdint.h>
#include "f_util.h"

```

Data Structures

- struct **f_block_transfer_t**
- struct **f_nano_encrypted_wallet_t**
- struct **f_nano_crypto_wallet_t**
- struct **f_nano_wallet_info_bdy_t**
- struct **f_nano_wallet_info_t**

Macros

- #define **F_NANO_POW_MAX_THREAD** (size_t)10
- #define **MAX_STR_NANO_CHAR** (size_t)70
- #define **PUB_KEY_EXTENDED_MAX_LEN** (size_t)40
- #define **NANO_PREFIX** "nano_"
- #define **XRB_PREFIX** "xrb_"
- #define **NANO_ENCRYPTED_SEED_FILE** "/spiffs/secure/nano.nse"
- #define **NANO_PASSWD_MAX_LEN** (size_t)80
- #define **STR_NANO_SZ** (size_t)66
- #define **NANO_FILE_WALLETS_INFO** "/spiffs/secure/walletsinfo.i"
- #define **REP_XRB** (uint8_t)0x4
- #define **SENDER_XRB** (uint8_t)0x02
- #define **DEST_XRB** (uint8_t)0x01
- #define **F_BRAIN_WALLET_VERY_POOR** (uint32_t)0
- #define **F_BRAIN_WALLET_POOR** (uint32_t)1
- #define **F_BRAIN_WALLET_VERY_BAD** (uint32_t)2
- #define **F_BRAIN_WALLET_BAD** (uint32_t)3
- #define **F_BRAIN_WALLET_VERY_WEAK** (uint32_t)4
- #define **F_BRAIN_WALLET_WEAK** (uint32_t)5
- #define **F_BRAIN_WALLET_STILL_WEAK** (uint32_t)6

- `#define F_BRAIN_WALLET_MAYBE_GOOD (uint32_t)7`
- `#define F_BRAIN_WALLET_GOOD (uint32_t)8`
- `#define F_BRAIN_WALLET_VERY_GOOD (uint32_t)9`
- `#define F_BRAIN_WALLET_NICE (uint32_t)10`
- `#define F_BRAIN_WALLET_PERFECT (uint32_t)11`
- `#define F_SIGNATURE_RAW (uint32_t)1`
- `#define F_SIGNATURE_STRING (uint32_t)2`
- `#define F_SIGNATURE_OUTPUT_RAW_PK (uint32_t)4`
- `#define F_SIGNATURE_OUTPUT_STRING_PK (uint32_t)8`
- `#define F_SIGNATURE_OUTPUT_XRB_PK (uint32_t)16`
- `#define F_SIGNATURE_OUTPUT_NANO_PK (uint32_t)32`
- `#define F_IS_SIGNATURE_RAW_HEX_STRING (uint32_t)64`
- `#define F_MESSAGE_IS_HASH_STRING (uint32_t)128`
- `#define F_DEFAULT_THRESHOLD (uint64_t) 0xffffffff00000000`
- `#define F_VERIFY_SIG_NANO_WALLET (uint32_t)1`
- `#define F_VERIFY_SIG_RAW_HEX (uint32_t)2`
- `#define F_VERIFY_SIG_ASCII_HEX (uint32_t)4`

Typedefs

- `typedef uint8_t F_TOKEN[16]`
- `typedef uint8_t NANO_SEED[crypto_sign_SEEDBYTES]`
- `typedef uint8_t f_uint128_t[16]`
- `typedef uint8_t NANO_PRIVATE_KEY[sizeof(NANO_SEED)]`
- `typedef uint8_t NANO_PRIVATE_KEY_EXTENDED[crypto_sign_ed25519_SECRETKEYBYTES]`
- `typedef uint8_t NANO_PUBLIC_KEY[crypto_sign_ed25519_PUBLICKEYBYTES]`
- `typedef uint8_t NANO_PUBLIC_KEY_EXTENDED[PUB_KEY_EXTENDED_MAX_LEN]`
- `typedef enum f_nano_err_t f_nano_err`
- `typedef enum f_write_seed_err_t f_write_seed_err`
- `typedef enum f_file_info_err_t F_FILE_INFO_ERR`

Enumerations

- `enum f_nano_err_t {`
`NANO_ERR_OK =0, NANO_ERR_CANT_PARSE_BN_STR =5151, NANO_ERR_MALLOC, NANO_ERR_CANT_PARSE_FACTOR,`
`NANO_ERR_MPI_MULT, NANO_ERR_CANT_PARSE_TO_BLK_TRANSFER, NANO_ERR_EMPTY_STRING, NANO_ERR_CANT_PARSE_VALUE,`
`NANO_ERR_PARSE_MPI_TO_STR, NANO_ERR_CANT_COMPLETE_NULL_CHAR, NANO_ERR_CANT_PARSE_TO_MPI, NANO_ERR_INSUFICIENT_FUNDS,`
`NANO_ERR_SUB_MPI, NANO_ERR_ADD_MPI, NANO_ERR_NO_SENSE_VALUE_TO_SEND_NEGATIVE, NANO_ERR_NO_SENSE_VALUE_TO_SEND_ZERO,`
`NANO_ERR_NO_SENSE_BALANCE_NEGATIVE, NANO_ERR_VAL_A_INVALID_MODE, NANO_ERR_CANT_PARSE_TO_TEMP_UINT128_T, NANO_ERR_VAL_B_INVALID_MODE,`
`NANO_ERR_CANT_PARSE_RAW_A_TO_MPI, NANO_ERR_CANT_PARSE_RAW_B_TO_MPI, NANO_ERR_UNKNOWN_ADD_SUB_MODE, NANO_ERR_INVALID_RES_OUTPUT }`
- `enum f_write_seed_err_t {`
`WRITE_ERR_OK =0, WRITE_ERR_NULL_PASSWORD =7180, WRITE_ERR_EMPTY_STRING, WRITE_ERR_MALLOC,`
`WRITE_ERR_ENCRYPT_PRIV_KEY, WRITE_ERR_GEN_SUB_PRIV_KEY, WRITE_ERR_GEN_MAIN_PRIV_KEY, WRITE_ERR_ENCRYPT_SUB_BLOCK,`
`WRITE_ERR_UNKNOWN_OPTION, WRITE_ERR_FILE_ALREADY_EXISTS, WRITE_ERR_CREATING_FILE, WRITE_ERR_WRITING_FILE }`

```

• enum f_file_info_err_t {
    F_FILE_INFO_ERR_OK = 0, F_FILE_INFO_ERR_CANT_OPEN_INFO_FILE = 7001, F_FILE_INFO_ER↵
    R_NANO_SEED_ENCRYPTED_FILE_NOT_FOUND, F_FILE_INFO_ERR_CANT_DELETE_NANO_IN↵
    FO_FILE,
    F_FILE_INFO_ERR_MALLOC, F_FILE_INFO_ERR_CANT_READ_NANO_SEED_ENCRYPTED_FILE,
    F_FILE_INFO_ERR_CANT_READ_INFO_FILE, F_FILE_INFO_INVALID_HEADER_FILE,
    F_FILE_INFO_ERR_INVALID_SHA256_INFO_FILE, F_FILE_INFO_ERR_NANO_SEED_HASH_FAIL,
    F_FILE_INFO_ERR_NANO_INVALID_REPRESENTATIVE, F_FILE_INFO_ERR_NANO_INVALID_MA↵
    X_FEE_VALUE,
    F_FILE_INFO_ERR_OPEN_FOR_WRITE_INFO, F_FILE_INFO_ERR_EXISTING_FILE, F_FILE_INFO↵
    _ERR_CANT_WRITE_FILE_INFO }

```

Functions

```

• struct f_block_transfer_t __attribute__((packed)) F_BLOCK_TRANSFER
• double to_multiplier (uint64_t, uint64_t)
• uint64_t from_multiplier (double, uint64_t)
• void f_set_dictionary_path (const char *)
• char * f_get_dictionary_path (void)
• int f_generate_token ( F_TOKEN, void *, size_t, const char *)
• int f_verify_token ( F_TOKEN, void *, size_t, const char *)
• int f_cloud_crypto_wallet_nano_create_seed (size_t, char *, char *)
• int f_generate_nano_seed ( NANO_SEED, uint32_t)
• int pk_to_wallet (char *, char *, NANO_PUBLIC_KEY_EXTENDED)
• int f_seed_to_nano_wallet ( NANO_PRIVATE_KEY, NANO_PUBLIC_KEY, NANO_SEED, uint32_t)
• int f_nano_is_valid_block (F_BLOCK_TRANSFER *)
• int f_nano_block_to_json (char *, size_t *, size_t, F_BLOCK_TRANSFER *)
• int f_nano_get_block_hash (uint8_t *, F_BLOCK_TRANSFER *)
• int f_nano_get_p2pow_block_hash (uint8_t *, uint8_t *, F_BLOCK_TRANSFER *)
• int f_nano_p2pow_to_JSON (char *, size_t *, size_t, F_BLOCK_TRANSFER *)
• char * f_nano_key_to_str (char *, unsigned char *)
• int f_nano_seed_to_bip39 (char *, size_t, size_t *, NANO_SEED, char *)
• int f_bip39_to_nano_seed (uint8_t *, char *, char *)
• int f_parse_nano_seed_and_bip39_to_JSON (char *, size_t, size_t *, void *, int, const char *)
• int f_read_seed (uint8_t *, const char *, void *, int, int)
• int f_nano_raw_to_string (char *, size_t *, size_t, void *, int)
• int f_nano_valid_nano_str_value (const char *)
• int valid_nano_wallet (const char *)
• int nano_base_32_2_hex (uint8_t *, char *)
• int f_nano_transaction_to_JSON (char *, size_t, size_t *, NANO_PRIVATE_KEY_EXTENDED, F_BLOCK_TRANSFER *)
• int valid_raw_balance (const char *)
• int is_null_hash (uint8_t *)
• int is_nano_prefix (const char *, const char *)
• F_FILE_INFO_ERR f_get_nano_file_info (F_NANO_WALLET_INFO *)
• F_FILE_INFO_ERR f_set_nano_file_info (F_NANO_WALLET_INFO *, int)
• f_nano_err f_nano_value_compare_value (void *, void *, uint32_t *)
• f_nano_err f_nano_verify_nano_funds (void *, void *, void *, uint32_t)
• f_nano_err f_nano_parse_raw_str_to_raw128_t (uint8_t *, const char *)
• f_nano_err f_nano_parse_real_str_to_raw128_t (uint8_t *, const char *)
• f_nano_err f_nano_add_sub (void *, void *, void *, uint32_t)
• int f_nano_sign_block (F_BLOCK_TRANSFER *, F_BLOCK_TRANSFER *, NANO_PRIVATE_KEY_EXTENDED)
• f_write_seed_err f_write_seed (void *, int, uint8_t *, char *)

```

- **f_nano_err f_nano_balance_to_str** (char *, size_t, size_t *, **f_uint128_t**)
- **int f_extract_seed_from_brainwallet** (uint8_t *, char **, uint32_t, const char *, const char *)
- **int f_verify_work** (uint64_t *, const unsigned char *, uint64_t *, uint64_t)
- **int f_sign_data** (unsigned char * **signature**, void *out_public_key, uint32_t output_type, const unsigned char *message, size_t msg_len, const unsigned char *private_key)
- **int f_verify_signed_data** (const unsigned char * **signature**, const unsigned char *message, size_t message_len, const void *public_key, uint32_t pk_type)
- **int f_nano_pow** (uint64_t *, unsigned char *, const uint64_t, int)

Variables

- uint8_t **preamble** [32]
- uint8_t **account** [32]
- uint8_t **previous** [32]
- uint8_t **representative** [32]
- **f_uint128_t balance**
- uint8_t **link** [32]
- uint8_t **signature** [64]
- uint8_t **prefixes**
- uint64_t **work**
- uint8_t **sub_salt** [32]
- uint8_t **iv** [16]
- uint8_t **reserved** [16]
- uint8_t **hash_sk_unencrypted** [32]
- uint8_t **sk_encrypted** [32]
- uint8_t **nano_hdr** [sizeof(NANO_WALLET_MAGIC)]
- uint32_t **ver**
- uint8_t **description** [F_DESC_SZ]
- uint8_t **salt** [32]
- F_ENCRYPTED_BLOCK **seed_block**
- uint8_t **wallet_prefix**
- uint32_t **last_used_wallet_number**
- char **wallet_representative** [MAX_STR_NANO_CHAR]
- char **max_fee** [F_RAW_STR_MAX_SZ]
- uint8_t **header** [sizeof(F_NANO_WALLET_INFO_MAGIC)]
- uint16_t **version**
- char **desc** [F_NANO_DESC_SZ]
- uint8_t **nanoseed_hash** [32]
- uint8_t **file_info_integrity** [32]
- F_NANO_WALLET_INFO_BODY **body**

5.3.1 Detailed Description

This API Integrates Nano Cryptocurrency to low computational devices.

Definition in file **f_nano_crypto_util.h**.

5.3.2 Macro Definition Documentation

5.3.2.1 DEST_XRB

```
#define DEST_XRB (uint8_t)0x01
```

Definition at line **433** of file **f_nano_crypto_util.h**.

5.3.2.2 F_BRAIN_WALLET_BAD

```
#define F_BRAIN_WALLET_BAD (uint32_t)3
```

[bad].

Crack within one day

Definition at line **1169** of file **f_nano_crypto_util.h**.

5.3.2.3 F_BRAIN_WALLET_GOOD

```
#define F_BRAIN_WALLET_GOOD (uint32_t)8
```

[good].

Crack within one thousand year

Definition at line **1200** of file **f_nano_crypto_util.h**.

5.3.2.4 F_BRAIN_WALLET_MAYBE_GOOD

```
#define F_BRAIN_WALLET_MAYBE_GOOD (uint32_t)7
```

[maybe good for you].

Crack within one century

Definition at line **1193** of file **f_nano_crypto_util.h**.

5.3.2.5 F_BRAIN_WALLET_NICE

```
#define F_BRAIN_WALLET_NICE (uint32_t)10
```

[very nice].

Crack withing one hundred thousand year

Definition at line **1212** of file **f_nano_crypto_util.h**.

5.3.2.6 F_BRAIN_WALLET_PERFECT

```
#define F_BRAIN_WALLET_PERFECT (uint32_t)11
```

[Perfect!] 3.34x10⁵³ Years to crack

Definition at line **1218** of file **f_nano_crypto_util.h**.

5.3.2.7 F_BRAIN_WALLET_POOR

```
#define F_BRAIN_WALLET_POOR (uint32_t)1
```

[poor].

Crack within minutes

Definition at line **1157** of file **f_nano_crypto_util.h**.

5.3.2.8 F_BRAIN_WALLET_STILL_WEAK

```
#define F_BRAIN_WALLET_STILL_WEAK (uint32_t)6
```

[still weak].

Crack within one year

Definition at line **1187** of file **f_nano_crypto_util.h**.

5.3.2.9 F_BRAIN_WALLET_VERY_BAD

```
#define F_BRAIN_WALLET_VERY_BAD (uint32_t)2
```

[very bad].

Crack within one hour

Definition at line **1163** of file **f_nano_crypto_util.h**.

5.3.2.10 F_BRAIN_WALLET_VERY_GOOD

```
#define F_BRAIN_WALLET_VERY_GOOD (uint32_t)9
```

[very good].

Crack within ten thousand year

Definition at line **1206** of file **f_nano_crypto_util.h**.

5.3.2.11 F_BRAIN_WALLET_VERY_POOR

```
#define F_BRAIN_WALLET_VERY_POOR (uint32_t)0
```

[very poor].

Crack within seconds or less

Definition at line **1151** of file **f_nano_crypto_util.h**.

5.3.2.12 F_BRAIN_WALLET_VERY_WEAK

```
#define F_BRAIN_WALLET_VERY_WEAK (uint32_t)4
```

[very weak].

Crack within one week

Definition at line **1175** of file **f_nano_crypto_util.h**.

5.3.2.13 F_BRAIN_WALLET_WEAK

```
#define F_BRAIN_WALLET_WEAK (uint32_t)5
```

[weak].

Crack within one month

Definition at line **1181** of file **f_nano_crypto_util.h**.

5.3.2.14 **F_DEFAULT_THRESHOLD**

```
#define F_DEFAULT_THRESHOLD (uint64_t) 0xffffffffc000000000
```

Default Nano Proof of Work Threshold.

Definition at line **1321** of file **f_nano_crypto_util.h**.

5.3.2.15 **F_IS_SIGNATURE_RAW_HEX_STRING**

```
#define F_IS_SIGNATURE_RAW_HEX_STRING (uint32_t) 64
```

Signature is raw hex string flag.

See also

f_sign_data() (p. ??)

Definition at line **1308** of file **f_nano_crypto_util.h**.

5.3.2.16 **F_MESSAGE_IS_HASH_STRING**

```
#define F_MESSAGE_IS_HASH_STRING (uint32_t) 128
```

Message is raw hex hash string.

See also

f_sign_data() (p. ??)

Definition at line **1315** of file **f_nano_crypto_util.h**.

5.3.2.17 **F_NANO_POW_MAX_THREAD**

```
#define F_NANO_POW_MAX_THREAD (size_t) 10
```

(desktop only) Number of threads for Proof of Work routines.

Default 10

Definition at line **136** of file **f_nano_crypto_util.h**.

5.3.2.18 F_SIGNATURE_OUTPUT_NANO_PK

```
#define F_SIGNATURE_OUTPUT_NANO_PK (uint32_t)32
```

Public key is a NANO wallet encoded base32 string.

See also

f_sign_data() (p. ??)

Definition at line 1301 of file **f_nano_crypto_util.h**.

5.3.2.19 F_SIGNATURE_OUTPUT_RAW_PK

```
#define F_SIGNATURE_OUTPUT_RAW_PK (uint32_t)4
```

Public key is raw data.

See also

f_sign_data() (p. ??)

Definition at line 1280 of file **f_nano_crypto_util.h**.

5.3.2.20 F_SIGNATURE_OUTPUT_STRING_PK

```
#define F_SIGNATURE_OUTPUT_STRING_PK (uint32_t)8
```

Public key is hex ASCII encoded string.

See also

f_sign_data() (p. ??)

Definition at line 1287 of file **f_nano_crypto_util.h**.

5.3.2.21 F_SIGNATURE_OUTPUT_XRB_PK

```
#define F_SIGNATURE_OUTPUT_XRB_PK (uint32_t)16
```

Public key is a XRB wallet encoded base32 string.

See also

f_sign_data() (p. ??)

Definition at line 1294 of file **f_nano_crypto_util.h**.

5.3.2.22 F_SIGNATURE_RAW

```
#define F_SIGNATURE_RAW (uint32_t)1
```

Signature is raw data.

See also

f_sign_data() (p. ??)

Definition at line 1266 of file **f_nano_crypto_util.h**.

5.3.2.23 F_SIGNATURE_STRING

```
#define F_SIGNATURE_STRING (uint32_t)2
```

Signature is hex ASCII encoded string.

See also

f_sign_data() (p. ??)

Definition at line 1273 of file **f_nano_crypto_util.h**.

5.3.2.24 F_VERIFY_SIG_ASCII_HEX

```
#define F_VERIFY_SIG_ASCII_HEX (uint32_t)4
```

Public key is a hex ASCII encoded string.

See also

f_verify_signed_data() (p. ??)

Definition at line 1373 of file **f_nano_crypto_util.h**.

5.3.2.25 F_VERIFY_SIG_NANO_WALLET

```
#define F_VERIFY_SIG_NANO_WALLET (uint32_t)1
```

Public key is a NANO wallet with *XRB* or *NANO* prefixes encoded base32 string.

See also

f_verify_signed_data() (p. ??)

Definition at line 1359 of file **f_nano_crypto_util.h**.

5.3.2.26 F_VERIFY_SIG_RAW_HEX

```
#define F_VERIFY_SIG_RAW_HEX (uint32_t)2
```

Public key raw 32 bytes data.

See also

f_verify_signed_data() (p. ??)

Definition at line **1366** of file **f_nano_crypto_util.h**.

5.3.2.27 MAX_STR_NANO_CHAR

```
#define MAX_STR_NANO_CHAR (size_t)70
```

Defines a max size of Nano char (70 bytes)

Definition at line **148** of file **f_nano_crypto_util.h**.

5.3.2.28 NANO_ENCRYPTED_SEED_FILE

```
#define NANO_ENCRYPTED_SEED_FILE "/spiffs/secure/nano.nse"
```

Path to non deterministic encrypted file with password.

File containing the SEED of the Nano wallets generated by TRNG (if available in your Hardware) or PRNG.
Default name: "nano.nse"

Definition at line **190** of file **f_nano_crypto_util.h**.

5.3.2.29 NANO_FILE_WALLETS_INFO

```
#define NANO_FILE_WALLETS_INFO "/spiffs/secure/walletsinfo.i"
```

Custom information file path about Nano SEED wallet stored in "walletsinfo.i".

Definition at line **208** of file **f_nano_crypto_util.h**.

5.3.2.30 NANO_PASSWD_MAX_LEN

```
#define NANO_PASSWD_MAX_LEN (size_t)80
```

Password max length.

Definition at line **196** of file **f_nano_crypto_util.h**.

5.3.2.31 NANO_PREFIX

```
#define NANO_PREFIX "nano_"
```

Nano prefix.

Definition at line **160** of file **f_nano_crypto_util.h**.

5.3.2.32 PUB_KEY_EXTENDED_MAX_LEN

```
#define PUB_KEY_EXTENDED_MAX_LEN (size_t)40
```

Max size of public key (extended)

Definition at line **154** of file **f_nano_crypto_util.h**.

5.3.2.33 REP_XRB

```
#define REP_XRB (uint8_t)0x4
```

Representative XRB flag.

Destination XRB flag.

Sender XRB flag.

5.3.2.34 SENDER_XRB

```
#define SENDER_XRB (uint8_t)0x02
```

Definition at line **427** of file **f_nano_crypto_util.h**.

5.3.2.35 STR_NANO_SZ

```
#define STR_NANO_SZ (size_t)66
```

String size of Nano encoded Base32 including NULL char.

Definition at line **202** of file **f_nano_crypto_util.h**.

5.3.2.36 XRB_PREFIX

```
#define XRB_PREFIX "xrb_"
```

XRB (old Raiblocks) prefix.

Definition at line **166** of file **f_nano_crypto_util.h**.

5.3.3 Typedef Documentation

5.3.3.1 F_FILE_INFO_ERR

```
F_FILE_INFO_ERR
```

Typedef Error enumerator for info file functions.

5.3.3.2 f_nano_err

```
f_nano_err
```

Error function enumerator.

See also

f_nano_err_t (p. ??)

5.3.3.3 F_TOKEN

```
typedef uint8_t F_TOKEN[16]
```

Definition at line **214** of file **f_nano_crypto_util.h**.

5.3.3.4 **f_uint128_t**

`f_uint128_t`

128 bit big number of Nano balance

Definition at line **226** of file **f_nano_crypto_util.h**.

5.3.3.5 **f_write_seed_err**

```
typedef enum f_write_seed_err_t f_write_seed_err
```

5.3.3.6 **NANO_PRIVATE_KEY**

`NANO_PRIVATE_KEY`

Size of Nano Private Key.

Definition at line **236** of file **f_nano_crypto_util.h**.

5.3.3.7 **NANO_PRIVATE_KEY_EXTENDED**

`NANO_PRIVATE_KEY_EXTENDED`

Size of Nano Private Key extended.

Definition at line **242** of file **f_nano_crypto_util.h**.

5.3.3.8 **NANO_PUBLIC_KEY**

`NANO_PUBLIC_KEY`

Size of Nano Public Key.

Definition at line **248** of file **f_nano_crypto_util.h**.

5.3.3.9 NANO_PUBLIC_KEY_EXTENDED

NANO_PUBLIC_KEY_EXTENDED

Size of Public Key Extended.

Definition at line **254** of file **f_nano_crypto_util.h**.

5.3.3.10 NANO_SEED

NANO_SEED

Size of Nano SEED.

Definition at line **220** of file **f_nano_crypto_util.h**.

5.3.4 Enumeration Type Documentation

5.3.4.1 f_file_info_err_t

enum **f_file_info_err_t**

Enumerator

F_FILE_INFO_ERR_OK	SUCCESS.
F_FILE_INFO_ERR_CANT_OPEN_INFO_FILE	Can't open info file.
F_FILE_INFO_ERR_NANO_SEED_ENCRYPTED_FILE_NOT_FOUND	Encrypted file with Nano SEED not found.
F_FILE_INFO_ERR_CANT_DELETE_NANO_INFO_FILE	Can not delete Nano info file.
F_FILE_INFO_ERR_MALLOC	Fatal Error MALLOC.
F_FILE_INFO_ERR_CANT_READ_NANO_SEED_ENCRYPTED_FILE	Can not read encrypted Nano SEED in file.
F_FILE_INFO_ERR_CANT_READ_INFO_FILE	Can not read info file.
F_FILE_INFO_INVALID_HEADER_FILE	Invalid info file header.
F_FILE_INFO_ERR_INVALID_SHA256_INFO_FILE	Invalid SHA256 info file.
F_FILE_INFO_ERR_NANO_SEED_HASH_FAIL	Nano SEED hash failed.
F_FILE_INFO_ERR_NANO_INVALID_REPRESENTATIVE	Invalid representative.
F_FILE_INFO_ERR_NANO_INVALID_MAX_FEE_VALUE	Invalid max fee value.
F_FILE_INFO_ERR_OPEN_FOR_WRITE_INFO	Can not open info file for write.
F_FILE_INFO_ERR_EXISTING_FILE	Error File Exists.
F_FILE_INFO_ERR_CANT_WRITE_FILE_INFO	Can not write info file.

Definition at line **539** of file **f_nano_crypto_util.h**.

5.3.4.2 f_nano_err_t

enum **f_nano_err_t**

Enumerator

NANO_ERR_OK	SUCCESS.
NANO_ERR_CANT_PARSE_BN_STR	Can not parse string big number.
NANO_ERR_MALLOC	Fatal ERROR MALLOC.
NANO_ERR_CANT_PARSE_FACTOR	Can not parse big number factor.
NANO_ERR_MPI_MULT	Error multiplication MPI.
NANO_ERR_CANT_PARSE_TO_BLK_TRANSFER	Can not parse to block transfer.
NANO_ERR_EMPTY_STR	Error empty string.
NANO_ERR_CANT_PARSE_VALUE	Can not parse value.
NANO_ERR_PARSE_MPI_TO_STR	Can not parse MPI to string.
NANO_ERR_CANT_COMPLETE_NULL_CHAR	Can not complete NULL char.
NANO_ERR_CANT_PARSE_TO_MPI	Can not parse to MPI.
NANO_ERR_INSUFICIENT_FUNDS	Insuficient funds.
NANO_ERR_SUB_MPI	Error subtract MPI.
NANO_ERR_ADD_MPI	Error add MPI.
NANO_ERR_NO_SENSE_VALUE_TO_SEND_NEGATIVE	Does not make sense send negativative balance.
NANO_ERR_NO_SENSE_VALUE_TO_SEND_ZERO	Does not make sense send empty value.
NANO_ERR_NO_SENSE_BALANCE_NEGATIVE	Does not make sense negative balance.
NANO_ERR_VAL_A_INVALID_MODE	Invalid A mode value.
NANO_ERR_CANT_PARSE_TO_TEMP_UINT128_T	Can not parse temporary memory to uint_128_t.
NANO_ERR_VAL_B_INVALID_MODE	Invalid A mode value.
NANO_ERR_CANT_PARSE_RAW_A_TO_MPI	Can not parse raw A value to MPI.
NANO_ERR_CANT_PARSE_RAW_B_TO_MPI	Can not parse raw B value to MPI.
NANO_ERR_UNKNOWN_ADD_SUB_MODE	Unknown ADD/SUB mode.
NANO_ERR_INVALID_RES_OUTPUT	Invalid output result.

Definition at line 298 of file **f_nano_crypto_util.h**.

5.3.4.3 f_write_seed_err_t

enum **f_write_seed_err_t**

Enumerator

WRITE_ERR_OK	Error SUCCESS.
WRITE_ERR_NULL_PASSWORD	Error NULL password.
WRITE_ERR_EMPTY_STRING	Empty string.
WRITE_ERR_MALLOC	Error MALLOC.
WRITE_ERR_ENCRYPT_PRIV_KEY	Error encrypt private key.
WRITE_ERR_GEN_SUB_PRIV_KEY	Can not generate sub private key.
WRITE_ERR_GEN_MAIN_PRIV_KEY	Can not generate main private key.
WRITE_ERR_ENCRYPT_SUB_BLOCK	Can not encrypt sub block.

Enumerator

WRITE_ERR_UNKNOWN_OPTION	Unknown option.
WRITE_ERR_FILE_ALREADY_EXISTS	File already exists.
WRITE_ERR_CREATING_FILE	Can not create file.
WRITE_ERR_WRITING_FILE	Can not write file.

Definition at line **435** of file **f_nano_crypto_util.h**.

5.3.5 Function Documentation

5.3.5.1 __attribute__()

```
struct f_nano_wallet_info_t __attribute__ (
    (packed) )
```

5.3.5.2 f_bip39_to_nano_seed()

```
int f_bip39_to_nano_seed (
    uint8_t * seed,
    char * str,
    char * dictionary )
```

Parse Nano Bip39 encoded string to raw Nano SEED given a dictionary file.

Parameters

out	<i>seed</i>	Nano SEED
in	<i>str</i>	A encoded Bip39 string pointer
in	<i>dictionary</i>	A string pointer path to file

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_nano_seed_to_bip39() (p. ??)

5.3.5.3 f_cloud_crypto_wallet_nano_create_seed()

```
int f_cloud_crypto_wallet_nano_create_seed (
    size_t entropy,
    char * file_name,
    char * password )
```

Generates a new SEED and saves it to an non deterministic encrypted file.

password is mandatory

Parameters

in	<i>entropy</i>	Entropy type. Entropy type are: F_ENTROPY_TYPE_PARANOIC F_ENTROPY_TYPE_EXCELENT F_ENTROPY_TYPE_GOOD F_ENTROPY_TYPE_NOT_ENOUGH F_ENTROPY_TYPE_NOT_RECOMENDED
in	<i>file_name</i>	The file and path to be stored in your file system directory. It can be <i>NULL</i> . If you parse a <i>NULL</i> value then file will be stored in <i>NANO_ENCRYPTED_SEED_FILE</i> variable file system pointer.
in	<i>password</i>	Password of the encrypted file. It can NOT be <i>NULL</i> or <i>EMPTY</i>

WARNING

f_cloud_crypto_wallet_nano_create_seed() (p. ??) does not verify your password. It is recommended to use a strong password like symbols, capital letters and numbers to keep your SEED safe and avoid brute force attacks.

You can use **f_pass_must_have_at_least()** (p. ??) function to check passwords strength

Return values

0	On Success, otherwise Error
---	-----------------------------

5.3.5.4 f_extract_seed_from_brainwallet()

```
int f_extract_seed_from_brainwallet (
    uint8_t * seed,
    char ** warning_msg,
    uint32_t allow_mode,
    const char * brainwallet,
    const char * salt )
```

Analyzes a text given a *mode* and if pass then the text in *brainwallet* is translated to a Nano SEED.

Parameters

out	<i>seed</i>	Output Nano SEED extracted from <i>brainwallet</i>
-----	-------------	--

Parameters

out	<i>warning_msg</i>	Warning message parsed to application. It can be NULL
in	<i>allow_mode</i>	<p>Allow <i>mode</i>. Funtion will return SUCCESS only if permitted mode set by user</p> <p>Allow mode are:</p> <ul style="list-style-type: none"> • <i>F_BRAIN_WALLET_VERY_POOR</i> Crack within seconds or less • <i>F_BRAIN_WALLET_POOR</i> Crack within minutes • <i>F_BRAIN_WALLET_VERY_BAD</i> Crack within one hour • <i>F_BRAIN_WALLET_BAD</i> Crack within one day • <i>F_BRAIN_WALLET_VERY_WEAK</i> Crack within one week • <i>F_BRAIN_WALLET_WEAK</i> Crack within one month • <i>F_BRAIN_WALLET_STILL_WEAK</i> Crack within one year • <i>F_BRAIN_WALLET_MAYBE_GOOD</i> Crack within one century • <i>F_BRAIN_WALLET_GOOD</i> Crack within one thousand year • <i>F_BRAIN_WALLET_VERY_GOOD</i> Crack within ten thousand year • <i>F_BRAIN_WALLET_NICE</i> Crack withing one hundred thousand year • <i>F_BRAIN_WALLET_PERFECT</i> 3.34x10⁵³ Years to crack
in	<i>brainwallet</i>	Brainwallet text to be parsed. It can be NOT NULL or null string
in	<i>salt</i>	Salt of the Braiwallet. It can be NOT NULL or null string

Return values

0	If success, otherwise error.
---	------------------------------

See also

f_bip39_to_nano_seed() (p. ??)

5.3.5.5 f_generate_nano_seed()

```
int f_generate_nano_seed (
    NANO_SEED seed,
    uint32_t entropy )
```

Generates a new SEED and stores it to *seed* pointer.

Parameters

out	<i>seed</i>	SEED generated in system PRNG or TRNG
-----	-------------	---------------------------------------

Parameters

in	<i>entropy</i>	Entropy type. Entropy type are: F_ENTROPY_TYPE_PARANOIC F_ENTROPY_TYPE_EXCELENT F_ENTROPY_TYPE_GOOD F_ENTROPY_TYPE_NOT_ENOUGH F_ENTROPY_TYPE_NOT_RECOMENDED
----	----------------	--

Return values

0	On Success, otherwise Error
---	-----------------------------

5.3.5.6 f_generate_token()

```
int f_generate_token (
    F_TOKEN signature,
    void * data,
    size_t data_sz,
    const char * password )
```

Generates a non deterministic token given a message data and a password.

Parameters

out	<i>signature</i>	128 bit non deterministic token
in	<i>data</i>	Data to be signed in token
in	<i>data_sz</i>	Size of data
in	<i>password</i>	Password

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_verify_token() (p. ??)

5.3.5.7 f_get_dictionary_path()

```
char * f_get_dictionary_path (
    void )
```

Get default dictionary path in **myNanoEmbedded** library.

Return values

<i>Path</i>	and name of the dictionary file
-------------	---------------------------------

See also

f_set_dictionary_path() (p. ??)

5.3.5.8 f_get_nano_file_info()

```
F_FILE_INFO_ERR f_get_nano_file_info (
    F_NANO_WALLET_INFO * info )
```

Opens default file *walletsinfo.i* (if exists) containing information *F_NANO_WALLET_INFO* structure and parsing to pointer *info* if success.

Parameters

out	<i>info</i>	Pointer to buffer to be parsed struct from <i>\$PATH/walletsinfo.i</i> file.
-----	-------------	--

Return values

<i>F_FILE_INFO_ERR_OK</i>	If Success, otherwise <i>F_FILE_INFO_ERR</i> enum type error
---------------------------	--

See also

F_FILE_INFO_ERR (p. ??) enum type error for detailed error and **f_nano_wallet_info_t** (p. ??) for info type details

5.3.5.9 f_nano_add_sub()

```
f_nano_err f_nano_add_sub (
    void * res,
    void * valA,
    void * valB,
    uint32_t mode )
```

Add/Subtract two Nano balance values and stores value in *res*

Parameters

out	<i>res</i>	Result value $res = valA + valB$ or $res = valA - valB$
in	<i>valA</i>	Input balance A value
in	<i>valB</i>	Input balance B value

Parameters

in	mode	Mode type: <ul style="list-style-type: none"> • <code>F_NANO_ADD_A_B</code> valA + valB • <code>F_NANO_SUB_A_B</code> valA - valB • <code>F_NANO_RES_RAW_128</code> Output is a raw data 128 bit big number result • <code>F_NANO_RES_RAW_STRING</code> Output is a 128 bit Big Integer string • <code>F_NANO_RES_REAL_STRING</code> Output is a Real string value • <code>F_NANO_A_RAW_128</code> if <i>balance</i> is big number raw buffer type • <code>F_NANO_A_RAW_STRING</code> if <i>balance</i> is big number raw string type • <code>F_NANO_A_REAL_STRING</code> if <i>balance</i> is real number string type • <code>F_NANO_B_RAW_128</code> if <i>value_to_send</i> is big number raw buffer type • <code>F_NANO_B_RAW_STRING</code> if <i>value_to_send</i> is big number raw string type • <code>F_NANO_B_REAL_STRING</code> if <i>value_to_send</i> is real number string type
----	------	---

Return values

<code>NANO_ERR_OK</code>	If Success, otherwise <code>f_nano_err_t</code> enum type error
--------------------------	---

See also

`f_nano_err_t` (p. ??) for `f_nano_err` (p. ??) enum error type

5.3.5.10 f_nano_balance_to_str()

```

f_nano_err f_nano_balance_to_str (
    char * str,
    size_t str_len,
    size_t * out_len,
    f_uint128_t value )

```

Converts a raw Nano balance to string raw balance.

Parameters

out	<i>str</i>	Output string pointer
in	<i>str_len</i>	Size of string pointer memory
out	<i>out_len</i>	Output length of converted value to string. If <i>out_len</i> is NULL then <i>str</i> returns converted value with NULL terminated string
in	<i>value</i>	Raw Nano balance value

Return values

0	If success, otherwise error.
---	------------------------------

See also

function **f_nano_parse_raw_str_to_raw128_t()** (p. ??) and return errors **f_nano_err** (p. ??)

5.3.5.11 f_nano_block_to_json()

```
int f_nano_block_to_json (
    char * dest,
    size_t * olen,
    size_t dest_size,
    F_BLOCK_TRANSFER * user_block )
```

Parse a Nano Block to JSON.

Parameters

out	<i>dest</i>	Destination of the converted JSON block
out	<i>olen</i>	Output length of the converted JSON block. <i>olen</i> can be NULL. If NULL, destination size contains a NULL char
in	<i>dest_size</i>	Size of <i>dest</i> memory buffer
in	<i>user_block</i>	User Nano block

Returns

0 if success, non zero if error

5.3.5.12 f_nano_get_block_hash()

```
int f_nano_get_block_hash (
    uint8_t * hash,
    F_BLOCK_TRANSFER * block )
```

Gets a hash from Nano block.

Parameters

out	<i>hash</i>	Output hash
in	<i>block</i>	Nano Block

Returns

0 if success, non zero if error

5.3.5.13 f_nano_get_p2pow_block_hash()

```
int f_nano_get_p2pow_block_hash (
    uint8_t * user_hash,
    uint8_t * fee_hash,
    F_BLOCK_TRANSFER * block )
```

Get Nano user block hash and Nano fee block hashes from P2PoW block.

Parameters

out	<i>user_hash</i>	Hash of the user block
out	<i>fee_hash</i>	Hash of the P2PoW block
in	<i>block</i>	Input Nano Block

Returns

0 if success, non zero if error

5.3.5.14 f_nano_is_valid_block()

```
int f_nano_is_valid_block (
    F_BLOCK_TRANSFER * block )
```

Checks if Binary Nano Block is valid.

Parameters

in	<i>block</i>	Nano Block
----	--------------	------------

Returns

0 if is invalid block or 1 if is valid block

5.3.5.15 f_nano_key_to_str()

```
char * f_nano_key_to_str (
    char * out,
    unsigned char * key )
```

Parse a raw binary public key to string.

Parameters

out	<i>out</i>	Pointer to output string
in	<i>in</i>	Pointer to raw public key

Returns

A pointer to output string

5.3.5.16 f_nano_p2pow_to_JSON()

```
int f_nano_p2pow_to_JSON (
    char * buffer,
    size_t * olen,
    size_t buffer_sz,
    F_BLOCK_TRANSFER * block )
```

Parse binary P2PoW block to JSON.

Parameters

out	<i>buffer</i>	Output JSON string
out	<i>olen</i>	Output JSON string size. <i>olen</i> can be NULL. If NULL, <i>buffer</i> will be terminated with a NULL char
in	<i>buffer_sz</i>	Size of memory buffer
in	<i>block</i>	P2PoW block

Returns

0 if success, non zero if error

5.3.5.17 f_nano_parse_raw_str_to_raw128_t()

```
f_nano_err f_nano_parse_raw_str_to_raw128_t (
    uint8_t * res,
    const char * raw_str_value )
```

Parse a raw string balance to raw big number 128 bit.

Parameters

out	<i>res</i>	Binary raw balance
in	<i>raw_str_value</i>	Raw balance string

Return values

<i>NANO_ERR_OK</i>	If Success, otherwise f_nano_err_t enum type error
--------------------	--

See also

f_nano_err_t (p. ??) for **f_nano_err** (p. ??) enum error type

5.3.5.18 f_nano_parse_real_str_to_raw128_t()

```
f_nano_err f_nano_parse_real_str_to_raw128_t (
    uint8_t * res,
    const char * real_str_value )
```

Parse a real string balance to raw big number 128 bit.

Parameters

out	<i>res</i>	Binary raw balance
in	<i>real_str_value</i>	Real balance string

Return values

<i>NANO_ERR_OK</i>	If Success, otherwise f_nano_err_t enum type error
--------------------	--

See also

f_nano_err_t (p. ??) for **f_nano_err** (p. ??) enum error type

5.3.5.19 f_nano_pow()

```
int f_nano_pow (
    uint64_t * PoW_res,
    unsigned char * hash,
    const uint64_t threshold,
    int n_thr )
```

Calculates a Proof of Work given a *hash*, *threshold* and number of threads *n_thr*

Parameters

out	<i>PoW_res</i>	Output Proof of Work
in	<i>hash</i>	Input <i>hash</i>
in	<i>threshold</i>	Input <i>threshold</i>
in	<i>n_thr</i>	Number of threads. Default maximum value: 10. You can modify
		<i>F_NANO_POW_MAX_THREAD</i> in f_nano_crypto_util.h (p. ??)

Mandatory: You need to enable attach a random function to your project using **f_random_attach()** (p. ??)

Return values

0	If success, otherwise error.
---	------------------------------

See also

f_verify_work() (p. ??)

5.3.5.20 f_nano_raw_to_string()

```
int f_nano_raw_to_string (
    char * str,
    size_t * olen,
    size_t str_sz,
    void * raw,
    int raw_type )
```

Converts Nano raw balance [string | f_uint128_t] to real string value.

Parameters

out	<i>str</i>	Output real string value
out	<i>olen</i>	Size of output real string value. It can be NULL. If NULL output <i>str</i> will have a NULL char at the end.
in	<i>str_sz</i>	Size of <i>str</i> buffer
in	<i>raw</i>	Raw balance.
in	<i>raw_type</i>	Raw balance type: <ul style="list-style-type: none"> • F_RAW_TO_STR_UINT128 for raw f_uint128_t balance • F_RAW_TO_STR_STRING for raw char balance

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_nano_valid_nano_str_value() (p. ??)

5.3.5.21 f_nano_seed_to_bip39()

```
int f_nano_seed_to_bip39 (
    char * buf,
```

```

size_t buf_sz,
size_t * out_buf_len,
NANO_SEED seed,
char * dictionary_file )

```

Parse Nano SEED to Bip39 encoding given a dictionary file.

Parameters

out	<i>buf</i>	Output string containing encoded Bip39 SEED
in	<i>buf_sz</i>	Size of memory of buf pointer
out	<i>out_buf_len</i>	If <i>out_buf_len</i> is NOT NULL then <i>out_buf_len</i> returns the size of string encoded Bip39 and <i>out</i> with non NULL char. If <i>out_buf_len</i> is NULL then <i>out</i> has a string encoded Bip39 with a NULL char.
in	<i>seed</i>	Nano SEED
in	<i>dictionary_file</i>	Path to dictionary file

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_bip39_to_nano_seed() (p. ??)

5.3.5.22 f_nano_sign_block()

```

int f_nano_sign_block (
    F_BLOCK_TRANSFER * user_block,
    F_BLOCK_TRANSFER * fee_block,
    NANO_PRIVATE_KEY_EXTENDED private_key )

```

Signs *user_block* and worker *fee_block* given a private key *private_key*

Parameters

in, out	<i>user_block</i>	User block to be signed with a private key <i>private_key</i>
in, out	<i>fee_block</i>	Fee block to be signed with a private key <i>private_key</i> . Can be NULL if worker does not require fee
in	<i>private_key</i>	Private key to sign block(s)

Return values

0	If Success, otherwise error
---	-----------------------------

See also

f_nano_transaction_to_JSON() (p. ??)

5.3.5.23 f_nano_transaction_to_JSON()

```
int f_nano_transaction_to_JSON (
    char * str,
    size_t str_len,
    size_t * str_out,
    NANO_PRIVATE_KEY_EXTENDED private_key,
    F_BLOCK_TRANSFER * block_transfer )
```

Sign a block pointed in *block_transfer* with a given *private_key* and stores signed block to *block_transfer* and parse to JSON Nano RPC.

Parameters

out	<i>str</i>	A string pointer to store JSON Nano RPC
in	<i>str_len</i>	Size of buffer in <i>str</i> pointer
out	<i>str_out</i>	Size of JSON string. <i>str_out</i> can be NULL
in	<i>private_key</i>	Private key to sign the block <i>block_transfer</i>
in, out	<i>block_transfer</i>	Nano block containing raw data to be stored in Nano Blockchain

WARNING Sensitive data. Do not share any PRIVATE KEY

Return values

0	On Success, otherwise Error
---	-----------------------------

5.3.5.24 f_nano_valid_nano_str_value()

```
int f_nano_valid_nano_str_value (
    const char * str )
```

Check if a real string or raw string are valid Nano balance.

Parameters

in	<i>str</i>	Value to be checked
----	------------	---------------------

Return values

0	If valid, otherwise is invalid
---	--------------------------------

See also

f_nano_raw_to_string() (p. ??)

5.3.5.25 f_nano_value_compare_value()

```
f_nano_err f_nano_value_compare_value (
    void * valA,
    void * valB,
    uint32_t * mode_compare )
```

Compare two Nano balance.

Parameters

in	<i>valA</i>	Nano balance value A
in	<i>valB</i>	Nano balance value B
in, out	<i>mode_compare</i>	<p>Input mode and output result</p> <p>Input mode:</p> <ul style="list-style-type: none"> • <i>F_NANO_A_RAW_128</i> if <i>valA</i> is big number raw buffer type • <i>F_NANO_A_RAW_STRING</i> if <i>valA</i> is big number raw string type • <i>F_NANO_A_REAL_STRING</i> if <i>valA</i> is real number string type • <i>F_NANO_B_RAW_128</i> if <i>valB</i> is big number raw buffer type • <i>F_NANO_B_RAW_STRING</i> if <i>valB</i> is big number raw string type • <i>F_NANO_B_REAL_STRING</i> if <i>valB</i> is real number string type <p>Output type:</p> <ul style="list-style-type: none"> • <i>F_NANO_COMPARE_EQ</i> If <i>valA</i> is greater than <i>valB</i> • <i>F_NANO_COMPARE_LT</i> if <i>valA</i> is lesser than <i>valB</i> • <i>F_NANO_COMPARE_LEQ</i> if <i>valA</i> is lesser or equal than <i>valB</i> • <i>F_NANO_COMPARE_GT</i> if <i>valA</i> is greater than <i>valB</i> • <i>F_NANO_COMPARE_GEQ</i> If <i>valA</i> is greater or equal than <i>valB</i>

Return values

<i>NANO_ERR_OK</i>	If Success, otherwise f_nano_err_t enum type error
--------------------	--

See also

f_nano_err_t (p. ??) for **f_nano_err** (p. ??) enum error type

5.3.5.26 `f_nano_verify_nano_funds()`

```
f_nano_err f_nano_verify_nano_funds (
    void * balance,
    void * value_to_send,
    void * fee,
    uint32_t mode )
```

Check if Nano balance has sufficient funds.

Parameters

in	<i>balance</i>	Nano balance
in	<i>value_to_send</i>	Value to send
in	<i>fee</i>	Fee value (it can be NULL)
in	<i>mode</i>	Value type mode <ul style="list-style-type: none"> • <i>F_NANO_A_RAW_128</i> if <i>balance</i> is big number raw buffer type • <i>F_NANO_A_RAW_STRING</i> if <i>balance</i> is big number raw string type • <i>F_NANO_A_REAL_STRING</i> if <i>balance</i> is real number string type • <i>F_NANO_B_RAW_128</i> if <i>value_to_send</i> is big number raw buffer type • <i>F_NANO_B_RAW_STRING</i> if <i>value_to_send</i> is big number raw string type • <i>F_NANO_B_REAL_STRING</i> if <i>value_to_send</i> is real number string type • <i>F_NANO_C_RAW_128</i> if <i>fee</i> is big number raw buffer type (can be omitted if <i>fee</i> is NULL) • <i>F_NANO_C_RAW_STRING</i> if <i>fee</i> is big number raw string type (can be omitted if <i>fee</i> is NULL) • <i>F_NANO_C_REAL_STRING</i> if <i>fee</i> is real number string type (can be omitted if <i>fee</i> is NULL)

Return values

<i>NANO_ERR_OK</i>	If Success, otherwise <code>f_nano_err_t</code> enum type error
--------------------	---

See also

`f_nano_err_t` (p. ??) for `f_nano_err` (p. ??) enum error type

5.3.5.27 `f_parse_nano_seed_and_bip39_to_JSON()`

```
int f_parse_nano_seed_and_bip39_to_JSON (
    char * dest,
    size_t dest_sz,
    size_t * olen,
    void * source_data,
```

```
int source,
const char * password )
```

Parse Nano SEED and Bip39 to JSON given a encrypted data in memory or encrypted data in file or unencrypted seed in memory.

Parameters

out	<i>dest</i>	Destination JSON string pointer
in	<i>dest_sz</i>	Buffer size of <i>dest</i> pointer
out	<i>olen</i>	Size of the output JSON string. If NULL string JSON returns a NULL char at the end of string otherwise it will return the size of the string is stored into <i>olen</i> variable without NULL string in <i>dest</i>
in	<i>source_data</i>	Input data source (encrypted file encrypted data in memory unencrypted seed in memory)
in	<i>source</i>	Source data type: <ul style="list-style-type: none"> • PARSE_JSON_READ_SEED_GENERIC: If seed are in memory pointed in <i>source_data</i>. Password is ignored. Can be NULL. • READ_SEED_FROM_STREAM: Read encrypted data from stream pointed in <i>source_data</i>. Password is required. • READ_SEED_FROM_FILE: Read encrypted data stored in a file where <i>source_data</i> is path to file. Password is required.
in	<i>password</i>	Required for READ_SEED_FROM_STREAM and READ_SEED_FROM_FILE sources

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_read_seed() (p. ??)

5.3.5.28 f_read_seed()

```
int f_read_seed (
    uint8_t * seed,
    const char * passwd,
    void * source_data,
    int force_read,
    int source )
```

Extracts a Nano SEED from encrypted stream in memory or in a file.

Parameters

out	<i>seed</i>	Output Nano SEED
in	<i>passwd</i>	Password (always required)
in	<i>source_data</i>	Encrypted source data from memory or path pointed in <i>source_data</i>
in	<i>force_read</i>	If non zero value then forces reading from a corrupted file. This param is ignored when reading <i>source_data</i> from memory
in	<i>source</i>	Source data type: <ul style="list-style-type: none"> • READ_SEED_FROM_STREAM: Read encrypted data from stream pointed in <i>source_data</i>. Password is required. • READ_SEED_FROM_FILE: Read encrypted data stored in a file where <i>source_data</i> is path to file. Password is required.

WARNING Sensitive data. Do not share any SEED !

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_parse_nano_seed_and_bip39_to_JSON() (p. ??) **f_write_seed()** (p. ??)

5.3.5.29 f_seed_to_nano_wallet()

```
int f_seed_to_nano_wallet (
    NANO_PRIVATE_KEY private_key,
    NANO_PUBLIC_KEY public_key,
    NANO_SEED seed,
    uint32_t wallet_number )
```

Extracts one key pair from Nano SEED given a wallet number.

Parameters

out	<i>private_key</i>	Private key of the <i>wallet_number</i> from given <i>seed</i>
out	<i>public_key</i>	Public key of the <i>wallet_number</i> from given <i>seed</i>
in, out	<i>seed</i>	Nano SEED
in	<i>wallet_number</i>	Wallet number of key pair to be extracted from Nano SEED

WARNING 1:

- Seed must be read from memory
- Seed is destroyed when extracting public and private keys

WARNING 2:

- Never expose SEED and private key. This function destroys seed and any data after execution and finally parse public and private keys to output.

Return values

0	On Success, otherwise Error
---	-----------------------------

5.3.5.30 f_set_dictionary_path()

```
void f_set_dictionary_path (
    const char * path )
```

Set default dictionary file and path to **myNanoEmbedded** library.

Parameters

in	<i>path</i>	Path to dictionary file
----	-------------	-------------------------

If **f_set_dictionary_path()** (p. ??) is not used in **myNanoEmbedded** library then default path stored in *BIP39_DICTIONARY* is used

See also

f_get_dictionary_path() (p. ??)

5.3.5.31 f_set_nano_file_info()

```
F_FILE_INFO_ERR f_set_nano_file_info (
    F_NANO_WALLET_INFO * info,
    int overwrite_existing_file )
```

Saves wallet information stored at buffer struct *info* to file *walletsinfo.i*

Parameters

in	<i>info</i>	Pointer to data to be saved at <i>\$PATH/walletsinfo.i</i> file.
in	<i>overwrite_existing_file</i>	If non zero then overwrites file <i>\$PATH/walletsinfo.i</i>

Return values

<i>F_FILE_INFO_ERR_OK</i>	If Success, otherwise <i>F_FILE_INFO_ERR</i> enum type error
---------------------------	--

See also

F_FILE_INFO_ERR (p. ??) enum type error for detailed error and **f_nano_wallet_info_t** (p. ??) for info type details

5.3.5.32 f_sign_data()

```
int f_sign_data (
    unsigned char * signature,
    void * out_public_key,
    uint32_t output_type,
    const unsigned char * message,
    size_t msg_len,
    const unsigned char * private_key )
```

Signs a *message* with a deterministic signature given a *private key*

Parameters

out	<i>signature</i>	Output signature
out	<i>out_public_key</i>	Output public key. It can be NULL
in	<i>output_type</i>	Output type of public key. Public key types are: <ul style="list-style-type: none"> • <i>F_SIGNATURE_RAW</i> Signature is raw 64 bytes long • <i>F_SIGNATURE_STRING</i> Singnature is hex ASCII encoded string • <i>F_SIGNATURE_OUTPUT_RAW_PK</i> Public key is raw 32 bytes data • <i>F_SIGNATURE_OUTPUT_STRING_PK</i> Public key is hes ASCII encoded string • <i>F_SIGNATURE_OUTPUT_XRB_PK</i> Public key is a XRB wallet encoded base32 string • <i>F_SIGNATURE_OUTPUT_NANO_PK</i> Public key is a NANO wallet encoded base32 string
in	<i>message</i>	Message to be signed with Elliptic Curve Ed25519 with blake2b hash
in	<i>msg_len</i>	Size of message to be signed
in	<i>private_key</i>	Private key to sign message

Return values

0	If success, otherwise error.
---	------------------------------

See also

f_verify_signed_data() (p. ??)

5.3.5.33 f_verify_signed_data()

```
int f_verify_signed_data (
    const unsigned char * signature,
    const unsigned char * message,
    size_t message_len,
    const void * public_key,
    uint32_t pk_type )
```

Verifies if a signed message is valid.

Parameters

in	<i>signature</i>	Signature of the <i>message</i>
in	<i>message</i>	Message to be verified
in	<i>message_len</i>	Length of the message
in	<i>public_key</i>	Public key to verify signed message
in	<i>pk_type</i>	Type of the public key. Types are: <ul style="list-style-type: none"> • <i>F_VERIFY_SIG_NANO_WALLET</i> Public key is a NANO wallet with <i>XRB</i> or <i>NANO</i> prefixes encoded base32 string • <i>F_VERIFY_SIG_RAW_HEX</i> Public key is raw 32 bytes data • <i>F_VERIFY_SIG_ASCII_HEX</i> Public key is a hex ASCII encoded string

Return value are

- Greater than zero if *signature* is VALID
- 0 (zero) if *signature* is INVALID
- Negative if ERROR occurred

See also

f_sign_data() (p. ??)

5.3.5.34 f_verify_token()

```
int f_verify_token (
    F_TOKEN signature,
    void * data,
    size_t data_sz,
    const char * password )
```

Verifies if a token is valid given data and password.

Parameters

in	<i>signature</i>	128 bit non deterministic token
in	<i>data</i>	Data to be signed in token
in	<i>data_sz</i>	Size of data
in	<i>password</i>	Password

Return values

0	On if invalid; 1 if valid ; less than zero if an error occurs
---	---

See also

f_generate_token() (p. ??)

5.3.5.35 f_verify_work()

```
int f_verify_work (
    uint64_t * result,
    const unsigned char * hash,
    uint64_t * work,
    uint64_t threshold )
```

Verifies if Proof of Work of a given *hash* is valid.

Parameters

out	<i>result</i>	Result of work. It can be NULL
in	<i>hash</i>	Input <i>hash</i> for verification
in	<i>work</i>	Work previously calculated to be checked
in	<i>threshold</i>	Input <i>threshold</i>

Return values

0	If is not valid or less than zero if error or greater than zero if is valid
---	---

See also

f_nano_pow() (p. ??)

5.3.5.36 f_write_seed()

```
f_write_seed_err f_write_seed (
    void * source_data,
```



```
int source,
uint8_t * seed,
char * passwd )
```

Writes a SEED into a encrypted with password with non deterministic stream in memory or file.

Parameters

out	<i>source_data</i>	Memory pointer or file name
in	<i>source</i>	Source of output data: <ul style="list-style-type: none"> • <i>WRITE_SEED_TO_STREAM</i> Output data is a pointer to memory to store encrypted Nano SEED data • <i>WRITE_SEED_TO_FILE</i> Output is a string filename to store encrypted Nano SEED data
in	<i>seed</i>	Nano SEED to be stored in encrypted stream or file
in	<i>passwd</i>	(Mandatory) It can not be null string or NULL. See <i>f_pass_must_have_at_least()</i> (p. ??) function to check passwords strength

Return values

0	If Success, otherwise error
---	-----------------------------

See also

f_read_seed() (p. ??)

5.3.5.37 from_multiplier()

```
uint64_t from_multiplier (
    double multiplier,
    uint64_t base_difficulty )
```

Calculates a PoW given a multiplier and base difficulty.

Parameters

in	<i>multiplier</i>	Multiplier of the work
in	<i>base_difficulty</i>	Base difficulty Details here

See also

to_multiplier() (p. ??)

Return values

<i>Calculated</i>	value
-------------------	-------

5.3.5.38 is_nano_prefix()

```
int is_nano_prefix (
    const char * nano_wallet,
    const char * prefix )
```

Checks *prefix* in *nano_wallet*

Parameters

in	<i>nano_wallet</i>	Base32 Nano wallet encoded string
in	<i>prefix</i>	Prefix type <ul style="list-style-type: none"> • NANO_PREFIX for nano_ • XRB_PREFIX for xrb_

Return values

1	If <i>prefix</i> in <i>nano_wallet</i> , otherwise 0
---	--

5.3.5.39 is_null_hash()

```
int is_null_hash (
    uint8_t * hash )
```

Check if 32 bytes hash is filled with zeroes.

Parameters

in	<i>hash</i>	32 bytes binary <i>hash</i>
----	-------------	-----------------------------

Return values

1	If zero filled buffer, otherwise 0
---	------------------------------------

5.3.5.40 nano_base_32_2_hex()

```
int nano_base_32_2_hex (
    uint8_t * res,
    char * str_wallet )
```

Parse Nano Base32 wallet string to public key binary.

Parameters

out	<i>res</i>	Output raw binary public key
in	<i>str_wallet</i>	Valid Base32 encoded Nano string to be parsed

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

pk_to_wallet() (p. ??)

5.3.5.41 pk_to_wallet()

```
int pk_to_wallet (
    char * out,
    char * prefix,
    NANO_PUBLIC_KEY_EXTENDED pubkey_extended )
```

Parse a Nano public key to Base32 Nano wallet string.

Parameters

out	<i>out</i>	Output string containing the wallet
in	<i>prefix</i>	Nano prefix. <i>NANO_PREFIX</i> for nano_ <i>XRB_PREFIX</i> for xrb_
in, out	<i>pubkey_extended</i>	Public key to be parsed to string

WARNING: *pubkey_extended* is destroyed when parsing to Nano base32 encoding

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

nano_base_32_2_hex() (p. ??)

5.3.5.42 to_multiplier()

```
double to_multiplier (
    uint64_t difficulty,
    uint64_t base_difficulty )
```

Calculates a relative difficulty compared PoW with another.

Parameters

in	<i>difficulty</i>	Work difficulty
in	<i>base_difficulty</i>	Base difficulty Details here

See also

from_multiplier() (p. ??)

Return values

<i>Calculated</i>	value
-------------------	-------

5.3.5.43 valid_nano_wallet()

```
int valid_nano_wallet (
    const char * wallet )
```

Check if a string containing a Base32 Nano wallet is valid.

Parameters

in	<i>wallet</i>	Base32 Nano wallet encoded string
----	---------------	-----------------------------------

Return values

0	If valid wallet otherwise is invalid
---	--------------------------------------

5.3.5.44 valid_raw_balance()

```
int valid_raw_balance (
    const char * balance )
```

Checks if a string buffer pointed in *balance* is a valid raw balance.

Parameters

<code>in</code>	<code>balance</code>	Pointer containing a string buffer
-----------------	----------------------	------------------------------------

Return values

<code>0</code>	On Success, otherwise Error
----------------	-----------------------------

5.3.6 Variable Documentation

5.3.6.1 `account`

```
uint8_t account[32]
```

Account in raw binary data.

Definition at line **258** of file `f_nano_crypto_util.h`.

5.3.6.2 `balance`

```
f_uint128_t balance
```

Big number 128 bit raw balance.

See also

`f_uint128_t` (p. ??)

Definition at line **266** of file `f_nano_crypto_util.h`.

5.3.6.3 `body`

```
F_NANO_WALLET_INFO_BODY body
```

Body of the file info.

Definition at line **266** of file `f_nano_crypto_util.h`.

5.3.6.4 desc

```
char desc[F_NANO_DESC_SZ]
```

Description.

Definition at line **260** of file **f_nano_crypto_util.h**.

5.3.6.5 description

```
uint8_t description[F_DESC_SZ]
```

File description.

Definition at line **260** of file **f_nano_crypto_util.h**.

5.3.6.6 file_info_integrity

```
uint8_t file_info_integrity[32]
```

File info integrity of the body block.

Definition at line **264** of file **f_nano_crypto_util.h**.

5.3.6.7 hash_sk_unencrypted

```
uint8_t hash_sk_unencrypted[32]
```

hash of Nano SEED when unencrypted

Definition at line **262** of file **f_nano_crypto_util.h**.

5.3.6.8 header

```
uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)]
```

Header magic.

Definition at line **256** of file **f_nano_crypto_util.h**.

5.3.6.9 iv

```
uint8_t iv
```

Initial sub vector.

Initial vector of first encryption layer.

Definition at line **258** of file **f_nano_crypto_util.h**.

5.3.6.10 last_used_wallet_number

```
uint32_t last_used_wallet_number
```

Last used wallet number.

Definition at line **258** of file **f_nano_crypto_util.h**.

5.3.6.11 link

```
uint8_t link[32]
```

link or destination account

Definition at line **268** of file **f_nano_crypto_util.h**.

5.3.6.12 max_fee

```
char max_fee[F_RAW_STR_MAX_SZ]
```

Custom preferred max fee of Proof of Work.

Definition at line **262** of file **f_nano_crypto_util.h**.

5.3.6.13 nano_hdr

```
uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)]
```

Header of the file.

Definition at line **256** of file **f_nano_crypto_util.h**.

5.3.6.14 nanoseed_hash

```
uint8_t nanoseed_hash[32]
```

Nano SEED hash file.

Definition at line **262** of file **f_nano_crypto_util.h**.

5.3.6.15 preamble

```
uint8_t preamble[32]
```

Block preamble.

Definition at line **256** of file **f_nano_crypto_util.h**.

5.3.6.16 prefixes

```
uint8_t prefixes
```

Internal use for this API.

Definition at line **272** of file **f_nano_crypto_util.h**.

5.3.6.17 previous

```
uint8_t previous[32]
```

Previous block.

Definition at line **260** of file **f_nano_crypto_util.h**.

5.3.6.18 representative

```
uint8_t representative[32]
```

Representative for current account.

Definition at line **262** of file **f_nano_crypto_util.h**.

5.3.6.19 `reserved`

```
uint8_t reserved
```

Reserved (not used)

Reserved.

Definition at line **260** of file `f_nano_crypto_util.h`.

5.3.6.20 `salt`

```
uint8_t salt[32]
```

Salt of the first encryption layer.

Definition at line **262** of file `f_nano_crypto_util.h`.

5.3.6.21 `seed_block`

```
F_ENCRYPTED_BLOCK seed_block
```

Second encrypted block for Nano SEED.

Definition at line **266** of file `f_nano_crypto_util.h`.

5.3.6.22 `signature`

```
uint8_t signature[64]
```

Signature of the block.

Definition at line **270** of file `f_nano_crypto_util.h`.

5.3.6.23 `sk_encrypted`

```
uint8_t sk_encrypted[32]
```

Secret.

SEED encrypted (second layer)

Definition at line **264** of file `f_nano_crypto_util.h`.

5.3.6.24 sub_salt

```
uint8_t sub_salt[32]
```

Salt of the sub block to be stored.

Definition at line 256 of file `f_nano_crypto_util.h`.

5.3.6.25 ver

```
uint32_t ver
```

Version of the file.

Definition at line 258 of file `f_nano_crypto_util.h`.

5.3.6.26 version

```
uint16_t version
```

Version.

Definition at line 258 of file `f_nano_crypto_util.h`.

5.3.6.27 wallet_prefix

```
uint8_t wallet_prefix
```

Wallet prefix: 0 for NANO; 1 for XRB.

Definition at line 256 of file `f_nano_crypto_util.h`.

5.3.6.28 wallet_representative

```
char wallet_representative[ MAX_STR_NANO_CHAR]
```

Wallet representative.

Definition at line 260 of file `f_nano_crypto_util.h`.

5.3.6.29 work

```
uint64_t work
```

Internal use for this API.

Definition at line 274 of file f_nano_crypto_util.h.

5.4 f_nano_crypto_util.h

```
00001 /*
00002     AUTHOR: Fábio Pereira da Silva
00003     YEAR: 2019-20
00004     LICENSE: MIT
00005     EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006 */
00007
00008 #include <stdint.h>
00009 #include "f_util.h"
00010
00011 #ifndef F_DOC_SKIP
00012
00013     #ifdef F_XTENZA
00014
00015         #ifndef F_ESP32
00016             #define F_ESP32
00017         #endif
00018
00019         #include "esp_system.h"
00020
00021     #endif
00022
00023     #include "sodium/crypto_generichash.h"
00024     #include "sodium/crypto_sign.h"
00025     #include "sodium.h"
00026
00027     #ifdef F_ESP32
00028
00029         #include "sodium/private/curve25519_ref10.h"
00030
00031     #else
00032
00033         #include "sodium/private/ed25519_ref10.h"
00034
00035         #define ge_p3 ge25519_p3
00036         #define sc_reduce sc25519_reduce
00037         #define sc_muladd sc25519_muladd
00038         #define ge_scalarmult_base ge25519_scalarmult_base
00039         #define ge_p3_tobytes ge25519_p3_tobytes
00040
00041     #endif
00042
00043 #endif
00044
00127 #ifdef __cplusplus
00128 extern "C" {
00129 #endif
00130
00131
00136 #define F_NANO_POW_MAX_THREAD (size_t)10
00137
00138 #ifndef F_DOC_SKIP
00139     #ifdef F_ESP32
00140         #undef F_NANO_POW_MAX_THREAD
00141     #endif
00142 #endif
00143
00148 #define MAX_STR_NANO_CHAR (size_t)70 //5+56+8+1
00149
00154 #define PUB_KEY_EXTENDED_MAX_LEN (size_t)40
00155
00160 #define NANO_PREFIX "nano_"
00161
00166 #define XRB_PREFIX "xrb_"
00167
00168 #ifdef F_ESP32
00169
00174 #define BIP39_DICTIONARY "/spiffs/dictionary.dic"
```

```

00175 #else
00176
00177 #ifndef F_DOC_SKIP
00178     #define BIP39_DICTIONARY_SAMPLE "../dictionary.dic"
00179     #define BIP39_DICTIONARY "dictionary.dic"
00180 #endif
00181
00182 #endif
00183
00190 #define NANO_ENCRYPTED_SEED_FILE "/spiffs/secure/nano.nse"
00191
00196 #define NANO_PASSWD_MAX_LEN (size_t)80
00197
00202 #define STR_NANO_SZ (size_t)66// 65+1 Null included
00203
00208 #define NANO_FILE_WALLETS_INFO "/spiffs/secure/walletsinfo.i"
00209
00214 typedef uint8_t F_TOKEN[16];
00215
00220 typedef uint8_t NANO_SEED[crypto_sign_SEEDBYTES];
00221
00226 typedef uint8_t f_uint128_t[16];
00227
00228 #ifndef F_DOC_SKIP
00229     #define EXPORT_KEY_TO_CHAR_SZ (size_t)sizeof(NANO_SEED)+1
00230 #endif
00231
00236 typedef uint8_t NANO_PRIVATE_KEY[sizeof(NANO_SEED)];
00237
00242 typedef uint8_t NANO_PRIVATE_KEY_EXTENDED[crypto_sign_ed25519_SECRETKEYBYTES];
00243
00248 typedef uint8_t NANO_PUBLIC_KEY[crypto_sign_ed25519_PUBLICKEYBYTES];
00249
00254 typedef uint8_t NANO_PUBLIC_KEY_EXTENDED[PUB_KEY_EXTENDED_MAX_LEN];
00255
00264 typedef struct f_block_transfer_t {
00266     uint8_t preamble[32];
00268     uint8_t account[32];
00270     uint8_t previous[32];
00272     uint8_t representative[32];
00276     f_uint128_t balance;
00278     uint8_t link[32];
00280     uint8_t signature[64];
00282     uint8_t prefixes;
00284     uint64_t work;
00285 } __attribute__((packed)) F_BLOCK_TRANSFER;
00286
00287 #ifndef F_DOC_SKIP
00288     #define F_BLOCK_TRANSFER_SIGNABLE_SZ
00289         (size_t)(sizeof(F_BLOCK_TRANSFER)-64-sizeof(uint64_t)-sizeof(uint8_t))
00290 #endif
00290
00298 typedef enum f_nano_err_t {
00300     NANO_ERR_OK=0,
00302     NANO_ERR_CANT_PARSE_BN_STR=5151,
00304     NANO_ERR_MALLOC,
00306     NANO_ERR_CANT_PARSE_FACTOR,
00308     NANO_ERR_MPI_MULT,
00310     NANO_ERR_CANT_PARSE_TO_BLK_TRANSFER,
00312     NANO_ERR_EMPTY_STR,
00314     NANO_ERR_CANT_PARSE_VALUE,
00316     NANO_ERR_PARSE_MPI_TO_STR,
00318     NANO_ERR_CANT_COMPLETE_NULL_CHAR,
00320     NANO_ERR_CANT_PARSE_TO_MPI,
00322     NANO_ERR_INSUFFICIENT_FUNDS,
00324     NANO_ERR_SUB_MPI,
00326     NANO_ERR_ADD_MPI,
00328     NANO_ERR_NO_SENSE_VALUE_TO_SEND_NEGATIVE,
00330     NANO_ERR_NO_SENSE_VALUE_TO_SEND_ZERO,
00332     NANO_ERR_NO_SENSE_BALANCE_NEGATIVE,
00334     NANO_ERR_VAL_A_INVALID_MODE,
00336     NANO_ERR_CANT_PARSE_TO_TEMP_UINT128_T,
00338     NANO_ERR_VAL_B_INVALID_MODE,
00340     NANO_ERR_CANT_PARSE_RAW_A_TO_MPI,
00342     NANO_ERR_CANT_PARSE_RAW_B_TO_MPI,
00344     NANO_ERR_UNKNOWN_ADD_SUB_MODE,
00346     NANO_ERR_INVALID_RES_OUTPUT
00347 } f_nano_err;
00348
00349 #ifndef F_DOC_SKIP
00350
00351     #define READ_SEED_FROM_STREAM (int)1
00352     #define READ_SEED_FROM_FILE (int)2
00353     #define WRITE_SEED_TO_STREAM (int)4
00354     #define WRITE_SEED_TO_FILE (int)8
00355     #define PARSE_JSON_READ_SEED_GENERIC (int)16
00356     #define F_STREAM_DATA_FILE_VERSION (uint32_t)((1<<16)|0)

```

```

00357
00358 #endif
00359
00367 typedef struct f_nano_encrypted_wallet_t {
00369     uint8_t sub_salt[32];
00371     uint8_t iv[16];
00373     uint8_t reserved[16];
00375     uint8_t hash_sk_unencrypted[32];
00377     uint8_t sk_encrypted[32];
00378 } __attribute__((packed)) F_ENCRYPTED_BLOCK;
00379
00380 #ifndef F_DOC_SKIP
00381
00382     static const uint8_t NANO_WALLET_MAGIC[] = {'_', 'n', 'a', 'n', 'o', 'w', 'a', 'l', 'l', 'e', 't', 'f',
00383         'i', 'l', 'e', '_'};
00384     #define F_NANO_FILE_DESC "NANO Seed Encrypted file/stream. Keep it safe and backup it. This file is
00385         protected by password. BUY BITCOIN and NANO !!!"
00386     #define F_DESC_SZ (size_t) (160-sizeof(uint32_t))
00387 #endif
00388
00395 typedef struct f_nano_crypto_wallet_t {
00397     uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)];
00399     uint32_t ver;
00401     uint8_t description[F_DESC_SZ];
00403     uint8_t salt[32];
00405     uint8_t iv[16];
00407     F_ENCRYPTED_BLOCK seed_block;
00408 } __attribute__((packed)) F_NANO_CRYPTOWALLET;
00409
00410 #ifndef F_DOC_SKIP
00411
00412     _Static_assert((sizeof(F_NANO_CRYPTOWALLET)&0x1F)==0, "Error 1");
00413     _Static_assert((sizeof(F_ENCRYPTED_BLOCK)&0x1F)==0, "Error 2");
00414 #endif
00415
00416 #define REP_XRB (uint8_t)0x4
00422
00427 #define SENDER_XRB (uint8_t)0x02
00428
00433 #define DEST_XRB (uint8_t)0x01
00434
00435 typedef enum f_write_seed_err_t {
00437     WRITE_ERR_OK=0,
00439     WRITE_ERR_NULL_PASSWORD=7180,
00441     WRITE_ERR_EMPTY_STRING,
00443     WRITE_ERR_MALLOC,
00445     WRITE_ERR_ENCRYPT_PRIV_KEY,
00447     WRITE_ERR_GEN_SUB_PRIV_KEY,
00449     WRITE_ERR_GEN_MAIN_PRIV_KEY,
00451     WRITE_ERR_ENCRYPT_SUB_BLOCK,
00453     WRITE_ERR_UNKNOWN_OPTION,
00455     WRITE_ERR_FILE_ALREADY_EXISTS,
00457     WRITE_ERR_CREATING_FILE,
00459     WRITE_ERR_WRITING_FILE
00460 } f_write_seed_err;
00461
00462 #ifndef F_DOC_SKIP
00463
00464     #define F_RAW_TO_STR_UINT128 (int)1
00465     #define F_RAW_TO_STR_STRING (int)2
00466     #define F_RAW_STR_MAX_SZ (size_t)41 // 39 + '\0' + '.' -> 39 = log10(2^128)
00467     #define F_MAX_STR_RAW_BALANCE_MAX (size_t)40 //39+'\0'
00468     #define F_NANO_EMPTY_BALANCE "0.0"
00469 #endif
00470
00471
00479 typedef struct f_nano_wallet_info_bdy_t {
00481     uint8_t wallet_prefix; // 0 for NANO; 1 for XRB
00483     uint32_t last_used_wallet_number;
00485     char wallet_representative[MAX_STR_NANO_CHAR];
00487     char max_fee[F_RAW_STR_MAX_SZ];
00489     uint8_t reserved[44];
00490 } __attribute__((packed)) F_NANO_WALLET_INFO_BODY;
00491
00492 #ifndef F_DOC_SKIP
00493
00494     _Static_assert((sizeof(F_NANO_WALLET_INFO_BODY)&0x1F)==0, "Error F_NANO_WALLET_INFO_BODY is not byte
00495         aligned");
00496     #define F_NANO_WALLET_INFO_DESC "Nano file descriptor used for fast custom access. BUY BITCOIN AND NANO."
00497     #define F_NANO_WALLET_INFO_VERSION (uint16_t)((1<8)|1)
00498     static const uint8_t F_NANO_WALLET_INFO_MAGIC[] = {'_', 'n', 'a', 'n', 'o', 'w', 'a', 'l', 'l', 'e', 't',
00499         '_', 'n', 'f', 'o', '_'};
00500     #define F_NANO_DESC_SZ (size_t)78

```

```

00501
00502 #endif
00503
00511 typedef struct f_nano_wallet_info_t {
00513     uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)];
00515     uint16_t version;
00517     char desc[F_NANO_DESC_SZ];
00519     uint8_t nanoseed_hash[32];
00521     uint8_t file_info_integrity[32];
00523     F_NANO_WALLET_INFO_BODY body;
00524 } __attribute__((packed)) F_NANO_WALLET_INFO;
00525
00526 #ifndef F_DOC_SKIP
00527
00528     _Static_assert((sizeof(F_NANO_WALLET_INFO)&0x1F)==0, "Error F_NANO_WALLET_INFO is not byte aligned");
00529
00530 #endif
00531
00539 typedef enum f_file_info_err_t {
00541     F_FILE_INFO_ERR_OK=0,
00543     F_FILE_INFO_ERR_CANT_OPEN_INFO_FILE=7001,
00545     F_FILE_INFO_ERR_NANO_SEED_ENCRYPTED_FILE_NOT_FOUND,
00547     F_FILE_INFO_ERR_CANT_DELETE_NANO_INFO_FILE,
00549     F_FILE_INFO_ERR_MALLOC,
00551     F_FILE_INFO_ERR_CANT_READ_NANO_SEED_ENCRYPTED_FILE,
00553     F_FILE_INFO_ERR_CANT_READ_INFO_FILE,
00555     F_FILE_INFO_INVALID_HEADER_FILE,
00557     F_FILE_INFO_ERR_INVALID_SHA256_INFO_FILE,
00559     F_FILE_INFO_ERR_NANO_SEED_HASH_FAIL,
00561     F_FILE_INFO_ERR_NANO_INVALID_REPRESENTATIVE,
00563     F_FILE_INFO_ERR_NANO_INVALID_MAX_FEE_VALUE,
00565     F_FILE_INFO_ERR_OPEN_FOR_WRITE_INFO,
00567     F_FILE_INFO_ERR_EXISTING_FILE,
00569     F_FILE_INFO_ERR_CANT_WRITE_FILE_INFO
00570 } F_FILE_INFO_ERR;
00571
00572 #ifndef F_DOC_SKIP
00573
00574     #define F_NANO_ADD_A_B (uint32_t)(1<<0)
00575     #define F_NANO_SUB_A_B (uint32_t)(1<<1)
00576     #define F_NANO_A_RAW_128 (uint32_t)(1<<2)
00577     #define F_NANO_A_RAW_STRING (uint32_t)(1<<3)
00578     #define F_NANO_A_REAL_STRING (uint32_t)(1<<4)
00579     #define F_NANO_B_RAW_128 (uint32_t)(1<<5)
00580     #define F_NANO_B_RAW_STRING (uint32_t)(1<<6)
00581     #define F_NANO_B_REAL_STRING (uint32_t)(1<<7)
00582     #define F_NANO_RES_RAW_128 (uint32_t)(1<<8)
00583     #define F_NANO_RES_RAW_STRING (uint32_t)(1<<9)
00584     #define F_NANO_RES_REAL_STRING (uint32_t)(1<<10)
00585     #define F_NANO_C_RAW_128 (uint32_t)(F_NANO_B_RAW_128<<16)
00586     #define F_NANO_C_RAW_STRING (uint32_t)(F_NANO_B_RAW_STRING<<16)
00587     #define F_NANO_C_REAL_STRING (uint32_t)(F_NANO_B_REAL_STRING<<16)
00588
00589     #define F_NANO_COMPARE_EQ (uint32_t)(1<<16) //Equal
00590     #define F_NANO_COMPARE_LT (uint32_t)(1<<17) // Lesser than
00591     #define F_NANO_COMPARE_LEQ (F_NANO_COMPARE_LT|F_NANO_COMPARE_EQ) // Less or equal
00592     #define F_NANO_COMPARE_GT (uint32_t)(1<<18) // Greater
00593     #define F_NANO_COMPARE_GEQ (F_NANO_COMPARE_GT|F_NANO_COMPARE_EQ) // Greater or equal
00594     #define DEFAULT_MAX_FEE "0.001"
00595
00596 #endif
00597
00609 double to_multiplier(uint64_t, uint64_t);
00610
00622 uint64_t from_multiplier(double, uint64_t);
00623
00633 void f_set_dictionary_path(const char *);
00634
00642 char *f_get_dictionary_path(void);
00643
00656 int f_generate_token(F_TOKEN, void *, size_t, const char *);
00657
00670 int f_verify_token(F_TOKEN, void *, size_t, const char *);
00671
00694 int f_cloud_crypto_wallet_nano_create_seed(size_t, char *, char *);
00695
00708 int f_generate_nano_seed(NANO_SEED, uint32_t);
00709
00724 int pk_to_wallet(char *, char *, NANO_PUBLIC_KEY_EXTENDED);
00725
00743 int f_seed_to_nano_wallet(NANO_PRIVATE_KEY, NANO_PUBLIC_KEY, NANO_SEED, uint32_t);
00744
00754 int f_nano_is_valid_block(F_BLOCK_TRANSFER *);
00755
00768 int f_nano_block_to_json(char *, size_t *, size_t, F_BLOCK_TRANSFER *);
00769
00780 int f_nano_get_block_hash(uint8_t *, F_BLOCK_TRANSFER *);

```

```
00781
00793 int f_nano_get_p2pow_block_hash(uint8_t *, uint8_t *, F_BLOCK_TRANSFER *);
00794
00807 int f_nano_p2pow_to_JSON(char *, size_t *, size_t, F_BLOCK_TRANSFER *);
00808
00818 char *f_nano_key_to_str(char *, unsigned char *);
00819
00838 int f_nano_seed_to_bip39(char *, size_t, size_t *, NANO_SEED, char *);
00839
00854 int f_bip39_to_nano_seed(uint8_t *, char *, char *);
00855
00877 int f_parse_nano_seed_and_bip39_to_JSON(char *, size_t, size_t *, void *, int, const char *);
00878
00896 int f_read_seed(uint8_t *, const char *, void *, int, int);
00897
00912 int f_nano_raw_to_string(char *, size_t *, size_t, void *, int);
00913
00922 int f_nano_valid_nano_str_value(const char *);
00923
00931 int valid_nano_wallet(const char *);
00932
00942 int nano_base_32_2_hex(uint8_t *, char *);
00943
00958 int f_nano_transaction_to_JSON(char *, size_t, size_t *, NANO_PRIVATE_KEY_EXTENDED, F_BLOCK_TRANSFER *);
00959
00967 int valid_raw_balance(const char *);
00968
00976 int is_null_hash(uint8_t *);
00977
00989 int is_nano_prefix(const char *, const char *);
00990
00999 F_FILE_INFO_ERR f_get_nano_file_info(F_NANO_WALLET_INFO *);
01000
01010 F_FILE_INFO_ERR f_set_nano_file_info(F_NANO_WALLET_INFO *, int);
01011
01035 f_nano_err f_nano_value_compare_value(void *, void *, uint32_t *);
01036
01057 f_nano_err f_nano_verify_nano_funds(void *, void *, void *, uint32_t);
01058
01068 f_nano_err f_nano_parse_raw_str_to_rawl28_t(uint8_t *, const char *);
01069
01079 f_nano_err f_nano_parse_real_str_to_rawl28_t(uint8_t *, const char *);
01080
01103 f_nano_err f_nano_add_sub(void *, void *, void *, uint32_t);
01104
01115 int f_nano_sign_block(F_BLOCK_TRANSFER *, F_BLOCK_TRANSFER *, NANO_PRIVATE_KEY_EXTENDED);
01116
01130 f_write_seed_err f_write_seed(void *, int, uint8_t *, char *);
01131
01144 f_nano_err f_nano_balance_to_str(char *, size_t, size_t *, f_uintl28_t);
01145
01146
01151 #define F_BRAIN_WALLET_VERY_POOR (uint32_t)0
01152
01157 #define F_BRAIN_WALLET_POOR (uint32_t)1
01158
01163 #define F_BRAIN_WALLET_VERY_BAD (uint32_t)2
01164
01169 #define F_BRAIN_WALLET_BAD (uint32_t)3
01170
01175 #define F_BRAIN_WALLET_VERY_WEAK (uint32_t)4
01176
01181 #define F_BRAIN_WALLET_WEAK (uint32_t)5
01182
01187 #define F_BRAIN_WALLET_STILL_WEAK (uint32_t)6
01188
01193 #define F_BRAIN_WALLET_MAYBE_GOOD (uint32_t)7
01194
01195
01200 #define F_BRAIN_WALLET_GOOD (uint32_t)8
01201
01206 #define F_BRAIN_WALLET_VERY_GOOD (uint32_t)9
01207
01212 #define F_BRAIN_WALLET_NICE (uint32_t)10
01213
01218 #define F_BRAIN_WALLET_PERFECT (uint32_t)11
01219
01246 int f_extract_seed_from_brainwallet(uint8_t *, char **, uint32_t, const char *, const char *);
01247
01259 int f_verify_work(uint64_t *, const unsigned char *, uint64_t *, uint64_t);
01260
01266 #define F_SIGNATURE_RAW (uint32_t)1
01267
01273 #define F_SIGNATURE_STRING (uint32_t)2
01274
01280 #define F_SIGNATURE_OUTPUT_RAW_PK (uint32_t)4
01281
```

```

01287 #define F_SIGNATURE_OUTPUT_STRING_PK (uint32_t)8
01288
01294 #define F_SIGNATURE_OUTPUT_XRB_PK (uint32_t)16
01295
01301 #define F_SIGNATURE_OUTPUT_NANO_PK (uint32_t)32
01302
01308 #define F_IS_SIGNATURE_RAW_HEX_STRING (uint32_t)64
01309
01315 #define F_MESSAGE_IS_HASH_STRING (uint32_t)128
01316
01321 #define F_DEFAULT_THRESHOLD (uint64_t) 0xffffffffc000000000
01322
01346 int f_sign_data(
01347     unsigned char *signature,
01348     void *out_public_key,
01349     uint32_t ouput_type,
01350     const unsigned char *message,
01351     size_t msg_len,
01352     const unsigned char *private_key);
01353
01359 #define F_VERIFY_SIG_NANO_WALLET (uint32_t)1
01360
01366 #define F_VERIFY_SIG_RAW_HEX (uint32_t)2
01367
01373 #define F_VERIFY_SIG_ASCII_HEX (uint32_t)4
01374
01395 int f_verify_signed_data( const unsigned char *signature, const unsigned char *message, size_t message_len,
    const void *public_key, uint32_t pk_type);
01396
01397 #ifndef F_ESP32
01398
01411 int f_nano_pow(uint64_t *, unsigned char *, const uint64_t, int);
01412 #endif
01413
01414 #ifdef __cplusplus
01415 }
01416 #endif
01417

```

5.5 f_util.h File Reference

```

#include <stdint.h>
#include "mbedtls/sha256.h"
#include "mbedtls/aes.h"

```

Macros

- **#define F_ENTROPY_TYPE_PARANOIC** (uint32_t)1477682819
- **#define F_ENTROPY_TYPE_EXCELENT** (uint32_t)1476885281
- **#define F_ENTROPY_TYPE_GOOD** (uint32_t)1472531015
- **#define F_ENTROPY_TYPE_NOT_ENOUGH** (uint32_t)1471001808
- **#define F_ENTROPY_TYPE_NOT_RECOMENDED** (uint32_t)1470003345
- **#define ENTROPY_BEGIN** f_verify_system_entropy_begin();
- **#define ENTROPY_END** f_verify_system_entropy_finish();
- **#define F_PASS_MUST_HAVE_AT_LEAST_NONE** (int)0
- **#define F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER** (int)1
- **#define F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL** (int)2
- **#define F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE** (int)4
- **#define F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE** (int)8
- **#define F_PASS_IS_TOO_LONG** (int)256
- **#define F_PASS_IS_TOO_SHORT** (int)512
- **#define F_PASS_IS_OUT_OVF** (int)1024
- **#define F_GET_CH_MODE_NO_ECHO** (int)(1<<16)
- **#define F_GET_CH_MODE_ANY_KEY** (int)(1<<17)

Typedefs

- typedef void(* **rnd_fn**) (void *, size_t)

Functions

- int **f_verify_system_entropy** (uint32_t, void *, size_t, int)
- int **f_pass_must_have_at_least** (char *, size_t, size_t, size_t, int)
- int **f_passwd_comp_safe** (char *, char *, size_t, size_t, size_t)
- char * **f_get_entropy_name** (uint32_t)
- uint32_t **f_sel_to_entropy_level** (int)
- int **f_str_to_hex** (uint8_t *, char *)
- void **f_random_attach** (**rnd_fn**)
- void **f_random** (void *, size_t)
- int **get_console_passwd** (char *, size_t)
- int **f_get_char_no_block** (int)
- int **f_convert_to_long_int** (unsigned long int *, char *, size_t)
- int **f_convert_to_unsigned_int** (unsigned int *, char *, size_t)
- int **f_convert_to_long_int0x** (unsigned long int *, char *, size_t)
- int **f_convert_to_long_int0** (unsigned long int *, char *, size_t)
- int **f_convert_to_long_int_std** (unsigned long int *, char *, size_t)
- void * **f_is_random_attached** ()
- void **f_random_detach** ()
- int **f_convert_to_unsigned_int0x** (unsigned int *val, char *value, size_t value_sz)
- int **f_convert_to_unsigned_int0** (unsigned int *val, char *value, size_t value_sz)
- int **f_convert_to_unsigned_int_std** (unsigned int *val, char *value, size_t value_sz)
- int **f_convert_to_double** (double *, const char *)
- uint32_t **crc32_init** (unsigned char *, size_t, uint32_t)

5.5.1 Detailed Description

This ABI is a utility for myNanoEmbedded library and sub routines are implemented here.

Definition in file **f_util.h**.

5.5.2 Macro Definition Documentation

5.5.2.1 ENTROPY_BEGIN

```
#define ENTROPY_BEGIN f_verify_system_entropy_begin();
```

Begins and prepares a entropy function.

See also

f_verify_system_entropy() (p. ??)

Definition at line **152** of file **f_util.h**.

5.5.2.2 ENTROPY_END

```
#define ENTROPY_END f_verify_system_entropy_finish();
```

Ends a entropy function.

See also

f_verify_system_entropy() (p. ??)

Definition at line **159** of file **f_util.h**.

5.5.2.3 F_ENTROPY_TYPE_EXCELENT

```
#define F_ENTROPY_TYPE_EXCELENT (uint32_t)1476885281
```

Type of the excelent entropy used for verifier.

Slow

Definition at line **124** of file **f_util.h**.

5.5.2.4 F_ENTROPY_TYPE_GOOD

```
#define F_ENTROPY_TYPE_GOOD (uint32_t)1472531015
```

Type of the good entropy used for verifier.

Not so slow

Definition at line **131** of file **f_util.h**.

5.5.2.5 F_ENTROPY_TYPE_NOT_ENOUGH

```
#define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1471001808
```

Type of the moderate entropy used for verifier.

Fast

Definition at line **138** of file **f_util.h**.

5.5.2.6 F_ENTROPY_TYPE_NOT_RECOMENDED

```
#define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1470003345
```

Type of the not recommended entropy used for verifier.

Very fast

Definition at line 145 of file **f_util.h**.

5.5.2.7 F_ENTROPY_TYPE_PARANOIC

```
#define F_ENTROPY_TYPE_PARANOIC (uint32_t)1477682819
```

Type of the very excelent entropy used for verifier.

Very slow

Definition at line 117 of file **f_util.h**.

5.5.2.8 F_GET_CH_MODE_ANY_KEY

```
#define F_GET_CH_MODE_ANY_KEY (int) (1<<17)
```

See also

f_get_char_no_block() (p. ??)

Definition at line 334 of file **f_util.h**.

5.5.2.9 F_GET_CH_MODE_NO_ECHO

```
#define F_GET_CH_MODE_NO_ECHO (int) (1<<16)
```

See also

f_get_char_no_block() (p. ??)

Definition at line 328 of file **f_util.h**.

5.5.2.10 F_PASS_IS_OUT_OVF

```
#define F_PASS_IS_OUT_OVF (int)1024
```

Password is overflow and cannot be stored.

Definition at line **207** of file **f_util.h**.

5.5.2.11 F_PASS_IS_TOO_LONG

```
#define F_PASS_IS_TOO_LONG (int)256
```

Password is too long.

Definition at line **195** of file **f_util.h**.

5.5.2.12 F_PASS_IS_TOO_SHORT

```
#define F_PASS_IS_TOO_SHORT (int)512
```

Password is too short.

Definition at line **201** of file **f_util.h**.

5.5.2.13 F_PASS_MUST_HAVE_AT_LEAST_NONE

```
#define F_PASS_MUST_HAVE_AT_LEAST_NONE (int)0
```

Password does not need any criteria to pass.

Definition at line **165** of file **f_util.h**.

5.5.2.14 F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE (int)8
```

Password must have at least one lower case.

Definition at line **189** of file **f_util.h**.

5.5.2.15 F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER (int)1
```

Password must have at least one number.

Definition at line **171** of file **f_util.h**.

5.5.2.16 F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL (int)2
```

Password must have at least one symbol.

Definition at line **177** of file **f_util.h**.

5.5.2.17 F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE (int)4
```

Password must have at least one upper case.

Definition at line **183** of file **f_util.h**.

5.5.3 Typedef Documentation

5.5.3.1 rnd_fn

```
rnd_fn
```

Pointer caller for random function.

Definition at line **293** of file **f_util.h**.

5.5.4 Function Documentation

5.5.4.1 crc32_init()

```
uint32_t crc32_init (
    unsigned char * p,
    size_t len,
    uint32_t crcinit )
```

Performs a CRC32 of a given data.

Parameters

in	<i>p</i>	Pointer of the data
in	<i>len</i>	Size of data in pointer <i>p</i>
in	<i>crcinit</i>	Init vector of the CRC32

Return values

<i>CRC32</i>	hash
--------------	------

5.5.4.2 f_convert_to_double()

```
int f_convert_to_double (
    double * val,
    const char * value )
```

Convert any valid number in *value* and converts it to double *val*

Parameters

out	<i>val</i>	Value converted to double
in	<i>value</i>	Value in string to be converted

Return values

0	On Success, Otherwise error
---	-----------------------------

5.5.4.3 f_convert_to_long_int()

```
int f_convert_to_long_int (
    unsigned long int * val,
    char * value,
    size_t value_sz )
```

Converts a string value to unsigned long int.

Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_unsigned_int() (p. ??)

5.5.4.4 f_convert_to_long_int0()

```
int f_convert_to_long_int0 (
    unsigned long int * val,
    char * value,
    size_t value_sz )
```

Converts a octal value in ASCII string to unsigned long int.

Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_long_int0x() (p. ??)

5.5.4.5 f_convert_to_long_int0x()

```
int f_convert_to_long_int0x (
    unsigned long int * val,
    char * value,
    size_t value_sz )
```

Converts a hex value in ASCII string to unsigned long int.

Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_long_int0() (p. ??)

5.5.4.6 f_convert_to_long_int_std()

```
int f_convert_to_long_int_std (
    unsigned long int * val,
    char * value,
    size_t value_sz )
```

Converts a actal/decimal/hexadecimal into ASCII string to unsigned long int.

Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int <ul style="list-style-type: none">• If a string contains only numbers, it will be parsed to unsigned long int decimal• If a string begins with 0 it will be parsed to octal EX.: 010(octal) = 08(decimal)• If a string contains 0x or 0X it will be parsed to hexadecimal. EX.: 0x10(hexadecimal) = 16 (decimal)
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_long_int() (p. ??)

5.5.4.7 f_convert_to_unsigned_int()

```
int f_convert_to_unsigned_int (
    unsigned int * val,
    char * value,
    size_t value_sz )
```

Converts a string value to unsigned int.

Parameters

out	<i>val</i>	Value stored in a unsigned int variable
in	<i>value</i>	Input value to be parsed to unsigned int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_long_int() (p. ??)

5.5.4.8 f_convert_to_unsigned_int0()

```
int f_convert_to_unsigned_int0 (
    unsigned int * val,
    char * value,
    size_t value_sz )
```

Converts a octal value in ASCII string to unsigned int.

Parameters

out	<i>val</i>	Value stored in a unsigned int variable
in	<i>value</i>	Input value to be parsed to unsigned int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_unsigned_int0x() (p. ??)

5.5.4.9 f_convert_to_unsigned_int0x()

```
int f_convert_to_unsigned_int0x (
    unsigned int * val,
    char * value,
    size_t value_sz )
```

Converts a hex value in ASCII string to unsigned int.

Parameters

out	<i>val</i>	Value stored in a unsigned int variable
in	<i>value</i>	Input value to be parsed to unsigned int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_unsigned_int0() (p. ??)

5.5.4.10 f_convert_to_unsigned_int_std()

```
int f_convert_to_unsigned_int_std (
    unsigned int * val,
    char * value,
    size_t value_sz )
```

Converts a actal/decimal/hexadecimal into ASCII string to unsigned int.

Parameters

out	<i>val</i>	Value stored in a unsigned int variable
in	<i>value</i>	Input value to be parsed to unsigned int <ul style="list-style-type: none"> • If a string contains only numbers, it will be parsed to unsigned int decimal • If a string begins with 0 it will be parsed to octal EX.: 010(octal) = 08(decimal) • If a string contains 0x or 0X it will be parsed to hexadecimal. EX.: 0x10(hexadecimal) = 16 (decimal)
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_unsigned_int() (p. ??)

5.5.4.11 f_get_char_no_block()

```
int f_get_char_no_block (
    int mode )
```

Reads a char from console.

Waits a char and returns its value

Parameters

in	mode	Mode and/or character to be returned
		<ul style="list-style-type: none">• <i>F_GET_CH_MODE_NO_ECHO</i> No echo is on the console string• <i>F_GET_CH_MODE_ANY_KEY</i> Returns any key pressed

Example:

```
key=f_get_char_no_block(F_GET_CH_MODE_NO_ECHO|'c'); // Waits 'c' char key and returns value 0x00000063
              without echo 'c' on the screen
```

Return values

key	code: On Success, Negative value on error
-----	---

5.5.4.12 f_get_entropy_name()

```
char * f_get_entropy_name (
    uint32_t val )
```

Returns a entropy name given a index/ASCII index or entropy value.

Parameters

in	val	Index/ASCII index or entropy value
----	-----	------------------------------------

Return values:

- *NULL* If no entropy index/ASCII/entropy found in *val*
- *F_ENTROPY_TYPE_** name if found in index/ASCII or entropy value

5.5.4.13 f_is_random_attached()

```
void * f_is_random_attached ( )
```

Verifies if system random function is attached in myNanoEmbedded API.

Return values

<i>NULL</i>	if not attached, Otherwise returns the pointer of random number generator function
-------------	--

See also

f_random_attach() (p. ??)

5.5.4.14 f_pass_must_have_at_least()

```
int f_pass_must_have_at_least (
    char * password,
    size_t n,
    size_t min,
    size_t max,
    int must_have )
```

Checks if a given password has enough requirements to be parsed to a function.

Parameters

in	<i>password</i>	Password string
in	<i>n</i>	Max buffer string permitted to store password including NULL char
in	<i>min</i>	Minimum size allowed in password string
in	<i>max</i>	Maximum size allowed in password
in	<i>must_have</i>	Must have a type: <ul style="list-style-type: none"> • F_PASS_MUST_HAVE_AT_LEAST_NONE Not need any special characters or number • F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER Must have at least one number • F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL Must have at least one symbol • F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE Must have at least one upper case • F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE Must have at least one lower case

Return values:

- 0 (zero): If password is passed in the test

- *F_PASS_IS_OUT_OVF*: If password length exceeds *n* value
- *F_PASS_IS_TOO_SHORT*: If password length is less than *min* value
- *F_PASS_IS_TOO_LONG*: If password length is greater than *m* value
- *F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE*: If password is required in *must_have* type upper case characters
- *F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE*: If password is required in *must_have* type lower case characters
- *F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL*: If password is required in *must_have* type to have symbol(s)
- *F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER*: if password is required in *must_have* type to have number(s)

5.5.4.15 f_passwd_comp_safe()

```
int f_passwd_comp_safe (
    char * pass1,
    char * pass2,
    size_t n,
    size_t min,
    size_t max )
```

Compares two passwords values with safe buffer.

Parameters

in	<i>pass1</i>	First password to compare with <i>pass2</i>
in	<i>pass2</i>	Second password to compare with <i>pass1</i>
in	<i>n</i>	Size of Maximum buffer of both <i>pass1</i> and <i>pass2</i>
in	<i>min</i>	Minimum value of both <i>pass1</i> and <i>pass2</i>
in	<i>max</i>	Maximum value of both <i>pass1</i> and <i>pass2</i>

Return values

0	If <i>pass1</i> is equal to <i>pass2</i> , otherwise value is less than 0 (zero) if password does not match
---	---

5.5.4.16 f_random()

```
void f_random (
    void * random,
    size_t random_sz )
```

Random function to be called to generate a *random* data with *random_sz*

Parameters

out	<i>random</i>	Random data to be parsed
in	<i>random_sz</i>	Size of random data to be filled

See also

f_random_attach() (p. ??)

5.5.4.17 f_random_attach()

```
void f_random_attach (
    rnd_fn fn )
```

Attaches a function to be called by **f_random()** (p. ??)

Parameters

in	<i>fn</i>	A function to be called
----	-----------	-------------------------

See also

rnd_fn() (p. ??)

5.5.4.18 f_random_detach()

```
void f_random_detach ( )
```

Detaches system random number generator from myNanoEmbedded API.

See also

f_random_attach() (p. ??)

5.5.4.19 f_sel_to_entropy_level()

```
uint32_t f_sel_to_entropy_level (
    int sel )
```

Return a given entropy number given a number encoded ASCII or index number.

Parameters

in	<i>sel</i>	ASCII or index value
----	------------	----------------------

Return values:

- *0 (zero)*: If no entropy number found in *sel*
- *F_ENTROPY_TYPE_PARANOIC*
- *F_ENTROPY_TYPE_EXCELENT*
- *F_ENTROPY_TYPE_GOOD*
- *F_ENTROPY_TYPE_NOT_ENOUGH*
- *F_ENTROPY_TYPE_NOT_RECOMENDED*

5.5.4.20 f_str_to_hex()

```
int f_str_to_hex (
    uint8_t * hex_stream,
    char * str )
```

Converts a *str* string buffer to raw *hex_stream* value stream.

Parameters

out	<i>hex</i>	Raw hex value
in	<i>str</i>	String buffer terminated with NULL char

Return values

<i>0</i>	On Success, otherwise Error
----------	-----------------------------

5.5.4.21 f_verify_system_entropy()

```
int f_verify_system_entropy (
    uint32_t type,
    void * rand,
    size_t rand_sz,
    int turn_on_wdt )
```

Take a random number generator function and returns random value only if randomized data have a desired entropy value.

Parameters

in	<i>type</i>	Entropy type. Entropy type values are: <ul style="list-style-type: none"> • <code>F_ENTROPY_TYPE_PARANOIC</code> Highest level entropy recommended for generate a Nano SEED with a paranoic entropy. Very slow • <code>F_ENTROPY_TYPE_EXCELENT</code> Gives a very excellent entropy for generating Nano SEED. Slow • <code>F_ENTROPY_TYPE_GOOD</code> Good entropy type for generating Nano SEED. Normal. • <code>F_ENTROPY_TYPE_NOT_ENOUGH</code> Moderate entropy for generating Nano SEED. Usually fast to create a temporary Nano SEED. Fast • <code>F_ENTROPY_TYPE_NOT_RECOMENDED</code> Fast but not recommended for generating Nano SEED.
out	<i>rand</i>	Random data with a satisfied type of entropy
in	<i>rand_sz</i>	Size of random data output
in	<i>turn_on_wdt</i>	For ESP32, Arduino platform and other microcontrollers only. Turns on/off WATCH DOG (0: OFF, NON ZERO: ON). For Raspberry PI and Linux native is ommited.

This implementation is based on topic in [Definition 7.12](#) in MIT opencourseware (7.3 A Statistical Definition of Entropy - 2005)

Many thanks to **Professor Z. S. Spakovszky** for this amazing topic

Return values

0	On Success, otherwise Error
---	-----------------------------

5.5.4.22 get_console_passwd()

```
int get_console_passwd (
    char * pass,
    size_t pass_sz )
```

Reads a password from console.

Parameters

out	<i>pass</i>	Password to be parsed to pointer
in	<i>pass_sz</i>	Size of buffer <i>pass</i>

Return values

0	On Success, otherwise Error
---	-----------------------------

5.6 f_util.h

```

00001 /*
00002     AUTHOR: Fábio Pereira da Silva
00003     YEAR: 2019-20
00004     LICENSE: MIT
00005     EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006 */
00007
00013 #include <stdint.h>
00014 #include "mbedtls/sha256.h"
00015 #include "mbedtls/aes.h"
00016
00017 #ifdef __cplusplus
00018 extern "C" {
00019 #endif
00020
00021 #ifndef F_DOC_SKIP
00022
00023     #define F_LOG_MAX 8*256
00024     #define LICENSE \
00025     "MIT License\n\n\
00026     Copyright (c) 2019 Fábio Pereira da Silva\n\n\
00027     Permission is hereby granted, free of charge, to any person obtaining a copy\n\
00028     of this software and associated documentation files (the \"Software\"), to deal\n\
00029     in the Software without restriction, including without limitation the rights\n\
00030     to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n\
00031     copies of the Software, and to permit persons to whom the Software is\n\
00032     furnished to do so, subject to the following conditions:\n\n\
00033     The above copyright notice and this permission notice shall be included in all\n\
00034     copies or substantial portions of the Software.\n\n\
00035     THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n\
00036     IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n\
00037     FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n\
00038     AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n\
00039     LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n\
00040     OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE\n\
00041     SOFTWARE.\n\n\"
00042
00043 #endif
00044
00045 #ifdef F_ESP32
00046
00047     #define F_WDT_MAX_ENTROPY_TIME 2*120
00048     #define F_WDT_PANIC true
00049     #define F_WDT_MIN_TIME 20//4
00050
00051 #endif
00052
00070 int f_verify_system_entropy(uint32_t, void *, size_t, int);
00071
00098 int f_pass_must_have_at_least(char *, size_t, size_t, size_t, int);
00099
00100 #ifndef F_DOC_SKIP
00101
00102 int f_verify_system_entropy_begin();
00103 void f_verify_system_entropy_finish();
00104 int f_file_exists(char *);
00105 int f_find_str(size_t *, char *, size_t, char *);
00106 int f_find_replace(char *, size_t *, size_t, char *, size_t, char *, char *);
00107 int f_is_integer(char *, size_t);
00108 int is_filled_with_value(uint8_t *, size_t, uint8_t);
00109
00110 #endif
00111
00112 // #define F_ENTROPY_TYPE_PARANOIC (uint32_t)1476682819
00117 #define F_ENTROPY_TYPE_PARANOIC (uint32_t)1477682819
00118
00119 // #define F_ENTROPY_TYPE_EXCELENT (uint32_t)1475885281
00124 #define F_ENTROPY_TYPE_EXCELENT (uint32_t)1476885281
00125
00126 // #define F_ENTROPY_TYPE_GOOD (uint32_t)1471531015
00131 #define F_ENTROPY_TYPE_GOOD (uint32_t)1472531015
00132
00133 // #define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1470001808
00138 #define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1471001808
00139
00140 // #define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1469703345
00145 #define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1470003345
00146
00152 #define ENTROPY_BEGIN f_verify_system_entropy_begin();
00153
00159 #define ENTROPY_END f_verify_system_entropy_finish();
00160
00165 #define F_PASS_MUST_HAVE_AT_LEAST_NONE (int)0
00166

```

```

00171 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER (int)1
00172
00177 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL (int)2
00178
00183 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE (int)4
00184
00189 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE (int)8
00190
00195 #define F_PASS_IS_TOO_LONG (int)256
00196
00201 #define F_PASS_IS_TOO_SHORT (int)512
00202
00207 #define F_PASS_IS_OUT_OVF (int)1024//768
00208
00209 #ifndef F_DOC_SKIP
00210
00211 #define F_PBKDF2_ITER_SZ 2*4096
00212
00213 typedef enum f_pbkdf2_err_t {
00214     F_PBKDF2_RESULT_OK=0,
00215     F_PBKDF2_ERR_CTX=95,
00216     F_PBKDF2_ERR_PKCS5,
00217     F_PBKDF2_ERR_INFO_SHA
00218 } f_pbkdf2_err;
00219
00220 typedef enum f_aes_err {
00221     F_AES_RESULT_OK=0,
00222     F_AES_ERR_ENCKEY=30,
00223     F_AES_ERR_DECKEY,
00224     F_AES_ERR_MALLOC,
00225     F_AES_UNKNOW_DIRECTION,
00226     F_ERR_ENC_DECRYPT_FAILED
00227 } f_aes_err;
00228
00229 char *fhex2strv2(char *, const void *, size_t, int);
00230 uint8_t *f_sha256_digest(uint8_t *, size_t);
00231 f_pbkdf2_err f_pbkdf2_hmac(unsigned char *, size_t, unsigned char *, size_t, uint8_t *);
00232 f_aes_err f_aes256cipher(uint8_t *, uint8_t *, void *, size_t, void *, int);
00233
00234 #endif
00235
00247 int f_passwd_comp_safe(char *, char *, size_t, size_t, size_t);
00248
00259 char *f_get_entropy_name(uint32_t);
00260
00275 uint32_t f_sel_to_entropy_level(int);
00276
00285 int f_str_to_hex(uint8_t *, char *);
00286
00287 #ifndef F_ESP32
00288
00293 typedef void (*rnd_fn)(void *, size_t);
00294
00302 void f_random_attach(rnd_fn);
00303
00312 void f_random(void *, size_t);
00313
00322 int get_console_passwd(char *, size_t);
00323
00328 #define F_GET_CH_MODE_NO_ECHO (int) (1<<16)
00329
00334 #define F_GET_CH_MODE_ANY_KEY (int) (1<<17)
00335
00351 int f_get_char_no_block(int);
00352
00353 #endif
00354
00365 int f_convert_to_long_int(unsigned long int *, char *, size_t);
00366
00367
00378 int f_convert_to_unsigned_int(unsigned int *, char *, size_t);
00379
00390 int f_convert_to_long_int0x(unsigned long int *, char *, size_t);
00391
00402 int f_convert_to_long_int0(unsigned long int *, char *, size_t);
00403
00417 int f_convert_to_long_int_std(unsigned long int *, char *, size_t);
00418
00426 void *f_is_random_attached();
00427
00434 void f_random_detach();
00435
00446 int f_convert_to_unsigned_int0x(unsigned int *val, char *value, size_t value_sz);
00447
00458 int f_convert_to_unsigned_int0(unsigned int *val, char *value, size_t value_sz);
00459
00473 int f_convert_to_unsigned_int_std(unsigned int *val, char *value, size_t value_sz);

```

```
00474
00484 int f_convert_to_double(double *, const char *);
00485
00496 uint32_t crc32_init(unsigned char *, size_t, uint32_t);
00497
00498 #ifdef __cplusplus
00499 }
00500 #endif
```

5.7 sodium.h File Reference

```
#include "sodium/version.h"
#include "sodium/core.h"
#include "sodium/crypto_aead_aes256gcm.h"
#include "sodium/crypto_aead_chacha20poly1305.h"
#include "sodium/crypto_aead_xchacha20poly1305.h"
#include "sodium/crypto_auth.h"
#include "sodium/crypto_auth_hmacsha256.h"
#include "sodium/crypto_auth_hmacsha512.h"
#include "sodium/crypto_auth_hmacsha512256.h"
#include "sodium/crypto_box.h"
#include "sodium/crypto_box_curve25519xsalsa20poly1305.h"
#include "sodium/crypto_core_hsalsa20.h"
#include "sodium/crypto_core_hchacha20.h"
#include "sodium/crypto_core_salsa20.h"
#include "sodium/crypto_core_salsa2012.h"
#include "sodium/crypto_core_salsa208.h"
#include "sodium/crypto_generichash.h"
#include "sodium/crypto_generichash_blake2b.h"
#include "sodium/crypto_hash.h"
#include "sodium/crypto_hash_sha256.h"
#include "sodium/crypto_hash_sha512.h"
#include "sodium/crypto_kdf.h"
#include "sodium/crypto_kdf_blake2b.h"
#include "sodium/crypto_kx.h"
#include "sodium/crypto_onetimeauth.h"
#include "sodium/crypto_onetimeauth_poly1305.h"
#include "sodium/crypto_pwhash.h"
#include "sodium/crypto_pwhash_argon2i.h"
#include "sodium/crypto_scalarmult.h"
#include "sodium/crypto_scalarmult_curve25519.h"
#include "sodium/crypto_secretbox.h"
#include "sodium/crypto_secretbox_xsalsa20poly1305.h"
#include "sodium/crypto_secretstream_xchacha20poly1305.h"
#include "sodium/crypto_shorthash.h"
#include "sodium/crypto_shorthash_siphhash24.h"
#include "sodium/crypto_sign.h"
#include "sodium/crypto_sign_ed25519.h"
#include "sodium/crypto_stream.h"
#include "sodium/crypto_stream_chacha20.h"
#include "sodium/crypto_stream_salsa20.h"
#include "sodium/crypto_stream_xsalsa20.h"
#include "sodium/crypto_verify_16.h"
#include "sodium/crypto_verify_32.h"
#include "sodium/crypto_verify_64.h"
#include "sodium/randombytes.h"
#include "sodium/randombytes_salsa20_random.h"
#include "sodium/randombytes_sysrandom.h"
```

```
#include "sodium/runtime.h"
#include "sodium/utils.h"
#include "sodium/crypto_box_curve25519xchacha20poly1305.h"
#include "sodium/crypto_core_ed25519.h"
#include "sodium/crypto_scalarmult_ed25519.h"
#include "sodium/crypto_secretbox_xchacha20poly1305.h"
#include "sodium/crypto_pwhash_scryptsalsa208sha256.h"
#include "sodium/crypto_stream_salsa2012.h"
#include "sodium/crypto_stream_salsa208.h"
#include "sodium/crypto_stream_xchacha20.h"
```

5.7.1 Detailed Description

This header file is an implementation of Libsodium library.

Definition in file **sodium.h**.

5.8 sodium.h

```
00001
00005 #ifndef sodium_H
00006 #define sodium_H
00007
00008 #include "sodium/version.h"
00009
00010 #include "sodium/core.h"
00011 #include "sodium/crypto_aead_aes256gcm.h"
00012 #include "sodium/crypto_aead_chacha20poly1305.h"
00013 #include "sodium/crypto_aead_xchacha20poly1305.h"
00014 #include "sodium/crypto_auth.h"
00015 #include "sodium/crypto_auth_hmacsha256.h"
00016 #include "sodium/crypto_auth_hmacsha512.h"
00017 #include "sodium/crypto_auth_hmacsha512256.h"
00018 #include "sodium/crypto_box.h"
00019 #include "sodium/crypto_box_curve25519xsalsa20poly1305.h"
00020 #include "sodium/crypto_core_hsalsa20.h"
00021 #include "sodium/crypto_core_hchacha20.h"
00022 #include "sodium/crypto_core_salsa20.h"
00023 #include "sodium/crypto_core_salsa2012.h"
00024 #include "sodium/crypto_core_salsa208.h"
00025 #include "sodium/crypto_generichash.h"
00026 #include "sodium/crypto_generichash_blake2b.h"
00027 #include "sodium/crypto_hash.h"
00028 #include "sodium/crypto_hash_sha256.h"
00029 #include "sodium/crypto_hash_sha512.h"
00030 #include "sodium/crypto_kdf.h"
00031 #include "sodium/crypto_kdf_blake2b.h"
00032 #include "sodium/crypto_kx.h"
00033 #include "sodium/crypto_onetimeauth.h"
00034 #include "sodium/crypto_onetimeauth_poly1305.h"
00035 #include "sodium/crypto_pwhash.h"
00036 #include "sodium/crypto_pwhash_argon2i.h"
00037 #include "sodium/crypto_scalarmult.h"
00038 #include "sodium/crypto_scalarmult_curve25519.h"
00039 #include "sodium/crypto_secretbox.h"
00040 #include "sodium/crypto_secretbox_xsalsa20poly1305.h"
00041 #include "sodium/crypto_secretstream_xchacha20poly1305.h"
00042 #include "sodium/crypto_shorthash.h"
00043 #include "sodium/crypto_shorthash_siphhash24.h"
00044 #include "sodium/crypto_sign.h"
00045 #include "sodium/crypto_sign_ed25519.h"
00046 #include "sodium/crypto_stream.h"
00047 #include "sodium/crypto_stream_chacha20.h"
00048 #include "sodium/crypto_stream_salsa20.h"
00049 #include "sodium/crypto_stream_xsalsa20.h"
00050 #include "sodium/crypto_verify_16.h"
00051 #include "sodium/crypto_verify_32.h"
00052 #include "sodium/crypto_verify_64.h"
00053 #include "sodium/randombytes.h"
00054 #ifdef __native_client__
```

```
00055 # include "sodium/randombytes_nativeclient.h"
00056 #endif
00057 #include "sodium/randombytes_salsa20_random.h"
00058 #include "sodium/randombytes_sysrandom.h"
00059 #include "sodium/runtime.h"
00060 #include "sodium/utils.h"
00061
00062 #ifndef SODIUM_LIBRARY_MINIMAL
00063 # include "sodium/crypto_box_curve25519xchacha20poly1305.h"
00064 # include "sodium/crypto_core_ed25519.h"
00065 # include "sodium/crypto_scalarmult_ed25519.h"
00066 # include "sodium/crypto_secretbox_xchacha20poly1305.h"
00067 # include "sodium/crypto_pwhash_scryptsalsa208sha256.h"
00068 # include "sodium/crypto_stream_salsa2012.h"
00069 # include "sodium/crypto_stream_salsa208.h"
00070 # include "sodium/crypto_stream_xchacha20.h"
00071 #endif
00072
00073 #endif
```

Index

__attribute__
 f_nano_crypto_util.h, 34

account
 f_block_transfer_t, 7
 f_nano_crypto_util.h, 59

balance
 f_block_transfer_t, 7
 f_nano_crypto_util.h, 59

body
 f_nano_crypto_util.h, 59
 f_nano_wallet_info_t, 15

crc32_init
 f_util.h, 75

DEST_XRB
 f_nano_crypto_util.h, 21

desc
 f_nano_crypto_util.h, 59
 f_nano_wallet_info_t, 15

description
 f_nano_crypto_util.h, 60
 f_nano_crypto_wallet_t, 10

ENTROPY_BEGIN
 f_util.h, 71

ENTROPY_END
 f_util.h, 71

F_ADD_288
 f_add_bn_288_le.h, 17

F_BRAIN_WALLET_BAD
 f_nano_crypto_util.h, 22

F_BRAIN_WALLET_GOOD
 f_nano_crypto_util.h, 22

F_BRAIN_WALLET_MAYBE_GOOD
 f_nano_crypto_util.h, 22

F_BRAIN_WALLET_NICE
 f_nano_crypto_util.h, 22

F_BRAIN_WALLET_PERFECT
 f_nano_crypto_util.h, 22

F_BRAIN_WALLET_POOR
 f_nano_crypto_util.h, 23

F_BRAIN_WALLET_STILL_WEAK
 f_nano_crypto_util.h, 23

F_BRAIN_WALLET_VERY_BAD
 f_nano_crypto_util.h, 23

F_BRAIN_WALLET_VERY_GOOD
 f_nano_crypto_util.h, 23

F_BRAIN_WALLET_VERY_POOR
 f_nano_crypto_util.h, 24

F_BRAIN_WALLET_VERY_WEAK
 f_nano_crypto_util.h, 24

F_BRAIN_WALLET_WEAK
 f_nano_crypto_util.h, 24

F_DEFAULT_THRESHOLD
 f_nano_crypto_util.h, 24

F_ENTROPY_TYPE_EXCELENT
 f_util.h, 72

F_ENTROPY_TYPE_GOOD
 f_util.h, 72

F_ENTROPY_TYPE_NOT_ENOUGH
 f_util.h, 72

F_ENTROPY_TYPE_NOT_RECOMENDED
 f_util.h, 72

F_ENTROPY_TYPE_PARANOIC
 f_util.h, 73

F_FILE_INFO_ERR
 f_nano_crypto_util.h, 30

F_GET_CH_MODE_ANY_KEY
 f_util.h, 73

F_GET_CH_MODE_NO_ECHO
 f_util.h, 73

F_IS_SIGNATURE_RAW_HEX_STRING
 f_nano_crypto_util.h, 25

F_MESSAGE_IS_HASH_STRING
 f_nano_crypto_util.h, 25

F_NANO_POW_MAX_THREAD
 f_nano_crypto_util.h, 25

F_PASS_IS_OUT_OVF
 f_util.h, 73

F_PASS_IS_TOO_LONG
 f_util.h, 74

F_PASS_IS_TOO_SHORT
 f_util.h, 74

F_PASS_MUST_HAVE_AT_LEAST_NONE
 f_util.h, 74

F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_↔
 CASE
 f_util.h, 74

F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER
 f_util.h, 74

F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL
 f_util.h, 75

F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_↔
 CASE
 f_util.h, 75

F_SIGNATURE_OUTPUT_NANO_PK

- f_nano_crypto_util.h, 25
- F_SIGNATURE_OUTPUT_RAW_PK
 - f_nano_crypto_util.h, 26
- F_SIGNATURE_OUTPUT_STRING_PK
 - f_nano_crypto_util.h, 26
- F_SIGNATURE_OUTPUT_XRB_PK
 - f_nano_crypto_util.h, 26
- F_SIGNATURE_RAW
 - f_nano_crypto_util.h, 26
- F_SIGNATURE_STRING
 - f_nano_crypto_util.h, 27
- F_TOKEN
 - f_nano_crypto_util.h, 30
- F_VERIFY_SIG_ASCII_HEX
 - f_nano_crypto_util.h, 27
- F_VERIFY_SIG_NANO_WALLET
 - f_nano_crypto_util.h, 27
- F_VERIFY_SIG_RAW_HEX
 - f_nano_crypto_util.h, 27
- f_add_bn_288_le.h, 17, 18
 - F_ADD_288, 17
- f_bip39_to_nano_seed
 - f_nano_crypto_util.h, 34
- f_block_transfer_t, 7
 - account, 7
 - balance, 7
 - link, 8
 - preamble, 8
 - prefixes, 8
 - previous, 8
 - representative, 8
 - signature, 9
 - work, 9
- f_cloud_crypto_wallet_nano_create_seed
 - f_nano_crypto_util.h, 34
- f_convert_to_double
 - f_util.h, 76
- f_convert_to_long_int
 - f_util.h, 76
- f_convert_to_long_int0
 - f_util.h, 77
- f_convert_to_long_int0x
 - f_util.h, 77
- f_convert_to_long_int_std
 - f_util.h, 78
- f_convert_to_unsigned_int
 - f_util.h, 78
- f_convert_to_unsigned_int0
 - f_util.h, 79
- f_convert_to_unsigned_int0x
 - f_util.h, 79
- f_convert_to_unsigned_int_std
 - f_util.h, 80
- f_extract_seed_from_brainwallet
 - f_nano_crypto_util.h, 35
- f_file_info_err_t, 9
 - f_nano_crypto_util.h, 32
- f_generate_nano_seed
 - f_nano_crypto_util.h, 36
- f_generate_token
 - f_nano_crypto_util.h, 37
- f_get_char_no_block
 - f_util.h, 80
- f_get_dictionary_path
 - f_nano_crypto_util.h, 37
- f_get_entropy_name
 - f_util.h, 81
- f_get_nano_file_info
 - f_nano_crypto_util.h, 38
- f_is_random_attached
 - f_util.h, 81
- f_nano_add_sub
 - f_nano_crypto_util.h, 38
- f_nano_balance_to_str
 - f_nano_crypto_util.h, 39
- f_nano_block_to_json
 - f_nano_crypto_util.h, 40
- f_nano_crypto_util.h, 18, 65
 - __attribute__, 34
 - account, 59
 - balance, 59
 - body, 59
 - DEST_XRB, 21
 - desc, 59
 - description, 60
 - F_BRAIN_WALLET_BAD, 22
 - F_BRAIN_WALLET_GOOD, 22
 - F_BRAIN_WALLET_MAYBE_GOOD, 22
 - F_BRAIN_WALLET_NICE, 22
 - F_BRAIN_WALLET_PERFECT, 22
 - F_BRAIN_WALLET_POOR, 23
 - F_BRAIN_WALLET_STILL_WEAK, 23
 - F_BRAIN_WALLET_VERY_BAD, 23
 - F_BRAIN_WALLET_VERY_GOOD, 23
 - F_BRAIN_WALLET_VERY_POOR, 24
 - F_BRAIN_WALLET_VERY_WEAK, 24
 - F_BRAIN_WALLET_WEAK, 24
 - F_DEFAULT_THRESHOLD, 24
 - F_FILE_INFO_ERR, 30
 - F_IS_SIGNATURE_RAW_HEX_STRING, 25
 - F_MESSAGE_IS_HASH_STRING, 25
 - F_NANO_POW_MAX_THREAD, 25
 - F_SIGNATURE_OUTPUT_NANO_PK, 25
 - F_SIGNATURE_OUTPUT_RAW_PK, 26
 - F_SIGNATURE_OUTPUT_STRING_PK, 26
 - F_SIGNATURE_OUTPUT_XRB_PK, 26
 - F_SIGNATURE_RAW, 26
 - F_SIGNATURE_STRING, 27
 - F_TOKEN, 30
 - F_VERIFY_SIG_ASCII_HEX, 27
 - F_VERIFY_SIG_NANO_WALLET, 27
 - F_VERIFY_SIG_RAW_HEX, 27
 - f_bip39_to_nano_seed, 34
 - f_cloud_crypto_wallet_nano_create_seed, 34
 - f_extract_seed_from_brainwallet, 35
 - f_file_info_err_t, 32

- f_generate_nano_seed, 36
- f_generate_token, 37
- f_get_dictionary_path, 37
- f_get_nano_file_info, 38
- f_nano_add_sub, 38
- f_nano_balance_to_str, 39
- f_nano_block_to_json, 40
- f_nano_err, 30
- f_nano_err_t, 32
- f_nano_get_block_hash, 40
- f_nano_get_p2pow_block_hash, 41
- f_nano_is_valid_block, 41
- f_nano_key_to_str, 41
- f_nano_p2pow_to_JSON, 42
- f_nano_parse_raw_str_to_raw128_t, 42
- f_nano_parse_real_str_to_raw128_t, 43
- f_nano_pow, 43
- f_nano_raw_to_string, 44
- f_nano_seed_to_bip39, 44
- f_nano_sign_block, 45
- f_nano_transaction_to_JSON, 46
- f_nano_valid_nano_str_value, 46
- f_nano_value_compare_value, 47
- f_nano_verify_nano_funds, 47
- f_parse_nano_seed_and_bip39_to_JSON, 48
- f_read_seed, 49
- f_seed_to_nano_wallet, 50
- f_set_dictionary_path, 51
- f_set_nano_file_info, 51
- f_sign_data, 52
- f_uint128_t, 30
- f_verify_signed_data, 52
- f_verify_token, 53
- f_verify_work, 54
- f_write_seed, 54
- f_write_seed_err, 31
- f_write_seed_err_t, 33
- file_info_integrity, 60
- from_multiplier, 55
- hash_sk_unencrypted, 60
- header, 60
- is_nano_prefix, 56
- is_null_hash, 56
- iv, 60
- last_used_wallet_number, 61
- link, 61
- MAX_STR_NANO_CHAR, 28
- max_fee, 61
- NANO_ENCRYPTED_SEED_FILE, 28
- NANO_FILE_WALLETS_INFO, 28
- NANO_PASSWD_MAX_LEN, 28
- NANO_PREFIX, 29
- NANO_PRIVATE_KEY_EXTENDED, 31
- NANO_PRIVATE_KEY, 31
- NANO_PUBLIC_KEY_EXTENDED, 31
- NANO_PUBLIC_KEY, 31
- NANO_SEED, 32
- nano_base_32_2_hex, 56
- nano_hdr, 61
- nanoseed_hash, 61
- PUB_KEY_EXTENDED_MAX_LEN, 29
- pk_to_wallet, 57
- preamble, 62
- prefixes, 62
- previous, 62
- REP_XRB, 29
- representative, 62
- reserved, 62
- SENDER_XRB, 29
- STR_NANO_SZ, 29
- salt, 63
- seed_block, 63
- signature, 63
- sk_encrypted, 63
- sub_salt, 63
- to_multiplier, 57
- valid_nano_wallet, 58
- valid_raw_balance, 58
- ver, 64
- version, 64
- wallet_prefix, 64
- wallet_representative, 64
- work, 64
- XRB_PREFIX, 30
- f_nano_crypto_wallet_t, 9
 - description, 10
 - iv, 10
 - nano_hdr, 10
 - salt, 10
 - seed_block, 11
 - ver, 11
- f_nano_encrypted_wallet_t, 11
 - hash_sk_unencrypted, 12
 - iv, 12
 - reserved, 12
 - sk_encrypted, 12
 - sub_salt, 12
- f_nano_err
 - f_nano_crypto_util.h, 30
- f_nano_err_t
 - f_nano_crypto_util.h, 32
- f_nano_get_block_hash
 - f_nano_crypto_util.h, 40
- f_nano_get_p2pow_block_hash
 - f_nano_crypto_util.h, 41
- f_nano_is_valid_block
 - f_nano_crypto_util.h, 41
- f_nano_key_to_str
 - f_nano_crypto_util.h, 41
- f_nano_p2pow_to_JSON
 - f_nano_crypto_util.h, 42
- f_nano_parse_raw_str_to_raw128_t
 - f_nano_crypto_util.h, 42
- f_nano_parse_real_str_to_raw128_t
 - f_nano_crypto_util.h, 43
- f_nano_pow

- f_nano_crypto_util.h, 43
- f_nano_raw_to_string
 - f_nano_crypto_util.h, 44
- f_nano_seed_to_bip39
 - f_nano_crypto_util.h, 44
- f_nano_sign_block
 - f_nano_crypto_util.h, 45
- f_nano_transaction_to_JSON
 - f_nano_crypto_util.h, 46
- f_nano_valid_nano_str_value
 - f_nano_crypto_util.h, 46
- f_nano_value_compare_value
 - f_nano_crypto_util.h, 47
- f_nano_verify_nano_funds
 - f_nano_crypto_util.h, 47
- f_nano_wallet_info_bdy_t, 13
 - last_used_wallet_number, 13
 - max_fee, 13
 - reserved, 14
 - wallet_prefix, 14
 - wallet_representative, 14
- f_nano_wallet_info_t, 14
 - body, 15
 - desc, 15
 - file_info_integrity, 15
 - header, 15
 - nanoseed_hash, 16
 - version, 16
- f_parse_nano_seed_and_bip39_to_JSON
 - f_nano_crypto_util.h, 48
- f_pass_must_have_at_least
 - f_util.h, 82
- f_passwd_comp_safe
 - f_util.h, 83
- f_random
 - f_util.h, 83
- f_random_attach
 - f_util.h, 85
- f_random_detach
 - f_util.h, 85
- f_read_seed
 - f_nano_crypto_util.h, 49
- f_seed_to_nano_wallet
 - f_nano_crypto_util.h, 50
- f_sel_to_entropy_level
 - f_util.h, 85
- f_set_dictionary_path
 - f_nano_crypto_util.h, 51
- f_set_nano_file_info
 - f_nano_crypto_util.h, 51
- f_sign_data
 - f_nano_crypto_util.h, 52
- f_str_to_hex
 - f_util.h, 86
- f_uint128_t
 - f_nano_crypto_util.h, 30
- f_util.h, 70, 88
 - crc32_init, 75
- ENTROPY_BEGIN, 71
- ENTROPY_END, 71
- F_ENTROPY_TYPE_EXCELENT, 72
- F_ENTROPY_TYPE_GOOD, 72
- F_ENTROPY_TYPE_NOT_ENOUGH, 72
- F_ENTROPY_TYPE_NOT_RECOMENDED, 72
- F_ENTROPY_TYPE_PARANOIC, 73
- F_GET_CH_MODE_ANY_KEY, 73
- F_GET_CH_MODE_NO_ECHO, 73
- F_PASS_IS_OUT_OVF, 73
- F_PASS_IS_TOO_LONG, 74
- F_PASS_IS_TOO_SHORT, 74
- F_PASS_MUST_HAVE_AT_LEAST_NONE, 74
- F_PASS_MUST_HAVE_AT_LEAST_ONE_LO←
 - WER_CASE, 74
- F_PASS_MUST_HAVE_AT_LEAST_ONE_NU←
 - MBER, 74
- F_PASS_MUST_HAVE_AT_LEAST_ONE_SYM←
 - BOL, 75
- F_PASS_MUST_HAVE_AT_LEAST_ONE_UPP←
 - ER_CASE, 75
- f_convert_to_double, 76
- f_convert_to_long_int, 76
- f_convert_to_long_int0, 77
- f_convert_to_long_int0x, 77
- f_convert_to_long_int_std, 78
- f_convert_to_unsigned_int, 78
- f_convert_to_unsigned_int0, 79
- f_convert_to_unsigned_int0x, 79
- f_convert_to_unsigned_int_std, 80
- f_get_char_no_block, 80
- f_get_entropy_name, 81
- f_is_random_attached, 81
- f_pass_must_have_at_least, 82
- f_passwd_comp_safe, 83
- f_random, 83
- f_random_attach, 85
- f_random_detach, 85
- f_sel_to_entropy_level, 85
- f_str_to_hex, 86
- f_verify_system_entropy, 86
- get_console_passwd, 87
- rnd_fn, 75
- f_verify_signed_data
 - f_nano_crypto_util.h, 52
- f_verify_system_entropy
 - f_util.h, 86
- f_verify_token
 - f_nano_crypto_util.h, 53
- f_verify_work
 - f_nano_crypto_util.h, 54
- f_write_seed
 - f_nano_crypto_util.h, 54
- f_write_seed_err
 - f_nano_crypto_util.h, 31
- f_write_seed_err_t
 - f_nano_crypto_util.h, 33
- file_info_integrity

- f_nano_crypto_util.h, 60
 - f_nano_wallet_info_t, 15
- from_multiplier
 - f_nano_crypto_util.h, 55
- get_console_passwd
 - f_util.h, 87
- hash_sk_unencrypted
 - f_nano_crypto_util.h, 60
 - f_nano_encrypted_wallet_t, 12
- header
 - f_nano_crypto_util.h, 60
 - f_nano_wallet_info_t, 15
- is_nano_prefix
 - f_nano_crypto_util.h, 56
- is_null_hash
 - f_nano_crypto_util.h, 56
- iv
 - f_nano_crypto_util.h, 60
 - f_nano_crypto_wallet_t, 10
 - f_nano_encrypted_wallet_t, 12
- last_used_wallet_number
 - f_nano_crypto_util.h, 61
 - f_nano_wallet_info_bdy_t, 13
- link
 - f_block_transfer_t, 8
 - f_nano_crypto_util.h, 61
- MAX_STR_NANO_CHAR
 - f_nano_crypto_util.h, 28
- max_fee
 - f_nano_crypto_util.h, 61
 - f_nano_wallet_info_bdy_t, 13
- NANO_ENCRYPTED_SEED_FILE
 - f_nano_crypto_util.h, 28
- NANO_FILE_WALLETS_INFO
 - f_nano_crypto_util.h, 28
- NANO_PASSWD_MAX_LEN
 - f_nano_crypto_util.h, 28
- NANO_PREFIX
 - f_nano_crypto_util.h, 29
- NANO_PRIVATE_KEY_EXTENDED
 - f_nano_crypto_util.h, 31
- NANO_PRIVATE_KEY
 - f_nano_crypto_util.h, 31
- NANO_PUBLIC_KEY_EXTENDED
 - f_nano_crypto_util.h, 31
- NANO_PUBLIC_KEY
 - f_nano_crypto_util.h, 31
- NANO_SEED
 - f_nano_crypto_util.h, 32
- nano_base_32_2_hex
 - f_nano_crypto_util.h, 56
- nano_hdr
 - f_nano_crypto_util.h, 61
 - f_nano_crypto_wallet_t, 10
- nanoseed_hash
 - f_nano_crypto_util.h, 61
 - f_nano_wallet_info_t, 16
- PUB_KEY_EXTENDED_MAX_LEN
 - f_nano_crypto_util.h, 29
- pk_to_wallet
 - f_nano_crypto_util.h, 57
- preamble
 - f_block_transfer_t, 8
 - f_nano_crypto_util.h, 62
- prefixes
 - f_block_transfer_t, 8
 - f_nano_crypto_util.h, 62
- previous
 - f_block_transfer_t, 8
 - f_nano_crypto_util.h, 62
- REP_XRB
 - f_nano_crypto_util.h, 29
- representative
 - f_block_transfer_t, 8
 - f_nano_crypto_util.h, 62
- reserved
 - f_nano_crypto_util.h, 62
 - f_nano_encrypted_wallet_t, 12
 - f_nano_wallet_info_bdy_t, 14
- rnd_fn
 - f_util.h, 75
- SENDER_XRB
 - f_nano_crypto_util.h, 29
- STR_NANO_SZ
 - f_nano_crypto_util.h, 29
- salt
 - f_nano_crypto_util.h, 63
 - f_nano_crypto_wallet_t, 10
- seed_block
 - f_nano_crypto_util.h, 63
 - f_nano_crypto_wallet_t, 11
- signature
 - f_block_transfer_t, 9
 - f_nano_crypto_util.h, 63
- sk_encrypted
 - f_nano_crypto_util.h, 63
 - f_nano_encrypted_wallet_t, 12
- sodium.h, 90, 91
- sub_salt
 - f_nano_crypto_util.h, 63
 - f_nano_encrypted_wallet_t, 12
- to_multiplier
 - f_nano_crypto_util.h, 57
- valid_nano_wallet
 - f_nano_crypto_util.h, 58
- valid_raw_balance
 - f_nano_crypto_util.h, 58
- ver

- f_nano_crypto_util.h, 64
 - f_nano_crypto_wallet_t, 11
 - version
 - f_nano_crypto_util.h, 64
 - f_nano_wallet_info_t, 16
 - wallet_prefix
 - f_nano_crypto_util.h, 64
 - f_nano_wallet_info_bdy_t, 14
 - wallet_representative
 - f_nano_crypto_util.h, 64
 - f_nano_wallet_info_bdy_t, 14
 - work
 - f_block_transfer_t, 9
 - f_nano_crypto_util.h, 64
 - XRB_PREFIX
 - f_nano_crypto_util.h, 30