

Nano cryptocurrency C library with P2PoW/DPoW support for Embedded  
1.0.0

Generated by Doxygen 1.8.13



# Contents

<b>1</b>	<b>Overview</b>	<b>1</b>
<b>2</b>	<b>Data Structure Index</b>	<b>3</b>
2.1	Data Structures . . . . .	3
<b>3</b>	<b>File Index</b>	<b>5</b>
3.1	Files . . . . .	5
<b>4</b>	<b>Data Structure Documentation</b>	<b>7</b>
4.1	f_block_transfer_t Struct Reference . . . . .	7
4.1.1	Detailed Description . . . . .	7
4.1.2	Field Documentation . . . . .	7
4.1.2.1	account . . . . .	7
4.1.2.2	balance . . . . .	8
4.1.2.3	link . . . . .	8
4.1.2.4	preamble . . . . .	8
4.1.2.5	prefixes . . . . .	8
4.1.2.6	previous . . . . .	8
4.1.2.7	representative . . . . .	9
4.1.2.8	signature . . . . .	9
4.1.2.9	work . . . . .	9
4.2	f_file_info_err_t Struct Reference . . . . .	9
4.2.1	Detailed Description . . . . .	9
4.3	f_nano_crypto_wallet_t Struct Reference . . . . .	9
4.3.1	Detailed Description . . . . .	10

4.3.2	Field Documentation . . . . .	10
4.3.2.1	description . . . . .	10
4.3.2.2	iv . . . . .	10
4.3.2.3	nano_hdr . . . . .	10
4.3.2.4	salt . . . . .	11
4.3.2.5	seed_block . . . . .	11
4.3.2.6	ver . . . . .	11
4.4	f_nano_encrypted_wallet_t Struct Reference . . . . .	11
4.4.1	Detailed Description . . . . .	11
4.4.2	Field Documentation . . . . .	12
4.4.2.1	hash_sk_unencrypted . . . . .	12
4.4.2.2	iv . . . . .	12
4.4.2.3	reserved . . . . .	12
4.4.2.4	sk_encrypted . . . . .	12
4.4.2.5	sub_salt . . . . .	13
4.5	f_nano_wallet_info_bdy_t Struct Reference . . . . .	13
4.5.1	Detailed Description . . . . .	13
4.5.2	Field Documentation . . . . .	13
4.5.2.1	last_used_wallet_number . . . . .	13
4.5.2.2	max_fee . . . . .	14
4.5.2.3	reserved . . . . .	14
4.5.2.4	wallet_prefix . . . . .	14
4.5.2.5	wallet_representative . . . . .	14
4.6	f_nano_wallet_info_t Struct Reference . . . . .	14
4.6.1	Detailed Description . . . . .	15
4.6.2	Field Documentation . . . . .	15
4.6.2.1	body . . . . .	15
4.6.2.2	desc . . . . .	15
4.6.2.3	file_info_integrity . . . . .	15
4.6.2.4	header . . . . .	16
4.6.2.5	nanoseed_hash . . . . .	16
4.6.2.6	version . . . . .	16

<b>5 File Documentation</b>	<b>17</b>
5.1 f_add_bn_288_le.h File Reference . . . . .	17
5.1.1 Detailed Description . . . . .	17
5.1.2 Typedef Documentation . . . . .	17
5.1.2.1 F_ADD_288 . . . . .	17
5.2 f_add_bn_288_le.h . . . . .	18
5.3 f_nano_crypto_util.h File Reference . . . . .	18
5.3.1 Detailed Description . . . . .	21
5.3.2 Macro Definition Documentation . . . . .	21
5.3.2.1 DEST_XRB . . . . .	21
5.3.2.2 F_BRAIN_WALLET_BAD . . . . .	21
5.3.2.3 F_BRAIN_WALLET_GOOD . . . . .	21
5.3.2.4 F_BRAIN_WALLET_MAYBE_GOOD . . . . .	21
5.3.2.5 F_BRAIN_WALLET_NICE . . . . .	22
5.3.2.6 F_BRAIN_WALLET_PERFECT . . . . .	22
5.3.2.7 F_BRAIN_WALLET_POOR . . . . .	22
5.3.2.8 F_BRAIN_WALLET_STILL_WEAK . . . . .	22
5.3.2.9 F_BRAIN_WALLET_VERY_BAD . . . . .	23
5.3.2.10 F_BRAIN_WALLET_VERY_GOOD . . . . .	23
5.3.2.11 F_BRAIN_WALLET_VERY_POOR . . . . .	23
5.3.2.12 F_BRAIN_WALLET_VERY_WEAK . . . . .	23
5.3.2.13 F_BRAIN_WALLET_WEAK . . . . .	24
5.3.2.14 MAX_STR_NANO_CHAR . . . . .	24
5.3.2.15 NANO_ENCRYPTED_SEED_FILE . . . . .	24
5.3.2.16 NANO_FILE_WALLETS_INFO . . . . .	24
5.3.2.17 NANO_PASSWD_MAX_LEN . . . . .	24
5.3.2.18 NANO_PREFIX . . . . .	25
5.3.2.19 PUB_KEY_EXTENDED_MAX_LEN . . . . .	25
5.3.2.20 REP_XRB . . . . .	25
5.3.2.21 SENDER_XRB . . . . .	25

5.3.2.22	STR_NANO_SZ . . . . .	25
5.3.2.23	XRB_PREFIX . . . . .	26
5.3.3	Typedef Documentation . . . . .	26
5.3.3.1	F_FILE_INFO_ERR . . . . .	26
5.3.3.2	f_nano_err . . . . .	26
5.3.3.3	f_uint128_t . . . . .	26
5.3.3.4	f_write_seed_err . . . . .	26
5.3.3.5	NANO_PRIVATE_KEY . . . . .	27
5.3.3.6	NANO_PRIVATE_KEY_EXTENDED . . . . .	27
5.3.3.7	NANO_PUBLIC_KEY . . . . .	27
5.3.3.8	NANO_PUBLIC_KEY_EXTENDED . . . . .	27
5.3.3.9	NANO_SEED . . . . .	27
5.3.4	Enumeration Type Documentation . . . . .	27
5.3.4.1	f_file_info_err_t . . . . .	27
5.3.4.2	f_nano_err_t . . . . .	28
5.3.4.3	f_write_seed_err_t . . . . .	29
5.3.5	Function Documentation . . . . .	29
5.3.5.1	__attribute__() . . . . .	29
5.3.5.2	f_bip39_to_nano_seed() . . . . .	30
5.3.5.3	f_cloud_crypto_wallet_nano_create_seed() . . . . .	31
5.3.5.4	f_extract_seed_from_brainwallet() . . . . .	32
5.3.5.5	f_generate_nano_seed() . . . . .	33
5.3.5.6	f_get_nano_file_info() . . . . .	33
5.3.5.7	f_nano_add_sub() . . . . .	34
5.3.5.8	f_nano_balance_to_str() . . . . .	35
5.3.5.9	f_nano_key_to_str() . . . . .	35
5.3.5.10	f_nano_parse_raw_str_to_raw128_t() . . . . .	36
5.3.5.11	f_nano_parse_real_str_to_raw128_t() . . . . .	36
5.3.5.12	f_nano_raw_to_string() . . . . .	37
5.3.5.13	f_nano_seed_to_bip39() . . . . .	37

5.3.5.14	f_nano_sign_block()	38
5.3.5.15	f_nano_transaction_to_JSON()	38
5.3.5.16	f_nano_valid_nano_str_value()	39
5.3.5.17	f_nano_value_compare_value()	39
5.3.5.18	f_nano_verify_nano_funds()	40
5.3.5.19	f_parse_nano_seed_and_bip39_to_JSON()	41
5.3.5.20	f_read_seed()	42
5.3.5.21	f_seed_to_nano_wallet()	43
5.3.5.22	f_set_nano_file_info()	44
5.3.5.23	f_write_seed()	44
5.3.5.24	is_nano_prefix()	45
5.3.5.25	is_null_hash()	45
5.3.5.26	nano_base_32_2_hex()	45
5.3.5.27	pk_to_wallet()	46
5.3.5.28	valid_nano_wallet()	47
5.3.5.29	valid_raw_balance()	47
5.3.6	Variable Documentation	47
5.3.6.1	account	47
5.3.6.2	balance	48
5.3.6.3	body	48
5.3.6.4	desc	48
5.3.6.5	description	48
5.3.6.6	file_info_integrity	48
5.3.6.7	hash_sk_unencrypted	49
5.3.6.8	header	49
5.3.6.9	iv	49
5.3.6.10	last_used_wallet_number	49
5.3.6.11	link	49
5.3.6.12	max_fee	50
5.3.6.13	nano_hdr	50

5.3.6.14	nanoseed_hash . . . . .	50
5.3.6.15	preamble . . . . .	50
5.3.6.16	prefixes . . . . .	50
5.3.6.17	previous . . . . .	51
5.3.6.18	representative . . . . .	51
5.3.6.19	reserved . . . . .	51
5.3.6.20	salt . . . . .	51
5.3.6.21	seed_block . . . . .	51
5.3.6.22	signature . . . . .	52
5.3.6.23	sk_encrypted . . . . .	52
5.3.6.24	sub_salt . . . . .	52
5.3.6.25	ver . . . . .	52
5.3.6.26	version . . . . .	52
5.3.6.27	wallet_prefix . . . . .	53
5.3.6.28	wallet_representative . . . . .	53
5.3.6.29	work . . . . .	53
5.4	f_nano_crypto_util.h . . . . .	53
5.5	f_util.h File Reference . . . . .	58
5.5.1	Detailed Description . . . . .	58
5.5.2	Macro Definition Documentation . . . . .	59
5.5.2.1	ENTROPY_BEGIN . . . . .	59
5.5.2.2	ENTROPY_END . . . . .	59
5.5.2.3	F_ENTROPY_TYPE_EXCELENT . . . . .	59
5.5.2.4	F_ENTROPY_TYPE_GOOD . . . . .	60
5.5.2.5	F_ENTROPY_TYPE_NOT_ENOUGH . . . . .	60
5.5.2.6	F_ENTROPY_TYPE_NOT_RECOMENDED . . . . .	60
5.5.2.7	F_ENTROPY_TYPE_PARANOIC . . . . .	60
5.5.2.8	F_GET_CH_MODE_ANY_KEY . . . . .	61
5.5.2.9	F_GET_CH_MODE_NO_ECHO . . . . .	61
5.5.2.10	F_PASS_IS_OUT_OVF . . . . .	61



5.5.2.11	F_PASS_IS_TOO_LONG . . . . .	61
5.5.2.12	F_PASS_IS_TOO_SHORT . . . . .	61
5.5.2.13	F_PASS_MUST_HAVE_AT_LEAST_NONE . . . . .	62
5.5.2.14	F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE . . . . .	62
5.5.2.15	F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER . . . . .	62
5.5.2.16	F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL . . . . .	62
5.5.2.17	F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE . . . . .	62
5.5.3	Typedef Documentation . . . . .	63
5.5.3.1	rnd_fn . . . . .	63
5.5.4	Function Documentation . . . . .	63
5.5.4.1	f_convert_to_long_int() . . . . .	63
5.5.4.2	f_get_char_no_block() . . . . .	63
5.5.4.3	f_get_entropy_name() . . . . .	64
5.5.4.4	f_pass_must_have_at_least() . . . . .	64
5.5.4.5	f_passwd_comp_safe() . . . . .	65
5.5.4.6	f_random() . . . . .	66
5.5.4.7	f_random_attach() . . . . .	66
5.5.4.8	f_sel_to_entropy_level() . . . . .	67
5.5.4.9	f_str_to_hex() . . . . .	67
5.5.4.10	f_verify_system_entropy() . . . . .	68
5.5.4.11	get_console_passwd() . . . . .	68
5.6	f_util.h . . . . .	69
5.7	sodium.h File Reference . . . . .	71
5.7.1	Detailed Description . . . . .	72
5.8	sodium.h . . . . .	72



# Chapter 1

## Overview

*myNanoEmbedded* is a lightweight C library of source files that integrates Nano Cryptocurrency to low complexity computational devices to send/receive digital money to anywhere in the world with fast transaction and with a small fee by delegating a Proof of Work with your choice:

- DPoW (Distributed Proof of Work)
- P2PoW (a Decentralized P2P Proof of Work)

### API features

- Attaches a random function to TRNG hardware (if available)
- Self entropy verifier to ensure excellent TRNG or PRNG entropy
- Creates an encrypted by password your stream or file to store your Nano SEED
- Bip39 and Brainwallet support
- Convert raw data to Base32
- Parse SEED and Bip39 to JSON
- Sign a block using Blake2b hash with Ed25519 algorithm
- ARM-A, ARM-M, Thumb, Xtensa-LX6 and IA64 compatible
- Linux desktop, Raspberry PI, ESP32 and Olimex A20 tested platforms
- Communication over Fenix protocol bridge over TLS
- Libsodium and mbedTLS libraries with smaller resources and best performance
- Optimized for size and speed
- Non static functions (all data is cleared before processed for security)
- Fully written in C for maximum performance and portability

### To add this API in your project you must first:

1. Download the latest version.

```
git clone https://github.com/devfabiosilva/myNanoEmbedded.git --recurse-submodules
```

2. Include the main library files in the client application.

```
#include "f_nano_crypto_util.h"
```

### Initialize API

Function	Description
<code>f_random_attach()</code> (p. ??)	Initializes the PRNG or TRNG to be used in this API

## Transmit/Receive transactions

To transmit/receive your transaction you must use `Fenix` protocol to stabilish a DPoW/P2PoW support

## Examples using platforms

The repository has some examples with most common embedded and Linux systems

- Native Linux
- Raspberry Pi
- ESP32
- Olimex A20
- STM

## Credits

### Author

Fábio Pereira da Silva

### Date

Feb 2020

### Version

1.0

### Copyright

License MIT [see here](#)

## References:

[1] - Colin LeMahieu - *Nano: A Feeless Distributed Cryptocurrency Network* - (2015)

[2] - Z. S. Spakovszky - *7.3 A Statistical Definition of Entropy* - (2005) - NOTE: Entropy function for cryptography is implemented based on `Definition (7.12)` of this amazing topic

[3] - Kaique Anarkrypto - *Delegated Proof of Work* - (2019)

[4] - `docs.nano.org` - *Node RPCs documentation*

## Chapter 2

# Data Structure Index

### 2.1 Data Structures

Here are the data structures with brief descriptions:

<b>f_block_transfer_t</b>	
Nano signed block raw data defined in this <a href="#">reference</a> . . . . .	7
<b>f_file_info_err_t</b>	
Error enumerator for info file functions . . . . .	9
<b>f_nano_crypto_wallet_t</b>	
<b>struct</b> of the block of encrypted file to store Nano SEED . . . . .	9
<b>f_nano_encrypted_wallet_t</b>	
<b>struct</b> of the block of encrypted file to store Nano SEED . . . . .	11
<b>f_nano_wallet_info_bdy_t</b>	
<b>struct</b> of the body block of the info file . . . . .	13
<b>f_nano_wallet_info_t</b>	
<b>struct</b> of the body block of the info file . . . . .	14



## Chapter 3

# File Index

### 3.1 Files

Here is a list of all files with brief descriptions:

<b>f_add_bn_288_le.h</b>	
Low level implementation of Nano Cryptocurrency C library . . . . .	17
<b>f_nano_crypto_util.h</b>	
This API Integrates Nano Cryptocurrency to low computational devices . . . . .	18
<b>f_util.h</b>	
This ABI is a utility for myNanoEmbedded library and sub routines are implemented here . . .	58
<b>sodium.h</b>	
This header file is an implementation of Libsodium library . . . . .	71





## Chapter 4

# Data Structure Documentation

### 4.1 `f_block_transfer_t` Struct Reference

```
#include <f_nano_crypto_util.h>
```

#### Data Fields

- `uint8_t` **preamble** [32]
- `uint8_t` **account** [32]
- `uint8_t` **previous** [32]
- `uint8_t` **representative** [32]
- `f_uint128_t` **balance**
- `uint8_t` **link** [32]
- `uint8_t` **signature** [64]
- `uint8_t` **prefixes**
- `uint64_t` **work**

#### 4.1.1 Detailed Description

Nano signed block raw data defined in this [reference](#)

Definition at line **246** of file **f\_nano\_crypto\_util.h**.

#### 4.1.2 Field Documentation

##### 4.1.2.1 `account`

```
uint8_t account[32]
```

Account in raw binary data.

Definition at line **250** of file **f\_nano\_crypto\_util.h**.

#### 4.1.2.2 balance

`f_uint128_t balance`

Big number 128 bit raw balance.

See also

`f_uint128_t` (p. ??)

Definition at line **258** of file **f\_nano\_crypto\_util.h**.

#### 4.1.2.3 link

`uint8_t link[32]`

link or destination account

Definition at line **260** of file **f\_nano\_crypto\_util.h**.

#### 4.1.2.4 preamble

`uint8_t preamble[32]`

Block preamble.

Definition at line **248** of file **f\_nano\_crypto\_util.h**.

#### 4.1.2.5 prefixes

`uint8_t prefixes`

Internal use for this API.

Definition at line **264** of file **f\_nano\_crypto\_util.h**.

#### 4.1.2.6 previous

`uint8_t previous[32]`

Previous block.

Definition at line **252** of file **f\_nano\_crypto\_util.h**.

#### 4.1.2.7 `representative`

```
uint8_t representative[32]
```

Representative for current account.

Definition at line **254** of file `f_nano_crypto_util.h`.

#### 4.1.2.8 `signature`

```
uint8_t signature[64]
```

Signature of the block.

Definition at line **262** of file `f_nano_crypto_util.h`.

#### 4.1.2.9 `work`

```
uint64_t work
```

Internal use for this API.

Definition at line **266** of file `f_nano_crypto_util.h`.

The documentation for this struct was generated from the following file:

- `f_nano_crypto_util.h`

## 4.2 `f_file_info_err_t` Struct Reference

```
#include <f_nano_crypto_util.h>
```

### 4.2.1 Detailed Description

Error enumerator for info file functions.

The documentation for this struct was generated from the following file:

- `f_nano_crypto_util.h`

## 4.3 `f_nano_crypto_wallet_t` Struct Reference

```
#include <f_nano_crypto_util.h>
```

## Data Fields

- `uint8_t nano_hdr` [`sizeof(NANO_WALLET_MAGIC)`]
- `uint32_t ver`
- `uint8_t description` [`F_DESC_SZ`]
- `uint8_t salt` [32]
- `uint8_t iv` [16]
- `F_ENCRYPTED_BLOCK seed_block`

### 4.3.1 Detailed Description

**struct** of the block of encrypted file to store Nano SEED

Definition at line **377** of file **f\_nano\_crypto\_util.h**.

### 4.3.2 Field Documentation

#### 4.3.2.1 description

```
uint8_t description[F_DESC_SZ]
```

File description.

Definition at line **383** of file **f\_nano\_crypto\_util.h**.

#### 4.3.2.2 iv

```
uint8_t iv[16]
```

Initial vector of first encryption layer.

Definition at line **387** of file **f\_nano\_crypto\_util.h**.

#### 4.3.2.3 nano\_hdr

```
uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)]
```

Header of the file.

Definition at line **379** of file **f\_nano\_crypto\_util.h**.

#### 4.3.2.4 salt

```
uint8_t salt[32]
```

Salt of the first encryption layer.

Definition at line 385 of file `f_nano_crypto_util.h`.

#### 4.3.2.5 seed\_block

```
F_ENCRYPTED_BLOCK seed_block
```

Second encrypted block for Nano SEED.

Definition at line 389 of file `f_nano_crypto_util.h`.

#### 4.3.2.6 ver

```
uint32_t ver
```

Version of the file.

Definition at line 381 of file `f_nano_crypto_util.h`.

The documentation for this struct was generated from the following file:

- `f_nano_crypto_util.h`

## 4.4 f\_nano\_encrypted\_wallet\_t Struct Reference

```
#include <f_nano_crypto_util.h>
```

### Data Fields

- `uint8_t sub_salt` [32]
- `uint8_t iv` [16]
- `uint8_t reserved` [16]
- `uint8_t hash_sk_unencrypted` [32]
- `uint8_t sk_encrypted` [32]

#### 4.4.1 Detailed Description

**struct** of the block of encrypted file to store Nano SEED

Definition at line 349 of file `f_nano_crypto_util.h`.

## 4.4.2 Field Documentation

### 4.4.2.1 hash\_sk\_unencrypted

```
uint8_t hash_sk_unencrypted[32]
```

hash of Nano SEED when unencrypted

Definition at line **357** of file **f\_nano\_crypto\_util.h**.

### 4.4.2.2 iv

```
uint8_t iv[16]
```

Initial sub vector.

Definition at line **353** of file **f\_nano\_crypto\_util.h**.

### 4.4.2.3 reserved

```
uint8_t reserved[16]
```

Reserved (not used)

Definition at line **355** of file **f\_nano\_crypto\_util.h**.

### 4.4.2.4 sk\_encrypted

```
uint8_t sk_encrypted[32]
```

Secret.

SEED encrypted (second layer)

Definition at line **359** of file **f\_nano\_crypto\_util.h**.

#### 4.4.2.5 sub\_salt

```
uint8_t sub_salt[32]
```

Salt of the sub block to be stored.

Definition at line 351 of file `f_nano_crypto_util.h`.

The documentation for this struct was generated from the following file:

- `f_nano_crypto_util.h`

## 4.5 f\_nano\_wallet\_info\_bdy\_t Struct Reference

```
#include <f_nano_crypto_util.h>
```

### Data Fields

- `uint8_t wallet_prefix`
- `uint32_t last_used_wallet_number`
- `char wallet_representative [ MAX_STR_NANO_CHAR]`
- `char max_fee [F_RAW_STR_MAX_SZ]`
- `uint8_t reserved [44]`

### 4.5.1 Detailed Description

**struct** of the body block of the info file

Definition at line 461 of file `f_nano_crypto_util.h`.

### 4.5.2 Field Documentation

#### 4.5.2.1 last\_used\_wallet\_number

```
uint32_t last_used_wallet_number
```

Last used wallet number.

Definition at line 465 of file `f_nano_crypto_util.h`.

#### 4.5.2.2 max\_fee

```
char max_fee[F_RAW_STR_MAX_SZ]
```

Custom preferred max fee of Proof of Work.

Definition at line **469** of file **f\_nano\_crypto\_util.h**.

#### 4.5.2.3 reserved

```
uint8_t reserved[44]
```

Reserved.

Definition at line **471** of file **f\_nano\_crypto\_util.h**.

#### 4.5.2.4 wallet\_prefix

```
uint8_t wallet_prefix
```

Wallet prefix: 0 for NANO; 1 for XRB.

Definition at line **463** of file **f\_nano\_crypto\_util.h**.

#### 4.5.2.5 wallet\_representative

```
char wallet_representative[ MAX_STR_NANO_CHAR]
```

Wallet representative.

Definition at line **467** of file **f\_nano\_crypto\_util.h**.

The documentation for this struct was generated from the following file:

- **f\_nano\_crypto\_util.h**

## 4.6 f\_nano\_wallet\_info\_t Struct Reference

```
#include <f_nano_crypto_util.h>
```



## Data Fields

- `uint8_t header` [sizeof(F\_NANO\_WALLET\_INFO\_MAGIC)]
- `uint16_t version`
- `char desc` [F\_NANO\_DESC\_SZ]
- `uint8_t nanoseed_hash` [32]
- `uint8_t file_info_integrity` [32]
- F\_NANO\_WALLET\_INFO\_BODY `body`

### 4.6.1 Detailed Description

**struct** of the body block of the info file

Definition at line **493** of file `f_nano_crypto_util.h`.

### 4.6.2 Field Documentation

#### 4.6.2.1 `body`

```
F_NANO_WALLET_INFO_BODY body
```

Body of the file info.

Definition at line **505** of file `f_nano_crypto_util.h`.

#### 4.6.2.2 `desc`

```
char desc[F_NANO_DESC_SZ]
```

Description.

Definition at line **499** of file `f_nano_crypto_util.h`.

#### 4.6.2.3 `file_info_integrity`

```
uint8_t file_info_integrity[32]
```

File info integrity of the body block.

Definition at line **503** of file `f_nano_crypto_util.h`.

#### 4.6.2.4 header

```
uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)]
```

Header magic.

Definition at line **495** of file **f\_nano\_crypto\_util.h**.

#### 4.6.2.5 nanoseed\_hash

```
uint8_t nanoseed_hash[32]
```

Nano SEED hash file.

Definition at line **501** of file **f\_nano\_crypto\_util.h**.

#### 4.6.2.6 version

```
uint16_t version
```

Version.

Definition at line **497** of file **f\_nano\_crypto\_util.h**.

The documentation for this struct was generated from the following file:

- **f\_nano\_crypto\_util.h**

## Chapter 5

# File Documentation

### 5.1 `f_add_bn_288_le.h` File Reference

```
#include <stdint.h>
```

#### Typedefs

- typedef uint8\_t **F\_ADD\_288**[36]

#### 5.1.1 Detailed Description

Low level implementation of Nano Cryptocurrency C library.

Definition in file `f_add_bn_288_le.h`.

#### 5.1.2 Typedef Documentation

##### 5.1.2.1 `F_ADD_288`

`F_ADD_288`

288 bit big number

Definition at line **19** of file `f_add_bn_288_le.h`.

## 5.2 f\_add\_bn\_288\_le.h

```

00001  /*
00002      AUTHOR: Fábio Pereira da Silva
00003      YEAR: 2019-20
00004      LICENSE: MIT
00005      EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006  */
00007
00008  #include <stdint.h>
00009
00019  typedef uint8_t F_ADD_288[36];
00020
00021
00022  #ifndef F_DOC_SKIP
00023
00033  void f_add_bn_288_le(F_ADD_288, F_ADD_288, F_ADD_288, int *, int);
00034  void f_sl_elv_add_le(F_ADD_288, int);
00035
00036  #endif
00037

```

## 5.3 f\_nano\_crypto\_util.h File Reference

```

#include <stdint.h>
#include "f_util.h"

```

### Data Structures

- struct **f\_block\_transfer\_t**
- struct **f\_nano\_encrypted\_wallet\_t**
- struct **f\_nano\_crypto\_wallet\_t**
- struct **f\_nano\_wallet\_info\_bdy\_t**
- struct **f\_nano\_wallet\_info\_t**

### Macros

- #define **MAX\_STR\_NANO\_CHAR** (size\_t)70
- #define **PUB\_KEY\_EXTENDED\_MAX\_LEN** (size\_t)40
- #define **NANO\_PREFIX** "nano\_"
- #define **XRB\_PREFIX** "xrb\_"
- #define **NANO\_ENCRYPTED\_SEED\_FILE** "/spiffs/secure/nano.nse"
- #define **NANO\_PASSWD\_MAX\_LEN** (size\_t)80
- #define **STR\_NANO\_SZ** (size\_t)66
- #define **NANO\_FILE\_WALLETS\_INFO** "/spiffs/secure/walletsinfo.i"
- #define **REP\_XRB** (uint8\_t)0x4
- #define **SENDER\_XRB** (uint8\_t)0x02
- #define **DEST\_XRB** (uint8\_t)0x01
- #define **F\_BRAIN\_WALLET\_VERY\_POOR** (uint32\_t)0
- #define **F\_BRAIN\_WALLET\_POOR** (uint32\_t)1
- #define **F\_BRAIN\_WALLET\_VERY\_BAD** (uint32\_t)2
- #define **F\_BRAIN\_WALLET\_BAD** (uint32\_t)3
- #define **F\_BRAIN\_WALLET\_VERY\_WEAK** (uint32\_t)4
- #define **F\_BRAIN\_WALLET\_WEAK** (uint32\_t)5
- #define **F\_BRAIN\_WALLET\_STILL\_WEAK** (uint32\_t)6
- #define **F\_BRAIN\_WALLET\_MAYBE\_GOOD** (uint32\_t)7
- #define **F\_BRAIN\_WALLET\_GOOD** (uint32\_t)8
- #define **F\_BRAIN\_WALLET\_VERY\_GOOD** (uint32\_t)9
- #define **F\_BRAIN\_WALLET\_NICE** (uint32\_t)10
- #define **F\_BRAIN\_WALLET\_PERFECT** (uint32\_t)11

## Typedefs

- typedef uint8\_t **NANO\_SEED**[crypto\_sign\_SEEDBYTES]
- typedef uint8\_t **f\_uint128\_t**[16]
- typedef uint8\_t **NANO\_PRIVATE\_KEY**[sizeof( **NANO\_SEED**)]
- typedef uint8\_t **NANO\_PRIVATE\_KEY\_EXTENDED**[crypto\_sign\_ed25519\_SECRETKEYBYTES]
- typedef uint8\_t **NANO\_PUBLIC\_KEY**[crypto\_sign\_ed25519\_PUBLICKEYBYTES]
- typedef uint8\_t **NANO\_PUBLIC\_KEY\_EXTENDED**[**PUB\_KEY\_EXTENDED\_MAX\_LEN**]
- typedef enum **f\_nano\_err\_t** **f\_nano\_err**
- typedef enum **f\_write\_seed\_err\_t** **f\_write\_seed\_err**
- typedef enum **f\_file\_info\_err\_t** **F\_FILE\_INFO\_ERR**

## Enumerations

- enum **f\_nano\_err\_t** {  
**NANO\_ERR\_OK** = 0, **NANO\_ERR\_CANT\_PARSE\_BN\_STR** = 5151, **NANO\_ERR\_MALLOC**, **NANO\_ERR\_CANT\_PARSE\_FACTOR**,  
**NANO\_ERR\_MPI\_MULT**, **NANO\_ERR\_CANT\_PARSE\_TO\_BLK\_TRANSFER**, **NANO\_ERR\_EMPTY\_STRING**, **NANO\_ERR\_CANT\_PARSE\_VALUE**,  
**NANO\_ERR\_PARSE\_MPI\_TO\_STR**, **NANO\_ERR\_CANT\_COMPLETE\_NULL\_CHAR**, **NANO\_ERR\_CANT\_PARSE\_TO\_MPI**, **NANO\_ERR\_INSUFICIENT\_FUNDS**,  
**NANO\_ERR\_SUB\_MPI**, **NANO\_ERR\_ADD\_MPI**, **NANO\_ERR\_NO\_SENSE\_VALUE\_TO\_SEND\_NEGATIVE**, **NANO\_ERR\_NO\_SENSE\_VALUE\_TO\_SEND\_ZERO**,  
**NANO\_ERR\_NO\_SENSE\_BALANCE\_NEGATIVE**, **NANO\_ERR\_VAL\_A\_INVALID\_MODE**, **NANO\_ERR\_CANT\_PARSE\_TO\_TEMP\_UINT128\_T**, **NANO\_ERR\_VAL\_B\_INVALID\_MODE**,  
**NANO\_ERR\_CANT\_PARSE\_RAW\_A\_TO\_MPI**, **NANO\_ERR\_CANT\_PARSE\_RAW\_B\_TO\_MPI**, **NANO\_ERR\_UNKNOWN\_ADD\_SUB\_MODE**, **NANO\_ERR\_INVALID\_RES\_OUTPUT** }
- enum **f\_write\_seed\_err\_t** {  
**WRITE\_ERR\_OK** = 0, **WRITE\_ERR\_NULL\_PASSWORD** = 7180, **WRITE\_ERR\_EMPTY\_STRING**, **WRITE\_ERR\_MALLOC**,  
**WRITE\_ERR\_ENCRYPT\_PRIV\_KEY**, **WRITE\_ERR\_GEN\_SUB\_PRIV\_KEY**, **WRITE\_ERR\_GEN\_MAIN\_PRIV\_KEY**, **WRITE\_ERR\_ENCRYPT\_SUB\_BLOCK**,  
**WRITE\_ERR\_UNKNOWN\_OPTION**, **WRITE\_ERR\_FILE\_ALREADY\_EXISTS**, **WRITE\_ERR\_CREATING\_FILE**, **WRITE\_ERR\_WRITING\_FILE** }
- enum **f\_file\_info\_err\_t** {  
**F\_FILE\_INFO\_ERR\_OK** = 0, **F\_FILE\_INFO\_ERR\_CANT\_OPEN\_INFO\_FILE** = 7001, **F\_FILE\_INFO\_ERR\_NANO\_SEED\_ENCRYPTED\_FILE\_NOT\_FOUND**, **F\_FILE\_INFO\_ERR\_CANT\_DELETE\_NANO\_INFO\_FILE**,  
**F\_FILE\_INFO\_ERR\_MALLOC**, **F\_FILE\_INFO\_ERR\_CANT\_READ\_NANO\_SEED\_ENCRYPTED\_FILE**, **F\_FILE\_INFO\_ERR\_CANT\_READ\_INFO\_FILE**, **F\_FILE\_INFO\_INVALID\_HEADER\_FILE**,  
**F\_FILE\_INFO\_ERR\_INVALID\_SHA256\_INFO\_FILE**, **F\_FILE\_INFO\_ERR\_NANO\_SEED\_HASH\_FAIL**, **F\_FILE\_INFO\_ERR\_NANO\_INVALID\_REPRESENTATIVE**, **F\_FILE\_INFO\_ERR\_NANO\_INVALID\_MAX\_FEE\_VALUE**,  
**F\_FILE\_INFO\_ERR\_OPEN\_FOR\_WRITE\_INFO**, **F\_FILE\_INFO\_ERR\_EXISTING\_FILE**, **F\_FILE\_INFO\_ERR\_CANT\_WRITE\_FILE\_INFO** }

## Functions

- struct **f\_block\_transfer\_t** **\_\_attribute\_\_((packed))** **F\_BLOCK\_TRANSFER**
- int **f\_cloud\_crypto\_wallet\_nano\_create\_seed** (size\_t, char \*, char \*)
- int **f\_generate\_nano\_seed** ( **NANO\_SEED**, uint32\_t)
- int **pk\_to\_wallet** (char \*, char \*, **NANO\_PUBLIC\_KEY\_EXTENDED**)
- int **f\_seed\_to\_nano\_wallet** ( **NANO\_PRIVATE\_KEY**, **NANO\_PUBLIC\_KEY**, **NANO\_SEED**, uint32\_t)
- char \* **f\_nano\_key\_to\_str** (char \*, unsigned char \*)
- int **f\_nano\_seed\_to\_bip39** (char \*, size\_t, size\_t \*, **NANO\_SEED**, char \*)

- int **f\_bip39\_to\_nano\_seed** (uint8\_t \*, char \*, char \*)
- int **f\_parse\_nano\_seed\_and\_bip39\_to\_JSON** (char \*, size\_t, size\_t \*, void \*, int, const char \*)
- int **f\_read\_seed** (uint8\_t \*, const char \*, void \*, int, int)
- int **f\_nano\_raw\_to\_string** (char \*, size\_t \*, size\_t, void \*, int)
- int **f\_nano\_valid\_nano\_str\_value** (const char \*)
- int **valid\_nano\_wallet** (const char \*)
- int **nano\_base\_32\_2\_hex** (uint8\_t \*, char \*)
- int **f\_nano\_transaction\_to\_JSON** (char \*, size\_t, size\_t \*, **NANO\_PRIVATE\_KEY\_EXTENDED**, F\_BLOCK\_TRANSFER \*)
- int **valid\_raw\_balance** (const char \*)
- int **is\_null\_hash** (uint8\_t \*)
- int **is\_nano\_prefix** (const char \*, const char \*)
- **F\_FILE\_INFO\_ERR** **f\_get\_nano\_file\_info** (F\_NANO\_WALLET\_INFO \*)
- **F\_FILE\_INFO\_ERR** **f\_set\_nano\_file\_info** (F\_NANO\_WALLET\_INFO \*, int)
- **f\_nano\_err** **f\_nano\_value\_compare\_value** (void \*, void \*, uint32\_t \*)
- **f\_nano\_err** **f\_nano\_verify\_nano\_funds** (void \*, void \*, void \*, uint32\_t)
- **f\_nano\_err** **f\_nano\_parse\_raw\_str\_to\_raw128\_t** (uint8\_t \*, const char \*)
- **f\_nano\_err** **f\_nano\_parse\_real\_str\_to\_raw128\_t** (uint8\_t \*, const char \*)
- **f\_nano\_err** **f\_nano\_add\_sub** (void \*, void \*, void \*, uint32\_t)
- int **f\_nano\_sign\_block** (F\_BLOCK\_TRANSFER \*, F\_BLOCK\_TRANSFER \*, **NANO\_PRIVATE\_KEY\_EXTENDED**)
- **f\_write\_seed\_err** **f\_write\_seed** (void \*, int, uint8\_t \*, char \*)
- **f\_nano\_err** **f\_nano\_balance\_to\_str** (char \*, size\_t, size\_t \*, **f\_uint128\_t**)
- int **f\_extract\_seed\_from\_brainwallet** (uint8\_t \*, char \*\*, uint32\_t, const char \*, const char \*)

## Variables

- uint8\_t **preamble** [32]
- uint8\_t **account** [32]
- uint8\_t **previous** [32]
- uint8\_t **representative** [32]
- **f\_uint128\_t** **balance**
- uint8\_t **link** [32]
- uint8\_t **signature** [64]
- uint8\_t **prefixes**
- uint64\_t **work**
- uint8\_t **sub\_salt** [32]
- uint8\_t **iv** [16]
- uint8\_t **reserved** [16]
- uint8\_t **hash\_sk\_unencrypted** [32]
- uint8\_t **sk\_encrypted** [32]
- uint8\_t **nano\_hdr** [sizeof(NANO\_WALLET\_MAGIC)]
- uint32\_t **ver**
- uint8\_t **description** [F\_DESC\_SZ]
- uint8\_t **salt** [32]
- F\_ENCRYPTED\_BLOCK **seed\_block**
- uint8\_t **wallet\_prefix**
- uint32\_t **last\_used\_wallet\_number**
- char **wallet\_representative** [MAX\_STR\_NANO\_CHAR]
- char **max\_fee** [F\_RAW\_STR\_MAX\_SZ]
- uint8\_t **header** [sizeof(F\_NANO\_WALLET\_INFO\_MAGIC)]
- uint16\_t **version**
- char **desc** [F\_NANO\_DESC\_SZ]
- uint8\_t **nanoseed\_hash** [32]
- uint8\_t **file\_info\_integrity** [32]
- F\_NANO\_WALLET\_INFO\_BODY **body**

### 5.3.1 Detailed Description

This API Integrates Nano Cryptocurrency to low computational devices.

Definition in file **f\_nano\_crypto\_util.h**.

### 5.3.2 Macro Definition Documentation

#### 5.3.2.1 DEST\_XRB

```
#define DEST_XRB (uint8_t)0x01
```

Definition at line **415** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.2 F\_BRAIN\_WALLET\_BAD

```
#define F_BRAIN_WALLET_BAD (uint32_t)3
```

[bad].

Crack within one day

Definition at line **1013** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.3 F\_BRAIN\_WALLET\_GOOD

```
#define F_BRAIN_WALLET_GOOD (uint32_t)8
```

[good].

Crack within one thousand year

Definition at line **1044** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.4 F\_BRAIN\_WALLET\_MAYBE\_GOOD

```
#define F_BRAIN_WALLET_MAYBE_GOOD (uint32_t)7
```

[maybe good for you].

Crack within one century

Definition at line **1037** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.5 F\_BRAIN\_WALLET\_NICE

```
#define F_BRAIN_WALLET_NICE (uint32_t)10
```

[very nice].

Crack withing one hundred thousand year

Definition at line **1056** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.6 F\_BRAIN\_WALLET\_PERFECT

```
#define F_BRAIN_WALLET_PERFECT (uint32_t)11
```

[Perfect!]  $3.34 \times 10^{53}$  Years to crack

Definition at line **1062** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.7 F\_BRAIN\_WALLET\_POOR

```
#define F_BRAIN_WALLET_POOR (uint32_t)1
```

[poor].

Crack within minutes

Definition at line **1001** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.8 F\_BRAIN\_WALLET\_STILL\_WEAK

```
#define F_BRAIN_WALLET_STILL_WEAK (uint32_t)6
```

[still weak].

Crack within one year

Definition at line **1031** of file **f\_nano\_crypto\_util.h**.



#### 5.3.2.9 **F\_BRAIN\_WALLET\_VERY\_BAD**

```
#define F_BRAIN_WALLET_VERY_BAD (uint32_t)2
```

[very bad].

Crack within one hour

Definition at line **1007** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.10 **F\_BRAIN\_WALLET\_VERY\_GOOD**

```
#define F_BRAIN_WALLET_VERY_GOOD (uint32_t)9
```

[very good].

Crack within ten thousand year

Definition at line **1050** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.11 **F\_BRAIN\_WALLET\_VERY\_POOR**

```
#define F_BRAIN_WALLET_VERY_POOR (uint32_t)0
```

[very poor].

Crack within seconds or less

Definition at line **995** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.12 **F\_BRAIN\_WALLET\_VERY\_WEAK**

```
#define F_BRAIN_WALLET_VERY_WEAK (uint32_t)4
```

[very weak].

Crack within one week

Definition at line **1019** of file **f\_nano\_crypto\_util.h**.

### 5.3.2.13 F\_BRAIN\_WALLET\_WEAK

```
#define F_BRAIN_WALLET_WEAK (uint32_t)5
```

[weak].

Crack within one month

Definition at line **1025** of file **f\_nano\_crypto\_util.h**.

### 5.3.2.14 MAX\_STR\_NANO\_CHAR

```
#define MAX_STR_NANO_CHAR (size_t)70
```

Defines a max size of Nano char (70 bytes)

Definition at line **135** of file **f\_nano\_crypto\_util.h**.

### 5.3.2.15 NANO\_ENCRYPTED\_SEED\_FILE

```
#define NANO_ENCRYPTED_SEED_FILE "/spiffs/secure/nano.nse"
```

Path to non deterministic encrypted file with password.

File containing the SEED of the Nano wallets generated by TRNG (if available in your Hardware) or PRNG.  
Default name: "nano.nse"

Definition at line **178** of file **f\_nano\_crypto\_util.h**.

### 5.3.2.16 NANO\_FILE\_WALLETS\_INFO

```
#define NANO_FILE_WALLETS_INFO "/spiffs/secure/walletsinfo.i"
```

Custom information file path about Nano SEED wallet stored in "walletsinfo.i".

Definition at line **196** of file **f\_nano\_crypto\_util.h**.

### 5.3.2.17 NANO\_PASSWD\_MAX\_LEN

```
#define NANO_PASSWD_MAX_LEN (size_t)80
```

Password max length.

Definition at line **184** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.18 NANO\_PREFIX

```
#define NANO_PREFIX "nano_"
```

Nano prefix.

Definition at line **147** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.19 PUB\_KEY\_EXTENDED\_MAX\_LEN

```
#define PUB_KEY_EXTENDED_MAX_LEN (size_t)40
```

Max size of public key (extended)

Definition at line **141** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.20 REP\_XRB

```
#define REP_XRB (uint8_t)0x4
```

Representative XRB flag.

Destination XRB flag.

Sender XRB flag.

#### 5.3.2.21 SENDER\_XRB

```
#define SENDER_XRB (uint8_t)0x02
```

Definition at line **409** of file **f\_nano\_crypto\_util.h**.

#### 5.3.2.22 STR\_NANO\_SZ

```
#define STR_NANO_SZ (size_t)66
```

String size of Nano encoded Base32 including NULL char.

Definition at line **190** of file **f\_nano\_crypto\_util.h**.

### 5.3.2.23 XRB\_PREFIX

```
#define XRB_PREFIX "xrb_"
```

XRB (old Raiblocks) prefix.

Definition at line **153** of file **f\_nano\_crypto\_util.h**.

## 5.3.3 Typedef Documentation

### 5.3.3.1 F\_FILE\_INFO\_ERR

```
F_FILE_INFO_ERR
```

Typedef Error enumerator for info file functions.

### 5.3.3.2 f\_nano\_err

```
f_nano_err
```

Error function enumerator.

See also

**f\_nano\_err\_t** (p. ??)

### 5.3.3.3 f\_uint128\_t

```
f_uint128_t
```

128 bit big number of Nano balance

Definition at line **208** of file **f\_nano\_crypto\_util.h**.

### 5.3.3.4 f\_write\_seed\_err

```
typedef enum f_write_seed_err_t f_write_seed_err
```

#### 5.3.3.5 `NANO_PRIVATE_KEY`

`NANO_PRIVATE_KEY`

Size of Nano Private Key.

Definition at line **218** of file `f_nano_crypto_util.h`.

#### 5.3.3.6 `NANO_PRIVATE_KEY_EXTENDED`

`NANO_PRIVATE_KEY_EXTENDED`

Size of Nano Private Key extended.

Definition at line **224** of file `f_nano_crypto_util.h`.

#### 5.3.3.7 `NANO_PUBLIC_KEY`

`NANO_PUBLIC_KEY`

Size of Nano Public Key.

Definition at line **230** of file `f_nano_crypto_util.h`.

#### 5.3.3.8 `NANO_PUBLIC_KEY_EXTENDED`

`NANO_PUBLIC_KEY_EXTENDED`

Size of Public Key Extended.

Definition at line **236** of file `f_nano_crypto_util.h`.

#### 5.3.3.9 `NANO_SEED`

`NANO_SEED`

Size of Nano SEED.

Definition at line **202** of file `f_nano_crypto_util.h`.

### 5.3.4 Enumeration Type Documentation

#### 5.3.4.1 `f_file_info_err_t`

enum `f_file_info_err_t`

## Enumerator

F_FILE_INFO_ERR_OK	SUCCESS.
F_FILE_INFO_ERR_CANT_OPEN_INFO_FILE	Can't open info file.
F_FILE_INFO_ERR_NANO_SEED_ENCRYPTED_FILE_NOT_FOUND	Encrypted file with Nano SEED not found.
F_FILE_INFO_ERR_CANT_DELETE_NANO_INFO_FILE	Can not delete Nano info file.
F_FILE_INFO_ERR_MALLOC	Fatal Error MALLOC.
F_FILE_INFO_ERR_CANT_READ_NANO_SEED_ENCRYPTED_FILE	Can not read encrypted Nano SEED in file.
F_FILE_INFO_ERR_CANT_READ_INFO_FILE	Can not read info file.
F_FILE_INFO_INVALID_HEADER_FILE	Invalid info file header.
F_FILE_INFO_ERR_INVALID_SHA256_INFO_FILE	Invalid SHA256 info file.
F_FILE_INFO_ERR_NANO_SEED_HASH_FAIL	Nano SEED hash failed.
F_FILE_INFO_ERR_NANO_INVALID_REPRESENTATIVE	Invalid representative.
F_FILE_INFO_ERR_NANO_INVALID_MAX_FEE_VALUE	Invalid max fee value.
F_FILE_INFO_ERR_OPEN_FOR_WRITE_INFO	Can not open info file for write.
F_FILE_INFO_ERR_EXISTING_FILE	Error File Exists.
F_FILE_INFO_ERR_CANT_WRITE_FILE_INFO	Can not write info file.

Definition at line 521 of file **f\_nano\_crypto\_util.h**.

## 5.3.4.2 f\_nano\_err\_t

```
enum f_nano_err_t
```

## Enumerator

NANO_ERR_OK	SUCCESS.
NANO_ERR_CANT_PARSE_BN_STR	Can not parse string big number.
NANO_ERR_MALLOC	Fatal ERROR MALLOC.
NANO_ERR_CANT_PARSE_FACTOR	Can not parse big number factor.
NANO_ERR_MPI_MULT	Error multiplication MPI.
NANO_ERR_CANT_PARSE_TO_BLK_TRANSFER	Can not parse to block transfer.
NANO_ERR_EMPTY_STR	Error empty string.
NANO_ERR_CANT_PARSE_VALUE	Can not parse value.
NANO_ERR_PARSE_MPI_TO_STR	Can not parse MPI to string.
NANO_ERR_CANT_COMPLETE_NULL_CHAR	Can not complete NULL char.
NANO_ERR_CANT_PARSE_TO_MPI	Can not parse to MPI.
NANO_ERR_INSUFICIENT_FUNDS	Insuficient funds.
NANO_ERR_SUB_MPI	Error subtract MPI.
NANO_ERR_ADD_MPI	Error add MPI.
NANO_ERR_NO_SENSE_VALUE_TO_SEND_NEGATIVE	Does not make sense send negativative balance.
NANO_ERR_NO_SENSE_VALUE_TO_SEND_ZERO	Does not make sense send empty value.
NANO_ERR_NO_SENSE_BALANCE_NEGATIVE	Does not make sense negative balance.
NANO_ERR_VAL_A_INVALID_MODE	Invalid A mode value.
NANO_ERR_CANT_PARSE_TO_TEMP_UINT128_T	Can not parse temporary memory to uint_128_t.
NANO_ERR_VAL_B_INVALID_MODE	Invalid A mode value.

## Enumerator

NANO_ERR_CANT_PARSE_RAW_A_TO_MPI	Can not parse raw A value to MPI.
NANO_ERR_CANT_PARSE_RAW_B_TO_MPI	Can not parse raw B value to MPI.
NANO_ERR_UNKNOWN_ADD_SUB_MODE	Unknown ADD/SUB mode.
NANO_ERR_INVALID_RES_OUTPUT	Invalid output result.

Definition at line 280 of file `f_nano_crypto_util.h`.

## 5.3.4.3 f\_write\_seed\_err\_t

```
enum f_write_seed_err_t
```

## Enumerator

WRITE_ERR_OK	Error SUCCESS.
WRITE_ERR_NULL_PASSWORD	Error NULL password.
WRITE_ERR_EMPTY_STRING	Empty string.
WRITE_ERR_MALLOC	Error MALLOC.
WRITE_ERR_ENCRYPT_PRIV_KEY	Error encrypt private key.
WRITE_ERR_GEN_SUB_PRIV_KEY	Can not generate sub private key.
WRITE_ERR_GEN_MAIN_PRIV_KEY	Can not generate main private key.
WRITE_ERR_ENCRYPT_SUB_BLOCK	Can not encrypt sub block.
WRITE_ERR_UNKNOWN_OPTION	Unknown option.
WRITE_ERR_FILE_ALREADY_EXISTS	File already exists.
WRITE_ERR_CREATING_FILE	Can not create file.
WRITE_ERR_WRITING_FILE	Can not write file.

Definition at line 417 of file `f_nano_crypto_util.h`.

## 5.3.5 Function Documentation

## 5.3.5.1 \_\_attribute\_\_((packed))

```
struct f_nano_wallet_info_t __attribute__((packed)) {
```

#### 5.3.5.2 f\_bip39\_to\_nano\_seed()

```
int f_bip39_to_nano_seed (
    uint8_t * seed,
    char * str,
    char * dictionary )
```

Parse Nano Bip39 encoded string to raw Nano SEED given a dictionary file.



## Parameters

out	<i>seed</i>	Nano SEED
in	<i>str</i>	A encoded Bip39 string pointer
in	<i>dictionary</i>	A string pointer path to file

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

## Return values

0	On Success, otherwise Error
---	-----------------------------

## See also

**f\_nano\_seed\_to\_bip39()** (p. ??)

## 5.3.5.3 f\_cloud\_crypto\_wallet\_nano\_create\_seed()

```
int f_cloud_crypto_wallet_nano_create_seed (
    size_t entropy,
    char * file_name,
    char * password )
```

Generates a new SEED and saves it to an non deterministic encrypted file.

*password* is mandatory

## Parameters

in	<i>entropy</i>	Entropy type. Entropy type are:  F_ENTROPY_TYPE_PARANOIC F_ENTROPY_TYPE_EXCELENT F_ENTROPY_TYPE_GOOD F_ENTROPY_TYPE_NOT_ENOUGH F_ENTROPY_TYPE_NOT_RECOMENDED
in	<i>file_name</i>	The file and path to be stored in your file system directory. It can be <i>NULL</i> . If you parse a <i>NULL</i> value then file will be stored in <i>NANO_ENCRYPTED_SEED_FILE</i> variable file system pointer.
in	<i>password</i>	Password of the encrypted file. It can NOT be <i>NULL</i> or EMPTY

## WARNING

**f\_cloud\_crypto\_wallet\_nano\_create\_seed()** (p. ??) does not verify your password. It is recommended to use a strong password like symbols, capital letters and numbers to keep your SEED safe and avoid brute force attacks.

You can use **f\_pass\_must\_have\_at\_least()** (p. ??) function to check passwords strength

## Return values

0	On Success, otherwise Error
---	-----------------------------

## 5.3.5.4 f\_extract\_seed\_from\_brainwallet()

```
int f_extract_seed_from_brainwallet (
    uint8_t * seed,
    char ** warning_msg,
    uint32_t allow_mode,
    const char * brainwallet,
    const char * salt )
```

Analyzes a text given a *mode* and if pass then the text in *brainwallet* is translated to a Nano SEED.

## Parameters

out	<i>seed</i>	Output Nano SEED extracted from <i>brainwallet</i>
out	<i>warning_msg</i>	Warning message parsed to application. It can be NULL
in	<i>allow_mode</i>	<p>Allow <i>mode</i>. Funtion will return SUCCESS only if permitted mode set by user</p> <p>Allow mode are:</p> <ul style="list-style-type: none"> <li>• <i>F_BRAIN_WALLET_VERY_POOR</i> Crack within seconds or less</li> <li>• <i>F_BRAIN_WALLET_POOR</i> Crack within minutes</li> <li>• <i>F_BRAIN_WALLET_VERY_BAD</i> Crack within one hour</li> <li>• <i>F_BRAIN_WALLET_BAD</i> Crack within one day</li> <li>• <i>F_BRAIN_WALLET_VERY_WEAK</i> Crack within one week</li> <li>• <i>F_BRAIN_WALLET_WEAK</i> Crack within one month</li> <li>• <i>F_BRAIN_WALLET_STILL_WEAK</i> Crack within one year</li> <li>• <i>F_BRAIN_WALLET_MAYBE_GOOD</i> Crack within one century</li> <li>• <i>F_BRAIN_WALLET_GOOD</i> Crack within one thousand year</li> <li>• <i>F_BRAIN_WALLET_VERY_GOOD</i> Crack within ten thousand year</li> <li>• <i>F_BRAIN_WALLET_NICE</i> Crack withing one hundred thousand year</li> <li>• <i>F_BRAIN_WALLET_PERFECT</i> 3.34x10<sup>53</sup> Years to crack</li> </ul>
in	<i>brainwallet</i>	Brainwallet text to be parsed. It can be NOT NULL or null string
in	<i>salt</i>	Salt of the Braiwallet. It can be NOT NULL or null string

## Return values

0	If success, otherwise error.
---	------------------------------

See also

**f\_bip39\_to\_nano\_seed()** (p. ??)

#### 5.3.5.5 f\_generate\_nano\_seed()

```
int f_generate_nano_seed (
    NANO_SEED seed,
    uint32_t entropy )
```

Generates a new SEED and stores it to *seed* pointer.

##### Parameters

out	<i>seed</i>	SEED generated in system PRNG or TRNG
in	<i>entropy</i>	Entropy type. Entropy type are:  F_ENTROPY_TYPE_PARANOIC F_ENTROPY_TYPE_EXCELENT F_ENTROPY_TYPE_GOOD F_ENTROPY_TYPE_NOT_ENOUGH F_ENTROPY_TYPE_NOT_RECOMENDED

##### Return values

0	On Success, otherwise Error
---	-----------------------------

#### 5.3.5.6 f\_get\_nano\_file\_info()

```
F_FILE_INFO_ERR f_get_nano_file_info (
    F_NANO_WALLET_INFO * info )
```

Opens default file *walletsinfo.i* (if exists) containing information *F\_NANO\_WALLET\_INFO* structure and parsing to pointer *info* if success.

##### Parameters

out	<i>info</i>	Pointer to buffer to be parsed struct from <i>\$PATH/walletsinfo.i</i> file.
-----	-------------	--

##### Return values

F_FILE_INFO_ERR_OK	If Success, otherwise <i>F_FILE_INFO_ERR</i> enum type error
--------------------	--

See also

**F\_FILE\_INFO\_ERR** (p. ??) enum type error for detailed error and **f\_nano\_wallet\_info\_t** (p. ??) for info type details

#### 5.3.5.7 f\_nano\_add\_sub()

```
f_nano_err f_nano_add_sub (
    void * res,
    void * valA,
    void * valB,
    uint32_t mode )
```

Add/Subtract two Nano balance values and stores value in *res*

##### Parameters

out	<i>res</i>	Result value $res = valA + valB$ or $res = valA - valB$
in	<i>valA</i>	Input balance A value
in	<i>valB</i>	Input balance B value
in	<i>mode</i>	Mode type: <ul style="list-style-type: none"> <li>• <i>F_NANO_ADD_A_B</i> <math>valA + valB</math></li> <li>• <i>F_NANO_SUB_A_B</i> <math>valA - valB</math></li> <li>• <i>F_NANO_RES_RAW_128</i> Output is a raw data 128 bit big number result</li> <li>• <i>F_NANO_RES_RAW_STRING</i> Output is a 128 bit Big Integer string</li> <li>• <i>F_NANO_RES_REAL_STRING</i> Output is a Real string value</li> <li>• <i>F_NANO_A_RAW_128</i> if <i>balance</i> is big number raw buffer type</li> <li>• <i>F_NANO_A_RAW_STRING</i> if <i>balance</i> is big number raw string type</li> <li>• <i>F_NANO_A_REAL_STRING</i> if <i>balance</i> is real number string type</li> <li>• <i>F_NANO_B_RAW_128</i> if <i>value_to_send</i> is big number raw buffer type</li> <li>• <i>F_NANO_B_RAW_STRING</i> if <i>value_to_send</i> is big number raw string type</li> <li>• <i>F_NANO_B_REAL_STRING</i> if <i>value_to_send</i> is real number string type</li> </ul>

##### Return values

<i>NANO_ERR_OK</i>	If Success, otherwise <b>f_nano_err_t</b> enum type error
--------------------	---

See also

**f\_nano\_err\_t** (p. ??) for **f\_nano\_err** (p. ??) enum error type

## 5.3.5.8 f\_nano\_balance\_to\_str()

```
f_nano_err f_nano_balance_to_str (
    char * str,
    size_t str_len,
    size_t * out_len,
    f_uint128_t value )
```

Converts a raw Nano balance to string raw balance.

## Parameters

out	<i>str</i>	Output string pointer
in	<i>str_len</i>	Size of string pointer memory
out	<i>out_len</i>	Output length of converted value to string. If <i>out_len</i> is NULL then <i>str</i> returns converted value with NULL terminated string
in	<i>value</i>	Raw Nano balance value

## Return values

0	If success, otherwise error.
---	------------------------------

## See also

function **f\_nano\_parse\_raw\_str\_to\_raw128\_t()** (p. ??) and return errors **f\_nano\_err** (p. ??)

## 5.3.5.9 f\_nano\_key\_to\_str()

```
char * f_nano_key_to_str (
    char * out,
    unsigned char * key )
```

Parse a raw binary public key to string.

## Parameters

out	<i>out</i>	Pointer to outuput string
in	<i>in</i>	Pointer to raw public key

## Returns

A pointer to output string

5.3.5.10 `f_nano_parse_raw_str_to_raw128_t()`

```
f_nano_err f_nano_parse_raw_str_to_raw128_t (
    uint8_t * res,
    const char * raw_str_value )
```

Parse a raw string balance to raw big number 128 bit.

## Parameters

out	<i>res</i>	Binary raw balance
in	<i>raw_str_value</i>	Raw balance string

## Return values

<i>NANO_ERR_OK</i>	If Success, otherwise <code>f_nano_err_t</code> enum type error
--------------------	---

## See also

`f_nano_err_t` (p. ??) for `f_nano_err` (p. ??) enum error type

5.3.5.11 `f_nano_parse_real_str_to_raw128_t()`

```
f_nano_err f_nano_parse_real_str_to_raw128_t (
    uint8_t * res,
    const char * real_str_value )
```

Parse a real string balance to raw big number 128 bit.

## Parameters

out	<i>res</i>	Binary raw balance
in	<i>real_str_value</i>	Real balance string

## Return values

<i>NANO_ERR_OK</i>	If Success, otherwise <code>f_nano_err_t</code> enum type error
--------------------	---

## See also

`f_nano_err_t` (p. ??) for `f_nano_err` (p. ??) enum error type

## 5.3.5.12 f\_nano\_raw\_to\_string()

```
int f_nano_raw_to_string (
    char * str,
    size_t * olen,
    size_t str_sz,
    void * raw,
    int raw_type )
```

Converts Nano raw balance [string | f\_uint128\_t] to real string value.

## Parameters

out	<i>str</i>	Output real string value
out	<i>olen</i>	Size of output real string value. It can be NULL. If NULL output <i>str</i> will have a NULL char at the end.
in	<i>str_sz</i>	Size of <i>str</i> buffer
in	<i>raw</i>	Raw balance.
in	<i>raw_type</i>	Raw balance type: <ul style="list-style-type: none"> <li>• F_RAW_TO_STR_UINT128 for raw <b>f_uint128_t</b> balance</li> <li>• F_RAW_TO_STR_STRING for raw <b>char</b> balance</li> </ul>

## Return values

0	On Success, otherwise Error
---	-----------------------------

## See also

**f\_nano\_valid\_nano\_str\_value()** (p. ??)

## 5.3.5.13 f\_nano\_seed\_to\_bip39()

```
int f_nano_seed_to_bip39 (
    char * buf,
    size_t buf_sz,
    size_t * out_buf_len,
    NANO_SEED seed,
    char * dictionary_file )
```

Parse Nano SEED to Bip39 encoding given a dictionary file.

## Parameters

out	<i>buf</i>	Output string containing encoded Bip39 SEED
in	<i>buf_sz</i>	Size of memory of buf pointer
out	<i>out_buf_len</i>	If <i>out_buf_len</i> is NOT NULL then <i>out_buf_len</i> returns the size of string encoded Bip39 and <i>out</i> with non NULL char. If <i>out_buf_len</i> is NULL then <i>out</i> has a string encoded Bip39 with a NULL char.
in	<i>seed</i>	Nano SEED
Generated by Doxygen in	<i>dictionary_file</i>	Path to dictionary file

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

#### Return values

0	On Success, otherwise Error
---	-----------------------------

#### See also

**f\_bip39\_to\_nano\_seed()** (p. ??)

#### 5.3.5.14 f\_nano\_sign\_block()

```
int f_nano_sign_block (
    F_BLOCK_TRANSFER * user_block,
    F_BLOCK_TRANSFER * fee_block,
    NANO_PRIVATE_KEY_EXTENDED private_key )
```

Signs *user\_block* and worker *fee\_block* given a private key *private\_key*

#### Parameters

in, out	<i>user_block</i>	User block to be signed with a private key <i>private_key</i>
in, out	<i>fee_block</i>	Fee block to be signed with a private key <i>private_key</i> . Can be NULL if worker does not require fee
in	<i>private_key</i>	Private key to sign block(s)

#### Return values

0	If Success, otherwise error
---	-----------------------------

#### See also

**f\_nano\_transaction\_to\_JSON()** (p. ??)

#### 5.3.5.15 f\_nano\_transaction\_to\_JSON()

```
int f_nano_transaction_to_JSON (
    char * str,
    size_t str_len,
    size_t * str_out,
    NANO_PRIVATE_KEY_EXTENDED private_key,
    F_BLOCK_TRANSFER * block_transfer )
```

Sign a block pointed in *block\_transfer* with a given *private\_key* and stores signed block to *block\_transfer* and parse to JSON Nano RPC.



## Parameters

out	<i>str</i>	A string pointer to store JSON Nano RPC
in	<i>str_len</i>	Size of buffer in <i>str</i> pointer
out	<i>str_out</i>	Size of JSON string. <i>str_out</i> can be NULL
in	<i>private_key</i>	Private key to sign the block <i>block_transfer</i>
in, out	<i>block_transfer</i>	Nano block containing raw data to be stored in Nano Blockchain

WARNING Sensitive data. Do not share any PRIVATE KEY

## Return values

0	On Success, otherwise Error
---	-----------------------------

## 5.3.5.16 f\_nano\_valid\_nano\_str\_value()

```
int f_nano_valid_nano_str_value (
    const char * str )
```

Check if a real string or raw string are valid Nano balance.

## Parameters

in	<i>str</i>	Value to be checked
----	------------	---------------------

## Return values

0	If valid, otherwise is invalid
---	--------------------------------

## See also

**f\_nano\_raw\_to\_string()** (p. ??)

## 5.3.5.17 f\_nano\_value\_compare\_value()

```
f_nano_err f_nano_value_compare_value (
    void * valA,
    void * valB,
    uint32_t * mode_compare )
```

Compare two Nano balance.

## Parameters

in	<i>valA</i>	Nano balance value A
in	<i>valB</i>	Nano balance value B
in, out	<i>mode_compare</i>	<p>Input mode and output result</p> <p>Input mode:</p> <ul style="list-style-type: none"> <li>• <i>F_NANO_A_RAW_128</i> if <i>valA</i> is big number raw buffer type</li> <li>• <i>F_NANO_A_RAW_STRING</i> if <i>valA</i> is big number raw string type</li> <li>• <i>F_NANO_A_REAL_STRING</i> if <i>valA</i> is real number string type</li> <li>• <i>F_NANO_B_RAW_128</i> if <i>valB</i> is big number raw buffer type</li> <li>• <i>F_NANO_B_RAW_STRING</i> if <i>valB</i> is big number raw string type</li> <li>• <i>F_NANO_B_REAL_STRING</i> if <i>valB</i> is real number string type</li> </ul> <p>Output type:</p> <ul style="list-style-type: none"> <li>• <i>F_NANO_COMPARE_EQ</i> If <i>valA</i> is greater than <i>valB</i></li> <li>• <i>F_NANO_COMPARE_LT</i> if <i>valA</i> is lesser than <i>valB</i></li> <li>• <i>F_NANO_COMPARE_LEQ</i> if <i>valA</i> is lesser or equal than <i>valB</i></li> <li>• <i>F_NANO_COMPARE_GT</i> if <i>valA</i> is greater than <i>valB</i></li> <li>• <i>F_NANO_COMPARE_GEQ</i> If <i>valA</i> is greater or equal than <i>valB</i></li> </ul>

## Return values

<i>NANO_ERR_OK</i>	If Success, otherwise <i>f_nano_err_t</i> enum type error
--------------------	---

## See also

**f\_nano\_err\_t** (p. ??) for **f\_nano\_err** (p. ??) enum error type

## 5.3.5.18 f\_nano\_verify\_nano\_funds()

```
f_nano_err f_nano_verify_nano_funds (
    void * balance,
    void * value_to_send,
    void * fee,
    uint32_t mode )
```

Check if Nano balance has sufficient funds.

## Parameters

in	<i>balance</i>	Nano balance
in	<i>value_to_send</i>	Value to send

## Parameters

in	<i>fee</i>	Fee value (it can be NULL)
in	<i>mode</i>	Value type mode <ul style="list-style-type: none"> <li>• <i>F_NANO_A_RAW_128</i> if <i>balance</i> is big number raw buffer type</li> <li>• <i>F_NANO_A_RAW_STRING</i> if <i>balance</i> is big number raw string type</li> <li>• <i>F_NANO_A_REAL_STRING</i> if <i>balance</i> is real number string type</li> <li>• <i>F_NANO_B_RAW_128</i> if <i>value_to_send</i> is big number raw buffer type</li> <li>• <i>F_NANO_B_RAW_STRING</i> if <i>value_to_send</i> is big number raw string type</li> <li>• <i>F_NANO_B_REAL_STRING</i> if <i>value_to_send</i> is real number string type</li> <li>• <i>F_NANO_C_RAW_128</i> if <i>fee</i> is big number raw buffer type (can be omitted if <i>fee</i> is NULL)</li> <li>• <i>F_NANO_C_RAW_STRING</i> if <i>fee</i> is big number raw string type (can be omitted if <i>fee</i> is NULL)</li> <li>• <i>F_NANO_C_REAL_STRING</i> if <i>fee</i> is real number string type (can be omitted if <i>fee</i> is NULL)</li> </ul>

## Return values

<i>NANO_ERR_OK</i>	If Success, otherwise f_nano_err_t enum type error
--------------------	--

## See also

**f\_nano\_err\_t** (p. ??) for **f\_nano\_err** (p. ??) enum error type

## 5.3.5.19 f\_parse\_nano\_seed\_and\_bip39\_to\_JSON()

```
int f_parse_nano_seed_and_bip39_to_JSON (
    char * dest,
    size_t dest_sz,
    size_t * olen,
    void * source_data,
    int source,
    const char * password )
```

Parse Nano SEED and Bip39 to JSON given a encrypted data in memory or encrypted data in file or unencrypted seed in memory.

## Parameters

out	<i>dest</i>	Destination JSON string pointer
in	<i>dest_sz</i>	Buffer size of <i>dest</i> pointer
out	<i>olen</i>	Size of the output JSON string. If NULL string JSON returns a NULL char at the end of string otherwise it will return the size of the string is stored into <i>olen</i> variable without NULL string in <i>dest</i>

## Parameters

in	<i>source_data</i>	Input data source (encrypted file   encrypted data in memory   unencrypted seed in memory)
in	<i>source</i>	Source data type: <ul style="list-style-type: none"> <li>• PARSE_JSON_READ_SEED_GENERIC: If seed are in memory pointed in <i>source_data</i>. Password is ignored. Can be NULL.</li> <li>• READ_SEED_FROM_STREAM: Read encrypted data from stream pointed in <i>source_data</i>. Password is required.</li> <li>• READ_SEED_FROM_FILE: Read encrypted data stored in a file where <i>source_data</i> is path to file. Password is required.</li> </ul>
in	<i>password</i>	Required for READ_SEED_FROM_STREAM and READ_SEED_FROM_FILE sources

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

## Return values

0	On Success, otherwise Error
---	-----------------------------

## See also

**f\_read\_seed()** (p. ??)

## 5.3.5.20 f\_read\_seed()

```
int f_read_seed (
    uint8_t * seed,
    const char * passwd,
    void * source_data,
    int force_read,
    int source )
```

Extracts a Nano SEED from encrypted stream in memory or in a file.

## Parameters

out	<i>seed</i>	Output Nano SEED
in	<i>passwd</i>	Password (always required)
in	<i>source_data</i>	Encrypted source data from memory or path pointed in <i>source_data</i>
in	<i>force_read</i>	If non zero value then forces reading from a corrupted file. This param is ignored when reading <i>source_data</i> from memory
in	<i>source</i>	Source data type: <ul style="list-style-type: none"> <li>• READ_SEED_FROM_STREAM: Read encrypted data from stream pointed in <i>source_data</i>. Password is required.</li> <li>• READ_SEED_FROM_FILE: Read encrypted data stored in a file where <i>source_data</i> is path to file. Password is required.</li> </ul>
		Generated by Doxygen

WARNING Sensitive data. Do not share any SEED !

#### Return values

0	On Success, otherwise Error
---	-----------------------------

See also

**f\_parse\_nano\_seed\_and\_bip39\_to\_JSON()** (p. ??) **f\_write\_seed()** (p. ??)

#### 5.3.5.21 f\_seed\_to\_nano\_wallet()

```
int f_seed_to_nano_wallet (
    NANO_PRIVATE_KEY private_key,
    NANO_PUBLIC_KEY public_key,
    NANO_SEED seed,
    uint32_t wallet_number )
```

Extracts one key pair from Nano SEED given a wallet number.

#### Parameters

out	<i>private_key</i>	Private key of the <i>wallet_number</i> from given <i>seed</i>
out	<i>public_key</i>	Public key of the <i>wallet_number</i> from given <i>seed</i>
in, out	<i>seed</i>	Nano SEED
in	<i>wallet_number</i>	Wallet number of key pair to be extracted from Nano SEED

WARNING 1:

- Seed must be read from memory
- Seed is destroyed when extracting public and private keys

WARNING 2:

- Never expose SEED and private key. This function destroys seed and any data after execution and finally parse public and private keys to output.

#### Return values

0	On Success, otherwise Error
---	-----------------------------

5.3.5.22 `f_set_nano_file_info()`

```
F_FILE_INFO_ERR f_set_nano_file_info (
    F_NANO_WALLET_INFO * info,
    int overwrite_existing_file )
```

Saves wallet information stored at buffer struct *info* to file *walletsinfo.i*

## Parameters

in	<i>info</i>	Pointer to data to be saved at <i>\$PATH/walletsinfo.i</i> file.
in	<i>overwrite_existing_file</i>	If non zero then overwrites file <i>\$PATH/walletsinfo.i</i>

## Return values

<i>F_FILE_INFO_ERR_OK</i>	If Success, otherwise <i>F_FILE_INFO_ERR</i> enum type error
---------------------------	--

## See also

**F\_FILE\_INFO\_ERR** (p. ??) enum type error for detailed error and **f\_nano\_wallet\_info\_t** (p. ??) for info type details

5.3.5.23 `f_write_seed()`

```
f_write_seed_err f_write_seed (
    void * source_data,
    int source,
    uint8_t * seed,
    char * passwd )
```

Writes a SEED into a encrypted with password with non deterministic stream in memory or file.

## Parameters

out	<i>source_data</i>	Memory pointer or file name
in	<i>source</i>	Source of output data: <ul style="list-style-type: none"> <li>• <i>WRITE_SEED_TO_STREAM</i> Output data is a pointer to memory to store encrypted Nano SEED data</li> <li>• <i>WRITE_SEED_TO_FILE</i> Output is a string filename to store encrypted Nano SEED data</li> </ul>
in	<i>seed</i>	Nano SEED to be stored in encrypted stream or file
in	<i>passwd</i>	(Mandatory) It can not be null string or NULL. See <b>f_pass_must_have_at_least()</b> (p. ??) function to check passwords strength

## Return values

0	If Success, otherwise error
---	-----------------------------

See also

**f\_read\_seed()** (p. ??)

#### 5.3.5.24 is\_nano\_prefix()

```
int is_nano_prefix (
    const char * nano_wallet,
    const char * prefix )
```

Checks *prefix* in *nano\_wallet*

##### Parameters

in	<i>nano_wallet</i>	Base32 Nano wallet encoded string
in	<i>prefix</i>	Prefix type <ul style="list-style-type: none"> <li>• NANO_PREFIX for nano_</li> <li>• XRB_PREFIX for xrb_</li> </ul>

##### Return values

1	If <i>prefix</i> in <i>nano_wallet</i> , otherwise 0
---	--

#### 5.3.5.25 is\_null\_hash()

```
int is_null_hash (
    uint8_t * hash )
```

Check if 32 bytes hash is filled with zeroes.

##### Parameters

in	<i>hash</i>	32 bytes binary <i>hash</i>
----	-------------	-----------------------------

##### Return values

1	If zero filled buffer, otherwise 0
---	------------------------------------

#### 5.3.5.26 nano\_base\_32\_2\_hex()

```
int nano_base_32_2_hex (
```

```
uint8_t * res,
char * str_wallet )
```

Parse Nano Base32 wallet string to public key binary.

#### Parameters

out	<i>res</i>	Output raw binary public key
in	<i>str_wallet</i>	Valid Base32 encoded Nano string to be parsed

#### Return values

0	On Success, otherwise Error
---	-----------------------------

#### See also

**pk\_to\_wallet()** (p. ??)

#### 5.3.5.27 pk\_to\_wallet()

```
int pk_to_wallet (
    char * out,
    char * prefix,
    NANO_PUBLIC_KEY_EXTENDED pubkey_extended )
```

Parse a Nano public key to Base32 Nano wallet string.

#### Parameters

out	<i>out</i>	Output string containing the wallet
in	<i>prefix</i>	Nano prefix.  <i>NANO_PREFIX</i> for nano_ <i>XRB_PREFIX</i> for xrb_
in, out	<i>pubkey_extended</i>	Public key to be parsed to string

WARNING: *pubkey\_extended* is destroyed when parsing to Nano base32 encoding

#### Return values

0	On Success, otherwise Error
---	-----------------------------

#### See also

**nano\_base\_32\_2\_hex()** (p. ??)



#### 5.3.5.28 valid\_nano\_wallet()

```
int valid_nano_wallet (
    const char * wallet )
```

Check if a string containing a Base32 Nano wallet is valid.

##### Parameters

in	<i>wallet</i>	Base32 Nano wallet encoded string
----	---------------	-----------------------------------

##### Return values

0	If valid wallet otherwise is invalid
---	--------------------------------------

#### 5.3.5.29 valid\_raw\_balance()

```
int valid_raw_balance (
    const char * balance )
```

Checks if a string buffer pointed in *balance* is a valid raw balance.

##### Parameters

in	<i>balance</i>	Pointer containing a string buffer
----	----------------	------------------------------------

##### Return values

0	On Success, otherwise Error
---	-----------------------------

### 5.3.6 Variable Documentation

#### 5.3.6.1 account

```
uint8_t account[32]
```

Account in raw binary data.

Definition at line **240** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.2 balance

```
f_uint128_t balance
```

Big number 128 bit raw balance.

See also

`f_uint128_t` (p. ??)

Definition at line **248** of file `f_nano_crypto_util.h`.

#### 5.3.6.3 body

```
F_NANO_WALLET_INFO_BODY body
```

Body of the file info.

Definition at line **248** of file `f_nano_crypto_util.h`.

#### 5.3.6.4 desc

```
char desc[F_NANO_DESC_SZ]
```

Description.

Definition at line **242** of file `f_nano_crypto_util.h`.

#### 5.3.6.5 description

```
uint8_t description[F_DESC_SZ]
```

File description.

Definition at line **242** of file `f_nano_crypto_util.h`.

#### 5.3.6.6 file\_info\_integrity

```
uint8_t file_info_integrity[32]
```

File info integrity of the body block.

Definition at line **246** of file `f_nano_crypto_util.h`.

#### 5.3.6.7 hash\_sk\_unencrypted

```
uint8_t hash_sk_unencrypted[32]
```

hash of Nano SEED when unencrypted

Definition at line **244** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.8 header

```
uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)]
```

Header magic.

Definition at line **238** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.9 iv

```
uint8_t iv
```

Initial sub vector.

Initial vector of first encryption layer.

Definition at line **240** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.10 last\_used\_wallet\_number

```
uint32_t last_used_wallet_number
```

Last used wallet number.

Definition at line **240** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.11 link

```
uint8_t link[32]
```

link or destination account

Definition at line **250** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.12 max\_fee

```
char max_fee[F_RAW_STR_MAX_SZ]
```

Custom preferred max fee of Proof of Work.

Definition at line **244** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.13 nano\_hdr

```
uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)]
```

Header of the file.

Definition at line **238** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.14 nanoseed\_hash

```
uint8_t nanoseed_hash[32]
```

Nano SEED hash file.

Definition at line **244** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.15 preamble

```
uint8_t preamble[32]
```

Block preamble.

Definition at line **238** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.16 prefixes

```
uint8_t prefixes
```

Internal use for this API.

Definition at line **254** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.17 previous

```
uint8_t previous[32]
```

Previous block.

Definition at line 242 of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.18 representative

```
uint8_t representative[32]
```

Representative for current account.

Definition at line 244 of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.19 reserved

```
uint8_t reserved
```

Reserved (not used)

Reserved.

Definition at line 242 of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.20 salt

```
uint8_t salt[32]
```

Salt of the first encryption layer.

Definition at line 244 of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.21 seed\_block

```
F_ENCRYPTED_BLOCK seed_block
```

Second encrypted block for Nano SEED.

Definition at line 248 of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.22 signature

```
uint8_t signature[64]
```

Signature of the block.

Definition at line **252** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.23 sk\_encrypted

```
uint8_t sk_encrypted[32]
```

Secret.

SEED encrypted (second layer)

Definition at line **246** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.24 sub\_salt

```
uint8_t sub_salt[32]
```

Salt of the sub block to be stored.

Definition at line **238** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.25 ver

```
uint32_t ver
```

Version of the file.

Definition at line **240** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.26 version

```
uint16_t version
```

Version.

Definition at line **240** of file **f\_nano\_crypto\_util.h**.

#### 5.3.6.27 wallet\_prefix

```
uint8_t wallet_prefix
```

Wallet prefix: 0 for NANO; 1 for XRB.

Definition at line 238 of file `f_nano_crypto_util.h`.

#### 5.3.6.28 wallet\_representative

```
char wallet_representative[ MAX_STR_NANO_CHAR]
```

Wallet representative.

Definition at line 242 of file `f_nano_crypto_util.h`.

#### 5.3.6.29 work

```
uint64_t work
```

Internal use for this API.

Definition at line 256 of file `f_nano_crypto_util.h`.

## 5.4 f\_nano\_crypto\_util.h

```
00001 /*
00002     AUTHOR: Fábio Pereira da Silva
00003     YEAR: 2019-20
00004     LICENSE: MIT
00005     EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006 */
00007
00008 #include <stdint.h>
00009 #include "f_util.h"
00010
00011 #ifndef F_DOC_SKIP
00012     #ifdef F_XTensa
00013         #ifndef F_ESP32
00014             #define F_ESP32
00015         #endif
00016     #endif
00017     #include "esp_system.h"
00018 #endif
00019
00020 #endif
00021
00022 #include "sodium/crypto_generichash.h"
00023 #include "sodium/crypto_sign.h"
00024 #include "sodium.h"
00025
00026 #ifdef F_ESP32
00027     #include "sodium/private/curve25519_ref10.h"
00028 #else
00029     #include "sodium/private/ed25519_ref10.h"
00030 #endif
```

```

00034
00035     #define ge_p3 ge25519_p3
00036     #define sc_reduce sc25519_reduce
00037     #define sc_muladd sc25519_muladd
00038     #define ge_scalarmult_base ge25519_scalarmult_base
00039     #define ge_p3_tobytes ge25519_p3_tobytes
00040
00041     #endif
00042
00043 #endif
00044
00127 #ifdef __cplusplus
00128 extern "C" {
00129 #endif
00130
00135 #define MAX_STR_NANO_CHAR (size_t)70 //5+56+8+1
00136
00141 #define PUB_KEY_EXTENDED_MAX_LEN (size_t)40
00142
00147 #define NANO_PREFIX "nano_"
00148
00153 #define XRB_PREFIX "xrb_"
00154
00155 #ifdef F_ESP32
00156
00161 #define BIP39_DICTIONARY "/spiffs/dictionary.dic"
00162 #else
00163
00164     #ifndef F_DOC_SKIP
00165         // #define BIP39_DICTIONARY "/spiffs/dictionary.dic"
00166         #define BIP39_DICTIONARY_SAMPLE "../../dictionary.dic"
00167         #define BIP39_DICTIONARY "dictionary.dic"
00168     #endif
00169
00170 #endif
00171
00178 #define NANO_ENCRYPTED_SEED_FILE "/spiffs/secure/nano.nse"
00179
00184 #define NANO_PASSWD_MAX_LEN (size_t)80
00185
00190 #define STR_NANO_SZ (size_t)66// 65+1 Null included
00191
00196 #define NANO_FILE_WALLETS_INFO "/spiffs/secure/walletsinfo.i"
00197
00202 typedef uint8_t NANO_SEED[crypto_sign_SEEDBYTES];
00203
00208 typedef uint8_t f_uint128_t[16];
00209
00210 #ifndef F_DOC_SKIP
00211     #define EXPORT_KEY_TO_CHAR_SZ (size_t)sizeof(NANO_SEED)+1
00212 #endif
00213
00218 typedef uint8_t NANO_PRIVATE_KEY[sizeof(NANO_SEED)];
00219
00224 typedef uint8_t NANO_PRIVATE_KEY_EXTENDED[crypto_sign_ed25519_SECRETKEYBYTES];
00225
00230 typedef uint8_t NANO_PUBLIC_KEY[crypto_sign_ed25519_PUBLICKEYBYTES];
00231
00236 typedef uint8_t NANO_PUBLIC_KEY_EXTENDED[PUB_KEY_EXTENDED_MAX_LEN];
00237
00246 typedef struct f_block_transfer_t {
00248     uint8_t preamble[32];
00250     uint8_t account[32];
00252     uint8_t previous[32];
00254     uint8_t representative[32];
00258     f_uint128_t balance;
00260     uint8_t link[32];
00262     uint8_t signature[64];
00264     uint8_t prefixes;
00266     uint64_t work;
00267 } __attribute__((packed)) F_BLOCK_TRANSFER;
00268
00269 #ifndef F_DOC_SKIP
00270     #define F_BLOCK_TRANSFER_SIGNABLE_SZ
00271     (size_t)(sizeof(F_BLOCK_TRANSFER)-64-sizeof(uint64_t)-sizeof(uint8_t))
00272 #endif
00273
00280 typedef enum f_nano_err_t {
00282     NANO_ERR_OK=0,
00284     NANO_ERR_CANT_PARSE_BN_STR=5151,
00286     NANO_ERR_MALLOC,
00288     NANO_ERR_CANT_PARSE_FACTOR,
00290     NANO_ERR_MPI_MULT,
00292     NANO_ERR_CANT_PARSE_TO_BLK_TRANSFER,
00294     NANO_ERR_EMPTY_STR,
00296     NANO_ERR_CANT_PARSE_VALUE,
00298     NANO_ERR_PARSE_MPI_TO_STR,

```



```

00300     NANO_ERR_CANT_COMPLETE_NULL_CHAR,
00302     NANO_ERR_CANT_PARSE_TO_MPI,
00304     NANO_ERR_INSUFFICIENT_FUNDS,
00306     NANO_ERR_SUB_MPI,
00308     NANO_ERR_ADD_MPI,
00310     NANO_ERR_NO_SENSE_VALUE_TO_SEND_NEGATIVE,
00312     NANO_ERR_NO_SENSE_VALUE_TO_SEND_ZERO,
00314     NANO_ERR_NO_SENSE_BALANCE_NEGATIVE,
00316     NANO_ERR_VAL_A_INVALID_MODE,
00318     NANO_ERR_CANT_PARSE_TO_TEMP_UINT128_T,
00320     NANO_ERR_VAL_B_INVALID_MODE,
00322     NANO_ERR_CANT_PARSE_RAW_A_TO_MPI,
00324     NANO_ERR_CANT_PARSE_RAW_B_TO_MPI,
00326     NANO_ERR_UNKNOWN_ADD_SUB_MODE,
00328     NANO_ERR_INVALID_RES_OUTPUT
00329 } f_nano_err;
00330
00331 #ifndef F_DOC_SKIP
00332
00333 #define READ_SEED_FROM_STREAM (int)1
00334 #define READ_SEED_FROM_FILE (int)2
00335 #define WRITE_SEED_TO_STREAM (int)4
00336 #define WRITE_SEED_TO_FILE (int)8
00337 #define PARSE_JSON_READ_SEED_GENERIC (int)16
00338 #define F_STREAM_DATA_FILE_VERSION (uint32_t) ((1<<16)|0)
00339
00340 #endif
00341
00342 typedef struct f_nano_encrypted_wallet_t {
00351     uint8_t sub_salt[32];
00353     uint8_t iv[16];
00355     uint8_t reserved[16];
00357     uint8_t hash_sk_unencrypted[32];
00359     uint8_t sk_encrypted[32];
00360 } __attribute__((packed)) F_ENCRYPTED_BLOCK;
00361
00362 #ifndef F_DOC_SKIP
00363
00364 static const uint8_t NANO_WALLET_MAGIC[] = {'_', 'n', 'a', 'n', 'o', 'w', 'a', 'l', 'l', 'e', 't', 'f',
'i', 'l', 'e', '_'};
00365 #define F_NANO_FILE_DESC "NANO Seed Encrypted file/stream. Keep it safe and backup it. This file is
protected by password. BUY BITCOIN and NANO !!!"
00366 #define F_DESC_SZ (size_t) (160-sizeof(uint32_t))
00367
00368 #endif
00369
00370 typedef struct f_nano_crypto_wallet_t {
00379     uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)];
00381     uint32_t ver;
00383     uint8_t description[F_DESC_SZ];
00385     uint8_t salt[32];
00387     uint8_t iv[16];
00389     F_ENCRYPTED_BLOCK seed_block;
00390 } __attribute__((packed)) F_NANO_CRYPTOWALLET;
00391
00392 #ifndef F_DOC_SKIP
00393
00394 _Static_assert((sizeof(F_NANO_CRYPTOWALLET)&0x1F)==0, "Error 1");
00395 _Static_assert((sizeof(F_ENCRYPTED_BLOCK)&0x1F)==0, "Error 2");
00396
00397 #endif
00398
00403 #define REP_XRB (uint8_t)0x4
00404
00409 #define SENDER_XRB (uint8_t)0x02
00410
00415 #define DEST_XRB (uint8_t)0x01
00416
00417 typedef enum f_write_seed_err_t {
00419     WRITE_ERR_OK=0,
00421     WRITE_ERR_NULL_PASSWORD=7180,
00423     WRITE_ERR_EMPTY_STRING,
00425     WRITE_ERR_MALLOC,
00427     WRITE_ERR_ENCRYPT_PRIV_KEY,
00429     WRITE_ERR_GEN_SUB_PRIV_KEY,
00431     WRITE_ERR_GEN_MAIN_PRIV_KEY,
00433     WRITE_ERR_ENCRYPT_SUB_BLOCK,
00435     WRITE_ERR_UNKNOWN_OPTION,
00437     WRITE_ERR_FILE_ALREADY_EXISTS,
00439     WRITE_ERR_CREATING_FILE,
00441     WRITE_ERR_WRITING_FILE
00442 } f_write_seed_err;
00443
00444 #ifndef F_DOC_SKIP
00445
00446 #define F_RAW_TO_STR_UINT128 (int)1
00447 #define F_RAW_TO_STR_STRING (int)2

```

```

00448 #define F_RAW_STR_MAX_SZ (size_t)41 // 39 + '\0' + '.' -> 39 = log10(2^128)
00449 #define F_MAX_STR_RAW_BALANCE_MAX (size_t)40 //39+'\0'
00450 #define F_NANO_EMPTY_BALANCE "0.0"
00451
00452 #endif
00453
00461 typedef struct f_nano_wallet_info_bdy_t {
00463     uint8_t wallet_prefix; // 0 for NANO; 1 for XRB
00465     uint32_t last_used_wallet_number;
00467     char wallet_representative[MAX_STR_NANO_CHAR];
00469     char max_fee[F_RAW_STR_MAX_SZ];
00471     uint8_t reserved[44];
00472 } __attribute__((packed)) F_NANO_WALLET_INFO_BODY;
00473
00474 #ifndef F_DOC_SKIP
00475
00476 _Static_assert((sizeof(F_NANO_WALLET_INFO_BODY)&0x1F)==0, "Error F_NANO_WALLET_INFO_BODY is not byte
aligned");
00477
00478 #define F_NANO_WALLET_INFO_DESC "Nano file descriptor used for fast custom access. BUY BITCOIN AND NANO."
00479 #define F_NANO_WALLET_INFO_VERSION (uint16_t)((1<<8)|1)
00480 static const uint8_t F_NANO_WALLET_INFO_MAGIC[] = {'_', 'n', 'a', 'n', 'o', 'w', 'a', 'l', 'l', 'e', 't',
'_', 'n', 'f', 'o', '_'};
00481
00482 #define F_NANO_DESC_SZ (size_t)78
00483
00484 #endif
00485
00493 typedef struct f_nano_wallet_info_t {
00495     uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)];
00497     uint16_t version;
00499     char desc[F_NANO_DESC_SZ];
00501     uint8_t nanoseed_hash[32];
00503     uint8_t file_info_integrity[32];
00505     F_NANO_WALLET_INFO_BODY body;
00506 } __attribute__((packed)) F_NANO_WALLET_INFO;
00507
00508 #ifndef F_DOC_SKIP
00509
00510 _Static_assert((sizeof(F_NANO_WALLET_INFO)&0x1F)==0, "Error F_NANO_WALLET_INFO is not byte aligned");
00511
00512 #endif
00513
00521 typedef enum f_file_info_err_t {
00523     F_FILE_INFO_ERR_OK=0,
00525     F_FILE_INFO_ERR_CANT_OPEN_INFO_FILE=7001,
00527     F_FILE_INFO_ERR_NANO_SEED_ENCRYPTED_FILE_NOT_FOUND,
00529     F_FILE_INFO_ERR_CANT_DELETE_NANO_INFO_FILE,
00531     F_FILE_INFO_ERR_MALLOC,
00533     F_FILE_INFO_ERR_CANT_READ_NANO_SEED_ENCRYPTED_FILE,
00535     F_FILE_INFO_ERR_CANT_READ_INFO_FILE,
00537     F_FILE_INFO_INVALID_HEADER_FILE,
00539     F_FILE_INFO_ERR_INVALID_SHA256_INFO_FILE,
00541     F_FILE_INFO_ERR_NANO_SEED_HASH_FAIL,
00543     F_FILE_INFO_ERR_NANO_INVALID_REPRESENTATIVE,
00545     F_FILE_INFO_ERR_NANO_INVALID_MAX_FEE_VALUE,
00547     F_FILE_INFO_ERR_OPEN_FOR_WRITE_INFO,
00549     F_FILE_INFO_ERR_EXISTING_FILE,
00551     F_FILE_INFO_ERR_CANT_WRITE_FILE_INFO
00552 } F_FILE_INFO_ERR;
00553
00554 #ifndef F_DOC_SKIP
00555
00556 #define F_NANO_ADD_A_B (uint32_t)(1<<0)
00557 #define F_NANO_SUB_A_B (uint32_t)(1<<1)
00558 #define F_NANO_A_RAW_128 (uint32_t)(1<<2)
00559 #define F_NANO_A_RAW_STRING (uint32_t)(1<<3)
00560 #define F_NANO_A_REAL_STRING (uint32_t)(1<<4)
00561 #define F_NANO_B_RAW_128 (uint32_t)(1<<5)
00562 #define F_NANO_B_RAW_STRING (uint32_t)(1<<6)
00563 #define F_NANO_B_REAL_STRING (uint32_t)(1<<7)
00564 #define F_NANO_RES_RAW_128 (uint32_t)(1<<8)
00565 #define F_NANO_RES_RAW_STRING (uint32_t)(1<<9)
00566 #define F_NANO_RES_REAL_STRING (uint32_t)(1<<10)
00567 #define F_NANO_C_RAW_128 (uint32_t)(F_NANO_B_RAW_128<<16)
00568 #define F_NANO_C_RAW_STRING (uint32_t)(F_NANO_B_RAW_STRING<<16)
00569 #define F_NANO_C_REAL_STRING (uint32_t)(F_NANO_B_REAL_STRING<<16)
00570
00571 #define F_NANO_COMPARE_EQ (uint32_t)(1<<16) //Equal
00572 #define F_NANO_COMPARE_LT (uint32_t)(1<<17) // Lesser than
00573 #define F_NANO_COMPARE_LEQ (F_NANO_COMPARE_LT|F_NANO_COMPARE_EQ) // Less or equal
00574 #define F_NANO_COMPARE_GT (uint32_t)(1<<18) // Greater
00575 #define F_NANO_COMPARE_GEQ (F_NANO_COMPARE_GT|F_NANO_COMPARE_EQ) // Greater or equal
00576 #define DEFAULT_MAX_FEE "0.001"
00577
00578 #endif
00579

```

```
00602 int f_cloud_crypto_wallet_nano_create_seed(size_t, char *, char *);
00603
00616 int f_generate_nano_seed(NANO_SEED, uint32_t);
00617
00632 int pk_to_wallet(char *, char *, NANO_PUBLIC_KEY_EXTENDED);
00633
00651 int f_seed_to_nano_wallet(NANO_PRIVATE_KEY, NANO_PUBLIC_KEY, NANO_SEED, uint32_t);
00652
00662 char *f_nano_key_to_str(char *, unsigned char *);
00663
00682 int f_nano_seed_to_bip39(char *, size_t, size_t *, NANO_SEED, char *);
00683
00698 int f_bip39_to_nano_seed(uint8_t *, char *, char *);
00699
00721 int f_parse_nano_seed_and_bip39_to_JSON(char *, size_t, size_t *, void *, int, const char *);
00722
00740 int f_read_seed(uint8_t *, const char *, void *, int, int);
00741
00756 int f_nano_raw_to_string(char *, size_t *, size_t, void *, int);
00757
00766 int f_nano_valid_nano_str_value(const char *);
00767
00775 int valid_nano_wallet(const char *);
00776
00786 int nano_base_32_2_hex(uint8_t *, char *);
00787
00802 int f_nano_transaction_to_JSON(char *, size_t, size_t *, NANO_PRIVATE_KEY_EXTENDED, F_BLOCK_TRANSFER *);
00803
00811 int valid_raw_balance(const char *);
00812
00820 int is_null_hash(uint8_t *);
00821
00833 int is_nano_prefix(const char *, const char *);
00834
00843 F_FILE_INFO_ERR f_get_nano_file_info(F_NANO_WALLET_INFO *);
00844
00854 F_FILE_INFO_ERR f_set_nano_file_info(F_NANO_WALLET_INFO *, int);
00855
00879 f_nano_err f_nano_value_compare_value(void *, void *, uint32_t *);
00880
00901 f_nano_err f_nano_verify_nano_funds(void *, void *, void *, uint32_t);
00902
00912 f_nano_err f_nano_parse_raw_str_to_rawl28_t(uint8_t *, const char *);
00913
00923 f_nano_err f_nano_parse_real_str_to_rawl28_t(uint8_t *, const char *);
00924
00947 f_nano_err f_nano_add_sub(void *, void *, void *, uint32_t);
00948
00959 int f_nano_sign_block(F_BLOCK_TRANSFER *, F_BLOCK_TRANSFER *, NANO_PRIVATE_KEY_EXTENDED);
00960
00974 f_write_seed_err f_write_seed(void *, int, uint8_t *, char *);
00975
00988 f_nano_err f_nano_balance_to_str(char *, size_t, size_t *, f_uintl28_t);
00989
00990
00995 #define F_BRAIN_WALLET_VERY_POOR (uint32_t)0
00996
01001 #define F_BRAIN_WALLET_POOR (uint32_t)1
01002
01007 #define F_BRAIN_WALLET_VERY_BAD (uint32_t)2
01008
01013 #define F_BRAIN_WALLET_BAD (uint32_t)3
01014
01019 #define F_BRAIN_WALLET_VERY_WEAK (uint32_t)4
01020
01025 #define F_BRAIN_WALLET_WEAK (uint32_t)5
01026
01031 #define F_BRAIN_WALLET_STILL_WEAK (uint32_t)6
01032
01037 #define F_BRAIN_WALLET_MAYBE_GOOD (uint32_t)7
01038
01039
01044 #define F_BRAIN_WALLET_GOOD (uint32_t)8
01045
01050 #define F_BRAIN_WALLET_VERY_GOOD (uint32_t)9
01051
01056 #define F_BRAIN_WALLET_NICE (uint32_t)10
01057
01062 #define F_BRAIN_WALLET_PERFECT (uint32_t)11
01063
01090 int f_extract_seed_from_brainwallet(uint8_t *, char **, uint32_t, const char *, const char *);
01091
01092 #ifdef __cplusplus
01093 }
01094 #endif
01095
```

## 5.5 f\_util.h File Reference

```
#include <stdint.h>
#include "mbedtls/sha256.h"
#include "mbedtls/aes.h"
```

### Macros

- `#define F_ENTROPY_TYPE_PARANOIC (uint32_t)1477682819`
- `#define F_ENTROPY_TYPE_EXCELENT (uint32_t)1476885281`
- `#define F_ENTROPY_TYPE_GOOD (uint32_t)1472531015`
- `#define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1471001808`
- `#define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1470003345`
- `#define ENTROPY_BEGIN f_verify_system_entropy_begin();`
- `#define ENTROPY_END f_verify_system_entropy_finish();`
- `#define F_PASS_MUST_HAVE_AT_LEAST_NONE (int)0`
- `#define F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER (int)1`
- `#define F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL (int)2`
- `#define F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE (int)4`
- `#define F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE (int)8`
- `#define F_PASS_IS_TOO_LONG (int)256`
- `#define F_PASS_IS_TOO_SHORT (int)512`
- `#define F_PASS_IS_OUT_OVF (int)1024`
- `#define F_GET_CH_MODE_NO_ECHO (int)(1<<16)`
- `#define F_GET_CH_MODE_ANY_KEY (int)(1<<17)`

### Typedefs

- `typedef void(* rnd_fn) (void *, size_t)`

### Functions

- `int f_verify_system_entropy (uint32_t, void *, size_t, int)`
- `int f_pass_must_have_at_least (char *, size_t, size_t, size_t, int)`
- `int f_passwd_comp_safe (char *, char *, size_t, size_t, size_t)`
- `char * f_get_entropy_name (uint32_t)`
- `uint32_t f_sel_to_entropy_level (int)`
- `int f_str_to_hex (uint8_t *, char *)`
- `void f_random_attach ( rnd_fn)`
- `void f_random (void *, size_t)`
- `int get_console_passwd (char *, size_t)`
- `int f_get_char_no_block (int)`
- `int f_convert_to_long_int (unsigned long int *, char *, size_t)`

#### 5.5.1 Detailed Description

This ABI is a utility for myNanoEmbedded library and sub routines are implemented here.

Definition in file `f_util.h`.

## 5.5.2 Macro Definition Documentation

### 5.5.2.1 ENTROPY\_BEGIN

```
#define ENTROPY_BEGIN f_verify_system_entropy_begin();
```

Begins and prepares a entropy function.

See also

**f\_verify\_system\_entropy()** (p. ??)

Definition at line **152** of file **f\_util.h**.

### 5.5.2.2 ENTROPY\_END

```
#define ENTROPY_END f_verify_system_entropy_finish();
```

Ends a entropy function.

See also

**f\_verify\_system\_entropy()** (p. ??)

Definition at line **159** of file **f\_util.h**.

### 5.5.2.3 F\_ENTROPY\_TYPE\_EXCELENT

```
#define F_ENTROPY_TYPE_EXCELENT (uint32_t)1476885281
```

Type of the excelent entropy used for verifier.

Slow

Definition at line **124** of file **f\_util.h**.

#### 5.5.2.4 F\_ENTROPY\_TYPE\_GOOD

```
#define F_ENTROPY_TYPE_GOOD (uint32_t)1472531015
```

Type of the good entropy used for verifier.

Not so slow

Definition at line **131** of file **f\_util.h**.

#### 5.5.2.5 F\_ENTROPY\_TYPE\_NOT\_ENOUGH

```
#define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1471001808
```

Type of the moderate entropy used for verifier.

Fast

Definition at line **138** of file **f\_util.h**.

#### 5.5.2.6 F\_ENTROPY\_TYPE\_NOT\_RECOMENDED

```
#define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1470003345
```

Type of the not recommended entropy used for verifier.

Very fast

Definition at line **145** of file **f\_util.h**.

#### 5.5.2.7 F\_ENTROPY\_TYPE\_PARANOIC

```
#define F_ENTROPY_TYPE_PARANOIC (uint32_t)1477682819
```

Type of the very excelent entropy used for verifier.

Very slow

Definition at line **117** of file **f\_util.h**.

### 5.5.2.8 F\_GET\_CH\_MODE\_ANY\_KEY

```
#define F_GET_CH_MODE_ANY_KEY (int) (1<<17)
```

See also

**f\_get\_char\_no\_block()** (p. ??)

Definition at line **334** of file **f\_util.h**.

### 5.5.2.9 F\_GET\_CH\_MODE\_NO\_ECHO

```
#define F_GET_CH_MODE_NO_ECHO (int) (1<<16)
```

See also

**f\_get\_char\_no\_block()** (p. ??)

Definition at line **328** of file **f\_util.h**.

### 5.5.2.10 F\_PASS\_IS\_OUT\_OVF

```
#define F_PASS_IS_OUT_OVF (int) 1024
```

Password is overflow and cannot be stored.

Definition at line **207** of file **f\_util.h**.

### 5.5.2.11 F\_PASS\_IS\_TOO\_LONG

```
#define F_PASS_IS_TOO_LONG (int) 256
```

Password is too long.

Definition at line **195** of file **f\_util.h**.

### 5.5.2.12 F\_PASS\_IS\_TOO\_SHORT

```
#define F_PASS_IS_TOO_SHORT (int) 512
```

Password is too short.

Definition at line **201** of file **f\_util.h**.

#### 5.5.2.13 F\_PASS\_MUST\_HAVE\_AT\_LEAST\_NONE

```
#define F_PASS_MUST_HAVE_AT_LEAST_NONE (int)0
```

Password does not need any criteria to pass.

Definition at line **165** of file **f\_util.h**.

#### 5.5.2.14 F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_LOWER\_CASE

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE (int)8
```

Password must have at least one lower case.

Definition at line **189** of file **f\_util.h**.

#### 5.5.2.15 F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_NUMBER

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER (int)1
```

Password must have at least one number.

Definition at line **171** of file **f\_util.h**.

#### 5.5.2.16 F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_SYMBOL

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL (int)2
```

Password must have at least one symbol.

Definition at line **177** of file **f\_util.h**.

#### 5.5.2.17 F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_UPPER\_CASE

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE (int)4
```

Password must have at least one upper case.

Definition at line **183** of file **f\_util.h**.



### 5.5.3 Typedef Documentation

#### 5.5.3.1 rnd\_fn

`rnd_fn`

Pointer caller for random function.

Definition at line **293** of file **f\_util.h**.

### 5.5.4 Function Documentation

#### 5.5.4.1 f\_convert\_to\_long\_int()

```
int f_convert_to_long_int (
    unsigned long int * val,
    char * value,
    size_t value_sz )
```

Converts a string value to unsigned long int.

##### Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

##### Return values

0	On Success, Otherwise error
---	-----------------------------

#### 5.5.4.2 f\_get\_char\_no\_block()

```
int f_get_char_no_block (
    int mode )
```

Reads a char from console.

Waits a char and returns its value

## Parameters

in	mode	Mode and/or character to be returned <ul style="list-style-type: none"> <li>• <i>F_GET_CH_MODE_NO_ECHO</i> No echo is on the console string</li> <li>• <i>F_GET_CH_MODE_ANY_KEY</i> Returns any key pressed&lt;br&gt;</li> </ul>
----	------	--

## Example:

```
key=f_get_char_no_block(F_GET_CH_MODE_NO_ECHO|'c'); // Waits 'c' char key and returns value 0x00000063
without echo 'c' on the screen
```

## Return values

key	code: On Success, Negative value on error
-----	---

## 5.5.4.3 f\_get\_entropy\_name()

```
char * f_get_entropy_name (
    uint32_t val )
```

Returns a entropy name given a index/ASCII index or entropy value.

## Parameters

in	val	Index/ASCII index or entropy value
----	-----	------------------------------------

## Return values:

- *NULL* If no entropy index/ASCII/entropy found in *val*
- *F\_ENTROPY\_TYPE\_\** name if found in index/ASCII or entropy value

## 5.5.4.4 f\_pass\_must\_have\_at\_least()

```
int f_pass_must_have_at_least (
    char * password,
    size_t n,
    size_t min,
    size_t max,
    int must_have )
```

Checks if a given password has enough requirements to be parsed to a function.

## Parameters

in	<i>password</i>	Password string
in	<i>n</i>	Max buffer string permitted to store password including NULL char
in	<i>min</i>	Minimum size allowed in password string
in	<i>max</i>	Maximum size allowed in password
in	<i>must_have</i>	Must have a type: <ul style="list-style-type: none"> <li>• <code>F_PASS_MUST_HAVE_AT_LEAST_NONE</code> Not need any special characters or number</li> <li>• <code>F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER</code> Must have at least one number</li> <li>• <code>F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL</code> Must have at least one symbol</li> <li>• <code>F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE</code> Must have at least one upper case</li> <li>• <code>F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE</code> Must have at least one lower case</li> </ul>

## Return values:

- `0 (zero)`: If password is passed in the test
- `F_PASS_IS_OUT_OVF`: If password length exceeds *n* value
- `F_PASS_IS_TOO_SHORT`: If password length is less than *min* value
- `F_PASS_IS_TOO_LONG`: If password length is greater than *m* value
- `F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE`: If password is required in *must\_have* type upper case characters
- `F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE`: If password is required in *must\_have* type lower case characters
- `F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL`: If password is required in *must\_have* type to have symbol(s)
- `F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER`: if password is required in *must\_have* type to have number(s)

## 5.5.4.5 f\_passwd\_comp\_safe()

```
int f_passwd_comp_safe (
    char * pass1,
    char * pass2,
    size_t n,
    size_t min,
    size_t max )
```

Compares two passwords values with safe buffer.

**Parameters**

in	<i>pass1</i>	First password to compare with <i>pass2</i>
in	<i>pass2</i>	Second password to compare with <i>pass1</i>
in	<i>n</i>	Size of Maximum buffer of both <i>pass1</i> and <i>pass2</i>
in	<i>min</i>	Minimun value of both <i>pass1</i> and <i>pass2</i>
in	<i>max</i>	Maximum value of both <i>pass1</i> and <i>pass2</i>

**Return values**

0	If <i>pass1</i> is equal to <i>pass2</i> , otherwise value is less than 0 (zero) if password does not match
---	---

**5.5.4.6 f\_random()**

```
void f_random (
    void * random,
    size_t random_sz )
```

Random function to be called to generate a *random* data with *random\_sz*

**Parameters**

out	<i>random</i>	Random data to be parsed
in	<i>random_sz</i>	Size of random data to be filled

**See also**

**f\_random\_attach()** (p. ??)

**5.5.4.7 f\_random\_attach()**

```
void f_random_attach (
    rnd_fn fn )
```

Attaches a function to be called by **f\_random()** (p. ??)

**Parameters**

in	<i>fn</i>	A function to be called
----	-----------	-------------------------

**See also**

**rnd\_fn** (p. ??)

#### 5.5.4.8 f\_sel\_to\_entropy\_level()

```
uint32_t f_sel_to_entropy_level (
    int sel )
```

Return a given entropy number given a number encoded ASCII or index number.

##### Parameters

in	sel	ASCII or index value
----	-----	----------------------

##### Return values:

- *0 (zero)*: If no entropy number found in *sel*
- *F\_ENTROPY\_TYPE\_PARANOIC*
- *F\_ENTROPY\_TYPE\_EXCELENT*
- *F\_ENTROPY\_TYPE\_GOOD*
- *F\_ENTROPY\_TYPE\_NOT\_ENOUGH*
- *F\_ENTROPY\_TYPE\_NOT\_RECOMENDED*

#### 5.5.4.9 f\_str\_to\_hex()

```
int f_str_to_hex (
    uint8_t * hex_stream,
    char * str )
```

Converts a *str* string buffer to raw *hex\_stream* value stream.

##### Parameters

out	hex	Raw hex value
in	str	String buffer terminated with NULL char

##### Return values

0	On Success, otherwise Error
---	-----------------------------

#### 5.5.4.10 f\_verify\_system\_entropy()

```
int f_verify_system_entropy (
    uint32_t type,
    void * rand,
    size_t rand_sz,
    int turn_on_wdt )
```

Take a random number generator function and returns random value only if randomized data have a desired entropy value.

##### Parameters

in	<i>type</i>	Entropy type. Entropy type values are: <ul style="list-style-type: none"> <li>• F_ENTROPY_TYPE_PARANOIC Highest level entropy recommended for generate a Nano SEED with a paranoic entropy. Very slow</li> <li>• F_ENTROPY_TYPE_EXCELENT Gives a very excellent entropy for generating Nano SEED. Slow</li> <li>• F_ENTROPY_TYPE_GOOD Good entropy type for generating Nano SEED. Normal.</li> <li>• F_ENTROPY_TYPE_NOT_ENOUGH Moderate entropy for generating Nano SEED. Usually fast to create a temporary Nano SEED. Fast</li> <li>• F_ENTROPY_TYPE_NOT_RECOMENDED Fast but not recommended for generating Nano SEED.</li> </ul>
out	<i>rand</i>	Random data with a satisfied type of entropy
in	<i>rand_sz</i>	Size of random data output
in	<i>turn_on_wdt</i>	For ESP32, Arduino platform and other microcontrollers only. Turns on/off WATCH DOG (0: OFF, NON ZERO: ON). For Raspberry PI and Linux native is ommited.

This implementation is based on topic in [Definition 7.12](#) in MIT opencourseware (7.3 A Statistical Definition of Entropy - 2005)

Many thanks to **Professor Z. S. Spakovszky** for this amazing topic

##### Return values

0	On Success, otherwise Error
---	-----------------------------

#### 5.5.4.11 get\_console\_passwd()

```
int get_console_passwd (
    char * pass,
    size_t pass_sz )
```

Reads a password from console.

## Parameters

out	<i>pass</i>	Password to be parsed to pointer
in	<i>pass_sz</i>	Size of buffer <i>pass</i>

## Return values

0	On Success, otherwise Error
---	-----------------------------

## 5.6 f\_util.h

```

00001 /*
00002     AUTHOR: Fábio Pereira da Silva
00003     YEAR: 2019-20
00004     LICENSE: MIT
00005     EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006 */
00007
00013 #include <stdint.h>
00014 #include "mbedtls/sha256.h"
00015 #include "mbedtls/aes.h"
00016
00017 #ifdef __cplusplus
00018 extern "C" {
00019 #endif
00020
00021 #ifndef F_DOC_SKIP
00022
00023     #define F_LOG_MAX 8*256
00024     #define LICENSE \
00025 "MIT License\n\n\
00026 Copyright (c) 2019 Fábio Pereira da Silva\n\n\
00027 Permission is hereby granted, free of charge, to any person obtaining a copy\n\
00028 of this software and associated documentation files (the \"Software\"), to deal\n\
00029 in the Software without restriction, including without limitation the rights\n\
00030 to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n\
00031 copies of the Software, and to permit persons to whom the Software is\n\
00032 furnished to do so, subject to the following conditions:\n\n\
00033 The above copyright notice and this permission notice shall be included in all\n\
00034 copies or substantial portions of the Software.\n\n\
00035 THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n\
00036 IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n\
00037 FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n\
00038 AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n\
00039 LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n\
00040 OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE\n\
00041 SOFTWARE.\n\n\
00042
00043 #endif
00044
00045 #ifdef F_ESP32
00046
00047     #define F_WDT_MAX_ENTROPY_TIME 2*120
00048     #define F_WDT_PANIC true
00049     #define F_WDT_MIN_TIME 20//4
00050
00051 #endif
00052
00070 int f_verify_system_entropy(uint32_t, void *, size_t, int);
00071
00098 int f_pass_must_have_at_least(char *, size_t, size_t, size_t, int);
00099
00100 #ifndef F_DOC_SKIP
00101
00102 int f_verify_system_entropy_begin();
00103 void f_verify_system_entropy_finish();
00104 int f_file_exists(char *);
00105 int f_find_str(size_t *, char *, size_t, char *);
00106 int f_find_replace(char *, size_t *, size_t *, char *, size_t, char *, char *);
00107 int f_is_integer(char *, size_t);
00108 int is_filled_with_value(uint8_t *, size_t, uint8_t);
00109
00110 #endif
00111

```

```

00112 // #define F_ENTROPY_TYPE_PARANOIC (uint32_t)1476682819
00117 #define F_ENTROPY_TYPE_PARANOIC (uint32_t)1477682819
00118
00119 // #define F_ENTROPY_TYPE_EXCELENT (uint32_t)1475885281
00124 #define F_ENTROPY_TYPE_EXCELENT (uint32_t)1476885281
00125
00126 // #define F_ENTROPY_TYPE_GOOD (uint32_t)1471531015
00131 #define F_ENTROPY_TYPE_GOOD (uint32_t)1472531015
00132
00133 // #define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1470001808
00138 #define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1471001808
00139
00140 // #define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1469703345
00145 #define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1470003345
00146
00152 #define ENTROPY_BEGIN f_verify_system_entropy_begin();
00153
00159 #define ENTROPY_END f_verify_system_entropy_finish();
00160
00165 #define F_PASS_MUST_HAVE_AT_LEAST_NONE (int)0
00166
00171 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER (int)1
00172
00177 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL (int)2
00178
00183 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE (int)4
00184
00189 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE (int)8
00190
00195 #define F_PASS_IS_TOO_LONG (int)256
00196
00201 #define F_PASS_IS_TOO_SHORT (int)512
00202
00207 #define F_PASS_IS_OUT_OVF (int)1024//768
00208
00209 #ifndef F_DOC_SKIP
00210
00211 #define F_PBKDF2_ITER_SZ 2*4096
00212
00213 typedef enum f_pbkdf2_err_t {
00214     F_PBKDF2_RESULT_OK=0,
00215     F_PBKDF2_ERR_CTX=95,
00216     F_PBKDF2_ERR_PKCS5,
00217     F_PBKDF2_ERR_INFO_SHA
00218 } f_pbkdf2_err;
00219
00220 typedef enum f_aes_err {
00221     F_AES_RESULT_OK=0,
00222     F_AES_ERR_ENCKEY=30,
00223     F_AES_ERR_DECKEY,
00224     F_AES_ERR_MALLOC,
00225     F_AES_UNKNOW_DIRECTION,
00226     F_ERR_ENC_DECRYPT_FAILED
00227 } f_aes_err;
00228
00229 char *fhextstrv2(char *, const void *, size_t, int);
00230 uint8_t *f_sha256_digest(uint8_t *, size_t);
00231 f_pbkdf2_err f_pbkdf2_hmac(unsigned char *, size_t, unsigned char *, size_t, uint8_t *);
00232 f_aes_err f_aes256cipher(uint8_t *, uint8_t *, void *, size_t, void *, int);
00233
00234 #endif
00235
00247 int f_passwd_comp_safe(char *, char *, size_t, size_t, size_t);
00248
00259 char *f_get_entropy_name(uint32_t);
00260
00275 uint32_t f_sel_to_entropy_level(int);
00276
00285 int f_str_to_hex(uint8_t *, char *);
00286
00287 #ifndef F_ESP32
00288
00293 typedef void (*rnd_fn)(void *, size_t);
00294
00302 void f_random_attach(rnd_fn);
00303
00312 void f_random(void *, size_t);
00313
00322 int get_console_passwd(char *, size_t);
00323
00328 #define F_GET_CH_MODE_NO_ECHO (int)(1<<16)
00329
00334 #define F_GET_CH_MODE_ANY_KEY (int)(1<<17)
00335
00351 int f_get_char_no_block(int);
00352
00362 int f_convert_to_long_int(unsigned long int *, char *, size_t);

```



```
00363
00364 #endif
00365
00366 #ifdef __cplusplus
00367 }
00368 #endif
```

## 5.7 sodium.h File Reference

```
#include "sodium/version.h"
#include "sodium/core.h"
#include "sodium/crypto_aead_aes256gcm.h"
#include "sodium/crypto_aead_chacha20poly1305.h"
#include "sodium/crypto_aead_xchacha20poly1305.h"
#include "sodium/crypto_auth.h"
#include "sodium/crypto_auth_hmacsha256.h"
#include "sodium/crypto_auth_hmacsha512.h"
#include "sodium/crypto_auth_hmacsha512256.h"
#include "sodium/crypto_box.h"
#include "sodium/crypto_box_curve25519xsalsa20poly1305.h"
#include "sodium/crypto_core_hsalsa20.h"
#include "sodium/crypto_core_hchacha20.h"
#include "sodium/crypto_core_salsa20.h"
#include "sodium/crypto_core_salsa2012.h"
#include "sodium/crypto_core_salsa208.h"
#include "sodium/crypto_generichash.h"
#include "sodium/crypto_generichash_blake2b.h"
#include "sodium/crypto_hash.h"
#include "sodium/crypto_hash_sha256.h"
#include "sodium/crypto_hash_sha512.h"
#include "sodium/crypto_kdf.h"
#include "sodium/crypto_kdf_blake2b.h"
#include "sodium/crypto_kx.h"
#include "sodium/crypto_onetimeauth.h"
#include "sodium/crypto_onetimeauth_poly1305.h"
#include "sodium/crypto_pwhash.h"
#include "sodium/crypto_pwhash_argon2i.h"
#include "sodium/crypto_scalarmult.h"
#include "sodium/crypto_scalarmult_curve25519.h"
#include "sodium/crypto_secretbox.h"
#include "sodium/crypto_secretbox_xsalsa20poly1305.h"
#include "sodium/crypto_secretstream_xchacha20poly1305.h"
#include "sodium/crypto_shorthash.h"
#include "sodium/crypto_shorthash_siphhash24.h"
#include "sodium/crypto_sign.h"
#include "sodium/crypto_sign_ed25519.h"
#include "sodium/crypto_stream.h"
#include "sodium/crypto_stream_chacha20.h"
#include "sodium/crypto_stream_salsa20.h"
#include "sodium/crypto_stream_xsalsa20.h"
#include "sodium/crypto_verify_16.h"
#include "sodium/crypto_verify_32.h"
#include "sodium/crypto_verify_64.h"
#include "sodium/randombytes.h"
#include "sodium/randombytes_salsa20_random.h"
#include "sodium/randombytes_sysrandom.h"
#include "sodium/runtime.h"
```

```
#include "sodium/utils.h"
#include "sodium/crypto_box_curve25519xchacha20poly1305.h"
#include "sodium/crypto_core_ed25519.h"
#include "sodium/crypto_scalarmult_ed25519.h"
#include "sodium/crypto_secretbox_xchacha20poly1305.h"
#include "sodium/crypto_pwhash_scryptsalsa208sha256.h"
#include "sodium/crypto_stream_salsa2012.h"
#include "sodium/crypto_stream_salsa208.h"
#include "sodium/crypto_stream_xchacha20.h"
```

### 5.7.1 Detailed Description

This header file is an implementation of Libsodium library.

Definition in file **sodium.h**.

## 5.8 sodium.h

```
00001
00005 #ifndef sodium_H
00006 #define sodium_H
00007
00008 #include "sodium/version.h"
00009
00010 #include "sodium/core.h"
00011 #include "sodium/crypto_aead_aes256gcm.h"
00012 #include "sodium/crypto_aead_chacha20poly1305.h"
00013 #include "sodium/crypto_aead_xchacha20poly1305.h"
00014 #include "sodium/crypto_auth.h"
00015 #include "sodium/crypto_auth_hmacsha256.h"
00016 #include "sodium/crypto_auth_hmacsha512.h"
00017 #include "sodium/crypto_auth_hmacsha512256.h"
00018 #include "sodium/crypto_box.h"
00019 #include "sodium/crypto_box_curve25519xsalsa20poly1305.h"
00020 #include "sodium/crypto_core_hsalsa20.h"
00021 #include "sodium/crypto_core_hchacha20.h"
00022 #include "sodium/crypto_core_salsa20.h"
00023 #include "sodium/crypto_core_salsa2012.h"
00024 #include "sodium/crypto_core_salsa208.h"
00025 #include "sodium/crypto_generichash.h"
00026 #include "sodium/crypto_generichash_blake2b.h"
00027 #include "sodium/crypto_hash.h"
00028 #include "sodium/crypto_hash_sha256.h"
00029 #include "sodium/crypto_hash_sha512.h"
00030 #include "sodium/crypto_kdf.h"
00031 #include "sodium/crypto_kdf_blake2b.h"
00032 #include "sodium/crypto_kx.h"
00033 #include "sodium/crypto_onetimeauth.h"
00034 #include "sodium/crypto_onetimeauth_poly1305.h"
00035 #include "sodium/crypto_pwhash.h"
00036 #include "sodium/crypto_pwhash_argon2i.h"
00037 #include "sodium/crypto_scalarmult.h"
00038 #include "sodium/crypto_scalarmult_curve25519.h"
00039 #include "sodium/crypto_secretbox.h"
00040 #include "sodium/crypto_secretbox_xsalsa20poly1305.h"
00041 #include "sodium/crypto_secretstream_xchacha20poly1305.h"
00042 #include "sodium/crypto_shorthash.h"
00043 #include "sodium/crypto_shorthash_siphhash24.h"
00044 #include "sodium/crypto_sign.h"
00045 #include "sodium/crypto_sign_ed25519.h"
00046 #include "sodium/crypto_stream.h"
00047 #include "sodium/crypto_stream_chacha20.h"
00048 #include "sodium/crypto_stream_salsa20.h"
00049 #include "sodium/crypto_stream_xsalsa20.h"
00050 #include "sodium/crypto_verify_16.h"
00051 #include "sodium/crypto_verify_32.h"
00052 #include "sodium/crypto_verify_64.h"
00053 #include "sodium/randombytes.h"
00054 #ifdef __native_client__
00055 # include "sodium/randombytes_nativeclient.h"
```

```
00056 #endif
00057 #include "sodium/randombytes_salsa20_random.h"
00058 #include "sodium/randombytes_sysrandom.h"
00059 #include "sodium/runtime.h"
00060 #include "sodium/utils.h"
00061
00062 #ifndef SODIUM_LIBRARY_MINIMAL
00063 # include "sodium/crypto_box_curve25519xchacha20poly1305.h"
00064 # include "sodium/crypto_core_ed25519.h"
00065 # include "sodium/crypto_scalarmult_ed25519.h"
00066 # include "sodium/crypto_secretbox_xchacha20poly1305.h"
00067 # include "sodium/crypto_pwhash_scryptsalsa208sha256.h"
00068 # include "sodium/crypto_stream_salsa2012.h"
00069 # include "sodium/crypto_stream_salsa208.h"
00070 # include "sodium/crypto_stream_xchacha20.h"
00071 #endif
00072
00073 #endif
```



# Index

- `__attribute__`
    - `f_nano_crypto_util.h`, 29
- account
  - `f_block_transfer_t`, 7
  - `f_nano_crypto_util.h`, 47
- balance
  - `f_block_transfer_t`, 7
  - `f_nano_crypto_util.h`, 47
- body
  - `f_nano_crypto_util.h`, 48
  - `f_nano_wallet_info_t`, 15
- DEST\_XRB
  - `f_nano_crypto_util.h`, 21
- desc
  - `f_nano_crypto_util.h`, 48
  - `f_nano_wallet_info_t`, 15
- description
  - `f_nano_crypto_util.h`, 48
  - `f_nano_crypto_wallet_t`, 10
- ENTROPY\_BEGIN
  - `f_util.h`, 59
- ENTROPY\_END
  - `f_util.h`, 59
- F\_ADD\_288
  - `f_add_bn_288_le.h`, 17
- F\_BRAIN\_WALLET\_BAD
  - `f_nano_crypto_util.h`, 21
- F\_BRAIN\_WALLET\_GOOD
  - `f_nano_crypto_util.h`, 21
- F\_BRAIN\_WALLET\_MAYBE\_GOOD
  - `f_nano_crypto_util.h`, 21
- F\_BRAIN\_WALLET\_NICE
  - `f_nano_crypto_util.h`, 21
- F\_BRAIN\_WALLET\_PERFECT
  - `f_nano_crypto_util.h`, 22
- F\_BRAIN\_WALLET\_POOR
  - `f_nano_crypto_util.h`, 22
- F\_BRAIN\_WALLET\_STILL\_WEAK
  - `f_nano_crypto_util.h`, 22
- F\_BRAIN\_WALLET\_VERY\_BAD
  - `f_nano_crypto_util.h`, 22
- F\_BRAIN\_WALLET\_VERY\_GOOD
  - `f_nano_crypto_util.h`, 23
- F\_BRAIN\_WALLET\_VERY\_POOR
  - `f_nano_crypto_util.h`, 23
- F\_BRAIN\_WALLET\_VERY\_WEAK
  - `f_nano_crypto_util.h`, 23
- F\_BRAIN\_WALLET\_WEAK
  - `f_nano_crypto_util.h`, 23
- F\_ENTROPY\_TYPE\_EXCELENT
  - `f_util.h`, 59
- F\_ENTROPY\_TYPE\_GOOD
  - `f_util.h`, 59
- F\_ENTROPY\_TYPE\_NOT\_ENOUGH
  - `f_util.h`, 60
- F\_ENTROPY\_TYPE\_NOT\_RECOMENDED
  - `f_util.h`, 60
- F\_ENTROPY\_TYPE\_PARANOIC
  - `f_util.h`, 60
- F\_FILE\_INFO\_ERR
  - `f_nano_crypto_util.h`, 26
- F\_GET\_CH\_MODE\_ANY\_KEY
  - `f_util.h`, 60
- F\_GET\_CH\_MODE\_NO\_ECHO
  - `f_util.h`, 61
- F\_PASS\_IS\_OUT\_OVF
  - `f_util.h`, 61
- F\_PASS\_IS\_TOO\_LONG
  - `f_util.h`, 61
- F\_PASS\_IS\_TOO\_SHORT
  - `f_util.h`, 61
- F\_PASS\_MUST\_HAVE\_AT\_LEAST\_NONE
  - `f_util.h`, 61
- F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_LOWER\_↵
  - CASE
  - `f_util.h`, 62
- F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_NUMBER
  - `f_util.h`, 62
- F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_SYMBOL
  - `f_util.h`, 62
- F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_UPPER\_↵
  - CASE
  - `f_util.h`, 62
- `f_add_bn_288_le.h`, 17, 18
  - F\_ADD\_288, 17
- `f_bip39_to_nano_seed`
  - `f_nano_crypto_util.h`, 29
- `f_block_transfer_t`, 7
  - account, 7
  - balance, 7
  - link, 8
  - preamble, 8
  - prefixes, 8
  - previous, 8
  - representative, 8

- signature, 9
- work, 9
- f\_cloud\_crypto\_wallet\_nano\_create\_seed
  - f\_nano\_crypto\_util.h, 31
- f\_convert\_to\_long\_int
  - f\_util.h, 63
- f\_extract\_seed\_from\_brainwallet
  - f\_nano\_crypto\_util.h, 32
- f\_file\_info\_err\_t, 9
  - f\_nano\_crypto\_util.h, 27
- f\_generate\_nano\_seed
  - f\_nano\_crypto\_util.h, 33
- f\_get\_char\_no\_block
  - f\_util.h, 63
- f\_get\_entropy\_name
  - f\_util.h, 64
- f\_get\_nano\_file\_info
  - f\_nano\_crypto\_util.h, 33
- f\_nano\_add\_sub
  - f\_nano\_crypto\_util.h, 34
- f\_nano\_balance\_to\_str
  - f\_nano\_crypto\_util.h, 34
- f\_nano\_crypto\_util.h, 18, 53
  - \_\_attribute\_\_, 29
  - account, 47
  - balance, 47
  - body, 48
  - DEST\_XRB, 21
  - desc, 48
  - description, 48
  - F\_BRAIN\_WALLET\_BAD, 21
  - F\_BRAIN\_WALLET\_GOOD, 21
  - F\_BRAIN\_WALLET\_MAYBE\_GOOD, 21
  - F\_BRAIN\_WALLET\_NICE, 21
  - F\_BRAIN\_WALLET\_PERFECT, 22
  - F\_BRAIN\_WALLET\_POOR, 22
  - F\_BRAIN\_WALLET\_STILL\_WEAK, 22
  - F\_BRAIN\_WALLET\_VERY\_BAD, 22
  - F\_BRAIN\_WALLET\_VERY\_GOOD, 23
  - F\_BRAIN\_WALLET\_VERY\_POOR, 23
  - F\_BRAIN\_WALLET\_VERY\_WEAK, 23
  - F\_BRAIN\_WALLET\_WEAK, 23
  - F\_FILE\_INFO\_ERR, 26
  - f\_bip39\_to\_nano\_seed, 29
  - f\_cloud\_crypto\_wallet\_nano\_create\_seed, 31
  - f\_extract\_seed\_from\_brainwallet, 32
  - f\_file\_info\_err\_t, 27
  - f\_generate\_nano\_seed, 33
  - f\_get\_nano\_file\_info, 33
  - f\_nano\_add\_sub, 34
  - f\_nano\_balance\_to\_str, 34
  - f\_nano\_err, 26
  - f\_nano\_err\_t, 28
  - f\_nano\_key\_to\_str, 35
  - f\_nano\_parse\_raw\_str\_to\_raw128\_t, 35
  - f\_nano\_parse\_real\_str\_to\_raw128\_t, 36
  - f\_nano\_raw\_to\_string, 36
  - f\_nano\_seed\_to\_bip39, 37
  - f\_nano\_sign\_block, 38
  - f\_nano\_transaction\_to\_JSON, 38
  - f\_nano\_valid\_nano\_str\_value, 39
  - f\_nano\_value\_compare\_value, 39
  - f\_nano\_verify\_nano\_funds, 40
  - f\_parse\_nano\_seed\_and\_bip39\_to\_JSON, 41
  - f\_read\_seed, 42
  - f\_seed\_to\_nano\_wallet, 43
  - f\_set\_nano\_file\_info, 43
  - f\_uint128\_t, 26
  - f\_write\_seed, 44
  - f\_write\_seed\_err, 26
  - f\_write\_seed\_err\_t, 29
  - file\_info\_integrity, 48
  - hash\_sk\_unencrypted, 48
  - header, 49
  - is\_nano\_prefix, 45
  - is\_null\_hash, 45
  - iv, 49
  - last\_used\_wallet\_number, 49
  - link, 49
  - MAX\_STR\_NANO\_CHAR, 24
  - max\_fee, 49
  - NANO\_ENCRYPTED\_SEED\_FILE, 24
  - NANO\_FILE\_WALLETS\_INFO, 24
  - NANO\_PASSWD\_MAX\_LEN, 24
  - NANO\_PREFIX, 24
  - NANO\_PRIVATE\_KEY\_EXTENDED, 27
  - NANO\_PRIVATE\_KEY, 26
  - NANO\_PUBLIC\_KEY\_EXTENDED, 27
  - NANO\_PUBLIC\_KEY, 27
  - NANO\_SEED, 27
  - nano\_base\_32\_2\_hex, 45
  - nano\_hdr, 50
  - nanoseed\_hash, 50
  - PUB\_KEY\_EXTENDED\_MAX\_LEN, 25
  - pk\_to\_wallet, 46
  - preamble, 50
  - prefixes, 50
  - previous, 50
  - REP\_XRB, 25
  - representative, 51
  - reserved, 51
  - SENDER\_XRB, 25
  - STR\_NANO\_SZ, 25
  - salt, 51
  - seed\_block, 51
  - signature, 51
  - sk\_encrypted, 52
  - sub\_salt, 52
  - valid\_nano\_wallet, 46
  - valid\_raw\_balance, 47
  - ver, 52
  - version, 52
  - wallet\_prefix, 52
  - wallet\_representative, 53
  - work, 53
  - XRB\_PREFIX, 25

- f\_nano\_crypto\_wallet\_t, 9
  - description, 10
  - iv, 10
  - nano\_hdr, 10
  - salt, 10
  - seed\_block, 11
  - ver, 11
- f\_nano\_encrypted\_wallet\_t, 11
  - hash\_sk\_unencrypted, 12
  - iv, 12
  - reserved, 12
  - sk\_encrypted, 12
  - sub\_salt, 12
- f\_nano\_err
  - f\_nano\_crypto\_util.h, 26
- f\_nano\_err\_t
  - f\_nano\_crypto\_util.h, 28
- f\_nano\_key\_to\_str
  - f\_nano\_crypto\_util.h, 35
- f\_nano\_parse\_raw\_str\_to\_raw128\_t
  - f\_nano\_crypto\_util.h, 35
- f\_nano\_parse\_real\_str\_to\_raw128\_t
  - f\_nano\_crypto\_util.h, 36
- f\_nano\_raw\_to\_string
  - f\_nano\_crypto\_util.h, 36
- f\_nano\_seed\_to\_bip39
  - f\_nano\_crypto\_util.h, 37
- f\_nano\_sign\_block
  - f\_nano\_crypto\_util.h, 38
- f\_nano\_transaction\_to\_JSON
  - f\_nano\_crypto\_util.h, 38
- f\_nano\_valid\_nano\_str\_value
  - f\_nano\_crypto\_util.h, 39
- f\_nano\_value\_compare\_value
  - f\_nano\_crypto\_util.h, 39
- f\_nano\_verify\_nano\_funds
  - f\_nano\_crypto\_util.h, 40
- f\_nano\_wallet\_info\_bdy\_t, 13
  - last\_used\_wallet\_number, 13
  - max\_fee, 13
  - reserved, 14
  - wallet\_prefix, 14
  - wallet\_representative, 14
- f\_nano\_wallet\_info\_t, 14
  - body, 15
  - desc, 15
  - file\_info\_integrity, 15
  - header, 15
  - nanoseed\_hash, 16
  - version, 16
- f\_parse\_nano\_seed\_and\_bip39\_to\_JSON
  - f\_nano\_crypto\_util.h, 41
- f\_pass\_must\_have\_at\_least
  - f\_util.h, 64
- f\_passwd\_comp\_safe
  - f\_util.h, 65
- f\_random
  - f\_util.h, 66
- f\_random\_attach
  - f\_util.h, 66
- f\_read\_seed
  - f\_nano\_crypto\_util.h, 42
- f\_seed\_to\_nano\_wallet
  - f\_nano\_crypto\_util.h, 43
- f\_sel\_to\_entropy\_level
  - f\_util.h, 67
- f\_set\_nano\_file\_info
  - f\_nano\_crypto\_util.h, 43
- f\_str\_to\_hex
  - f\_util.h, 67
- f\_uint128\_t
  - f\_nano\_crypto\_util.h, 26
- f\_util.h, 58, 69
  - ENTROPY\_BEGIN, 59
  - ENTROPY\_END, 59
  - F\_ENTROPY\_TYPE\_EXCELENT, 59
  - F\_ENTROPY\_TYPE\_GOOD, 59
  - F\_ENTROPY\_TYPE\_NOT\_ENOUGH, 60
  - F\_ENTROPY\_TYPE\_NOT\_RECOMENDED, 60
  - F\_ENTROPY\_TYPE\_PARANOIC, 60
  - F\_GET\_CH\_MODE\_ANY\_KEY, 60
  - F\_GET\_CH\_MODE\_NO\_ECHO, 61
  - F\_PASS\_IS\_OUT\_OVF, 61
  - F\_PASS\_IS\_TOO\_LONG, 61
  - F\_PASS\_IS\_TOO\_SHORT, 61
  - F\_PASS\_MUST\_HAVE\_AT\_LEAST\_NONE, 61
  - F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_LO←  
WER\_CASE, 62
  - F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_NU←  
MBER, 62
  - F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_SYM←  
BOL, 62
  - F\_PASS\_MUST\_HAVE\_AT\_LEAST\_ONE\_UPP←  
ER\_CASE, 62
  - f\_convert\_to\_long\_int, 63
  - f\_get\_char\_no\_block, 63
  - f\_get\_entropy\_name, 64
  - f\_pass\_must\_have\_at\_least, 64
  - f\_passwd\_comp\_safe, 65
  - f\_random, 66
  - f\_random\_attach, 66
  - f\_sel\_to\_entropy\_level, 67
  - f\_str\_to\_hex, 67
  - f\_verify\_system\_entropy, 67
  - get\_console\_passwd, 68
  - rnd\_fn, 63
- f\_verify\_system\_entropy
  - f\_util.h, 67
- f\_write\_seed
  - f\_nano\_crypto\_util.h, 44
- f\_write\_seed\_err
  - f\_nano\_crypto\_util.h, 26
- f\_write\_seed\_err\_t
  - f\_nano\_crypto\_util.h, 29
- file\_info\_integrity
  - f\_nano\_crypto\_util.h, 48

- f\_nano\_wallet\_info\_t, 15
- get\_console\_passwd
  - f\_util.h, 68
- hash\_sk\_unencrypted
  - f\_nano\_crypto\_util.h, 48
  - f\_nano\_encrypted\_wallet\_t, 12
- header
  - f\_nano\_crypto\_util.h, 49
  - f\_nano\_wallet\_info\_t, 15
- is\_nano\_prefix
  - f\_nano\_crypto\_util.h, 45
- is\_null\_hash
  - f\_nano\_crypto\_util.h, 45
- iv
  - f\_nano\_crypto\_util.h, 49
  - f\_nano\_crypto\_wallet\_t, 10
  - f\_nano\_encrypted\_wallet\_t, 12
- last\_used\_wallet\_number
  - f\_nano\_crypto\_util.h, 49
  - f\_nano\_wallet\_info\_bdy\_t, 13
- link
  - f\_block\_transfer\_t, 8
  - f\_nano\_crypto\_util.h, 49
- MAX\_STR\_NANO\_CHAR
  - f\_nano\_crypto\_util.h, 24
- max\_fee
  - f\_nano\_crypto\_util.h, 49
  - f\_nano\_wallet\_info\_bdy\_t, 13
- NANO\_ENCRYPTED\_SEED\_FILE
  - f\_nano\_crypto\_util.h, 24
- NANO\_FILE\_WALLETS\_INFO
  - f\_nano\_crypto\_util.h, 24
- NANO\_PASSWD\_MAX\_LEN
  - f\_nano\_crypto\_util.h, 24
- NANO\_PREFIX
  - f\_nano\_crypto\_util.h, 24
- NANO\_PRIVATE\_KEY\_EXTENDED
  - f\_nano\_crypto\_util.h, 27
- NANO\_PRIVATE\_KEY
  - f\_nano\_crypto\_util.h, 26
- NANO\_PUBLIC\_KEY\_EXTENDED
  - f\_nano\_crypto\_util.h, 27
- NANO\_PUBLIC\_KEY
  - f\_nano\_crypto\_util.h, 27
- NANO\_SEED
  - f\_nano\_crypto\_util.h, 27
- nano\_base\_32\_2\_hex
  - f\_nano\_crypto\_util.h, 45
- nano\_hdr
  - f\_nano\_crypto\_util.h, 50
  - f\_nano\_crypto\_wallet\_t, 10
- nanoseed\_hash
  - f\_nano\_crypto\_util.h, 50
  - f\_nano\_wallet\_info\_t, 16
- PUB\_KEY\_EXTENDED\_MAX\_LEN
  - f\_nano\_crypto\_util.h, 25
- pk\_to\_wallet
  - f\_nano\_crypto\_util.h, 46
- preamble
  - f\_block\_transfer\_t, 8
  - f\_nano\_crypto\_util.h, 50
- prefixes
  - f\_block\_transfer\_t, 8
  - f\_nano\_crypto\_util.h, 50
- previous
  - f\_block\_transfer\_t, 8
  - f\_nano\_crypto\_util.h, 50
- REP\_XRB
  - f\_nano\_crypto\_util.h, 25
- representative
  - f\_block\_transfer\_t, 8
  - f\_nano\_crypto\_util.h, 51
- reserved
  - f\_nano\_crypto\_util.h, 51
  - f\_nano\_encrypted\_wallet\_t, 12
  - f\_nano\_wallet\_info\_bdy\_t, 14
- rnd\_fn
  - f\_util.h, 63
- SENDER\_XRB
  - f\_nano\_crypto\_util.h, 25
- STR\_NANO\_SZ
  - f\_nano\_crypto\_util.h, 25
- salt
  - f\_nano\_crypto\_util.h, 51
  - f\_nano\_crypto\_wallet\_t, 10
- seed\_block
  - f\_nano\_crypto\_util.h, 51
  - f\_nano\_crypto\_wallet\_t, 11
- signature
  - f\_block\_transfer\_t, 9
  - f\_nano\_crypto\_util.h, 51
- sk\_encrypted
  - f\_nano\_crypto\_util.h, 52
  - f\_nano\_encrypted\_wallet\_t, 12
- sodium.h, 71, 72
- sub\_salt
  - f\_nano\_crypto\_util.h, 52
  - f\_nano\_encrypted\_wallet\_t, 12
- valid\_nano\_wallet
  - f\_nano\_crypto\_util.h, 46
- valid\_raw\_balance
  - f\_nano\_crypto\_util.h, 47
- ver
  - f\_nano\_crypto\_util.h, 52
  - f\_nano\_crypto\_wallet\_t, 11
- version
  - f\_nano\_crypto\_util.h, 52
  - f\_nano\_wallet\_info\_t, 16
- wallet\_prefix



f\_nano\_crypto\_util.h, 52  
f\_nano\_wallet\_info\_bdy\_t, 14  
wallet\_representative  
f\_nano\_crypto\_util.h, 53  
f\_nano\_wallet\_info\_bdy\_t, 14  
work  
f\_block\_transfer\_t, 9  
f\_nano\_crypto\_util.h, 53  
XRB\_PREFIX  
f\_nano\_crypto\_util.h, 25