

APACHE AIRFLOW + SPARK

1. PROJECT OVERVIEW

This guide covers the Python/PySpark part of building an end-to-end data engineering project using Apache Airflow, Docker, and a Spark cluster. The project demonstrates how to orchestrate Spark jobs written in Python using Airflow's SparkSubmitOperator.

Focus: Creating a PySpark job (e.g., WordCount) and submitting it to a Spark cluster via Airflow DAG running in Docker.

2. ARCHITECTURE OVERVIEW

The setup uses Docker Compose to spin up:

- Spark Master + Workers
- Airflow Webserver + Scheduler (based on Python 3.12 image)
- PostgreSQL as Airflow metadata database
- Shared volumes for jobs/ directory between containers

Airflow DAG uses SparkSubmitOperator to submit the Python job to the Spark master (spark://spark-master:7077).

3. TECHNOLOGY STACK

Component	Technology	Role in Python Job Flow
Orchestration	Apache Airflow 2.10	DAG definition, scheduling, SparkSubmitOperator
Compute	Apache Spark (Standalone)	PySpark job execution on cluster
Language	Python 3.12+ PySpark	Spark job code (wordcountjob.py)
Containerization	Docker + Docker Compose	Unified environment for Airflow + Spark
Storage	Shared Docker Volume (jobs/)	Job scripts accessible to both Airflow & Spark
Metadata DB	PostgreSQL	Airflow task history and state

4. CREATING THE PYSARK JOB

4.1 Job Location & Structure

In the SparkingFlow project, Python jobs are placed in: jobs/python/

- Example file: jobs/python/wordcountjob.py

4.2 PySpark WordCount Job

A typical PySpark job used in the tutorial:

```

from pyspark.sql import SparkSession

spark = SparkSession.builder \
    .appName("WordCountJob") \
    .getOrCreate()

# Sample text
text = "Hello Spark Hello Python Hello Airflow Hello Docker Hello Himanshu"

# Simple word count using RDD
words = spark.sparkContext.parallelize(text.split(" "))
word_counts = words.map(lambda word: (word, 1)) \
    .reduceByKey(lambda a: {__add__}, b: a + b)

# Print results
print("=== Word Count Results ===")
for word, count in sorted(word_counts.collect()):
    print(f"{word}: {count}")

spark.stop()

```

5. SUBMITTING THE PYTHON JOB VIA AIRFLOW

5.1 DAG Structure (sparking_flow)

The main DAG typically includes:

- **start task:** PythonOperator that prints a start message
- **python_job task:** SparkSubmitOperator pointing to the Python job
- **end task:** PythonOperator that prints an end message
- Dependencies: start >> python_job >> end

5.2 SparkSubmitOperator Configuration

Key parameters used in the DAG for the Python job:

- task_id: 'python_job'
- conn_id: configured Spark connection (spark-conn)
- application: 'jobs/python/wordcountjob.py' (path inside container)
- master: 'spark://spark-master:7077'
- deploy_mode: 'client'
- executor_cores, executor_memory as needed

Important: The application path must be relative to the volume mount shared between Airflow and Spark containers.

6. KEY TECHNICAL POINTS

- Use shared Docker volumes so Airflow can see the job files and Spark can execute them.
- Ensure Java is installed in the Airflow image (required for spark-submit even for PySpark).
- Set proper SPARK_HOME and PATH in the Airflow container if needed.

- Use env_vars in SparkSubmitOperator if job needs environment variables.
- For production, consider packaging dependencies or using virtualenvs with --py-files.
- Test the job manually first with spark-submit before wiring it into Airflow.

7. COMMON ISSUES & TROUBLESHOOTING

- JAVA_HOME not set → Install OpenJDK in Airflow Dockerfile and set ENV JAVA_HOME.
- File not found → Check volume mounts in docker-compose.yml (jobs/ → /opt/spark/jobs).
- Connection error → Verify spark://master:7077 is reachable from Airflow container (use same network).
- Permission issues → Ensure the airflow user has read access to job files.

8. SKILLS DEMONSTRATED

- Writing and packaging simple PySpark applications (DataFrame API)
- Integrating PySpark jobs with Apache Airflow using SparkSubmitOperator
- Docker Compose multi-service architecture (Airflow + Spark Master/Workers)
- Volume mounting strategies for job code sharing
- Basic orchestration patterns (start → submit job)
- Understanding spark-submit mechanics from Airflow context

9. LIVE EXECUTION

Below are screenshots from actual running SparkingFlow environment, confirming successful implementation of the Python job submission flow.




Figure 1: DAG Graph View - start (PythonOperator) → python_job (SparkSubmitOperator) → end




Figure 2: Successful python_job Logs - WordCountJob completed with expected output (Airflow: 1, Data: 1, Docker: 1, etc.)

The screenshot shows the 'Edit Connection' form for 'spark-conn'. The form includes the following fields:

- Connection id ***: spark-conn
- Connection Type ***: Spark
- Description**: spark cluster connection details
- Host**: spark://spark-master-1
- Port**: 7077
- YARN queue**: Default YARN queue to use
- Deploy mode**: client
- Spark binary**: spark-submit
- Kubernetes namespace**
- Principal**
- Keytab**: <base64 encoded Keytab Content>

Figure 3: Spark Connection Configuration (spark-conn) - Host: spark://...spark-master-1, Port 7077, Deploy Mode: client

