maintaining the integrity of fresh

Duraflex

INSULATED
TRANSPORT PRODUCTS
REFRIGERATED TRANSPORTATION SPECIALISTS

light weight, durable, flexible, user friendly bulkhead

Features:

- 2" Flexible core and laminated skin design for rigidity and durability
- Ability to bend and flex when hit.
- 25% lighter than the standard 3" construction, making the DuraFlex easier to maneuver throughout the trailer
- 50 mil UHMW Scuff Plate protects bottom from non-skid floors with 5 Year Warranty against wear
- Entire exterior is easy to clean
- Rips and tears are repaired within minutes
- Flush mounted hardware
- Available in multiple configurations to fit most applications
- 10 Year Warranty against delamination of the core

www.insulatedtransportproducts.com

(800) 233.6180
FAX (706) 882.9536

Maximize use of interior trailer space with our many configurations.

Available Options

Fan Kit

As an alternative to a rear evaporator, the Two-Temp Fan Kit allows temperature control in the second compartment. Specifications include: 10" diameter; 10 prong blade; 12 volt, 6000 hour brush life motor; displacement of 650 CFM; temperature range from -40° F to +80° F, and an On/Off switch.

Vent Kit

10" Diameter Vent with Adjustable Velcro Flap provides controlled air flow to rear compartment or return air flow when installed with a Fan Kit.

Two-Way Hinge

Webbing reinforced on top and bottom, the two-way hinge allows entry from both compartments and prevents damage.

E or F Straps

Installed with flush mounted hardware and comes with a UHMW abrasion guard to protect against premature wear from the track.



Cold Draw Ventilation System

As an alternative to a rear evaporator, the Cold Draw is mounted in the upper corner of the trailer. Air is drawn into the center of the compartment by a 12 volt motor and distributed across the ceiling to maintain a constant temperature.

Abrasion Plate

Available 2' and 4' high, 100 mil HDPE offers protection from forklift and pallet damage. Installed with flush mounted hardware.

Custom Labeling Up to 3" High

Identify your bulkhead with your company name and trailer number.