

1 MotionBlur

1.1 总体流程

1.1.1 渲染前，保存当前帧的时间

```
// Remember the frame the scene was at so we can restore it later.
originalTime = ManimControl::currentTime();
```

1.1.2 渲染后，恢复最初的时间值

```
void liqRibTranslator::postActions(const MString& originalLayer__)
{
    // return to the frame we were at before we ran the animation
    MGlobal::viewFrame (originalTime);
    ...
}
```

1.1.3 每一帧

```
liqRibTranslator::processOneFrame(...)
{
    // calculate sampling time
    calculateSamplingTime(scanTime); //计算采样的时间点

    ...
    if( liqglo.doCameraMotion || liqglo_.liqglo_doMotion || liqglo_.liqglo_doDef )
    {
        for ( int msampleOn = 0; msampleOn < liqglo_.liqglo_motionSamples; msampleOn++ ) /*沿时间轴采样*/
        {
            scanScene__( liqglo_.liqglo_sampleTimes[ msampleOn ] , msampleOn );
        } else {
            liqglo_.liqglo_sampleTimes[ 0 ] = scanTime;
            liqglo_.liqglo_sampleTimesOffsets[ 0 ] = 0;
            scanScene__( scanTime, 0 );
        }
        ....
    }
}

MStatus liqRibTranslator::scanScene__(float lframe, int sample )
{
    MTime mt( ( double )lframe, MTime::uiUnit() );
    if( MGlobal::viewFrame(mt) == MS::kSuccess ) //向前推进时间轴，以采样
    {...}

    ...
    scanSceneNodes(...); // 调用htable->insert(...);
}

liqRibTranslator::scanSceneNodes()
{
    ...
    if( currentNode.hasFn( MFn::kNurbsSurface )
        || currentNode.hasFn( MFn::kMesh )
        || currentNode.hasFn( MFn::kParticle )
        || currentNode.hasFn( MFn::kLocator )
```

```

        | currentNode.hasFn( MFn::kSubdiv )
        | (currentNode.hasFn( MFn::kPfxHair ) && !currentNode.hasFn( MFn::kPfxGeometry ))
        | currentNode.hasFn( MFn::kPfxToon )
        | currentNode.hasFn( MFn::kImplicitSphere )
        | currentNode.hasFn( MFn::kPluginShape ) ) // include plugin shapes as placeholders
    {
        if( ( sample > 0 ) && isObjectMotionBlur( path ))
            htable->insert( path, lframe, sample, MRT_Unknown, count++ );
        else
            htable->insert( path, lframe, 0, MRT_Unknown, count++ );
    }
    ...
}


int liqRibHT::insert( MDagPath &path, double /*lframe*/, int sample,
    ObjectType objType,
    int CountID,
    MMatrix *matrix,
    const MString instanceStr,
    int particleId )
{
    node->set( path, sample, objType, particleId );
}

void liqRibNode::set( const MDagPath &path, int sample, ObjectType objType, int particleId )
{
    // Create a new RIB object for the given path
    MObject obj( path.node() );
    liqRibObjPtr no( new liqRibObj( path, objType ) );
    LIQDEBUGPRINTF( "-> creating rib object for reference\n");
    no->ref();

    if( !objects[ sample ] ) {
        objects[ sample ] = no; //建立liqRibNode::object[i], 对path的第i次采样的数据, 记录在object[i]里
    } else {
        objects[ sample ]->unref();
        objects[ sample ] = no; //建立liqRibNode::object[i], 对path的第i次采样的数据, 记录在object[i]里
    }
}

```

1.2 Transform Motion Blur



```

liqRibObj::liqRibObj( const MDagPath &path, ObjectType objType )
{
    MFnDagNode nodeFn( obj );


    // Store the matrices for all instances of this node at this time
    // so that they can be used to determine if this node's transformation
    // is animated. This information is used for doing motion blur.
    MDagPathArray instanceArray;
    nodeFn.getAllPaths( instanceArray );
    unsigned last( instanceArray.length() );
}

```

```
instanceMatrices.resize( last );
for( unsigned i( 0 ); i < last; i++ )
    instanceMatrices[ i ] = instanceArray[ i ].inclusiveMatrix();
}
```

如何取transform motion的数据, 见elvishray::Renderer::exportOneObject()

1.3 Deform Motion Blur



```
liqRibMeshData::liqRibMeshData( MObject mesh )
{
    pointsPointerPair.set( "P", rPoint, numPoints );
    normalsPointerPair.set( "N", rNormal,...);
    pFaceVertexPointerPair.set( "st", rFloat, numFaceVertices, 2 );
    pFaceVertexSPointer.set( "u", rFloat, numFaceVertices );
    pFaceVertexTPointer.set( "v", rFloat, numFaceVertices );

    // Add tokens to array and clean up after
    tokenPointerArray.push_back( pointsPointerPair );
    tokenPointerArray.push_back( normalsPointerPair );
    tokenPointerArray.insert( tokenPointerArray.end(), UVSetsArray.begin(), UVSetsArray.end() );
    tokenPointerArray.push_back( pFaceVertexSPointer );
    tokenPointerArray.push_back( pFaceVertexTPointer );

    addAdditionalSurfaceParameters( mesh );
}
```

```
void liqRibData::addAdditionalSurfaceParameters( MObject node )
{
    // find the attributes
    MStringArray floatAttributesFound = findAttributesByPrefix( "rmanF", nodeFn );
    MStringArray pointAttributesFound = findAttributesByPrefix( "rmanP", nodeFn );
    MStringArray vectorAttributesFound = findAttributesByPrefix( "rmanV", nodeFn );
    MStringArray normalAttributesFound = findAttributesByPrefix( "rmanN", nodeFn );
    MStringArray colorAttributesFound = findAttributesByPrefix( "rmanC", nodeFn );
    MStringArray stringAttributesFound = findAttributesByPrefix( "rmanS", nodeFn );

    □ 于上面的每一个□量,先填入局部□量liqTokenPointer tokenPointerPair;然后
    tokenPointerArray.push_back( tokenPointerPair );

}
```

如何取deform motion的数据, 见elvishray::Renderer::exportOneGeometry_Mesh()