

# Compressive Deformation of Honeycomb Structure: A Discrete Simulation Approach

---

Tianyi Wang, Zhicheng Ren

# Background

1. Low weight-to-strength ratio
2. High energy absorption capacity
3. Cost-effective and crashworthy

## Applications

- Shock absorbers in **airplanes** and **high-speed trains**
- Absorbs energy during crashes via **plastic strain energy**

## Impact Effectiveness

- Superior performance in **out-of-plane impact**
- Effective energy absorption through **compressive strokes**

- Outstanding mechanical properties with reduced material usage
- Widely adopted in numerous promising applications in the fields of:
  - Architecture
  - Aerospace
  - Medical implant
  - 3d printing

# Project overview

## Goal:











- Simulate the **compressive deformation** of honeycomb structures using a discrete simulation approach.
- Analyze the mechanical behavior of honeycomb structures under **various applied loads**.

## Method:

- Based on **2D** discrete elastic beam model.
- Implicit solution using Newton-Raphson scheme.

## Assumption:


- Uniform density (and other mechanical properties) throughout the structure.
- Negligible viscous damping from air.
- External forces are applied **gradually** to simulate compression.



# Model setup

## Helper functions:

- `generate_hexagonal_nodes(rows, cols, edge_length)`
- `generate_rods(sorted_nodes, rows, cols)`
- `generate_flexible_nodes(rods, structure_nodes, nv_rod)`



- `calculate_curvature(connections, nodes)`: store the initial curvature for each main node in the honeycomb structure.

## Simulation parameters:

- Time Step:  $dt = 1 \times 10^{-3}$  seconds
- Total Time: 2 seconds

## Material properties:

- Density:  $7000 \text{ kg/m}^3$  (typical for metals)
- Total mass: 20 kg
- Young's modulus (E): 300 GPa




## Boundary Conditions:

- Bottom nodes are pinned

## Loading:


- Total maximum load: -20 kN (downward)
- Load is distributed evenly across top nodes
- Force increases linearly with time (starts from 0 and reaches the maximum in the end)

# Model setup




# Simulation results


Simulation Time: 0.000s



Simulation Time: 0.000s



Simulation Time: 0.000s



# Simulation results

We also played with some different loadings...

# Final analysis

1. Final compressed ratio vs. Cell counts (for a given total weight, it seems that more cells means more strength)
2. We only tested a limited number of models, not enough to get a strong conclusion
3. Future work could involve improving code efficiency(it's taking really long to run one larger than  $7*7$ )



# Reference

1. Aminanda, Y., B. Castanié, J.J. Barrau, et al. "Experimental Analysis and Modeling of the Crushing of Honeycomb Cores." *Applied Composite Materials*, vol. 12, 2005, pp. 213–227.
2. Galehdari, Seyed, et al. "Low Velocity Impact and Quasi-Static in-Plane Loading on a Graded Honeycomb Structure; Experimental, Analytical and Numerical Study." *Aerospace Science and Technology*, vol. 47, 2015, pp. 10-1016
3. Mousanezhad, D., S. Babaei, H. Ebrahimi, et al. "Hierarchical Honeycomb Auxetic Metamaterials." *Scientific Reports*, vol. 5, 2016, article 18306. Nature, <https://doi.org/10.1038/srep18306>.
4. Partovi Meran, Ahmad, et al. "Numerical and Experimental Study of Crashworthiness Parameters of Honeycomb Structures." *Thin-Walled Structures*, vol. 78, May 2014, pp. 87–94.
5. Papka, S.D., and S. Kyriakides. "Experiments and Full-Scale Numerical Simulations of In-Plane Crushing of a Honeycomb." *Acta Materialia*, vol. 46, no. 8, 1 May 1998, pp. 2765–2776.
6. Qi, Chang, et al. "Advanced Honeycomb Designs for Improving Mechanical Properties: A Review." *Composites Part B: Engineering*, vol. 227, 15 Dec. 2021, article 109393.
7. Yamashita, M., and M. Gotoh. "Impact Behavior of Honeycomb Structures with Various Cell Specifications—Numerical Simulation and Experiment." *International Journal of Impact Engineering*, vol. 32, nos. 1–4, Dec. 2005, pp. 618–630.