



IBM Developer SKILLS NETWORK

Area Plots, Histograms, and Bar Plots

Estimated time needed: **30** minutes

Objectives

After completing this lab you will be able to:

- Create additional labs namely area plots, histogram and bar charts

Table of Contents

1. [Exploring Datasets with *pandas*](#0)
2. [Downloading and Prepping Data](#2)
3. [Visualizing Data using Matplotlib](#4)
4. [Area Plots](#6)
5. [Histograms](#8)
6. [Bar Charts](#10)

Exploring Datasets with *pandas* and Matplotlib

Toolkits: The course heavily relies on [pandas](http://pandas.pydata.org/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01) (http://pandas.pydata.org/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01) and [Numpy](http://www.numpy.org/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01) (http://www.numpy.org/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01) for data wrangling, analysis, and visualization. The primary plotting library that we are exploring in the course is [Matplotlib](http://matplotlib.org/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01) (http://matplotlib.org/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01).

Dataset: Immigration to Canada from 1980 to 2013 - [International migration flows to and from selected countries - The 2015 revision](http://www.un.org/en/development/desa/population/migration/data/empirical2/migrationflows.shtml?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01) (http://www.un.org/en/development/desa/population/migration/data/empirical2/migrationflows.shtml?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01) from United Nation's website.


The dataset contains annual data on the flows of international migrants as recorded by the countries of destination. The data presents both inflows and outflows according to the place of birth, citizenship or place of previous / next residence both for foreigners and nationals. For this lesson, we will focus on the Canadian Immigration data.

Downloading and Prepping Data

The first thing we'll do is install **openpyxl** (formerly **xlrd**), a module that *pandas* requires to read Excel files.

In [2]:

```
!mamba install openpyxl==3.0.9 -y
```



mamba (0.15.3) supported by @QuantStack

GitHub: <https://github.com/mamba-org/mamba>

Twitter: <https://twitter.com/QuantStack>

Looking for: ['openpyxl==3.0.9']

```
pkgs/main/linux-64      Using cache
pkgs/main/noarch        Using cache
pkgs/r/linux-64         Using cache
pkgs/r/noarch           Using cache
```

Pinned packages:

```
- python 3.7.*
```

Transaction

Prefix: /home/jupyterlab/conda/envs/python

All requested packages already installed

Import Primary Modules. The first thing we'll do is import two key data analysis modules: `pandas` and `numpy`.

In [3]:

```
import numpy as np # useful for many scientific computing in Python
import pandas as pd # primary data structure library
```

Download the Canadian Immigration dataset and read it into a *pandas* dataframe.

In [4]:

```
df_can = pd.read_excel(
    'https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-DV0101EN-SkillsNetwork/Data%20Files/Canada.xlsx',
    sheet_name='Canada by Citizenship',
    skiprows=range(20),
    skipfooter=2)
print('Data downloaded and read into a dataframe!')
```

Data downloaded and read into a dataframe!

Let's take a look at the first five items in our dataset.

In [5]:

```
df_can.head()
```

Out[5]:

	Type	Coverage	OdName	AREA	AreaName	REG	RegName	DEV	DevName
0	Immigrants	Foreigners	Afghanistan	935	Asia	5501	Southern Asia	902	Developing regions
1	Immigrants	Foreigners	Albania	908	Europe	925	Southern Europe	901	Developed regions
2	Immigrants	Foreigners	Algeria	903	Africa	912	Northern Africa	902	Developing regions
3	Immigrants	Foreigners	American Samoa	909	Oceania	957	Polynesia	902	Developing regions
4	Immigrants	Foreigners	Andorra	908	Europe	925	Southern Europe	901	Developed regions

5 rows × 43 columns

Let's find out how many entries there are in our dataset.

In [6]:

```
# print the dimensions of the dataframe
print(df_can.shape)
```

(195, 43)

Clean up data. We will make some modifications to the original dataset to make it easier to create our visualizations. Refer to [Introduction to Matplotlib](#) and [Line Plots](#) lab for the rational and detailed description of the changes.

1. Clean up the dataset to remove columns that are not informative to us for visualization (eg. Type, AREA, REG).

In [7]:

```
df_can.drop(['AREA', 'REG', 'DEV', 'Type', 'Coverage'], axis=1, inplace=True)

# Let's view the first five elements and see how the dataframe was changed
df_can.head()
```

Out[7]:

	OdName	AreaName	RegName	DevName	1980	1981	1982	1983	1984	1985	...	200
0	Afghanistan	Asia	Southern Asia	Developing regions	16	39	39	47	71	340	...	29
1	Albania	Europe	Southern Europe	Developed regions	1	0	0	0	0	0	...	14
2	Algeria	Africa	Northern Africa	Developing regions	80	67	71	69	63	44	...	36
3	American Samoa	Oceania	Polynesia	Developing regions	0	1	0	0	0	0	...	
4	Andorra	Europe	Southern Europe	Developed regions	0	0	0	0	0	0	...	

5 rows × 38 columns

Notice how the columns Type, Coverage, AREA, REG, and DEV got removed from the dataframe.

2. Rename some of the columns so that they make sense.

In [8]:

```
df_can.rename(columns={'OdName': 'Country', 'AreaName': 'Continent', 'RegName': 'Region'},
inplace=True)

# Let's view the first five elements and see how the dataframe was changed
df_can.head()
```

Out[8]:

	Country	Continent	Region	DevName	1980	1981	1982	1983	1984	1985	...	200
0	Afghanistan	Asia	Southern Asia	Developing regions	16	39	39	47	71	340	...	297
1	Albania	Europe	Southern Europe	Developed regions	1	0	0	0	0	0	...	145
2	Algeria	Africa	Northern Africa	Developing regions	80	67	71	69	63	44	...	361
3	American Samoa	Oceania	Polynesia	Developing regions	0	1	0	0	0	0	...	
4	Andorra	Europe	Southern Europe	Developed regions	0	0	0	0	0	0	...	

5 rows × 38 columns

Notice how the column names now make much more sense, even to an outsider.

3. For consistency, ensure that all column labels of type string.

In [9]:

```
# Let's examine the types of the column labels
all(isinstance(column, str) for column in df_can.columns)
```

Out[9]:

False

Notice how the above line of code returned *False* when we tested if all the column labels are of type **string**. So let's change them all to **string** type.

In [10]:

```
df_can.columns = list(map(str, df_can.columns))

# Let's check the column labels types now
all(isinstance(column, str) for column in df_can.columns)
```

Out[10]:

True

4. Set the country name as index - useful for quickly looking up countries using .loc method.

In [11]:

```
df_can.set_index('Country', inplace=True)

# Let's view the first five elements and see how the dataframe was changed
df_can.head()
```

Out[11]:

	Continent	Region	DevName	1980	1981	1982	1983	1984	1985	1986	...
Country											
Afghanistan	Asia	Southern Asia	Developing regions	16	39	39	47	71	340	496	...
Albania	Europe	Southern Europe	Developed regions	1	0	0	0	0	0	1	...
Algeria	Africa	Northern Africa	Developing regions	80	67	71	69	63	44	69	...
American Samoa	Oceania	Polynesia	Developing regions	0	1	0	0	0	0	0	...
Andorra	Europe	Southern Europe	Developed regions	0	0	0	0	0	0	2	...

5 rows × 37 columns



Notice now the country names now serve as indices.

5. Add total column.

In [12]:

```
df_can['Total'] = df_can.sum(axis=1)
```

```
# Let's view the first five elements and see how the dataframe was changed
df_can.head()
```

/home/jupyterlab/conda/envs/python/lib/python3.7/site-packages/ipykernel_launcher.py:1: FutureWarning: Dropping of nuisance columns in DataFrame reductions (with 'numeric_only=None') is deprecated; in a future version this will raise TypeError. Select only valid columns before calling the reduction.

"""Entry point for launching an IPython kernel.

Out[12]:

	Continent	Region	DevName	1980	1981	1982	1983	1984	1985	1986	...
Country											
Afghanistan	Asia	Southern Asia	Developing regions	16	39	39	47	71	340	496	...
Albania	Europe	Southern Europe	Developed regions	1	0	0	0	0	0	1	...
Algeria	Africa	Northern Africa	Developing regions	80	67	71	69	63	44	69	...
American Samoa	Oceania	Polynesia	Developing regions	0	1	0	0	0	0	0	...
Andorra	Europe	Southern Europe	Developed regions	0	0	0	0	0	0	2	...

5 rows × 38 columns

Now the dataframe has an extra column that presents the total number of immigrants from each country in the dataset from 1980 - 2013. So if we print the dimension of the data, we get:

In [13]:

```
print('data dimensions:', df_can.shape)
```

data dimensions: (195, 38)

So now our dataframe has 38 columns instead of 37 columns that we had before.

In [14]:

```
# finally, let's create a list of years from 1980 - 2013
# this will come in handy when we start plotting the data
years = list(map(str, range(1980, 2014)))

years
```

Out[14]:

```
['1980',
 '1981',
 '1982',
 '1983',
 '1984',
 '1985',
 '1986',
 '1987',
 '1988',
 '1989',
 '1990',
 '1991',
 '1992',
 '1993',
 '1994',
 '1995',
 '1996',
 '1997',
 '1998',
 '1999',
 '2000',
 '2001',
 '2002',
 '2003',
 '2004',
 '2005',
 '2006',
 '2007',
 '2008',
 '2009',
 '2010',
 '2011',
 '2012',
 '2013']
```

Visualizing Data using Matplotlib

Import the `matplotlib` library.

In [15]:

```
# use the inline backend to generate the plots within the browser
%matplotlib inline

import matplotlib as mpl
import matplotlib.pyplot as plt

mpl.style.use('ggplot') # optional: for ggplot-like style

# check for latest version of Matplotlib
print('Matplotlib version: ', mpl.__version__) # >= 2.0.0
```

Matplotlib version: 3.5.0

Area Plots

In the last module, we created a line plot that visualized the top 5 countries that contributed the most immigrants to Canada from 1980 to 2013. With a little modification to the code, we can visualize this plot as a cumulative plot, also known as a **Stacked Line Plot** or **Area plot**.

In [16]:

```
df_can.sort_values(['Total'], ascending=False, axis=0, inplace=True)

# get the top 5 entries
df_top5 = df_can.head()

# transpose the dataframe
df_top5 = df_top5[years].transpose()

df_top5.head()
```

Out[16]:

Country	India	China	United Kingdom of Great Britain and Northern Ireland	Philippines	Pakistan
1980	8880	5123	22045	6051	978
1981	8670	6682	24796	5921	972
1982	8147	3308	20620	5249	1201
1983	7338	1863	10015	4562	900
1984	5704	1527	10170	3801	668


Area plots are stacked by default. And to produce a stacked area plot, each column must be either all positive or all negative values (any NaN, i.e. not a number, values will default to 0). To produce an unstacked plot, set parameter `stacked` to value `False`.

In [19]:

```
# Let's change the index values of df_top5 to type integer for plotting
df_top5.index = df_top5.index.map(int)
df_top5.plot(kind='area',
              stacked=False,
              figsize=(20, 10)) # pass a tuple (x, y) size

plt.title('Immigration Trend of Top 5 Countries')
plt.ylabel('Number of Immigrants')
plt.xlabel('Years')

plt.show()
```




The unstacked plot has a default transparency (alpha value) at 0.5. We can modify this value by passing in the `alpha` parameter.

In [20]:

```
df_top5.plot(kind='area',
              alpha=0.25, # 0 - 1, default value alpha = 0.5
              stacked=False,
              figsize=(20, 10))

plt.title('Immigration Trend of Top 5 Countries')
plt.ylabel('Number of Immigrants')
plt.xlabel('Years')

plt.show()
```



Two types of plotting

As we discussed in the video lectures, there are two styles/options of plotting with `matplotlib`, plotting using the Artist layer and plotting using the scripting layer.

****Option 1: Scripting layer (procedural method) - using `matplotlib.pyplot` as `'plt'` ****

You can use `plt` i.e. `matplotlib.pyplot` and add more elements by calling different methods procedurally; for example, `plt.title(...)` to add title or `plt.xlabel(...)` to add label to the x-axis.

```
# Option 1: This is what we have been using so far
df_top5.plot(kind='area', alpha=0.35, figsize=(20, 10))
plt.title('Immigration trend of top 5 countries')
plt.ylabel('Number of immigrants')
plt.xlabel('Years')
```

****Option 2: Artist layer (Object oriented method) - using an `Axes` instance from Matplotlib (preferred) ****

You can use an `Axes` instance of your current plot and store it in a variable (eg. `ax`). You can add more elements by calling methods with a little change in syntax (by adding " `set_`" to the previous methods). For example, use `ax.set_title()` instead of `plt.title()` to add title, or `ax.set_xlabel()` instead of `plt.xlabel()` to add label to the x-axis.

This option sometimes is more transparent and flexible to use for advanced plots (in particular when having multiple plots, as you will see later).

In this course, we will stick to the **scripting layer**, except for some advanced visualizations where we will need to use the **artist layer** to manipulate advanced aspects of the plots.


In [21]:

```
# option 2: preferred option with more flexibility
ax = df_top5.plot(kind='area', alpha=0.35, figsize=(20, 10))

ax.set_title('Immigration Trend of Top 5 Countries')
ax.set_ylabel('Number of Immigrants')
ax.set_xlabel('Years')
```

Out[21]:

Text(0.5, 0, 'Years')



Question: Use the scripting layer to create a stacked area plot of the 5 countries that contributed the least to immigration to Canada **from** 1980 to 2013. Use a transparency value of 0.45.

In [24]:

```
### type your answer here
```

```
# get the 5 countries with the least contribution
```

```
df_least5 = df_can.tail(5)
```

```
# transpose the dataframe
```

```
df_least5 = df_least5[years].transpose()
```

```
df_least5.head()
```

```
df_least5.index = df_least5.index.map(int) # Let's change the index values of df_least5  
to type integer for plotting
```


```
df_least5.plot(kind='area', alpha=0.45, figsize=(20, 10))
```

```
plt.title('Immigration Trend of 5 Countries with Least Contribution to Immigration')
```

```
plt.ylabel('Number of Immigrants')
```

```
plt.xlabel('Years')
```

```
plt.show()
```



[Click here for a sample python solution](#)

Question: Use the artist layer to create an unstacked area plot of the 5 countries that contributed the least to immigration to Canada **from** 1980 to 2013. Use a transparency value of 0.55.

In [25]:

```
### type your answer here
```

```
# get the 5 countries with the least contribution
df_least5 = df_can.tail(5)
```

```
# transpose the dataframe
df_least5 = df_least5[years].transpose()
```

```
df_least5.head()
```


```
df_least5.index = df_least5.index.map(int) # Let's change the index values of df_least5
to type integer for plotting
```

```
ax = df_least5.plot(kind='area', alpha=0.55, stacked=False, figsize=(20, 10))
```

```
ax.set_title('Immigration Trend of 5 Countries with Least Contribution to Immigration')
ax.set_ylabel('Number of Immigrants')
ax.set_xlabel('Years')
```

Out[25]:

```
Text(0.5, 0, 'Years')
```



[Click here for a sample python solution](#)

Histograms

A histogram is a way of representing the *frequency* distribution of numeric dataset. The way it works is it partitions the x-axis into *bins*, assigns each data point in our dataset to a bin, and then counts the number of data points that have been assigned to each bin. So the y-axis is the frequency or the number of data points in each bin. Note that we can change the bin size and usually one needs to tweak it so that the distribution is displayed nicely.

Question: What is the frequency distribution of the number (population) of new immigrants from the various countries to Canada in 2013?

Before we proceed with creating the histogram plot, let's first examine the data split into intervals. To do this, we will use **Numpy's** `histogram` method to get the bin ranges and frequency counts as follows:

In [26]:

```
# Let's quickly view the 2013 data
df_can['2013'].head()
```

Out[26]:

```
Country
India          33087
China          34129
United Kingdom of Great Britain and Northern Ireland    5827
Philippines    29544
Pakistan       12603
Name: 2013, dtype: int64
```

In [27]:

```
# np.histogram returns 2 values
count, bin_edges = np.histogram(df_can['2013'])

print(count) # frequency count
print(bin_edges) # bin ranges, default = 10 bins
```

```
[178  11   1   2   0   0   0   0   1   2]
[  0.   3412.9  6825.8 10238.7 13651.6 17064.5 20477.4 23890.3 27303.2
 30716.1 34129. ]
```

By default, the `histogram` method breaks up the dataset into 10 bins. The figure below summarizes the bin ranges and the frequency distribution of immigration in 2013. We can see that in 2013:

- 178 countries contributed between 0 to 3412.9 immigrants
- 11 countries contributed between 3412.9 to 6825.8 immigrants
- 1 country contributed between 6285.8 to 10238.7 immigrants, and so on..

	Bin 1	Bin 2	Bin 3	Bin 4	Bin 5	Bin 6	Bin 7	Bin 8	Bin 9	Bin 10
Range	0. to 3412.9	3412.9 to 6825.8	6825.8 to 10238.7	10238.7 to 13651.6	13651.6 to 17064.5	17064.5 to 20477.4	20477.4 to 23890.3	23890.3 to 27303.2	27303.2 to 30716.1	30716.1 to 34129.
Frequency	178	11	1	2	0	0	0	0	1	2


We can easily graph this distribution by passing `kind=hist` to `plot()` .

In [28]:

```
df_can['2013'].plot(kind='hist', figsize=(8, 5))

# add a title to the histogram
plt.title('Histogram of Immigration from 195 Countries in 2013')
# add y-label
plt.ylabel('Number of Countries')
# add x-label
plt.xlabel('Number of Immigrants')

plt.show()
```



In the above plot, the x-axis represents the population range of immigrants in intervals of 3412.9. The y-axis represents the number of countries that contributed to the aforementioned population.

Notice that the x-axis labels do not match with the bin size. This can be fixed by passing in a `xticks` keyword that contains the list of the bin sizes, as follows:


In [29]:

```
# 'bin_edges' is a list of bin intervals
count, bin_edges = np.histogram(df_can['2013'])

df_can['2013'].plot(kind='hist', figsize=(8, 5), xticks=bin_edges)

plt.title('Histogram of Immigration from 195 countries in 2013') # add a title to the h
istogram
plt.ylabel('Number of Countries') # add y-label
plt.xlabel('Number of Immigrants') # add x-label

plt.show()
```



Side Note: We could use `df_can['2013'].plot.hist()`, instead. In fact, throughout this lesson, using `some_data.plot(kind='type_plot', ...)` is equivalent to `some_data.plot.type_plot(...)`. That is, passing the type of the plot as argument or method behaves the same.

See the *pandas* documentation for more info <http://pandas.pydata.org/pandas-docs/stable/generated/pandas.Series.plot.html> (http://pandas.pydata.org/pandas-docs/stable/generated/pandas.Series.plot.html?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01).

We can also plot multiple histograms on the same plot. For example, let's try to answer the following questions using a histogram.

Question: What is the immigration distribution for Denmark, Norway, and Sweden for years 1980 - 2013?

In [30]:

```
# Let's quickly view the dataset
df_can.loc[['Denmark', 'Norway', 'Sweden'], years]
```

Out[30]:

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	...	2004	2005	200
Country														
Denmark	272	293	299	106	93	73	93	109	129	129	...	89	62	10
Norway	116	77	106	51	31	54	56	80	73	76	...	73	57	5
Sweden	281	308	222	176	128	158	187	198	171	182	...	129	205	13


3 rows × 34 columns

In [31]:

```
# generate histogram
df_can.loc[['Denmark', 'Norway', 'Sweden'], years].plot.hist()
```

Out[31]:

<AxesSubplot:ylabel='Frequency'>



That does not look right!

Don't worry, you'll often come across situations like this when creating plots. The solution often lies in how the underlying dataset is structured.

Instead of plotting the population frequency distribution of the population for the 3 countries, *pandas* instead plotted the population frequency distribution for the years .

This can be easily fixed by first transposing the dataset, and then plotting as shown below.

In [32]:

```
# transpose dataframe
df_t = df_can.loc[['Denmark', 'Norway', 'Sweden'], years].transpose()
df_t.head()
```

Out[32]:


Country	Denmark	Norway	Sweden
1980	272	116	281
1981	293	77	308
1982	299	106	222
1983	106	51	176
1984	93	31	128

In [33]:

```
# generate histogram
df_t.plot(kind='hist', figsize=(10, 6))

plt.title('Histogram of Immigration from Denmark, Norway, and Sweden from 1980 - 2013')
plt.ylabel('Number of Years')
plt.xlabel('Number of Immigrants')

plt.show()
```



Let's make a few modifications to improve the impact and aesthetics of the previous plot:

- increase the bin size to 15 by passing in `bins` parameter;
- set transparency to 60% by passing in `alpha` parameter;
- label the x-axis by passing in `x-label` parameter;
- change the colors of the plots by passing in `color` parameter.


In [34]:

```
# Let's get the x-tick values
count, bin_edges = np.histogram(df_t, 15)

# un-stacked histogram
df_t.plot(kind='hist',
          figsize=(10, 6),
          bins=15,
          alpha=0.6,
          xticks=bin_edges,
          color=['coral', 'darkslateblue', 'mediumseagreen']
        )

plt.title('Histogram of Immigration from Denmark, Norway, and Sweden from 1980 - 2013')
plt.ylabel('Number of Years')
plt.xlabel('Number of Immigrants')

plt.show()
```



Tip: For a full listing of colors available in Matplotlib, run the following code in your python shell:

```
import matplotlib
for name, hex in matplotlib.colors.names.items():
    print(name, hex)
```

If we do not want the plots to overlap each other, we can stack them using the `stacked` parameter. Let's also adjust the min and max x-axis labels to remove the extra gap on the edges of the plot. We can pass a tuple (min,max) using the `xlim` parameter, as show below.


In [35]:

```
count, bin_edges = np.histogram(df_t, 15)
xmin = bin_edges[0] - 10 # first bin value is 31.0, adding buffer of 10 for aestheti
c purposes
xmax = bin_edges[-1] + 10 # Last bin value is 308.0, adding buffer of 10 for aestheti
c purposes

# stacked Histogram
df_t.plot(kind='hist',
          figsize=(10, 6),
          bins=15,
          xticks=bin_edges,
          color=['coral', 'darkslateblue', 'mediumseagreen'],
          stacked=True,
          xlim=(xmin, xmax)
        )

plt.title('Histogram of Immigration from Denmark, Norway, and Sweden from 1980 - 2013')
plt.ylabel('Number of Years')
plt.xlabel('Number of Immigrants')

plt.show()
```



Question: Use the scripting layer to display the immigration distribution for Greece, Albania, and Bulgaria for years 1980 - 2013? Use an overlapping plot with 15 bins and a transparency value of 0.35.

In [36]:

```
### type your answer here
```

```
# create a dataframe of the countries of interest (cof)
```

```
df_cof = df_can.loc[['Greece', 'Albania', 'Bulgaria'], years]
```

```
# transpose the dataframe
```

```
df_cof = df_cof.transpose()
```

```
# Let's get the x-tick values
```

```
count, bin_edges = np.histogram(df_cof, 15)
```

```
# Un-stacked Histogram
```


```
df_cof.plot(kind='hist',
            figsize=(10, 6),
            bins=15,
            alpha=0.35,
            xticks=bin_edges,
            color=['coral', 'darkslateblue', 'mediumseagreen'])
```

```
plt.title('Histogram of Immigration from Greece, Albania, and Bulgaria from 1980 - 2013')
```

```
plt.ylabel('Number of Years')
```

```
plt.xlabel('Number of Immigrants')
```

```
plt.show()
```



[Click here for a sample python solution](#)

Bar Charts (Dataframe)

A bar plot is a way of representing data where the *length* of the bars represents the magnitude/size of the feature/variable. Bar graphs usually represent numerical and categorical variables grouped in intervals.

To create a bar plot, we can pass one of two arguments via `kind` parameter in `plot()` :

- `kind=bar` creates a *vertical* bar plot
- `kind=barh` creates a *horizontal* bar plot

Vertical bar plot

In vertical bar graphs, the x-axis is used for labelling, and the length of bars on the y-axis corresponds to the magnitude of the variable being measured. Vertical bar graphs are particularly useful in analyzing time series data. One disadvantage is that they lack space for text labelling at the foot of each bar.

Let's start off by analyzing the effect of Iceland's Financial Crisis:

The 2008 - 2011 Icelandic Financial Crisis was a major economic and political event in Iceland. Relative to the size of its economy, Iceland's systemic banking collapse was the largest experienced by any country in economic history. The crisis led to a severe economic depression in 2008 - 2011 and significant political unrest.

Question: Let's compare the number of Icelandic immigrants (country = 'Iceland') to Canada from year 1980 to 2013.

In [37]:

```
# step 1: get the data
df_iceland = df_can.loc['Iceland', years]
df_iceland.head()
```

Out[37]:


```
1980    17
1981    33
1982    10
1983     9
1984    13
Name: Iceland, dtype: object
```


In [38]:

```
# step 2: plot data
df_iceland.plot(kind='bar', figsize=(10, 6))

plt.xlabel('Year') # add to x-label to the plot
plt.ylabel('Number of immigrants') # add y-label to the plot
plt.title('Icelandic immigrants to Canada from 1980 to 2013') # add title to the plot

plt.show()
```



The bar plot above shows the total number of immigrants broken down by each year. We can clearly see the impact of the financial crisis; the number of immigrants to Canada started increasing rapidly after 2008.

Let's annotate this on the plot using the `annotate` method of the **scripting layer** or the **pyplot interface**. We will pass in the following parameters:

- `s` : str, the text of annotation.
- `xy` : Tuple specifying the (x,y) point to annotate (in this case, end point of arrow).
- `xytext` : Tuple specifying the (x,y) point to place the text (in this case, start point of arrow).
- `xycoords` : The coordinate system that xy is given in - 'data' uses the coordinate system of the object being annotated (default).
- `arrowprops` : Takes a dictionary of properties to draw the arrow:
 - `arrowstyle` : Specifies the arrow style, '-'>' is standard arrow.
 - `connectionstyle` : Specifies the connection type. 'arc3' is a straight line.
 - `color` : Specifies color of arrow.
 - `lw` : Specifies the line width.

I encourage you to read the Matplotlib documentation for more details on annotations:

http://matplotlib.org/api/pyplot_api.html#matplotlib.pyplot.annotate
(http://matplotlib.org/api/pyplot_api.html#matplotlib.pyplot.annotate).

In [41]:


```
df_iceland.plot(kind='bar', figsize=(10, 6), rot=90) # rotate the xticks(labelled points on x-axis) by 90 degrees

plt.xlabel('Year')
plt.ylabel('Number of Immigrants')
plt.title('Icelandic Immigrants to Canada from 1980 to 2013')

# Annotate arrow
plt.annotate('', # s: str. Will leave it blank for no text
             xy=(32, 70), # place head of the arrow at point (year 2012, pop 70)
             xytext=(28, 20), # place base of the arrow at point (year 2008, pop 20)
             xycoords='data', # will use the coordinate system of the object being annotated

             arrowprops=dict(arrowstyle='->', connectionstyle='arc3', color='blue', lw=2))

plt.show()
```



Let's also annotate a text to go over the arrow. We will pass in the following additional parameters:

- `rotation` : rotation angle of text in degrees (counter clockwise)
- `va` : vertical alignment of text ['center' | 'top' | 'bottom' | 'baseline']
- `ha` : horizontal alignment of text ['center' | 'right' | 'left']

In [42]:

```
df_iceland.plot(kind='bar', figsize=(10, 6), rot=90)


plt.xlabel('Year')
plt.ylabel('Number of Immigrants')
plt.title('Icelandic Immigrants to Canada from 1980 to 2013')

# Annotate arrow
plt.annotate('', # s: str. will leave it blank for no text
             xy=(32, 70), # place head of the arrow at point (year 2012 , pop 70)
             xytext=(28, 20), # place base of the arrow at point (year 2008 , pop 20)
             xycoords='data', # will use the coordinate system of the object being annotated

             arrowprops=dict(arrowstyle='->', connectionstyle='arc3', color='blue', lw=2))

# Annotate Text
plt.annotate('2008 - 2011 Financial Crisis', # text to display
             xy=(28, 30), # start the text at at point (year 2008 , pop 30)
             rotation=72.5, # based on trial and error to match the arrow
             va='bottom', # want the text to be vertically 'bottom' aligned
             ha='left', # want the text to be horizontally 'left' aligned.
             )

plt.show()
```



Horizontal Bar Plot

Sometimes it is more practical to represent the data horizontally, especially if you need more room for labelling the bars. In horizontal bar graphs, the y-axis is used for labelling, and the length of bars on the x-axis corresponds to the magnitude of the variable being measured. As you will see, there is more room on the y-axis to label categorical variables.

Question: Using the scripting later and the `df_can` dataset, create a *horizontal* bar plot showing the *total* number of immigrants to Canada from the top 15 countries, for the period 1980 - 2013. Label each country with the total immigrant count.

Step 1: Get the data pertaining to the top 15 countries.

In [43]:

```
### type your answer here

# sort dataframe on 'Total' column (descending)
df_can.sort_values(by='Total', ascending=True, inplace=True)

# get top 15 countries
df_top15 = df_can['Total'].tail(15)
df_top15
```

Out[43]:

Country	
Romania	93585
Viet Nam	97146
Jamaica	106431
France	109091
Lebanon	115359
Poland	139241
Republic of Korea	142581
Sri Lanka	148358
Iran (Islamic Republic of)	175923
United States of America	241122
Pakistan	241600
Philippines	511391
United Kingdom of Great Britain and Northern Ireland	551500
China	659962
India	691904
Name: Total, dtype: int64	

[Click here for a sample python solution](#)

Step 2: Plot data:

1. Use `kind='barh'` to generate a bar chart with horizontal bars.
2. Make sure to choose a good size for the plot and to label your axes and to give the plot a title.
3. Loop through the countries and annotate the immigrant population using the `anotate` function of the scripting interface.

In [47]:

```
### type your answer here
```

```
# generate plot
```

```
df_top15.plot(kind='barh', figsize=(12, 12), color='steelblue')
```

```
plt.xlabel('Number of Immigrants')
```

```
plt.title('Top 15 Conuntries Contributing to the Immigration to Canada between 1980 - 2013')
```

```
# annotate value labels to each country
```


```
for index, value in enumerate(df_top15):
```

```
    label = format(int(value), ',') # format int with commas
```

```
    # place text at the end of bar (subtracting 47000 from x, and 0.1 from y to make it fit within the bar)
```

```
    plt.annotate(label, xy=(value - 47000, index - 0.10), color='white')
```

```
plt.show()
```



[Click here for a sample python solution](#)

Thank you for completing this lab!

Author

[Alex Aklson \(https://www.linkedin.com/in/aklson/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01\)](https://www.linkedin.com/in/aklson/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01)

Other Contributors

[Jay Rajasekharan \(https://www.linkedin.com/in/jayrajasekharan/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01\)](https://www.linkedin.com/in/jayrajasekharan/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01), [Ehsan M. Kermani \(https://www.linkedin.com/in/ehsanmkermani/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01\)](https://www.linkedin.com/in/ehsanmkermani/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01), [Slobodan Markovic \(https://www.linkedin.com/in/slobodan-markovic/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01\)](https://www.linkedin.com/in/slobodan-markovic/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01), [Weiqing Wang \(https://www.linkedin.com/in/weiqing-wang-641640133/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01\)](https://www.linkedin.com/in/weiqing-wang-641640133/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkDV0101ENSkillsNetwork20297740-2021-01-01).

Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2021-05-29	2.4	Weiqing Wang	Fixed typos and code smells.
2021-01-20	2.3	Lakshmi Holla	Changed TOC cell markdown
2021-01-05	2.2	Lakshmi Holla	Changed solution code for annotate
2020-11-03	2.1	Lakshmi Holla	Changed the URL of excel file
2020-08-27	2.0	Lavanya	Moved lab to course repo in GitLab

© IBM Corporation 2020. All rights reserved.

