



## IBM Developer SKILLS NETWORK

# Density-Based Clustering

Estimated time needed: **25** minutes

## Objectives

After completing this lab you will be able to:

- Use DBSCAN to do Density based clustering
- Use Matplotlib to plot clusters

Most of the traditional clustering techniques, such as k-means, hierarchical and fuzzy clustering, can be used to group data without supervision.

However, when applied to tasks with arbitrary shape clusters, or clusters within a cluster, the traditional techniques might be unable to achieve good results. That is, elements in the same cluster might not share enough similarity or the performance may be poor. Additionally, Density-based clustering locates regions of high density that are separated from one another by regions of low density. Density, in this context, is defined as the number of points within a specified radius.

In this section, the main focus will be manipulating the data and properties of DBSCAN and observing the resulting clustering.

Import the following libraries:

- **numpy** as **np**
- **DBSCAN** from **sklearn.cluster**
- **make\_blobs** from **sklearn.datasets.samples\_generator**
- **StandardScaler** from **sklearn.preprocessing**
- **matplotlib.pyplot** as **plt**

Remember **%matplotlib inline** to display plots

In [2]:

```
# Notice: For visualization of map, you need basemap package.
# if you dont have basemap install on your machine, you can use the following line to i
nstaLL it
!pip install basemap==1.2.0 matplotlib==3.1
# Notice: you maight have to refresh your page and re-run the notebook after installati
on
```

```
Requirement already satisfied: basemap==1.2.0 in /home/jupyterlab/conda/en
vs/python/lib/python3.7/site-packages (1.2.0)
Requirement already satisfied: matplotlib==3.1 in /home/jupyterlab/conda/e
nvs/python/lib/python3.7/site-packages (3.1.0)
Requirement already satisfied: numpy>=1.2.1 in /home/jupyterlab/conda/env
s/python/lib/python3.7/site-packages (from basemap==1.2.0) (1.21.4)
Requirement already satisfied: pyshp>=1.2.0 in /home/jupyterlab/conda/env
s/python/lib/python3.7/site-packages (from basemap==1.2.0) (2.1.3)
Requirement already satisfied: six in /home/jupyterlab/conda/envs/python/l
ib/python3.7/site-packages (from basemap==1.2.0) (1.16.0)
Requirement already satisfied: pyproj>=1.9.3 in /home/jupyterlab/conda/env
s/python/lib/python3.7/site-packages (from basemap==1.2.0) (1.9.6)
Requirement already satisfied: pyparsing!=2.0.4,!=2.1.2,!=2.1.6,>=2.0.1 in
/home/jupyterlab/conda/envs/python/lib/python3.7/site-packages (from matpl
otlib==3.1) (3.0.6)
Requirement already satisfied: cycler>=0.10 in /home/jupyterlab/conda/env
s/python/lib/python3.7/site-packages (from matplotlib==3.1) (0.11.0)
Requirement already satisfied: python-dateutil>=2.1 in /home/jupyterlab/co
nda/envs/python/lib/python3.7/site-packages (from matplotlib==3.1) (2.8.2)
Requirement already satisfied: kiwisolver>=1.0.1 in /home/jupyterlab/cond
a/envs/python/lib/python3.7/site-packages (from matplotlib==3.1) (1.3.2)
```

In [4]:

```
import numpy as np
from sklearn.cluster import DBSCAN
from sklearn.datasets.samples_generator import make_blobs
from sklearn.preprocessing import StandardScaler
import matplotlib.pyplot as plt
%matplotlib inline
import warnings
warnings.filterwarnings("ignore", category=DeprecationWarning)
```

## Data generation

The function below will generate the data points and requires these inputs:

- **centroidLocation**: Coordinates of the centroids that will generate the random data.
  - Example: input: `[[4,3], [2,-1], [-1,4]]`
- **numSamples**: The number of data points we want generated, split over the number of centroids (# of centroids defined in centroidLocation)
  - Example: 1500
- **clusterDeviation**: The standard deviation of the clusters. The larger the number, the further the spacing of the data points within the clusters.
  - Example: 0.5

In [5]:

```
def createDataPoints(centroidLocation, numSamples, clusterDeviation):
    # Create random data and store in feature matrix X and response vector y.
    X, y = make_blobs(n_samples=numSamples, centers=centroidLocation,
                      cluster_std=clusterDeviation)

    # Standardize features by removing the mean and scaling to unit variance
    X = StandardScaler().fit_transform(X)
    return X, y
```

Use **createDataPoints** with the **3 inputs** and store the output into variables **X** and **y**.

In [6]:

```
X, y = createDataPoints([[4,3], [2,-1], [-1,4]] , 1500, 0.5)
```

## Modeling

DBSCAN stands for Density-Based Spatial Clustering of Applications with Noise. This technique is one of the most common clustering algorithms which works based on density of object. The whole idea is that if a particular point belongs to a cluster, it should be near to lots of other points in that cluster.

It works based on two parameters: Epsilon and Minimum Points\ **Epsilon** determine a specified radius that if includes enough number of points within, we call it dense area\ **minimumSamples** determine the minimum number of data points we want in a neighborhood to define a cluster.

In [7]:

```
epsilon = 0.3
minimumSamples = 7
db = DBSCAN(eps=epsilon, min_samples=minimumSamples).fit(X)
labels = db.labels_
labels
```

Out[7]:

```
array([0, 1, 0, ..., 2, 0, 0])
```

## Distinguish outliers

Let's Replace all elements with 'True' in `core_samples_mask` that are in the cluster, 'False' if the points are outliers.

In [8]:

```
# Firts, create an array of booleans using the labels from db.
core_samples_mask = np.zeros_like(db.labels_, dtype=bool)
core_samples_mask[db.core_sample_indices_] = True
core_samples_mask
```

Out[8]:

```
array([ True,  True,  True, ...,  True,  True,  True])
```

In [9]:

```
# Number of clusters in labels, ignoring noise if present.  
n_clusters_ = len(set(labels)) - (1 if -1 in labels else 0)  
n_clusters_
```

Out[9]:

3

In [11]:

```
# Remove repetition in labels by turning it into a set.  
unique_labels = set(labels)  
unique_labels
```

Out[11]:

{0, 1, 2}

## Data visualization

In [12]:

```
# Create colors for the clusters.  
colors = plt.cm.Spectral(np.linspace(0, 1, len(unique_labels)))
```


In [13]:

```
# Plot the points with colors
for k, col in zip(unique_labels, colors):
    if k == -1:
        # Black used for noise.
        col = 'k'

    class_member_mask = (labels == k)

    # Plot the datapoints that are clustered
    xy = X[class_member_mask & core_samples_mask]
    plt.scatter(xy[:, 0], xy[:, 1], s=50, c=[col], marker='o', alpha=0.5)

    # Plot the outliers
    xy = X[class_member_mask & ~core_samples_mask]
    plt.scatter(xy[:, 0], xy[:, 1], s=50, c=[col], marker='o', alpha=0.5)
```



## Practice

To better understand differences between partitional and density-based clustering, try to cluster the above dataset into 3 clusters using k-Means. Notice: do not generate data again, use the same dataset as above.

In [14]:


*# write your code here*

```
from sklearn.cluster import KMeans
k = 3
k_means3 = KMeans(init = "k-means++", n_clusters = k, n_init = 12)
k_means3.fit(X)
fig = plt.figure(figsize=(6, 4))
ax = fig.add_subplot(1, 1, 1)
for k, col in zip(range(k), colors):
    my_members = (k_means3.labels_ == k)
    plt.scatter(X[my_members, 0], X[my_members, 1], c=col, marker='o', alpha=0.5)
plt.show()
```

'c' argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with 'x' & 'y'. Please use a 2-D array with a single row if you really want to specify the same RGB or RGBA value for all points.

'c' argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with 'x' & 'y'. Please use a 2-D array with a single row if you really want to specify the same RGB or RGBA value for all points.

'c' argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with 'x' & 'y'. Please use a 2-D array with a single row if you really want to specify the same RGB or RGBA value for all points.



[Click here for the solution](#)

# Weather Station Clustering using DBSCAN & scikit-learn

---

DBSCAN is especially very good for tasks like class identification in a spatial context. The wonderful attribute of DBSCAN algorithm is that it can find out any arbitrary shape cluster without getting affected by noise. For example, this following example cluster the location of weather stations in Canada. \<Click 1> DBSCAN can be used here, for instance, to find the group of stations which show the same weather condition. As you can see, it not only finds different arbitrary shaped clusters, can find the denser part of data-centered samples by ignoring less-dense areas or noises.

Let's start playing with the data. We will be working according to the following workflow: </font>

## 1. Loading data

- Overview data
- Data cleaning
- Data selection
- Clusteing

## About the dataset

### Environment Canada Monthly Values for July - 2015

Name in the table	Meaning
<b>Stn_Name</b>	<b>Station Name</b>
<b>Lat</b>	<b>Latitude (North+, degrees)</b>
<b>Long</b>	<b>Longitude (West - , degrees)</b>
Prov	Province
Tm	Mean Temperature (°C)
DwTm	Days without Valid Mean Temperature
D	Mean Temperature difference from Normal (1981-2010) (°C)
Tx	Highest Monthly Maximum Temperature (°C)
DwTx	Days without Valid Maximum Temperature
Tn	Lowest Monthly Minimum Temperature (°C)
DwTn	Days without Valid Minimum Temperature
S	Snowfall (cm)
DwS	Days without Valid Snowfall
S%N	Percent of Normal (1981-2010) Snowfall
<b>P</b>	<b>Total Precipitation (mm)</b>
DwP	Days without Valid Precipitation
P%N	Percent of Normal (1981-2010) Precipitation
S_G	Snow on the ground at the end of the month (cm)
Pd	Number of days with Precipitation 1.0 mm or more
BS	Bright Sunshine (hours)
DwBS	Days without Valid Bright Sunshine
BS%	Percent of Normal (1981-2010) Bright Sunshine
HDD	Degree Days below 18 °C
CDD	Degree Days above 18 °C
Stn_No	Climate station identifier (first 3 digits indicate drainage basin, last 4 characters are for sorting alphabetically).
NA	Not Available

## 1-Download data

To download the data, we will use `!wget` to download it from IBM Object Storage. **Did you know?** When it comes to Machine Learning, you will likely be working with large datasets. As a business, where can you host your data? IBM is offering a unique opportunity for businesses, with 10 Tb of IBM Cloud Object Storage: [Sign up now for free \(http://cocl.us/ML0101EN-IBM-Offer-CC\)](http://cocl.us/ML0101EN-IBM-Offer-CC)



In [15]:

```
!wget -O weather-stations20140101-20141231.csv https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-ML0101EN-SkillsNetwork/labs/Module%204/data/weather-stations20140101-20141231.csv
```

```
--2021-12-30 21:02:42-- https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-ML0101EN-SkillsNetwork/labs/Module%204/data/weather-stations20140101-20141231.csv
Resolving cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud (cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud)... 169.63.118.104
Connecting to cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud (cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud)|169.63.118.104|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 129821 (127K) [text/csv]
Saving to: 'weather-stations20140101-20141231.csv'
```

```
weather-stations201 100%[=====>] 126.78K --.-KB/s in 0.002s
```

```
2021-12-30 21:02:43 (49.8 MB/s) - 'weather-stations20140101-20141231.csv' saved [129821/129821]
```

## 2- Load the dataset

We will import the .csv then we create the columns for year, month and day.

In [16]:

```
import csv
import pandas as pd
import numpy as np

filename='weather-stations20140101-20141231.csv'

#Read csv
pdf = pd.read_csv(filename)
pdf.head(5)
```

Out[16]:

	Stn_Name	long	Prov	Tm	Dw	Tm	D	Tx	Dw	Tm	...	Dw	PP	%NS	G	Pd	BS	Dw	BBS	%HDD	CDD	Stn_
0	CHEW	114.93523	WA	8.2	0.0	NaN	13.5	0.0	1.0	...	0.0	NaN	0.0	12.0	NaN	NaN	NaN	NaN	NaN	273.3	0.0	1011
	COWICHAN																					
1	LAKE	118.82424	BC	7.0	0.0	3.0	15.0	0.0	-3.0	...	0.0	104.0	0.0	12.0	NaN	NaN	NaN	NaN	NaN	307.0	0.0	1012
	FORESTRY																					
2	LAKE	118.82424	BC	6.8	13.0	2.8	16.0	9.0	-2.5	...	9.0	NaN	NaN	11.0	NaN	NaN	NaN	NaN	NaN	168.1	0.0	1012
	COWICHAN																					
3	DISCOVERY	118.42523	BC	NaN	NaN	NaN	12.5	0.0	NaN	...	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	1012
	ISLAND																					
	DUNCAN																					
4	KELVIN	118.73523	BC	7.7	2.0	3.4	14.5	2.0	-1.0	...	2.0	NaN	NaN	11.0	NaN	NaN	NaN	NaN	NaN	267.7	0.0	1012
	CREEK																					

5 rows × 25 columns



### 3-Cleaning

Let's remove rows that don't have any value in the **Tm** field.

In [17]:

```
pdf = pdf[pd.notnull(pdf["Tm"])]
pdf = pdf.reset_index(drop=True)
pdf.head(5)
```

Out[17]:

	Stn_Name	Long	Prov	Tm	DwTm	D	Tx	DwTx	Tn	...	DwPP	%NS	G	Pd	BS	DwBBS	%HDD	CDD	Stn_	
0	CHEWAGUAS	113.74	BC	8.2	0.0	NaN	13.5	0.0	1.0	...	0.0	NaN	0.0	12.0	NaN	NaN	NaN	273.3	0.0	1011
	COWICHAN																			
1	LAKE FORESTRY	118.82	BC	7.0	0.0	3.0	15.0	0.0	-3.0	...	0.0	104.0	0.0	12.0	NaN	NaN	NaN	307.0	0.0	1012
2	LAKE COWICHAN	118.82	BC	6.8	13.0	2.8	16.0	9.0	-2.5	...	9.0	NaN	NaN	11.0	NaN	NaN	NaN	168.1	0.0	1012
	DUNCAN																			
3	KELWAT CREEK	117.35	BC	7.7	2.0	3.4	14.5	2.0	-1.0	...	2.0	NaN	NaN	11.0	NaN	NaN	NaN	267.7	0.0	1012
4	ESQUIMALT HARBOUR	118.43	BC	8.8	0.0	NaN	13.1	0.0	1.9	...	8.0	NaN	NaN	12.0	NaN	NaN	NaN	258.6	0.0	1012

5 rows × 25 columns



## 4-Visualization

Visualization of stations on map using basemap package. The matplotlib basemap toolkit is a library for plotting 2D data on maps in Python. Basemap does not do any plotting on it's own, but provides the facilities to transform coordinates to a map projections.

Please notice that the size of each data points represents the average of maximum temperature for each station in a year.

In [18]:

```

from mpl_toolkits.basemap import Basemap
import matplotlib.pyplot as plt
from pylab import rcParams
%matplotlib inline
rcParams['figure.figsize'] = (14,10)

llon=-140
ulon=-50
llat=40
ulat=65

pdf = pdf[(pdf['Long'] > llon) & (pdf['Long'] < ulon) & (pdf['Lat'] > llat) & (pdf['Lat']
] < ulat)]

my_map = Basemap(projection='merc',
                  resolution = 'l', area_thresh = 1000.0,
                  llcrnrlon=llon, llcrnrlat=llat, #min Longitude (llcrnrlon) and Latitude (ll
crnrlat)
                  urcrnrlon=ulon, urcrnrlat=ulat) #max Longitude (urcrnrlon) and Latitude (ur
crnrlat)

my_map.drawcoastlines()
my_map.drawcountries()
# my_map.drawmapboundary()
my_map.fillcontinents(color = 'white', alpha = 0.3)
my_map.shadedrelief()


# To collect data based on stations

xs,ys = my_map(np.asarray(pdf.Long), np.asarray(pdf.Lat))
pdf['xm']= xs.tolist()
pdf['ym'] =ys.tolist()

#Visualization1
for index,row in pdf.iterrows():
    # x,y = my_map(row.Long, row.Lat)
    my_map.plot(row.xm, row.ym,markerfacecolor =([1,0,0]), marker='o', markersize= 5, a
lpha = 0.75)
    #plt.text(x,y,stn)
plt.show()

```

```
/home/jupyterlab/conda/envs/python/lib/python3.7/site-packages/ipykernel_launcher.py:17: MatplotlibDeprecationWarning:  
The dedent function was deprecated in Matplotlib 3.1 and will be removed in 3.3. Use inspect.cleandoc instead.  
/home/jupyterlab/conda/envs/python/lib/python3.7/site-packages/ipykernel_launcher.py:20: MatplotlibDeprecationWarning:  
The dedent function was deprecated in Matplotlib 3.1 and will be removed in 3.3. Use inspect.cleandoc instead.
```



## 5- Clustering of stations based on their location i.e. Lat & Lon

**DBSCAN** from sklearn library can run DBSCAN clustering from vector array or distance matrix. In our case, we pass it the Numpy array `Clus_dataSet` to find core samples of high density and expands clusters from them.

In [19]:

```

from sklearn.cluster import DBSCAN
import sklearn.utils
from sklearn.preprocessing import StandardScaler
sklearn.utils.check_random_state(1000)
Clus_dataSet = pdf[['xm', 'ym']]
Clus_dataSet = np.nan_to_num(Clus_dataSet)
Clus_dataSet = StandardScaler().fit_transform(Clus_dataSet)

# Compute DBSCAN
db = DBSCAN(eps=0.15, min_samples=10).fit(Clus_dataSet)
core_samples_mask = np.zeros_like(db.labels_, dtype=bool)
core_samples_mask[db.core_sample_indices_] = True
labels = db.labels_
pdf["Clus_Db"]=labels

realClusterNum=len(set(labels)) - (1 if -1 in labels else 0)
clusterNum = len(set(labels))

# A sample of clusters
pdf[["Stn_Name", "Tx", "Tm", "Clus_Db"]].head(5)

```

Out[19]:

	Stn_Name	Tx	Tm	Clus_Db
0	CHEMAINUS	13.5	8.2	0
1	COWICHAN LAKE FORESTRY	15.0	7.0	0
2	LAKE COWICHAN	16.0	6.8	0
3	DUNCAN KELVIN CREEK	14.5	7.7	0
4	ESQUIMALT HARBOUR	13.1	8.8	0

As you can see for outliers, the cluster label is -1

In [ ]:

```
set(labels)
```

## 6- Visualization of clusters based on location

Now, we can visualize the clusters using basemap:

In [20]:

```

from mpl_toolkits.basemap import Basemap
import matplotlib.pyplot as plt
from pylab import rcParams
%matplotlib inline
rcParams['figure.figsize'] = (14,10)

my_map = Basemap(projection='merc',
                  resolution = 'l', area_thresh = 1000.0,
                  llcrnrlon=llon, llcrnrlat=llat, #min Longitude (llcrnrlon) and Latitude (llcrnrlat)
                  urcrnrlon=ulon, urcrnrlat=ulat) #max Longitude (urcrnrlon) and Latitude (urcrnrlat)

my_map.drawcoastlines()
my_map.drawcountries()
#my_map.drawmapboundary()
my_map.fillcontinents(color = 'white', alpha = 0.3)
my_map.shadedrelief()


# To create a color map
colors = plt.get_cmap('jet')(np.linspace(0.0, 1.0, clusterNum))

#Visualization1
for clust_number in set(labels):
    c=([0.4,0.4,0.4]) if clust_number == -1 else colors[np.int(clust_number)]
    clust_set = pdf[pdf.Clus_Db == clust_number]
    my_map.scatter(clust_set.xm, clust_set.ym, color =c, marker='o', s= 20, alpha = 0.
85)
    if clust_number != -1:
        cenx=np.mean(clust_set.xm)
        ceny=np.mean(clust_set.ym)
        plt.text(cenx,ceny,str(clust_number), fontsize=25, color='red',)
        print ("Cluster "+str(clust_number)+', Avg Temp: '+ str(np.mean(clust_set.Tm)))

```

```
/home/jupyterlab/conda/envs/python/lib/python3.7/site-packages/ipykernel_launcher.py:10: MatplotlibDeprecationWarning:  
The dedent function was deprecated in Matplotlib 3.1 and will be removed i  
n 3.3. Use inspect.cleandoc instead.  
# Remove the CWD from sys.path while we load stuff.  
/home/jupyterlab/conda/envs/python/lib/python3.7/site-packages/ipykernel_launcher.py:13: MatplotlibDeprecationWarning:  
The dedent function was deprecated in Matplotlib 3.1 and will be removed i  
n 3.3. Use inspect.cleandoc instead.  
del sys.path[0]
```

```
Cluster 0, Avg Temp: -5.538747553816046  
Cluster 1, Avg Temp: 1.9526315789473685  
Cluster 2, Avg Temp: -9.195652173913045  
Cluster 3, Avg Temp: -15.300833333333333  
Cluster 4, Avg Temp: -7.769047619047619
```



## 7- Clustering of stations based on their location, mean, max, and min Temperature

In this section we re-run DBSCAN, but this time on a 5-dimensional dataset:



In [21]:

```

from sklearn.cluster import DBSCAN
import sklearn.utils
from sklearn.preprocessing import StandardScaler
sklearn.utils.check_random_state(1000)
Clus_dataSet = pdf[['xm', 'ym', 'Tx', 'Tm', 'Tn']]
Clus_dataSet = np.nan_to_num(Clus_dataSet)
Clus_dataSet = StandardScaler().fit_transform(Clus_dataSet)

# Compute DBSCAN
db = DBSCAN(eps=0.3, min_samples=10).fit(Clus_dataSet)
core_samples_mask = np.zeros_like(db.labels_, dtype=bool)
core_samples_mask[db.core_sample_indices_] = True
labels = db.labels_
pdf["Clus_Db"]=labels

realClusterNum=len(set(labels)) - (1 if -1 in labels else 0)
clusterNum = len(set(labels))

# A sample of clusters
pdf[["Stn_Name", "Tx", "Tm", "Clus_Db"]].head(5)

```

Out[21]:

	Stn_Name	Tx	Tm	Clus_Db
0	CHEMAINUS	13.5	8.2	0
1	COWICHAN LAKE FORESTRY	15.0	7.0	0
2	LAKE COWICHAN	16.0	6.8	0
3	DUNCAN KELVIN CREEK	14.5	7.7	0
4	ESQUIMALT HARBOUR	13.1	8.8	0

## 8- Visualization of clusters based on location and Temperture

In [22]:

```

from mpl_toolkits.basemap import Basemap
import matplotlib.pyplot as plt
from pylab import rcParams
%matplotlib inline
rcParams['figure.figsize'] = (14,10)

my_map = Basemap(projection='merc',
                  resolution = 'l', area_thresh = 1000.0,
                  llcrnrlon=llon, llcrnrlat=llat, #min Longitude (llcrnrlon) and Latitude (llcrnrlat)
                  urcrnrlon=ulon, urcrnrlat=ulat) #max Longitude (urcrnrlon) and Latitude (urcrnrlat)

my_map.drawcoastlines()
my_map.drawcountries()
#my_map.drawmapboundary()
my_map.fillcontinents(color = 'white', alpha = 0.3)
my_map.shadedrelief()


# To create a color map
colors = plt.get_cmap('jet')(np.linspace(0.0, 1.0, clusterNum))

#Visualization1
for clust_number in set(labels):
    c=([0.4,0.4,0.4]) if clust_number == -1 else colors[np.int(clust_number)]
    clust_set = pdf[pdf.Clus_Db == clust_number]
    my_map.scatter(clust_set.xm, clust_set.ym, color =c, marker='o', s= 20, alpha = 0.
85)
    if clust_number != -1:
        cenx=np.mean(clust_set.xm)
        ceny=np.mean(clust_set.ym)
        plt.text(cenx,ceny,str(clust_number), fontsize=25, color='red',)
        print ("Cluster "+str(clust_number)+', Avg Temp: '+ str(np.mean(clust_set.Tm)))

```

```
/home/jupyterlab/conda/envs/python/lib/python3.7/site-packages/ipykernel_launcher.py:10: MatplotlibDeprecationWarning:  
The dedent function was deprecated in Matplotlib 3.1 and will be removed in 3.3. Use inspect.cleandoc instead.  
# Remove the CWD from sys.path while we load stuff.  
/home/jupyterlab/conda/envs/python/lib/python3.7/site-packages/ipykernel_launcher.py:13: MatplotlibDeprecationWarning:  
The dedent function was deprecated in Matplotlib 3.1 and will be removed in 3.3. Use inspect.cleandoc instead.  
del sys.path[0]
```

```
Cluster 0, Avg Temp: 6.221192052980132  
Cluster 1, Avg Temp: 6.790000000000001  
Cluster 2, Avg Temp: -0.49411764705882344  
Cluster 3, Avg Temp: -13.87720930232558  
Cluster 4, Avg Temp: -4.186274509803922  
Cluster 5, Avg Temp: -16.301503759398496  
Cluster 6, Avg Temp: -13.599999999999998  
Cluster 7, Avg Temp: -9.753333333333334  
Cluster 8, Avg Temp: -4.258333333333334
```



## Want to learn more?

IBM SPSS Modeler is a comprehensive analytics platform that has many machine learning algorithms. It has been designed to bring predictive intelligence to decisions made by individuals, by groups, by systems – by your enterprise as a whole. A free trial is available through this course, available here: [SPSS Modeler \(https://www.ibm.com/analytics/spss-statistics-software?utm\\_medium=Exinfluencer&utm\\_source=Exinfluencer&utm\\_content=000026UJ&utm\\_term=10006555&utm\\_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkML0101ENSkillsNetwork20718538-2021-01-01\)](https://www.ibm.com/analytics/spss-statistics-software?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkML0101ENSkillsNetwork20718538-2021-01-01)

Also, you can use Watson Studio to run these notebooks faster with bigger datasets. Watson Studio is IBM's leading cloud solution for data scientists, built by data scientists. With Jupyter notebooks, RStudio, Apache Spark and popular libraries pre-packaged in the cloud, Watson Studio enables data scientists to collaborate on their projects without having to install anything. Join the fast-growing community of Watson Studio users today with a free account at [Watson Studio \(https://www.ibm.com/cloud/watson-studio?utm\\_medium=Exinfluencer&utm\\_source=Exinfluencer&utm\\_content=000026UJ&utm\\_term=10006555&utm\\_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkML0101ENSkillsNetwork20718538-2021-01-01\)](https://www.ibm.com/cloud/watson-studio?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkML0101ENSkillsNetwork20718538-2021-01-01)

**Thank you for completing this lab!**

## Author

Saeed Aghabozorgi

## Other Contributors

[Joseph Santarcangelo \(https://www.linkedin.com/in/joseph-s-50398b136/?utm\\_medium=Exinfluencer&utm\\_source=Exinfluencer&utm\\_content=000026UJ&utm\\_term=10006555&utm\\_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkML0101ENSkillsNetwork20718538-2021-01-01\)](https://www.linkedin.com/in/joseph-s-50398b136/?utm_medium=Exinfluencer&utm_source=Exinfluencer&utm_content=000026UJ&utm_term=10006555&utm_id:SkillsNetwork-Channel-SkillsNetworkCoursesIBMDeveloperSkillsNetworkML0101ENSkillsNetwork20718538-2021-01-01)

## Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2020-11-03	2.1	Lakshmi	Updated url of csv
2020-08-27	2.0	Lavanya	Moved lab to course repo in GitLab

**© IBM Corporation 2020. All rights reserved.**