

Shell Scripting 2

Week 2 – Wednesday

Overview

- In last lecture, we learnt
 - Regular expression
 - Advanced commands: grep, sed, etc.
 - Redirection & pipelines
- In this lecture, we will learn
 - How to program a shell script
 - Variables & values
 - Control structures
 - Functions
 - Misc

To begin with: Hello world in Shell

helloworld.sh

```
#!/bin/sh  
str="Hello World!"  
echo $str  
exit 0
```

- A script file
- The `#!` first line
- Assign a value to a variable
- Print a variable/execute a command
- Exit

The #! first line

- What's the difference between a shell script and a binary executable program?
 - Plain text is not an executable format
 - The system need to invoke a shell to run a script
- The first line tells the OS which shell to invoke
 - To avoid ambiguity
 - If missing, the OS calls the default shell

The “exit” command

Exit Value	Meaning
0	Success (recall the “return 0” in the main function)
1~125	Error codes can be used by script
126	The file is not executable
127	A command is not found
>=128	Command died due to a signal

Variable Names

- Legit variable names
 - Start with a letter/underscore
 - May contain any number of
 - Letters
 - Digits
 - Underscores
 - Similar to C/C++

Special Variable Names

Environment Variables	Description
\$PATH	A colon-separated list of directories to search for commands
\$HOME	The home directory of current user
\$0	The name of the shell script (argv[0])
\$1, \$2, ...	The first/second/... parameter given to the script (argv[1], argv[2], ...)
\$#	The number of parameters (argc - 1)
\$*	A list of all parameters (argv)

Write a Variable

- Two ways to write a variable
 - Read user input: “read”

Read input from user

```
read str  
echo $str
```

- Assign inside program
- What’s the difference between shell & C in assigning a value to a variable?

helloworld.sh

```
str="Hello World!"
```

helloworld.c

```
char *str = "Hello World!";
```


Write a Variable

- What's the type of a variable?
 - All strings!
 - Shell and some utilities can convert variables to numbers when required
 - Try to use “sort” to sort numbers (hint: 100 & 90, which goes first?)
 - Case sensitive
- Space or whitespace or ?
 - Can I add space into ...?

Type of a variable

```
str=7+5  
echo $str
```

Space in C

```
char *str="Hello World!";  
char *str="Hello World!";  
char *str= "Hello World!";  
char *str = "Hello World!";
```

Which are right in Shell?

```
str="Hello World!"  
str ="Hello World!"  
str= "Hello World!"  
str = "Hello World!"
```

Read a Variable

- `$ + variable_name` = the value of the variable
- What if I want to print a “\$str”?
 - Recall how to print a “ in C
 - How to assign the value of a variable to another variable?
- Quotation mark & strings
 - Single/double quotation marks?
 - Can I omit some quotation marks?

Play with \$

```
echo $str
echo "$str"
echo '$str'
echo \ $str
```

Play with quotation marks

```
str="Hello World!"
str='Hello World!'
str=Hello World!
```

String Manipulation

Expression	Description	Example
<code>\${#variable}</code>	Get the length of a string (<code>strlen()</code>)	<code>\${#str}</code>
<code>\${variable:position}</code>	Extract the substring from <i>variable</i> , which starts at <i>position</i>	<code>\${str:1}</code>
<code>\${variable:position:length}</code>	Extract the substring from <i>variable</i> , which starts at <i>position</i> with the length being <i>length</i>	<code>\${str:1:3}</code>
<code>\${variable:-default}</code>	If <i>variable</i> is null, return the value of <i>default</i>	<code>unset foo</code> <code>echo {foo:-bar}</code>

“unset”: remove
variables and functions
from current shell

String Manipulation

```
str="/usr/local/etc.d/a.txt"
```

Expression	Description	Example
<code>\${#variable%word}</code>	From the end, removes the smallest part of <i>variable</i> that matches <i>word</i>	<code>\${str%.*}</code>
<code>\${#variable%%word}</code>	From the end, removes the largest part of <i>variable</i> that matches <i>word</i>	<code>\${str%%.*}</code>
<code>\${#variable#word}</code>	From the beginning, removes the smallest part of <i>variable</i> that matches <i>word</i>	<code>\${str#*/}/</code>
<code>\${#variable##word}</code>	From the beginning, removes the largest part of <i>variable</i> that matches <i>word</i>	<code>\${str##*/}/</code>

Arithmetic Manipulation

- “expr”: evaluate its arguments as an expression
 - Commonly used handle arithmetic
 - Space matters!
 - Available operators for expr:
 - =, >, >=, <, <=, !=, +, -, *, /, %
 - expr1 | expr2: expr1 if expr1 is nonzero; otherwise expr2
 - expr1 & expr2: zero if either expression is zero; otherwise expr1
- “`”(backtick) and “\$()”
 - Make the variable take the result of executing the command

expr & backtick

```
expr 1+2  
expr 1 + 2
```

```
x=1  
x=`expr $x + 1`  
echo $x  
x=$(expr $x + 1)  
echo $x
```

```
x=`ls`  
echo $x
```

Control Structures

- I miss my if-else/while/for in C/C++, can I use it in shell to make a well-organized program?
 - Yes!
- Composition of a control structure
 - Type of control structure
 - Choice
 - Loop
 - Conditions
 - Bodies

A control structure example

```
if [ $str = "yes" ]  
then  
    echo "yes"  
else  
    echo "no"  
fi
```

Conditions: The test command

- Recall Assignment 1: “What executable programs have names that are just one character long, and what do they do?”
- The test or [command
 - Extensively used for condition expression
 - “man test” for help
 - Usage: “test blabla” or “[blabla]”

Conditions: The test command

String comparison	Description
string1 = string2	True if the strings are equal
string1 != string2	True if the strings are not equal
-n string	True if the string is not null
-z string	True if the string is null

Arithmetic Comparison	Description
expression1 -eq expression2	==
expression1 -ne expression2	!=
expression1 -gt expression2	>
expression1 -ge expression2	>=
expression1 -lt expression2	<
expression1 -le expression2	<=
! expression1	True if the expression is false; vice versa

Conditions: The test command

File Condition	Result
-d file	True if the file is a directory
-e file	True if the file exists
-f file	True if the file is a regular file
-r file	True if readable
-w file	True if writable
-x file	True if executable

Complex Conditions

- The AND/OR lists
 - Usage
 - `statement1 && statement2 && ...`
 - `statement1 || statement2 || ...`
 - Example
 - `"[-e file] && [-d file]"`
 - What's the priority of `&&` and `||`?
 - Can I use parenthesis inside a condition list?

Complex Conditions

- A tricky usage: execute commands in a condition list

Execute a command in a condition list

```
rm -f file_one
if [ -f file_one ] || echo "hello" || echo "world"
then
    echo "in if"
else
    echo "in else"
fi
```

What if replace with the following condition list:
`if [-f file_one] && echo "hello" || echo "world"`

What's the relationship between "exit 0" and true/false?

Try: `./your_script && echo "abc"`

Choice: if-elif-else

if-else

```
if [ $str = "yes" ]  
then  
    echo "yes"  
elif  
    echo "no"  
else  
    echo "error"  
fi
```

Choice: case

if-else

```
read num
case $num in
  1) echo "one";;
  2) echo "two";;
  3) echo "three";;
  4 | 5) echo "a large number";;
  *) echo "Sorry, I don't know";;
esac
```

Loop: while/until

while

```
read password
while [ $password != "12345" ]
do
    echo "Sorry, try again"
    read password
done
echo "Success"
```

until

```
read password
until [ $password == "12345" ]
do
    echo "Sorry, try again"
    read password
done
echo "Success"
```

“break” and “continue” also available

A different usage of “for”

- Recall the for-loop in C/C++
 - “for (int i = 0; i < n; ++ i)”
 - A typical usage: traverse an array
- The “for” in script languages
 - Used to enumerate all the elements in a container (array, list, etc.)
 - Usage: for variable in values

for

```
for i in foo bar 123
do
  echo $i
done
```

```
for file in $(ls)
do
  echo $file
done
```

Saving Lines when Writing Control Structures

- Use “;” to pack multiple statements into one line

if-else

```
if [ $str = "yes" ]  
then  
    echo "yes"  
else  
    echo "no"  
fi
```



if-else

```
if [ $str = "yes" ] ; then  
    echo "yes"  
else  
    echo "no"  
fi
```


Functions

- Define before used
- Parameters

Function

```
foo() {  
    echo "foo:"  
    echo $1  
}
```

```
echo "start"  
foo "abc"  
echo "end"
```

Comments

- Line-based comments:
 - Start with “#”
 - The rest of the line is taken as comments and will not be executed
 - It is good to include comments in your submissions!

Hints

- Extract a line with some tags
 - `sed -n "/<a>/p" <a.html`
- Work with multi-line pattern
 - `sed 'N;s/pattern//g;P;D'`
 - N: add next line to the work buffer
 - s: substitute
 - P: print top line
 - D: delete top line and continue
 - `sed -n '/<td>/,/<\td>/p'`
- How to delete every other lines
 - `sed '1~2d' file` #delete the odd lines
 - `sed '2~2d' file` #delete the even lines

Sign up for you presentation

- Make appointment in the google doc
 - https://docs.google.com/spreadsheets/ccc?key=0At5HvqRbh6GFdGpyb25xUUMyLUZvTTB2VmFXSEVKWHc&usp=drive_web#gid=0
- How to fill in the sign-up sheet
 - Select the slot
 - Title of the topic, name, UID, Email,
- First come, first served
 - DO NOT erase existing entries
 - Check all existing entries to avoid conflicts
- Tentative schedule
 - Week 3 ~ Week 10
 - 2 presentation per class
- Brief presentation: 10~15min