

CMPSC 201: PROGRAMMING LANGUAGES


Analysis
SYNTAX TREE
Optimizing
INTERMEDIATE REPRESENTATION(S)
Parsing
Code Generation
TREE-WALK
INTERP.
TOKENS
Transpiling
Scanning
VIRTUAL
MACHINE
SOURCE CODE
HIGH-LEVEL LANGUAGE
BYTECODE
MACHINE CODE

Lexical Analysis: Review



Lexical Analysis: Review

FUNCTION	FORM
ART	THE
NOUN	COMPLEX
VERB	HOUSES
ADJECTIVE	MARRIED
CONJUNCTION	AND
ADJECTIVE	SINGLE
SOLIDERS	SOLDIERS
CONJUNCTION	AND
PRONOUN	THEIR
NOUN	FAMILIES
EOF	.

Lexical Analysis (“Lexing”)

```
var num = 3.14;
print num;
```

Error



Character Stream

Token Stream

```
VAR var null
IDENTIFIER num null
EQUAL = null
NUMBER 3.14 3.14
SEMICOLON ; null
PRINT print null
IDENTIFIER num null
SEMICOLON ; null
EOF  null
```

Lexical Analysis: Lexemes vs. Tokens

FORM = LEXEME



FUNCTION = TOKEN

Lexical Analysis: Regular Expressions

`var\s[a-z0-9_]+`

`(?<=(?P<quote>"|'))([a-z0-9_+]+)(?:(?(quote)))`



Typically might be handled by regular expressions...

But, we ain’t got time for this nonsense.

Lexical Analysis: Maximal Munch

We're going to use *maximal munch*.

Rule #1 of *maximal munch:*
The most-matched token rule wins.

Lexical Analysis: Maximal Munch



Lexical Analysis: Maximal Munch





Lexical Analysis: Maximal Munch

This works because we reserve important words *first* using a switch statement.

AND	CLASS	ELSE	FALSE	FOR	FUN
IF	NIL	OR	PRINT	RETURN	SUPER
THIS	TRUE	VAR	WHILE		

RESERVED WORDS IN LOX

Lexical Analysis: Maximal Munch

It works the same way for things like multi-character symbols.

=	!=	<	>	>=	<=
==	;	(	)	{	}
/					

RESERVED SYMBOLS IN LOX