

Alle's ClinX

TECHNICAL DATA SHEET

Chimney & Exhaust Degreaser - Alkaline

1. PRODUCT IDENTIFICATION

Product name	Chimney & Exhaust Degreaser - Alkaline
Brand	Alle's ClinX
Product code / SKU	ACX-1234-VAR
Product category	Heavy-duty degreasing
Product form	Liquid formulation / see current label
Intended market	Hospitality / Education / Industrial / Labs
GHS pictogram	

2. PRODUCT DESCRIPTION

Chimney & Exhaust Degreaser - Alkaline is a professional heavy-duty degreasing product based on High-alkalinity surfactant + saponification system, with a stated pH of 11.0–12.0 (strongly alkaline). This sheet summarises supported identity, compatibility, safety, storage and packaging information.

3. KEY FEATURES AND BENEFITS

Feature	User / operational benefit
High-alkalinity surfactant + saponification system	Defines the formulation / active system used to identify the product.
pH: 11.0–12.0 (strongly alkaline)	Supports compatibility and handling decisions.
Defined compatible-use scope	Approved areas / surfaces are stated for easier site selection.

4. APPLICATIONS

Recommended environments	Hospitality / Education / Industrial / Labs
Recommended tasks	Heavy-duty degreasing
Use on	Kitchen extraction systems, cooking equipment, plant floors, industrial machinery, loading docks
Do not use on	causes etching and discolouration

5. TECHNICAL SPECIFICATIONS

Property	Specification
Active / chemistry	High-alkalinity surfactant + saponification system
pH	11.0–12.0 (strongly alkaline)
Product form	Liquid formulation / see current label
Specific gravity	1.04–1.07 at 25°C
Pack size	5 Litres concentrate

6. SAFETY AND HANDLING SUMMARY

PPE	Gloves + eye protection mandatory. Use in ventilated areas.
Critical restrictions / incompatibilities	Aluminium, painted surfaces, soft metals — high pH causes etching and discolouration
First aid / spill reference	Refer to the current product SDS, label and site emergency procedure.

7. STORAGE AND SHELF LIFE

Storage conditions	Keep in the original sealed container, away from direct sunlight and incompatible materials; follow current label / SDS storage limits.
Storage temperature	Follow current label / SDS
Shelf life - unopened	24 months from date of manufacture, unopened
Container requirements	Original, correctly labelled, tightly closed container unless the approved pack states otherwise.