1 A :- Program to demonstrate the features of dart language.

```
void main() {
  int num1=10;
  double num2=20.1;
  bool num3=true;
  String str1 = "Hello All";

  print(num1);
  print(num2);
  print(num3);
  print(str1);
}
```

1 B :- Sub Practical

```
void main() {
   int a=2;
   int b=3;

   var c=a+b;
   print("Sum of a and b is $c");
   var d=a-b;
   print("The difference between a and b is $d");
   var e=-d;
   print("The negation of difference between a and b is $e");
   var f=a*b;
   print("The product of a and b is $f");
   var g=b/a;
   print("The quotient of a and b is $g");
   var h=b~/a;
   print("The quotient of a and b is $h");
   var i=b%a;
   print("The remainder of a and b is $i");
}
```

1 C :- Sub practical

```
void main() {
   var marks=74;
   if(marks > 85)
   {
      print("Excellent");
   }
   else if(marks > 75)
   {
      print("Very Good");
   }
   else if(marks>65)
   {
      print("Good");
   }
   else
   {
      print("Average");
   }
}
```

2 A :- Sub practical

```
void main() {
   print(factorial(6));
}
factorial(number) {
   if(number <= 0) {
      return 1;
   } else {
      return (number * factorial(number - 1));
   }
}
```

2 B :- Sub Practical

```
bool isPrime(N) {
  for (var i=2;i <= N / i; ++i) {
    if (N % i == 0) {
      return false;
    }
  }
  return true;
}

void main() {
  print("Enter N");
  int N=12;
  if(isPrime(N)) {
    print("$N is a prime number.");
  } else {
    print("$N is not a prime number.");
  }
}
```

2 C :- Sub Practical

```
class Student {
  var stdName;
  var stdAge;
  var stdRoll_nu;

  showStdInfo() {
    print("Student name is : ${stdName}");
    print("Student Age is : ${stdAge}");
    print("Student Roll Number is : ${stdRoll_nu}");
  }
}
void main () {
  var std = new Student();
  std.stdName = "ABC";
  std.stdAge = 24;
  std.stdRoll_nu = 90001;
  std.showStdInfo();
}
```

Practical 4

```
import 'package:flutter/material.dart';

void main() {
  runApp(DemoApp());
}

class DemoApp extends StatelessWidget {
  @override
  Widget build(BuildContext context) {
    return MaterialApp(
      title: 'My Application',
      debugShowCheckedModeBanner: true,
      home: Scaffold(
        body: Padding(
          padding: const EdgeInsets.all(20.0),
          child: Column(
            mainAxisAlignment: MainAxisAlignment.center,
            children: [
              Row(
                mainAxisAlignment: MainAxisAlignment.spaceEvenly,
                children: [
                  Container(
                    height: 100,
```

```
      width: 100,
      color: Colors.teal,
    ),
    Container(
      height: 100,
      width: 100,
      color: Colors.teal[600],
    ),
    Container(
      height: 100,
      width: 100,
      color: Colors.teal[900],
    ),
  ],
),
Row(
  mainAxisAlignment: MainAxisAlignment.spaceEvenly,
  children: [
    Container(
      height: 100,
      width: 100,
      color: Colors.amberAccent,
    ),
    Container(
```

```
                height: 100,
                width: 100,
                color: Colors.amberAccent[100],
              ),
              Container(
                height: 100,
                width: 100,
                color: Colors.amberAccent[200],
              ),
            ],
          ),
        ],
      ),
    ),
  ),
);
}
}
```

Practical 7

```
import 'package:flutter/material.dart';

void main() {
  runApp(MyApp());
}

class MyApp extends StatelessWidget {
  const MyApp({Key? key}) : super(key: key);

  @override
  Widget build(BuildContext context) {
    return MaterialApp(
      home: Scaffold(
        appBar: AppBar(
          title: Text('Theming and Styling'),
        ),
        body: Center(
          child: Column(
            mainAxisAlignment: MainAxisAlignment.spaceEvenly,
            children: [
              Image.network(
                'https://flutter.github.io/assets-for-api-docs/assets/widgets/owl-2.jpg',
// Sample image link
                height: 250,
```

```
            width: 250,
          ),
        ],
      ),
    ),
  ),
);
}
}
```