

ActiveRecord

Refresher

Why ActiveRecord

1. SQL is rigid, limited and easy to make syntax errors. Ruby is less so.
2. Same Ruby commands for different databases. (SQLite isn't the only one there!)
3. More versatility and options with Ruby DataTypes.

Plain Ruby

```
class User
```

```
end
```

```
User.where(id:1) => #no method error
```

```
ActiveRecord Jr
```

```
class User < Database::Model
```

```
end
```

```
User.where('id=?', 1) => #User Object
```

ActiveRecord

```
class User < ActiveRecord::Base
```

```
end
```

```
User.where('id=?', 1) => #Argument error
```

```
User.where(id:1) => #User Object
```

Comparison

Ruby Land	SQL
User.all => List of users	SELECT * FROM users
User.where(id:1)	SELECT * FROM users WHERE users.id = 1
User.first.purchases.where(price:300) SELECT * FROM purchases WHERE purchases.price = 300	

ActiveRecord 101 : How it all begins

ActiveRecord is ... a way to simplify coding by defining a standardised way to execute commands to change your database.

Database Essentials: What do we start with?

Tables and columns To interact: Use SQL language

e.g

```
CREATE TABLE users
```

```
ALTER TABLE users ADD COLUMN first_name string
```

```
DROP TABLE users
```

Weaknesses of using SQL:

1. It's all strings! I can't standardise them easily.
2. Easy to make syntax errors.
3. Batch commands (Everything is a single command ended with ;)
4. How do I undo my previous changes?

Database phases in business e.g :

1. Grocery store has products and daily transactions.
2. Grocery store opens up new branches, products need to be tracked by location
3. Grocery store set up online service, need to keep track of deliveries and online transaction

phase_one CREATE TABLE products CREATE TABLE transactions phase_two
CREATE TABLE branches

```
ALTER TABLE products ADD COLUMN branch_id
```

```
ALTER TABLE transactions ADD COLUMN branch_id
```

phase_three CREATE TABLE deliveries CREATE TABLE online_transactions

The SOLUTION = ActiveRecord Migrations

Example

```
class CreateStudents < ActiveRecord::Migration
  def change
    create_table :students do |t|
      t.string :first_name
      t.string :last_name
      t.string :email
      t.string :phone_number
      t.date :birthday
      t.timestamps
    end

    add_column :teachers, :subject, :string
  end
end
```

ActiveRecord Migrations is how you set up your database tables and structures.

It's like creating the blueprint for your database, or in other words, your schema.

How it works:

1. Write your migration file. (Create blueprint)
2. Start your migration! (Submit blueprint for execution)
3. ActiveRecord checks which migration needs to be run! (Check blueprint)
4. ActiveRecord runs the migrations! (Execute blueprint)
5. Rollback to previous versions if you need to. (Remove changes)

ActiveRecord 102 : How to write your migration

1. Write your migration file. (Create blueprint)
2. ActiveRecord checks which migration needs to be run! (Check blueprint)

The typical migration file:

location : `db/migrate/<migration_file_name>` migration_file_name : `20170126103050_create_students.rb`

```
20170126103050 => YYYYMMDDhhmmss

create_students => file_name

YYYYMMDDhhmmss_file_name.rb

class CreateStudents < ActiveRecord::Migration
end
```

My db/migrate folder:

```
20170126103050_phase_one.rb
20170126113030_phase_two.rb
20170126124030_phase_three.rb
```

```
20170126125040_final_phase.rb
```

My db/migrate folder:

```
20170126103050_phase_one.rb
```

```
class PhaseOne < ActiveRecord::Migration
```

```
end
```

```
20170126113030_phase_two.rb
```

```
class PhaseTwo < ActiveRecord::Migration
```

```
end
```

```
20170126124030_phase_three.rb
```

```
class PhaseThree < ActiveRecord::Migration
```

```
end
```

```
20170126125040_final_phase.rb
```

```
class FinalPhase < ActiveRecord::Migration
```

```
end
```

ActiveRecord::Migration Convention

1. Timestamp in filename determines the version.

- Used to determine whether to execute or not.
 - A past version will not be executed
 - Or to rollback to a specific time
2. File_name has to correspond to the class name

ActiveRecord 103: Executing your migration

1. Start your migration! (Submit blueprint for execution)

Q: How to trigger? A: rake db:migrate

But, how does your app know what to do?

```
rake -T
```

Rakefile The location where all your rake tasks are stored

```
desc "create the database"
task "db:create" do
  touch 'db/ar-students.sqlite3'
end

desc "drop the database"
task "db:drop" do
  rm_f 'db/ar-students.sqlite3'
end
```

But everything is stored in different places! How do I know what to run?

```
ActiveRecord Jr => app.rb
```

```
ActiveRecord ar-student-schema =>
```

```
db/config.rb
```

```
Rakefile
```

ActiveRecord 104: Symmetric Migrations OR Rolling Back

Remember this?

1. Grocery store has products and daily transactions.
2. Grocery store opens up new branches, products need to be tracked b location
3. Grocery store set up online service, need to keep track of deliveries and online transaction

```
phase_one
```

```
CREATE TABLE products
```

```
CREATE TABLE transactions
```

```
phase_two
```

```
CREATE TABLE branches
```

```
ALTER TABLE products ADD COLUMN branch_id
```

```
ALTER TABLE transactions ADD COLUMN branch_id
```

```
phase_three
```

```
CREATE TABLE deliveries
```

```
CREATE TABLE online_transactions
```

I run `rake db:version = 20170126120000_phase_three.rb`

BUT IT'S NOT WORKING! MY CODE IS BROKEN!

How do I go back to phase_one?

in SQL:

```
DROP TABLE deliveries
```

```
DROP TABLE online_transactions
```

```
ALTER TABLE products DROP COLUMN branch_id
```

```
ALTER TABLE transactions DROP COLUMN branch_id
```

```
DROP TABLE branches
```

in ActiveRecord: `rake db:migrate version= 20170126113020_phase_two.rb`

Symmetric Migration:

If by running my migration I can execute changes to my database, I can revert the changes my migration made by running the reverse of my migration.

```
def up
```

```
  create_table :students do |t|
```

```
    ...
```

```
  end
```

```
end
```

```
def down
```

```
  drop_table :students
```

```
end
```

Some Git Fu

```
git add .           => Stages/ Prepares my files for commit and pushing.
```

```
git commit -m 'my_message'  => Commits the changes under a message for clarity
```

```
git push           => Pushes my changes to the remote repository
```


`git clone <url>` => Clones the file and generates a git init file for

my git configuration, i.e where my repository is.

If you didn't clone, you have no git init and you will have to set up your remote repository location manually.

`git init`

`git remote add origin git@github.com:<username>/<filename>`

Helpful commands to have an idea where you are:

`git status` => Shows information about your current git status(are you up to

date? What files have changed? What branch am I on?)

`git remote -v` => What's my repository?

`git help` => HELP!