

FAA Part 107 Practice Exam

50 questions • answer key with explanations • free from part107quiz.com

How to use this exam: give yourself 100 minutes (the real exam's pace), no notes, and circle your answers. The pass mark on the real test is 70% — 35 of 50 here. Score yourself with the key at the back: every answer includes a plain-English explanation and the FAA reference behind it. Miss a topic repeatedly? Drill it free at the online practice tests.

Original questions based on public FAA source material (14 CFR Part 107, the Remote Pilot ACS, FAA study guides). Not affiliated with or endorsed by the FAA. Not actual exam questions — no one outside the FAA has those.

1. The standing stadium TFR restricts flight near major sporting events within what radius and time window?

- A. 3 NM radius, from 1 hour before until 1 hour after the event
- B. 10 NM radius during the event
- C. 1 NM radius, during the event only
- D. 5 NM radius, all day on game day

2. Which statement about the preflight crew briefing is correct?

- A. It should assign roles, communication procedures, and contingencies before flight
- B. It is optional for a crew of two
- C. It is required only for night operations
- D. It should happen only after an incident

3. Prior to flight, the remote pilot in command must assess the operating environment, including:

- A. Only the official TAF forecast at the nearest Class B international airport
- B. Nothing, if the flight is under 15 minutes
- C. Only the battery level
- D. Local weather conditions, local airspace, and any ground hazards

4. On a sectional chart, a soft blue vignette (a wide, fuzzy blue band) marks a boundary. What does it separate?

- A. Airspace where a Part 107 pilot must obtain ATC authorization from airspace where no authorization is required
- B. Class D airspace from Class C airspace
- C. Two adjacent Maximum Elevation Figure quadrants
- D. Areas where the Class E floor is 1,200 ft AGL from areas where it starts higher

5. Crew Resource Management (CRM) is best defined as:

- A. Effective use of ALL available resources — people, hardware, and information
- B. A maintenance scheduling system
- C. A radio phraseology standard
- D. A checklist-reading method

6. Which statement about visual observers (VOs) under Part 107 is true?

- A. A VO is required for every commercial flight
- B. Using a VO is optional, and it does not remove the see-and-avoid responsibilities of the RPIC
- C. A VO may watch the aircraft through binoculars full-time
- D. VOs must hold their own remote pilot certificate

7. Situational awareness is best described as:

- A. Accurate perception of all factors and conditions affecting flight safety
- B. Knowing only your GPS position
- C. Reading back all radio calls
- D. Watching the aircraft at all times

8. A person may not operate an sUAS with a blood alcohol concentration at or above what level?

- A. 0.02
- B. 0.10
- C. 0.04
- D. 0.08

9. Next to an airport, the sectional chart shows 'CT - 118.3'. What does this mean?

- A. Runway 11/83 is in use
- B. The CTAF is unavailable at this field
- C. The field elevation is 1,183 ft MSL
- D. The control tower frequency is 118.3

10. A non-towered airport 2 NM away is ringed by a dashed magenta line. You intend to fly at 200 ft AGL inside that ring. You must:

- A. self-announce your intentions on the CTAF before every takeoff and every landing
- B. obtain FAA airspace authorization before flying
- C. notify the airport operator in writing at least 24 hours before the planned flight
- D. stay at or below 400 ft AGL, which is all that Part 107 asks of you at that location

11. A Part 107 waiver application must demonstrate what?

- A. That the operation can be performed safely under the terms of the certificate
- B. That the applicant carries liability insurance appropriate to the scale of the operation
- C. That the same operation has already been flown safely at least once under a certificate of authorization
- D. That no alternative method of complying with the rule exists for the proposed operation

12. An MEF shown as a large '2' with a small '3' means the highest feature in that quadrant is approximately:

- A. 2,300 ft MSL
- B. 2,300 ft AGL
- C. 23,000 ft MSL
- D. 230 ft MSL

13. Exceeding the manufacturer's maximum gross weight risks:

- A. Nothing, provided the overload lasts only a few minutes
- B. Better stability in wind
- C. Only a shorter warranty
- D. Structural overstress and degraded performance

14. After a near-miss with a helicopter that did not meet the 107.9 reporting threshold, the most useful next action is to:

- A. debrief the crew and revise the site's hazard assessment
- B. take no action, because no report is required
- C. abandon the site permanently and tell the client the location cannot be flown under any conditions
- D. submit an accident report anyway so a record exists

15. What is the minimum flight visibility for Part 107 operations?

- A. 1 statute mile
- B. There is no visibility minimum for sUAS operations below 400 ft
- C. 3 statute miles from the control station
- D. 5 statute miles

16. Two hours before a scheduled roof inspection you learn that a VIP TFR now covers the site. You should:

- A. fly anyway below 200 ft AGL, since TFRs restrict only manned aircraft above 500 ft
- B. cancel or reschedule the flight
- C. call local law enforcement and request a spot exemption for a short commercial flight
- D. launch immediately, before the effective time published in the NOTAM takes hold

17. Under Part 107, carrying hazardous materials on a small unmanned aircraft is:

- A. Prohibited
- B. Allowed with proper placards
- C. Allowed only over unpopulated areas
- D. Allowed if the total weight stays under 55 lb

18. Overhead your site the Class B segment is charted 80 over 30. Field elevation is 500 ft MSL and you plan to fly at 300 ft AGL. Do you need Class B authorization?

- A. Yes, because 300 ft AGL converts to 800 ft MSL, which is above the floor
- B. Yes - being laterally inside the Class B ring is what triggers the requirement
- C. No - the flight stays below the 3,000 ft MSL floor of that segment
- D. Only if the UAS Facility Map grid for the site reads 0, which it always does inside a Class B ring

19. Regarding lost-link (loss of control signal), the remote pilot should:

- A. Know the aircraft's programmed lost-link behavior before flight
- B. Assume the aircraft will always crash
- C. Treat it as a reportable accident in every case
- D. Wait indefinitely for reconnection before acting

20. For Part 107 purposes, night begins and ends at:

- A. one hour after sunset and one hour before sunrise, regardless of latitude or season
- B. the moment the remote pilot can no longer make out the aircraft's outline unaided
- C. sunset and sunrise as published for the operating location in the Chart Supplement
- D. the end of evening civil twilight and the beginning of morning civil twilight

21. Since the 2021 rule change, conducting a Part 107 operation at night requires:

- A. a 107.29 waiver, but only when the flight also passes over people or moving vehicles
- B. no additional action of any kind, because the FAA removed the night restriction from Part 107 entirely
- C. a 107.29 waiver, applied for through DroneZone at least 90 days in advance
- D. updated recurrent training plus anti-collision lighting visible for 3 statute miles

22. What must be done with a broadcast module's serial number?

- A. Nothing — it activates automatically
- B. Etch it on the propellers
- C. List it in the aircraft's FAA registration record
- D. Keep it strictly confidential for national security reasons

23. During takeoff and landing — the most critical phases — the crew should:

- A. Rotate crew roles between positions to build practice reps
- B. Play the mission soundtrack
- C. Minimize non-essential conversation and distractions
- D. Chat to stay relaxed

24. While filming near a small airport in Class G airspace, a helicopter enters the traffic pattern. Part 107 requires that you:

- A. Climb above the pattern altitude
- B. Not interfere with airport operations or traffic patterns, yielding right of way
- C. Land immediately and end all operations for the day
- D. Contact the helicopter on the radio

25. Which airspace classes require ATC authorization before a Part 107 flight?

- A. Only Class B
- B. Class B, C, D, and surface Class E
- C. All airspace classes, including uncontrolled Class G
- D. Class B and C only

26. At night a remote pilot's ability to judge the aircraft's distance and orientation degrades, mainly because:

- A. anti-collision strobes wash out the aircraft's silhouette at every distance
- B. the eye's colour receptors adapt to darkness faster than its low-light receptors do
- C. peripheral vision sharpens after dark while central vision stays unchanged
- D. depth perception relies on cues that darkness removes

27. What does it cost to register a drone for Part 107 operations, and how long is the registration valid?

- A. \$5 per pilot for all aircraft, valid 1 year
- B. \$25 per aircraft, valid 3 years
- C. \$5 per aircraft, valid 3 years
- D. Free, valid forever

28. What are the three ways to comply with the Remote ID rule?

- A. Filing a flight plan before each mission
- B. Registration, insurance, and a waiver
- C. A transponder, ADS-B Out, and radar contact
- D. A Standard Remote ID drone, a broadcast module, or flying at a FRIA

29. What is the maximum groundspeed allowed for a small unmanned aircraft under Part 107?

- A. 55 knots
- B. 87 mph
- C. 100 mph (87 knots)
- D. 120 mph when operating in Class G airspace

30. Which of the following still requires a waiver rather than a routine authorization or a standard preflight step?

- A. Climbing to 400 ft above a tower while remaining within 400 ft of it
- B. Flying at night with anti-collision lighting fitted to the aircraft
- C. Flying beyond visual line of sight
- D. Flying in Class C airspace at an altitude that LAANC has approved

31. What is the antidote for INVULNERABILITY ('It won't happen to me')?

- A. It could happen to me
- B. Not so fast — think first
- C. Taking chances is foolish
- D. Follow the rules

32. A small unmanned aircraft must yield the right of way to:

- A. Only aircraft below 400 ft AGL
- B. Only manned aircraft in distress
- C. All other aircraft
- D. Only other unmanned aircraft

33. The safest guidance for charging sUAS batteries is to:

- A. Always store packs fully charged so they're ready to fly
- B. Use any USB charger that fits
- C. Charge unattended overnight
- D. Follow the manufacturer's charging instructions

34. For 'direct supervision' of a non-certificated person flying the drone, the RPIC must be able to:

- A. Monitor the aircraft's live video feed from a remote location
- B. Sign the person's logbook
- C. Stand within 10 feet of the person
- D. Take immediate control of the small unmanned aircraft

35. To keep exercising the privileges of a remote pilot certificate, how often must you complete recurrent training?

- A. Every 12 calendar months
- B. Only once, before the initial knowledge test
- C. Every 36 calendar months
- D. Every 24 calendar months

36. How can you verify that your drone has Standard Remote ID?

- A. Ask the retailer
- B. Look it up on the FAA's public Declaration of Compliance (DOC) list
- C. Check whether the aircraft weighs over 250 g
- D. Assume that any drone manufactured after January 2020 complies automatically

37. A Certificate of Waiver is issued with special provisions attached. Those provisions:

- A. may be disregarded whenever the remote pilot in command judges conditions to be safer than anticipated
- B. expire 12 calendar months after issue regardless of the dates printed on the certificate
- C. apply only to the specific aircraft serial number that was listed in the application
- D. are binding, and operating outside them voids the waiver

38. How does cold weather typically affect drone battery performance?

- A. Cold prevents overcharging
- B. Voltage sag and reduced capacity shorten flight time
- C. There is no effect
- D. Capacity improves in cold air

39. A dashed magenta keyhole extends about 3 NM off one side of an airport's dashed magenta circle, and your launch point falls inside that extension. What does that mean for your flight?

- A. It is part of the Class E surface area and needs authorization just as the circle does
- B. It marks a published instrument approach advisory and carries no authorization requirement of its own
- C. The extension is Class G, so no authorization is required
- D. It is Class D airspace and the tower must be telephoned before launch

40. How does HIGH density altitude affect a multirotor drone?

- A. Battery endurance increases
- B. Rotor/propeller efficiency and overall performance decrease
- C. Rotor efficiency improves
- D. It has no measurable performance effect below 400 ft AGL

41. What is the minimum age to hold a remote pilot certificate with an sUAS rating?

- A. 16 years old
- B. 14 years old
- C. 21 years old
- D. 18 years old

42. The temperature/dewpoint spread is small and decreasing. What should you expect?

- A. A rapid drop in density altitude
- B. Fog or low clouds are likely to form
- C. Severe clear-air turbulence at the surface is imminent
- D. Visibility will improve

43. Upon request, the remote pilot in command must present the remote pilot certificate to which of the following?

- A. Only FAA aviation safety inspectors conducting a formal ramp inspection at the flight site
- B. The FAA, NTSB, TSA, or any federal, state, or local law enforcement officer
- C. Insurance company adjusters
- D. Airport managers within 5 NM

44. Advection fog forms when:

- A. Ground cools rapidly on a calm, clear night
- B. Air is forced down a mountain slope
- C. Moist air moves over a cooler surface
- D. Rain falls into a layer of dry air

45. On a VFR sectional chart, a dashed blue line around an airport depicts which airspace?

- A. Class E at the surface
- B. Class D
- C. Class C
- D. Class B

46. Under the PAVE checklist for preflight risk assessment, the 'E' stands for:

- A. Endurance
- B. Equipment
- C. External pressures
- D. Emergency procedures rehearsed with the crew before every departure

47. Your launch site sits under the faded magenta vignette but outside any dashed line. You will fly at 350 ft AGL. What authorization do you need?

- A. A 107.41 waiver through FAA DroneZone, because the vignette marks controlled airspace at the surface
- B. None — you are in Class G below 700 ft AGL
- C. Verbal permission from the nearest control tower on the CTAF frequency
- D. LAANC authorization for surface Class E, which the vignette depicts around every non-towered airport

48. A client wants footage of an antenna tower that stands 700 ft tall. Staying within 400 ft of the structure, how high may you legally fly?

- A. Up to 700 ft AGL, matching the height of the structure you are inspecting
- B. Up to 1,100 ft AGL
- C. Up to 400 ft AGL, because the Part 107 ceiling has no exception for tall structures
- D. Any altitude at all, as long as you remain within a 400-ft radius of the tower

49. Your aircraft has forward obstacle-avoidance sensors. When planning a route through a tree-lined corridor, you should treat those sensors as:

- A. sufficient justification for operating beyond visual line of sight without a waiver whenever the sensors are functioning normally
- B. an assurance that the aircraft will stop short of any obstacle
- C. a backup that may not detect thin branches or wires
- D. a substitute for visual line of sight inside the corridor

50. What does a Military Operations Area (MOA) mean for a small UA pilot?

- A. Military training occurs there — flight is not prohibited, but exercise extreme caution
- B. LAANC authorization is mandatory
- C. Drone flight is prohibited at all times
- D. Only military drones may fly

Answer Key & Explanations

Score: correct ÷ 50. The FAA pass mark is 70% (35 correct). 85%+ (43 correct) means you're comfortably ready. More free practice: <https://part107quiz.com>

1. A — Flights are restricted within 3 NM of qualifying stadium events (MLB, NFL, NCAA Division I football, major races) from one hour before to one hour after.

Reference: FDC NOTAM 4/3621 (stadium TFR)

2. A — Before flight, 14 CFR 107.49(b) requires the remote PIC to ensure everyone directly participating is informed about the operating conditions, emergency procedures, contingency procedures, roles and responsibilities, and potential hazards. How the crew will communicate belongs in the same briefing: when a VO is used, 107.33(a) requires effective communication at all times, and AC 107-2A 5.9.2.2 says the communication method must be determined prior to operation.

Reference: 14 CFR 107.49(b), 107.33(a); AC 107-2A 5.9.2.2

3. D — 107.49 requires assessing weather, airspace and flight restrictions, people and property on the ground, and other ground hazards before every flight.

Reference: 14 CFR 107.49(a)

4. D — A soft magenta vignette marks where Class E begins at 700 ft AGL. A soft blue one marks where Class E begins at 1,200 ft AGL next to uncontrolled airspace. On the shaded side, Class E starts at 1,200 ft AGL. On the sharp-edged side, Class G continues higher, up to 14,500 ft MSL unless a different floor is charted. At 400 ft AGL, outside any surface area, you are in Class G on either side, so the dashed and solid boundary lines drive your authorization decision, not the vignettes.

Reference: FAA Aeronautical Chart Users' Guide, Explanation of VFR Terms and Symbols: Airspace (Class E vignettes); AIM 3-2-6; 14 CFR 71.71(c)

5. A — CRM means integrating your crew (VOs, camera operators), equipment, and information sources to maximize safety — it applies to sUAS crews, not just airliners.

Reference: FAA Remote Pilot Study Guide

6. B — VOs are optional crew. Even with a VO, the RPIC and person flying must still be able to see the aircraft and maintain awareness; vision aids like binoculars may only be used momentarily.

Reference: 14 CFR 107.31, 107.33

7. A — The FAA defines situational awareness as the accurate perception and understanding of all the factors and conditions within the five fundamental risk elements (flight, pilot, aircraft, environment, and type of operation) that affect safety before, during, and after the flight, not just knowing where the drone is right now.

Reference: FAA-G-8082-22 (Remote Pilot Study Guide) Ch. 10, Situational Awareness; FAA-H-8083-25C (PHAK) Ch. 2

8. C — The limit that applies to airmen, including remote pilots, is .04 BAC — stricter than the typical .08 driving limit.

Reference: 14 CFR 107.27, 91.17

9. D — 'CT' identifies the control tower frequency. Monitoring it (or the CTAF at non-towered fields) builds situational awareness about nearby manned traffic.

Reference: Sectional chart legend

10. B — A dashed magenta line is Class E beginning at the surface — controlled airspace at ground level. Your altitude is irrelevant; any Part 107 flight inside that boundary needs prior FAA authorization.

Reference: 14 CFR 107.41; sectional chart legend

11. A — The applicant must show the FAA that the proposed operation can be conducted safely under the waiver's terms, usually by describing the mitigations that replace the protection the waived rule provided.

Reference: 14 CFR 107.200

12. A — Read MEF as thousands then hundreds of feet MSL: 2 and 3 = 2,300 ft MSL.

Reference: Sectional chart legend

13. D — Weight above design limits eats into structural margins and performance — and any payload attached counts toward the 55-lb Part 107 limit too.

Reference: FAA Remote Pilot Study Guide

14. A — Reportability and learning are separate questions. A debrief that feeds back into the site hazard assessment is what prevents a second occurrence; a voluntary ASRS filing is also available.

Reference: FAA-H-8083-25B Ch.2; 14 CFR 107.9

15. C — Minimum visibility, as observed from the control station, is 3 statute miles.

Reference: 14 CFR 107.51(c)

16. B — TFRs apply to unmanned aircraft too, and violating one risks certificate action plus federal penalties. No local authority can waive a TFR, so reschedule and re-check NOTAMs or B4UFLY before every flight.

Reference: 14 CFR 91.137-91.145; FAA NOTAM guidance

17. A — 107.36 flatly prohibits the carriage of hazardous materials (as defined in 49 CFR 171.8), including spare lithium batteries carried as cargo.

Reference: 14 CFR 107.36

18. C — Class B is only the charted volume. A segment marked 80/30 runs from 3,000 ft MSL to 8,000 ft MSL, so a flight topping out near 800 ft MSL passes underneath it, in whatever Class E or G lies below. No Class B authorization is needed - but check separately for a Class D or Class E surface area sitting under the shelf.

Reference: 14 CFR 107.41; FAA Chart User's Guide

19. A — Preflight planning includes knowing exactly what the aircraft will do on lost link (RTH altitude, hover time, land) and confirming those settings fit the site.

Reference: 14 CFR 107.49; ACS UA.V

20. D — Night runs from the end of evening civil twilight to the beginning of morning civil twilight, published in the Air Almanac and converted to local time. Civil twilight itself is not night, though it carries the same anti-collision lighting requirement.

Reference: 14 CFR 1.1, 107.29

21. D — The waiver requirement was removed, but two conditions replaced it: training that covers night operations, and anti-collision lighting visible for at least 3 statute miles. Removing the waiver did not remove the rule.

Reference: 14 CFR 107.29, 107.65

22. C — The module's serial number must be listed on the Certificate of Aircraft Registration of the aircraft it is flying on (14 CFR 89.115(a)(1)(ii)). Under Part 107 it may be listed on only one aircraft's registration at a time, so before moving the module to another aircraft, move its serial number to that aircraft's registration in FAADroneZone (AC 107-2A 5.17.1).

Reference: 14 CFR Part 89; FAA DroneZone guidance

23. C — A 'sterile crew' discipline during critical phases keeps attention on the aircraft and its surroundings when risk is highest.

Reference: CRM concepts; FAA Remote Pilot Study Guide

24. B — You may operate in Class G near an airport, but 107.43 and 107.37 require staying clear of patterns and yielding to all manned aircraft.

Reference: 14 CFR 107.37, 107.43

25. B — Controlled airspace for drones means B, C, D, and the surface areas of Class E. Class G needs no authorization.

Reference: 14 CFR 107.41

26. D — Judging distance depends on seeing size, shape, and the surroundings, and darkness takes all three away. A pair of navigation lights gives orientation but almost no distance information, which is why aircraft feel closer than they are at night.

Reference: FAA-H-8083-25C Ch. 17 (Night Vision; Distance Estimation and Depth Perception); AC 107-2A 5.9.3

27. C — Part 107 registration in FAA DroneZone is \$5 per aircraft and lasts 3 years. The registration number must be marked on the outside of the aircraft.

Reference: 14 CFR Part 48

28. D — Compliance paths: built-in Standard Remote ID, an add-on broadcast module, or flying without RID only inside an FAA-Recognized Identification Area.

Reference: 14 CFR Part 89

29. C — The groundspeed limit is 100 mph, which equals 87 knots. Remember it is groundspeed, not airspeed, so a tailwind counts against you.

Reference: 14 CFR 107.51(a)

30. C — Beyond visual line of sight is a deviation from 107.31 and needs a Certificate of Waiver. The other three are ordinary compliant operations, one of which needs an airspace authorization rather than a waiver.

Reference: 14 CFR 107.31, 107.51, 107.200

31. A — Believing accidents only happen to others is countered with 'It could happen to me.'

Reference: FAA Remote Pilot Study Guide; PHAK ch. 2

32. C — The sUAS must yield to ALL aircraft, airborne vehicles, and launch/reentry vehicles, and may not pass over, under, or ahead of them unless well clear.

Reference: 14 CFR 107.37

33. D — Manufacturer procedures govern charge rates, balance charging, and storage voltage — deviating is the most common cause of battery incidents.

Reference: FAA AC 107-2A, Appendix B, para B.5 (Battery Fires)

34. D — Direct supervision means the RPIC can immediately take over the controls — the legal basis for letting a trainee or camera operator fly.

Reference: 14 CFR 107.12, 107.19

35. D — Recurrent training (free, online) must be completed within the previous 24 calendar months to operate under Part 107. The certificate itself does not expire.

Reference: 14 CFR 107.65

36. B — The FAA's DOC database lists compliant makes/models; most current mainstream drones comply via firmware, but verification is the pilot's responsibility.

Reference: FAA UAS Declaration of Compliance listing

37. D — The provisions are the conditions on which the FAA accepted the risk. Flying outside them means flying without a waiver, so the underlying rule applies again and is being broken.

Reference: 14 CFR 107.200, 107.205

38. B — Cold slows the chemical reaction in lithium cells: expect voltage sag, shorter flights, and possible sudden capacity drops. Pre-warm packs and hover to warm them gently.

Reference: Manufacturer's aircraft/battery user manual (low-temperature operation notice)

39. A — Class E surface area extensions exist to protect aircraft flying instrument approaches, which is precisely why they are drawn where arriving traffic is low and slow. They are the same airspace class as the circle they hang off, so a Part 107 flight inside one needs authorization - and the approach traffic overhead is the real reason to care.

Reference: 14 CFR 107.41; FAA Chart User's Guide

40. B — Hot, high, and humid conditions thin the air. Props produce less thrust, motors work harder, and endurance drops.

Reference: FAA Remote Pilot Study Guide; PHAK ch. 11 concepts

41. A — You must be at least 16 years old to be eligible for a remote pilot certificate.

Reference: 14 CFR 107.61

42. B — When temperature approaches the dewpoint, air is near saturation — fog, mist, or low stratus become likely, threatening your 3-SM visibility minimum.

Reference: FAA Remote Pilot Study Guide

43. B — 107.7 requires presenting the certificate and identification on request to the FAA, NTSB, TSA, or law enforcement.

Reference: 14 CFR 107.7

44. C — Advection fog needs wind to push moist air across a colder surface — why it is common along coastlines, and it can persist under windier conditions than radiation fog.

Reference: FAA-H-8083-25C (PHAK) Ch.12, Fog; FAA-H-8083-28B, Aviation Weather Handbook, 18.1.1.1.2 Advection Fog

45. B — Class D airspace (smaller towered airports) is charted with a dashed blue line, typically from the surface to about 2,500 ft AGL.

Reference: Remote Pilot ACS UA.II; sectional legend

46. C — PAVE covers Pilot-in-command, Aircraft, enVironment, and External pressures. Deadlines, client expectations, and unpaid travel time are the category pilots most often leave out of the assessment.

Reference: FAA-H-8083-25B Ch.2

47. B — The fuzzy magenta vignette marks where Class E begins at 700 ft AGL. Below that floor the airspace is Class G, so no authorization is required. It is the dashed magenta line, not the vignette, that marks surface Class E.

Reference: Sectional chart legend; 14 CFR 107.41

48. B — Within a 400-ft radius of a structure you may fly up to 400 ft above that structure's uppermost limit, so $700 + 400 = 1,100$ ft AGL. Step outside the radius and the plain 400-ft ceiling applies again.

Reference: 14 CFR 107.51(b)

49. C — Obstacle sensors routinely miss thin, low-contrast objects such as wires, branches, and netting. They reduce risk but transfer none of the RPIC's responsibility and relax nothing in 107.31.

Reference: 14 CFR 107.31, 107.49; FAA-H-8083-25B Ch.2

50. A — MOAs separate military training from IFR traffic. Drones are not banned, but fast low-flying military aircraft demand extra vigilance.

Reference: [FAA Remote Pilot Study Guide](#)

Want the full experience? The free online mock exam at <https://part107quiz.com> runs 60 questions against a live 120-minute timer with automatic per-area scoring — the closest thing to test day without the fee.