Per-cell active-strain fit

C. Allier — HHMI Janelia Research Campus

Companion to `github.com/allierc/GNN_MPM_cardio`. §1 the data and the cell segmentation; §2 the model; §3 the material point method; §4 how the pulse drives the cells; §5 results; §6 install and run.

1 Data

Recordings. Two confluent sheets of human iPSC-derived cardiomyocytes on a 15 kPa gel, phase contrast, 2048×2048 px, 24 frames per second (41.7 ms per frame): one healthy (239 frames), one carrying a hypertrophic cardiomyopathy (HCM) mutation (299 frames). No electrical recording, no calcium dye, no stain, no force measurement.

Tracking (the "grid flow"). Each movie is tracked on a 137×137 lattice of points 15 px apart (18,769 points), giving the point positions $x_i(t)$ in image pixels, referenced to frame 0 (Lagrangian). Displacement amplitude: mean 1.7 px, maximum ≈15 px (healthy); mean 2.8 px (HCM). The sheet domain in the engine is $x^{\text{world}} = 0.15 + 0.70\, x^{\text{img}}/2048$. Shipped as `data/{healthy,hcm}/grid_flow.npz` with a sha256 of the array checked at load.

Cell segmentation (`cardio/segmentation.py`, `cardio/seg/`; Figs. 1 and 2). The pixels of one cell move together, so the cells can be found from the motion alone: the tracking nodes of one cell contract along the same direction, and a border lies where that direction changes between neighbouring nodes. The same procedure is used on the healthy and the HCM recording.

1. *Borders from the motion.* The contraction direction of each node is read from its trajectory averaged over the beats; borders are where this direction, smoothed over the lattice, changes sharply.
2. *Nuclei.* One dark nucleus per cell is found on the rest frame (flat-fielded with a 60-px blur, then Laplacian-of-Gaussian blobs of 25–60 px): 472 for the healthy sheet, 434 for HCM; each is the seed of one cell.
3. *Watershed.* Seeded by the nuclei, on the border strength plus the distance to the nearest seed, every node is given one cell: 472 (434) cells.
4. *Label image.* For the engine, a 2560×2560 map in which each pixel takes the label of the nearest node.




Figure 1: Segmentation on a 300×300 px detail of the healthy rest frame. (a) Borders from the motion: contraction axis of every second node (colour = angle) over the border strength (bright = border). (b) Nuclei. (c) Watershed: nodes coloured by cell, seeds in black. (d) The engine's label image, as outlines.




Figure 2: The data. (a, c) Rest frame of the healthy and HCM recordings with every 4th node of the tracking lattice. (b, d) The segmentation on the lattice, one colour per cell, nuclei in black.

2 The model

Every segmented cell is modelled as a patch of elastic material that shortens along its own fibre axis when a shared activation pulse reaches it, and is subject to a drag and a spring (see details below); gradient descent through the simulation returns the per-cell numbers that make the simulated sheet move like the recording, cell by cell.

The sheet is cut into the 472 segmented cells (434 for HCM), each filled with 120 material points. One step of the simulation is one recorded frame: $dt = 0.002$ engine time units, 41.7 ms of recording. In each step the engine first computes two accelerations on every point, a drag and a spring, from the state at the start of the step. It then runs 10 sub-steps of $dt = 2 \times 10^{-4}$ of the material point method (§3). The sub-steps take the points' positions, velocities, deformations and stiffnesses together with the two accelerations, and return new positions, velocities and deformations. Drag and spring are not recomputed inside the sub-steps: the same two accelerations act in all ten sub-steps. After the ten sub-steps, once per frame, every cell is shortened along its fibre axis in proportion to its activation (§4), and each cell is measured: the least-squares affine map of its points from their rest positions, A_j (a 2×2 matrix, the cell's mean deformation gradient: stretch, shear and rotation) and u_j (the shift of its centroid). The function `cell_affine` (`cardio/recording.py`) computes it, identically for the model's material points and for the recording's tracking nodes. It is what the fit is trained on: the loss is the mean squared mismatch of A_j and u_j between model and recording, each scaled by the recording's own spread.

Drag (operator `drag`, `operators/motion_ops.py`). Viscous friction: a point of velocity v gets the acceleration $-k\,v$, with $k = 150$ per engine time unit, so a point loses 63% of its speed in 3.3 frames. It stands for friction against the surroundings. Without it the sheet rings on its spring. With a weaker drag ($k = 30$), a step in the activation made the sheet overshoot to -32% of its plateau and stay 10% off twenty frames later. At $k = 150$ the drag is 0.75 of the value that would critically damp the spring ($2\sqrt{\kappa}$, with κ below).

Spring (operator `anchor_percell`, `cardio/ops_percell.py`). The cells sit on a 15 kPa gel, and every material point is attached to its own rest position X by a spring. A point displaced to x is pulled back with the acceleration $\kappa\,(X - x)$, where κ is the spring stiffness: $\kappa = 10^4$ in engine units times a factor learned per cell. The 10^4 is set by hand and not trained. The factor starts at 1, is held near 1 by a penalty and may range from 0.14 to 7.4; after training it lies between 0.89 and 1.19 (healthy). It stands for the cells' adhesion to the gel. Without it the whole sheet relaxes through the drag alone, an estimated 460 frames at $k = 150$ (90 at $k = 30$), against a beat of 55–65 frames.

3 Material point method

The material point method (MPM) of Sulsky et al. [2] simulates a continuum with particles that carry mass, velocity and deformation, coupled through a background grid; we use its moving-least-squares form (MLS-MPM) of Hu et al. [1]. Our PyTorch implementation is `https://github.com/saalfeldlab/MPM_pytorch`.

Implementation. Each step is one operator (`mpm_strain`, `mpm_scatter`, `mpm_grid_update`, `mpm_gather`); the four run together as the sub-step block, in their `differentiable` implementation after Xu et al. [3]: the same arithmetic as the default bodies, with each result bound to a new tensor so that automatic differentiation keeps what the backward pass needs. The grid has 128 by 128 nodes over the unit square; each point reaches the 3 by 3 nodes nearest to it, with quadratic B-spline weights. The drag and spring accelerations of §2 enter in the second step, as a body force; the pulse of §4 enters in the first step, as a change of the deformation gradient written once per frame, which the second step turns into stress.

The four steps, in the order they run in each of the 10 sub-steps.

1. **Advance the strain** (`mpm_strain`). Each point updates its deformation from the velocity gradient it carries, then the material rule is applied: elastic keeps the deformation as updated (this model); a liquid would keep only the volume; a plastic material (snow) would clip the singular values of F; a viscoelastic one would let F relax toward the current shape over a time constant.

$$F_p \leftarrow (I + \Delta t\, C_p)\, F_p, \qquad J_p = \det F_p$$

2. **Points to grid** (`mpm_scatter`). Each point computes its stress from its deformation, then spreads its mass, its momentum and the impulse of its stress onto the 9 nearest nodes, weighted by w_{np}. The stress impulse points back toward the rest shape. The drag and spring accelerations are added here, clamped.

$$\begin{aligned}
\sigma_p &= 2\mu_p\,(F_p - R_p)\,F_p^\top + \lambda_p\,(J_p - 1)\,J_p\,I \\
m_n &= \sum_p w_{np}\,m_p \\
p_n &= \sum_p w_{np}\Big[m_p\big(v_p + C_p(x_n - x_p)\big) - \frac{4\Delta t}{\Delta x^2}\,V_p\,\sigma_p\,(x_n - x_p) + \Delta t\,m_p\,\bar{a}_p\Big] \\
\bar{a}_p &= \mathrm{clamp}\big(-k\,v_p + \kappa_p(X_p - x_p),\ \pm a_{\max}\big)
\end{aligned}$$

3. **Solve the grid** (`mpm_grid_update`). Each node turns its momentum into a velocity; the wall condition is applied at the box faces.

$$v_n = \frac{p_n}{m_n}\ \ (m_n > 0,\ \text{else } 0), \qquad v_n \leftarrow \mathrm{BC}(v_n, x_n)$$

4. **Grid to points** (`mpm_gather`). Each point takes the velocity and the velocity gradient of the nodes around it, and moves.

$$v_p = \sum_n w_{np}\,v_n, \qquad C_p = \frac{4}{\Delta x^2}\sum_n w_{np}\,v_n\,(x_n - x_p)^\top, \qquad x_p \leftarrow x_p + \Delta t\,v_p$$

The weight of node n at point p is a product of one-dimensional quadratic B-splines:

$$w_{np} = \prod_{d=1}^{2} N\left(\frac{x_{n,d} - x_{p,d}}{\Delta x}\right), \qquad N(r) = \begin{cases} \frac{3}{4} - r^2 & |r| < \frac{1}{2} \\ \frac{1}{2}\left(\frac{3}{2} - |r|\right)^2 & \frac{1}{2} \le |r| < \frac{3}{2} \\ 0 & \text{else} \end{cases}$$

symbol	meaning
$F_p,\ R_p,\ J_p$	deformation gradient of point p, its rotation part ($F = R\,S$ with S the stretch), its determinant
σ_p	stress of point p in the fixed-corotated law: μ penalises change of shape ($F - R$), λ change of volume ($J - 1$); a rotation alone gives none
C_p	velocity gradient carried by point p
$x_p,\ v_p,\ X_p$	position, velocity and rest position of point p
$m_p,\ V_p$	mass and rest volume of point p; $m_p = \rho V_p$ with density $\rho = 1$
$m_n,\ p_n,\ v_n,\ x_n$	mass, momentum, velocity and position of grid node n
w_{np}	weight of node n at point p, over the 3 by 3 nodes around the point
$\bar{a}_p$	acceleration of point p from drag and spring, clamped at $a_{\max} = 200$
$\mu_p,\ \lambda_p$	Lamé stiffnesses of the point's cell: $\mu = E/2(1+\nu)$, $\lambda = E\nu/(1+\nu)(1-2\nu)$, E the Young's modulus, $\nu = 0.3$
$\Delta t,\ \Delta x$	sub-step 2×10^{-4} engine time units; grid spacing $1/128$ of the unit square
$k,\ \kappa_p$	drag 150 and spring stiffness of point p (10^4 times the cell's learnable factor)
BC	wall condition within 0.06 of a box face: the velocity into the wall is removed, the rest damped by 0.5; the sheet never reaches it

The sub-step stays below the stability limit $\Delta t < \Delta x/\sqrt{E/\rho}$: 8.7×10^{-4} against 2×10^{-4} for the starting Young's modulus $E = 80$.

4 Pulse activation

Nothing in §3 makes a cell move on its own: the material point method only relaxes elastic stress. The beat enters as a change of each cell's rest shape, once per frame, written into the deformation gradient of the cell's

points, and the material law of §3 turns it into motion during the following sub-steps. No force and no velocity are injected.

The shared pulse. One activation curve $\gamma(t)$, t the frame inside the beat (41.7 ms each; 57 frames per beat for the healthy sheet, 65 for HCM), a sigmoid rise and fall normalised to start at zero:

$$s(t) = \mathrm{sig}\left(\frac{t - t_0}{\tau_r}\right) \mathrm{sig}\left(\frac{t_0 + d - t}{\tau_d}\right), \qquad \gamma(t) = \frac{s(t) - s(0)}{1 - s(0)}, \qquad \mathrm{sig}(x) = \frac{1}{1 + e^{-x}}.$$

Its four numbers (onset t_0, rise time τ_r, plateau d, decay time τ_d) are learned, starting from a least-squares fit to the recording's mean shortening curve. The pulse does not travel: the recording's onsets show no correlation with position ($r \approx 0$), so every cell reads the same clock. In a rollout over several beats the same γ fires again at each recorded onset; nothing is reset between beats.

Each cell's own timing. Cell j reads the pulse shifted by its delay δ_j and with its own rise, plateau and decay, and adds two shared temporal modes with its own weights:

$$\gamma_j(t) = \left[\frac{s_j(t - \delta_j) - s_j(-\delta_j)}{1 - s_j(-\delta_j)}\right]_+ + \sum_{k=1}^{2} a_{jk}\, \psi_k(t), \qquad \text{clamped to } [0, 1.5],$$

where s_j is s with $\tau_r e^{u_{r,j}}$, $d\, e^{u_{d,j}}$, $\tau_d e^{u_{\tau,j}}$ in place of τ_r, d, τ_d. The modes $\psi_k(t)$ are one number per frame, shared by the sheet, with $\psi_k(0) = 0$; their frame steps and the weights are penalised, as are the per-cell logs u (zero = the shared pulse). The recording asks for this: its beat is 88% one time course, 6.7% a second (early-negative, late-positive: cells lead or lag) and 3% a third, and the per-cell peak frames spread over 14 frames (0.6 s) with no spatial gradient.

Injection into the material. At the end of every frame t (after its ten sub-steps, before the edge band is pinned and the cells are measured), for every material point p of cell j:

$$F_p \leftarrow G_j(t)\, F_p, \qquad G_j(t) = I + c_j(t)\, f_j f_j^{\top} + c_{2j}(t)\, f_j^{\perp} f_j^{\perp\top},$$

$$c_j(t) = \frac{(\gamma_j(t) - \gamma_j(t-1))\, g_j}{1 + \gamma_j(t-1)\, g_j}, \qquad c_{2j}(t) = \frac{(\gamma_j(t) - \gamma_j(t-1))\, g_{2j}}{1 + \gamma_j(t-1)\, g_{2j}},$$

with $f_j = (\cos\varphi_j, \sin\varphi_j)$ the fibre axis and $f_j^{\perp}$ its normal. The increments compound exactly: after any number of frames the active factor along the fibre is $1 + \gamma_j(t)\, g_j$, so the total active deformation at activation γ_j is $I + \gamma_j\,(g_j f_j f_j^{\top} + g_{2j} f_j^{\perp} f_j^{\perp\top})$. The deformation gradient now reads the cell's material as stretched by $1 + \gamma_j g_j$ along its fibre although no point has moved, so the stress of §3 step 2, $2\mu_p(F_p - R_p)F_p^{\top}$, pulls the cell's points together along f_j until that stretch is undone: the cell's rest length along its fibre is divided by $1 + \gamma_j g_j$, a shortening of about $\gamma_j g_j$ (g_j 0.037 median, healthy), realised at about 60% against the pull of the neighbours and the substrate spring. Across the fibre the same with g_{2j}: a negative g_{2j} widens the cell, and the fits return $g_{2j}/g_j \approx -0.7$, near area preservation. This is the active-strain form $F = F_e F_a$, F_e the elastic part and $F_a = G^{-1}$ the active one: the pulse moves the rest shape, the elasticity moves the points.

symbol	meaning
$\gamma(t),\ s(t)$	the shared pulse (0 at rest, about 1 at full activation) and its unnormalised sigmoid product
$t_0,\ \tau_r,\ d,\ \tau_d$	onset frame, rise time, plateau duration and decay time of the pulse, in frames; learned, 4 numbers per sheet
$\gamma_j(t)$	activation of cell j at frame t; $[\,\cdot\,]_+$ the positive part
δ_j	delay of cell j, in frames (bounded to ± 8)
$u_{r,j},\ u_{d,j},\ u_{\tau,j}$	cell j's log factors on the rise time, plateau and decay time; 0 = the shared pulse
$\psi_k(t),\ a_{jk}$	the two shared temporal modes (one number per frame, 0 at frame 0) and cell j's weight on each
$g_j,\ g_{2j}$	active strain of cell j along and across its fibre at full activation
$f_j,\ f_j^{\perp},\ \varphi_j$	fibre axis of cell j, its in-plane normal, and the axis angle
$G_j(t),\ c_j,\ c_{2j}$	the frame's active increment on the deformation gradient of cell j's points, and its two coefficients
$F_p,\ R_p,\ \mu_p$	deformation gradient and rotation of point p, and its shear stiffness (§3)

5 Results

Learnables. The model learns principally four parameters per cell:

1. **the strain**: g_j along the fibre at full activation and g_{2j} across it. The realised shortening is about 60% of g (healthy). Adding g_2 raised the explained variance of the per-cell strain maps from 0.69 to 0.82;
2. **its direction**: φ_j, inferred from motion alone; moved by the fit by a median of 10° from its starting value;
3. **a gain**: E_j (stiffness) and κ_j (adhesion to the gel), both shrunk toward uniform;
4. **a pulse** (§4): the shared $\gamma(t)$ (4 numbers) and per cell its delay δ_j, three time-course scalings and two mode weights.

In numbers, the fit returns 5,311 for the healthy sheet and 4,909 for the HCM sheet: eleven per cell (472 and 434 cells; every cell carries them, the loss reads the 331 and 298 interior ones of §1) and 119 and 135 shared by the sheet. Nothing else is learned: the drag k, the Poisson ratio ν, the hand-set spring scale 10^4, the segmentation and the starting state are fixed.

symbol	per	count (healthy / HCM)	what it is, and where it acts
g_j	cell	472 / 434	active strain along the fibre at full activation: the shortening of §2, applied once per frame as $I + \gamma_j(t)\,(g_j\, f_j f_j^{\top} + g_{2j}\, f_j^{\perp} f_j^{\perp\top})$
g_{2j}	cell	472 / 434	active strain across the fibre (positive = thickening); 0 is the rank-1 model
φ_j	cell	472 / 434	fibre axis $f_j = (\cos\varphi_j, \sin\varphi_j)$ of the same strain
$\log E_j$	cell	472 / 434	Young's modulus of the cell, bound to its points as μ_p, λ_p (§3, with $\nu = 0.3$); starts at $E = 80$ in the engine's own stress units, the value of the earlier recipes, not a kPa
$\log \kappa_j$	cell	472 / 434	factor on the substrate spring of the cell's points, $\kappa_p = 10^4\, e^{\log \kappa_0}\, e^{\log \kappa_j}$ (§2 spring, §3 $\bar{a}_p$)
δ_j	cell	472 / 434	delay of the cell's activation, $\gamma_j(t) = \gamma(t - \delta_j)$ (§4)
$u_{r,j},\ u_{d,j},\ u_{\tau,j}$	cell	3× 472 / 434	log factors on the cell's rise time, plateau duration and decay time against the shared pulse's (§4)
$a_{j1},\ a_{j2}$	cell	2× 472 / 434	weights of the two shared temporal modes in the cell's activation, $\gamma_j(t)$ += $\sum_k a_{jk}\, \psi_k(t)$
$\gamma(t)$	sheet	4 / 4	the shared pulse, a sigmoid rise and fall: onset t_0, rise time τ_r, plateau d, decay time τ_d (§4)
$\log \kappa_0$	sheet	1 / 1	the sheet's substrate stiffness factor (fitted 0.93 of the hand-set value)
$\psi_1(t),\ \psi_2(t)$	sheet	2 × 57 / 2 × 65	the two temporal modes, one number per frame of the beat window (§4)

Training. The fit is run with Adam for 250 steps. Each family of parameters has its own step size (g and g_2: 0.002; axis φ: 0.03; log stiffness: 0.06; shared pulse: 0.05; delay δ: 0.1; per-cell time-course and adhesion scalings: 0.05; temporal modes: 0.01, their weights: 0.02), decreasing along a cosine to 5% of its start. After every step the parameters are clipped to their bounds ($g \geq 0$, $|g_2| \leq 0.2$, E_j within a factor 10 of 80, $|\delta| \leq 8$ frames). The gradient is taken through every sub-step of every beat's rollout; the starting state is not learned. Starting values: g = the median peak shortening of the recording, φ = the axis of each cell's peak strain, the pulse = a least-squares fit to the recording's mean shortening curve, every cell's Young's modulus $E_j = 80$ (engine stress units, §3), everything else zero. One fit takes 108 min (healthy) and 144 min (HCM) on one RTX A6000; the loss falls from 1.78 to 0.19 and from 1.57 to 0.15.

Reconstruction. After optimisation the simulated sheet moves like the recording cell by cell (Fig. 3; Table 1). One rollout through beats 1–3 without a reset explains $R^2 = 0.849$ of the per-cell strain. The recording's own ceiling, from its singular value decomposition, is 0.87 / 0.94 / 0.97 with one / two / three fixed spatial patterns. Two independent fits (another optimiser seed and particle layout) agree per cell at $r = 0.90$–0.92 (g), 0.88–0.93 (g_2), 0.83–0.88 (δ), 7–10° (φ); the median cell-to-cell difference is about one fifth of each map's spread.

The movie `docs/cont_overlay_particles.mp4` (built by `scripts/make_cont_overlay_particles.sh`, §6) plays




Figure 3: Healthy sheet near peak contraction, from the continuous three-beat rollout (every beat is fitted; the model is never reset). Left: the microscope frame in green and the rest frame warped by the fitted motion in magenta, motion drawn ×4; grey where they agree. Right: the 18,769 tracking nodes (green) and the 56,640 material points (blue), displacement from rest ×10.

	beat 1	beat 2	beat 3	beat 4
healthy, R^2 strain maps A	0.870	0.872	0.871	
healthy, R^2 displacements u	0.935	0.937	0.935	
HCM, R^2 strain maps A	0.894	0.900	0.898	0.898
HCM, R^2 displacements u	0.949	0.958	0.958	0.958
per-cell shortening correlation	healthy 0.94		HCM 0.97	
replay of the fitted beat, A / u	healthy 0.98 / 0.96		HCM 0.96 / 0.95	

Table 1: Quality of the reconstruction, from the fits rerun in this repository (`parity/runs/full_repo_healthy`, `parity/runs/full_repo_hcm`): R^2 against the recording per beat, for the per-cell strain maps A and the displacements u. Every beat is fitted: spread across beats 0.002 (healthy), 0.006 (HCM). The archived fits of `reference/` give the same values to the third decimal.

the healthy sheet through beats 1–3 in one rollout that is never reset, two views side by side: left the microscope frame in green and the rest frame warped by the fitted motion in magenta, motion drawn ×4, grey where they agree; right the 18,769 tracking nodes (green) and the 56,640 material points (blue), displacement ×10. Fig. 3 is one frame of it. Then the two sheets, one dish per condition: Fig. 4 the fitted maps per cell (g, δ, $\log E$, g_2) and the fitted pulse against the recorded mean shortening, Fig. 5 the fibre axes, Table 2 the numbers.

The recording gives motion, not force, so the fit cannot separate a cell's stiffness from its active strain: a stiffer cell that contracts harder, or a weaker contraction held for longer, moves the sheet the same way. With planted parameters (the recording's rest-frame noise added, 3 seeds) the fit recovers g to 0.10 of its spread ($r = 0.93$) and φ to 5°, but $\log E$ only to 0.40 of its spread ($r \approx 0.65$); left free on the real data the per-cell E_j spreads over a factor of 200, and the shrinkage $\lambda_E = 0.3$ (the weight of the mean squared deviation of $\log E_j$ from its mean, added to the loss) holds it to ±12% at a cost of 0.04 in explained variance. The pulse length and the gain trade off in the same way. The healthy / HCM differences of Table 2 therefore describe one dish of each, fitted under one choice of prior; they are not a conclusion about the two conditions. That needs a post-processing of the fitted maps that reads what the trade-off does not touch (the realised per-cell shortening, the delays, the fibre-axis order, which come from the motion itself), and fits on more than one dish per condition.




Figure 4: Healthy (blue, 331 cells) against HCM (red, 298 cells). (a) Peak shortening per cell read off the recording. (b) Fitted g. (c) Fitted delay δ (s). (d) Fitted $\log E$ ($\lambda_E = 0.3$). (e) Fitted g_2. (f) Fitted pulse $\gamma(t)$ of each sheet (solid) and recorded mean shortening, normalised (dashed).

	healthy (331 cells)	HCM (298 cells)
recorded peak shortening per cell, median	0.025	0.040
fitted g, median	0.037	0.063
fitted g_2, median	-0.035	-0.033
g_2/g over active cells, median	-0.70	-0.48
cells with $g < 0.01$	19%	10%
axis order $\lvert\langle e^{2i\varphi}\rangle\rvert$, whole sheet / local median (Fig. 5d)	0.12 / 0.23	0.19 / 0.35
fitted E_j, median (engine stress units)	236	222
delay δ, s.d. across cells	0.079 s	0.076 s

Table 2: The two sheets, same model, same procedure, from the fits rerun in this repository (`cardio/figures_note.py --source parity --only tables` prints these). The archived fits give the same values to the printed digits.

Discussion. One caveat on reading Table 2. The recording gives motion, not force, so the fit cannot separate a cell's stiffness from its active strain: a stiffer cell that contracts harder, or a weaker contraction held for longer, moves the sheet the same way. We see this directly. With planted parameters the fit recovers the active strain to 10% of its spread but the stiffness only to 40% (correlation 0.65), and left free on the real data the per-cell stiffness spreads over a factor of 200, which we hold down with a prior. The pulse length and the gain trade off in the same way. So the healthy / HCM differences in Table 2 (fitted strain 0.037 vs 0.063, strain ratio across / along -0.70 vs -0.48, and the rest) describe one dish of each, fitted under one choice of prior; they are not a conclusion about the two conditions.




Figure 5: Fibre axes. (a, b) One line per interior cell along φ_j, length $\propto g_j$; grey dots the band cells. (c) Axis angle. (d) Local alignment: $|\langle e^{2i\varphi}\rangle|$ over the neighbours within three cell radii (0 random, 1 parallel).

6 Install, run, demo

Install. Python $\geq$ 3.10, CUDA PyTorch (reference: Python 3.12.12, torch 2.9.0+cu128, numpy 2.2.6, scipy 1.16.2, tifffile 2025.10.16). From the repository root:

```
pip install -e .              # torch, numpy, scipy, pyyaml, tifffile
pip install -e .[figures]     # + matplotlib (compare_sheets.py, figures_note.py)
```

`warp-lang` is optional (imported if present; this model names the pure-torch bodies).

Layout. `src/plexus/` the engine (13 modules, byte-identical to Plexus); `cardio/` model, loader, optimiser, scorer, segmentation; `data/healthy`, `data/hcm` grid flows, labels, label images; `specs/` per-beat engine specs (YAML); `configs/`, `scripts/` the recorded flags; `reference/` the fits as produced; `tools/compare_fits.py`; `PROVENANCE.md`.

The two reporting fits (110 and 150 min, 36 and 38 GB on an RTX A6000; fit, then scorer):

```
scripts/run_healthy_allbeats.sh --device cuda:0
scripts/run_hcm_allbeats.sh --device cuda:0
```

Flags after the script name override (`--tag`, `--iters`, `--per-parent`, ...). Output in `cardio/out/fits/<tag>/`: `fit.json` (config, per-iteration loss), `params.npz` (every learnable; `params_p20.npz`, `params_p50.npz` at 20% and 50%), `s4_score.json`.

Demo (minutes, under 4 GB): two iterations at 8 points per cell on a 48^2 grid; a comparison against the archived fit; the gradient check; the figures of this note.

```
scripts/run_healthy_allbeats.sh --tag smoke --iters 2 --per-parent 8 --n-grid 48 --fit-frames 10 --checkpoints ''
python tools/compare_fits.py cardio/out/fits/smoke reference/healthy_allbeats
PYTHONPATH=src python cardio/fd_check.py --device cuda:0 --dtype float64 --per-parent 12 --n-grid 48 --frames 10
PYTHONPATH=src python cardio/figures_note.py --only sheets,axes
```

The smoke loss at iteration 0 is 2.0178 (reduced layout; the nominal fit starts at 1.7780); the comparison reports its parameters as different from the reporting fit, as expected after two iterations at another resolution. The scorer runs on any parameter file, every beat beside the replay and do-nothing baselines:

```
PYTHONPATH=src python cardio/s4_score.py --params <params.npz> --specimen healthy --per-parent 120 --anchor-percell --drag 150 --
     fit-beats 1,2,3 --beats 1,2,3
```

`cardio/s4_residual.py` splits the residual by component and time. Other scripts:

```
python cardio/segmentation.py --tif <movie.ome.tif>          # rebuild the segmentation (not needed: outputs are shipped)
scripts/make_cont_overlay_particles.sh <movie.ome.tif> [fit dir]   # the continuous three-beat movie
```

References

[1] Hu, Y., Fang, Y., Ge, Z., Qu, Z., Zhu, Y., Pradhana, A., Jiang, C. (2018). A moving least squares material point method with displacement discontinuity and two-way rigid body coupling. *ACM Trans. Graph.* 37(4):150. Code: https://github.com/yuanming-hu/taichi_mpm.

[2] Sulsky, D., Chen, Z., Schreyer, H. L. (1994). A particle method for history-dependent materials. *Comput. Methods Appl. Mech. Eng.* 118:179–196.

[3] Xu, M., Song, C. Y., Levin, D. I. W., Hyde, D. (2025). A differentiable material point method framework for shape morphing. *IEEE TVCG* 31(10):9140–9153.