AFFIRM Integration API

Endpoint: AI Processing

Overview

In order to send a query and a response to AFFIRM for the analysis, a software developer from the Customer side should call the following API REST endpoint:
https://api.becompliant.ai/integrations-api/v1/autonomous-telemetry/send-data

- API token in `Authorization: Bearer <token>`
- `ai_input` (text)
- `ai_input_start_time` (DateTime, optional)
- `ai_output` (text)
- `ai_input_end_time` (DateTime, optional)
- `organization_id` (string)
- `ai_asset_id` (string)
- `test_id` (array of GUIDs, optional) – IDs of Tasks from the AI Asset to run evaluation on. If omitted or empty, AFFIRM runs **all** available Tasks for this run.

Method: `POST`

- **Path**: `/integrations-api/v1/autonomous-telemetry/send-data`
- **Protocol**: HTTPS
- **Content Type**: `application/json`
- **Authentication**: Bearer token via `Authorization` header

Authentication

All requests must include a valid API token:

```
Authorization: Bearer <API_TOKEN>
```

If missing or invalid, the API returns `401 Unauthorized`.

Request

URL

```
POST /integration-api/v1/autonomous-telemetry/send-data
Host: api.becompliant.ai
```

Headers

Name	Type	Required	Description

Authorization	string	Yes	`Bearer <API_TOKEN>`
Content-Type	string	Yes	`application/json`
Accept	string	No	`application/json` (default)

Request Body (JSON)

```
{
  "ai_input": "string",
  "ai_input_start_time": "2026-01-21T10:00:00Z",
  "ai_output": "string",
  "ai_input_end_time": "2026-01-21T10:05:00Z",
  "organization_id": "<GUID - Organization Id>",
  "ai_asset_id": "<GUID - AI Asset Id>",
  "test_id": [
    "<GUID - Task Id 1>",
    "<GUID - Task Id 2>"
  ]
}
```

Field	Type	Required	Description
ai_input	string	Yes	Input text to be processed by AI Asset.
ai_input_start_time	string	No	Optional DateTime (ISO 8601, e.g. `2026-01-21T10:00:00Z`) marking when input started.
ai_output	string	Yes	Output text produced by AI Asset (or expected/target output, depending on use).
ai_input_end_time	string	No	Optional DateTime (ISO

Bahar Ghahremani bahar@newworldangels.com Mon Mar 16 10:16:36 2026

			8601) marking when input ended.
organization_id	string	Yes	ID of the organization associated with this request.
ai_asset_id	string	Yes	ID of the AI asset that belongs to the organization and handled this request.
test_id	array<string>	No	Optional array of GUIDs specifying the IDs of Tasks from the AI Asset to run evaluation on. If this array is omitted or empty, AFFIRM runs all available Tasks for this specific run.

Example Request

```
POST https://api.becompliant.ai/integration-api/v1/autonomous-telemetry/send-data
Authorization: Bearer YOUR_API_TOKEN
Content-Type: application/json
Accept: application/json
{
  "ai_input": "Classify this ticket as bug, feature request, or question.",
  "ai_input_start_time": "2026-01-21T10:00:00Z",
  "ai_output": "bug",
  "ai_input_end_time": "2026-01-21T10:00:10Z",
  "organization_id": "org_12345",
  "ai_asset_id": "asset_67890",
  "test_id": [
    "11111111-1111-1111-1111-111111111111",
    "22222222-2222-2222-2222-222222222222"
  ]
}
```

Response

Bahar Ghahremani bahar@newworldangels.com Mon Mar 16 10:16:36 2026

Endpoint: Request Status

Overview

AFFIRM Integration API

Success (202 Accepted)

If `ai_output` is provided by the client (logging/analytics use case), the service replies with the request_id, which is a unique id, generated for each request:

```
{
  "request_id": "<GUID>"
}
```

Field	Type	Description
ai_output	string	AI-generated output text.
organization_id	string	Organization ID associated with the request.
ai_asset_id	string	AI Asset ID associated with the request.
test_id	array<string>	Test IDs

Error Responses

400 Bad Request

```
{
  "error": "invalid_request",
  "message": "Fields 'ai_input', 'ai_output', 'organization_id', and 'ai_asset_id' are required."
}
```

401 Unauthorized

```
{
  "error": "unauthorized",
  "message": "Missing or invalid API token."
}
```

429 Too Many Requests

```
{
  "error": "rate_limited",
  "message": "Too many requests. Please reduce request rate and try again later."
}
```

500 Internal Server Error

```
{
  "error": "server_error",
  "message": "An unexpected error occurred. Please try again later."
}
```

Endpoint: Request Status

Bahar Ghahremani bahar@newworldangels.com Mon Mar 16 10:16:36 2026

Overview

After submitting data via the AI Processing endpoint, a software developer from the Customer side can query the execution status of that request by calling the following API REST endpoint: https://api.becompliant.ai/integration-api/v1/autonomous-telemetry/check-status

This endpoint receives a `request_id` returned by the first endpoint and returns the current execution status, including any errors that may have occurred (for example: an incorrect Asset ID, an incorrect Test ID, an incorrect Organization ID, or a general request failure with a failure reason).

Method: `GET`

- **Path**: `integration-api/v1/autonomous-telemetry/check-status`
- **Protocol**: HTTPS
- **Content Type**: `application/json`
- **Authentication**: Bearer token via `Authorization` header

Authentication

All requests must include a valid API token:

```
Authorization: Bearer <API_TOKEN>
```

If missing or invalid, the API returns `401 Unauthorized`.

Request

URL

```
GET integration-api/v1/autonomous-telemetry/check-status?request_id=<REQUEST_ID>
Host: api.becompliant.ai
```

Headers

Name	Type	Required	Description
Authorization	string	Yes	`Bearer <API_TOKEN>`
Accept	string	No	`application/json` (default)

Query Parameters

Name	Type	Required	Description
request_id	string	Yes	The unique identifier returned by the

Bahar Ghahremani bahar@newworldangels.com Mon Mar 16 10:16:36 2026

			`/v1/integration-api/send-data` endpoint.

Response

Success (200 OK)

If the `request_id` is valid, the service returns the request's current status.

```
{
  "request_id": "<GUID>",
  "status": "received | accepted | running | executed | failed",
  "error_code": "asset_id_incorrect | test_id_incorrect | organization_id_incorrect | request_failed | null",
  "error_message": "string or null"
}
```

Field	Type	Description
request_id	string	The unique ID of the original request.
status	string	Current processing status: `pending`, `running`, `completed`, or `failed`.
error_code	string or null	Machine-readable error code, if any (e.g., `asset_id_incorrect`, `test_id_incorrect`, `organization_id_incorrect`, `request_failed`). `null` if no error.

Bahar Ghahremani bahar@newworldangels.com Mon Mar 16 10:16:36 2026

error_message	string or null	Human-readable description of the error or failure reason. `null` if status is not `failed`.

Error Responses

400 Bad Request

```
{
  "error": "invalid_request",
  "message": "Field 'request_id' is required and must be a valid identifier."
}
```

401 Unauthorized

```
{
  "error": "unauthorized",
  "message": "Missing or invalid API token."
}
```

404 Not Found

```
{
  "error": "not_found",
  "message": "Request with the specified 'request_id' was not found."
}
```

429 Too Many Requests

```
{
  "error": "rate_limited",
  "message": "Too many requests. Please reduce request rate and try again later."
}
```

500 Internal Server Error

```
{
  "error": "server_error",
  "message": "An unexpected error occurred. Please try again later."
}
```

Bahar Ghahremani bahar@newworldangels.com Mon Mar 16 10:16:36 2026