Surface mount flasher


From WikiSTEP

This example is a part of ElectroMechanical Pilot (http://empilot.aticorp.org/) test cases.


Contents

- 1 Example: Mentor Boardstation layout view
- 2 Example: STEP-Book with PCA design view
- 3 Example: STEP-Book with PCB design view (highlighted network)
- 4 Example: STEP-Book with PCB usage view
- 5 Example: Statistics
 - 5.1 Statistics for Assembly Module (PCA)
 - 5.2 Statistics for Interconnect Module (PCB)
- 6 Example: STEP Files

1 Example: Mentor Boardstation layout view




2 Example: STEP-Book with PCA design view



Meanings of colours:

- green interconnect module components: surface feature, terminal;
- light blue Bottom package component:
 - cross filling joint terminal;
 - boarder package body.
- light red Top package component:
 - cross filling joint terminal;
 - boarder package body.
- **dark blue** highlighted packaged component (R4).


3 Example: STEP-Book with PCB design view (highlighted network)



Meanings of colours:

- white interfacial connection
- **black** component termination passage
- light red (also cross filling) design layer stratum (LAYER_1)
- dark red highlighted network (ANALOG_GND)
- light blue (also cross filling) design layer stratum (LAYER_2)
- dark green Solder Mask
- green interconnect module (PCB usage view): cutout surface, edge surface

4 Example: STEP-Book with PCB usage view



Meanings of colours:

- light blue secondary surface terminals
- **dark blue** highlighted secondary surface terminal (R3-1)
- light red primary surface terminal
- green interconnect module cutout surface
- dark green interconnect module edge surface

5 Example: Statistics

5.1 Statistics for Assembly Module (PCA)

Number of:

packages: 12

packaged parts: 7

- packaged component: 10
- packaged component terminals: 26
- physical connectivity definitions: 10

5.2 Statistics for Interconnect Module (PCB)

Number of:

- physical networks: 10
- stratums: 11 (design: 2, docu: 8)
- interface terminals: 33
- component termination passages: 7
- contact size dependent lands (SMD-pads): 26
- vias: 5
- conductive interconnect elements (tracks): 35
- conductive filled areas: 0 (connected:0)
- entity instances AIM: 17370

6 Example: STEP Files

SurfaceMountFlasher.stp - the result of the conversion is available in AP210 file format

Retrieved from "http://www.wikistep.org/index.php/Surface_mount_flasher"

- This page was last modified on 2007-02-28, at 08:02:09.
- Content is available under GNU Free Documentation License 1.2.