

SPIN INSTALLTION TUTORIAL

Fan Zhiyu

ABSTRACT

This is a simple instruction to get SPIN setup for Mac/Linux/Windows systems. It includes three versions, which are Spin (for terminal user), jSpin, iSpin (for GUI user).

TABLE OF CONTENTS

I	INSTALLATIONS	2
A	<i>Spin</i>	2
1	Linux and Mac	2
2	Windows	2
B	<i>jSpin</i>	2
C	<i>iSpin</i>	3
II	USAGE	3
A	<i>Spin</i>	4
1	example-1.pml: Single Process	4
2	example-2.pml: Multiple Processes	4
3	example-3.pml: Program Verification - Violation	4
4	example-4.pml: Program Verification - No Violation	4
5	example-5.pml: Communication Channels	4
6	example-6.pml: Mutual Exclusion - Semaphore	5
7	example-7.pml: Sender Receiver	5
8	example-8.pml: Handling Procedures - Factorial Function	5
9	example-9.pml: LTL Verification	6
B	<i>jSpin</i>	6
1	Finite State Machine	6
2	State Diagrams - All State	7
C	<i>iSpin</i>	7
1	Finite State Machine	7
2	Simulation Run	9
3	Message Sequence Chart	9

I. INSTALLATIONS

In this section, we will present how to install SPIN model checker in Mac/Linux/Windows

A. *Spin*

1. Linux and Mac

You can download Spin binary files (spin*_System*.gz) from <https://github.com/nimble-code/Spin/tree/master/Bin> or Luminus (Files → SPIN Assignments → SPIN Binaries).

Commands to setup Spin

1. Unzip Spin from *.gz file: `gunzip *.gz`
2. Change the permission of spin file: `chmod u+x spin`
3. Modify the environment path: `export PATH=$PATH:<spin-path>`
4. Open terminal and check installation status: `spin -V`

2. Windows

1. Unzip Spin from *.gz file
2. Add spin*_Windows*.exe to System environment
3. Open Windows command line and check installation status: `spin -V`
4. Notice that you should install C compiler to use SPIN

If the terminal outputs `Spin Version *.*.* -- [Date]`, then it installed successfully

B. *jSpin*

You can download jSpin from [Linux and Mac Downloads](#) and [Windows Download](#) or get it from Luminus.

System environment prerequisites:

1. Spin (refer to I)
2. Java 1.5+
3. gcc compiler (Linux and Mac system should have this already)

4. brew (For mac only)
5. Dot (For Linux `sudo apt install graphviz`, For Mac `brew install graphviz`, For Windows, refer to [this video](#))

Setup steps

1. Unzip `jspin*.zip`
2. Replace `config.cfg` line 11 to `SPIN=PATH_TO_SPIN`
3. Replace `config.cfg` line 17 to `SOURCE_DIRECTORY=WORKING_DIR`
4. Replace `config.cfg` line 26 to `C_COMPILER=PATH_TO_GCC`
5. Replace `config.cfg` line 28 to `DOT=PATH_TO_DOT`
6. Double click on `jSpin.jar` or run `java -jar jSpin.jar` to launch jSpin

C. iSpin

iSpin is written in tcl/tk. You can install tcl/tk by the following commands:

1. Linux: `sudo apt install tk`
2. Mac: `brew install tcl-tk`
3. Windows: Refer to this website [Link](#)

Execute `info tclversion` in wish (a Tcl/Tk command shell, type `wish` to enter) to check if you installed tcl/tk correctly.

Download iSpin from Luminus (Files → SPIN Assignments Description → SPIN Binaries → `ispin`).

Make the `ispin.tcl` executable, use `wish ispin.tcl` to launch ispin

II. USAGE

In this section, we provide examples to show the basic usages of the three tools. Please download the examples from Luminus (Files → SPIN Assignments Description → SPIN Examples)

A. *Spin*

1. example-1.pml: Single Process

Command Line: `spin example-1.pml`

Output: `state = 1`

2. example-2.pml: Multiple Processes

Command Line: `spin example-2.pml`

Possible outputs:

1. `state=1`(from one A process)
`state=1`(from the other A process)
2. `state=1`(from one A process)
`state=2`(from the other A process)
3. `state=1`(from one A process)
`timeout`(from the other A process)

3. example-3.pml: Program Verification - Violation

Command Line:

`spin -a example-3.pml`

`gcc -o pan pan.c`

`./pan -a`

Output: `assertion violated (sem!=2) (at depth 9)`

4. example-4.pml: Program Verification - No Violation

Command Line:

`spin -a example-4.pml`

`gcc -o pan pan.c`

`./pan -a`

Output: No error

5. example-5.pml: Communication Channels

Command Line:

`spin example-5.pml`

Output: `state=124`

Command Line:

`spin -M example-5.pml`

Output: generate a message sequence chart like [Figure 1](#)




Figure 1: Sequence Chart generated by example-5.pml

6. example-6.pml: Mutual Exclusion - Semaphore

Command: `spin -s example-6.pml`

Output: endless loop. For each loop, the execution order is `dijkstra_semaphore` process followed by one of the users.

7. example-7.pml: Sender Receiver

Command: `spin -s example-7.pml`

Output: endless loop. Send and Receiver are executed alternately

To generate the finite state machine for Sender and Receiver, run commands:

1. `spin -a example-7.pml`
2. `gcc -o pan pan.c`
3. `./pan -D > dot.tmp cat dot.tmp`

Output: Instructions for dot to generate the graphs. save each digraph separately (`sender.dot` and `receiver.dot`) and run the following command to generate graphs from the code.

Command: `dot -T png sender.dot -o sender.png`

You will get the graphs like Figure 2(a) and Figure 2(b):

8. example-8.pml: Handling Procedures - Factorial Function

Command: `spin example-8.pml`

Output: result is 3628800




Figure 2: Finite state machine for example-7.pml

9. example-9.pml: LTL Verification

Commands:

1. `spin -a example-9.pml`
2. `gcc -o pan pan.c`
3. `./pan -a -N p1`

Output: No error

B. jSpin

Following examples will guide you to use jSpin as a GUI for Spin.

1. Finite State Machine

We will see how to use jSpin to generate the finite state machine for example-7.pml.

Open example-7.pml in jSpin, then click “SpinSpider”, in the appeared dialog box, select Automata option.




Figure 3: Finite State Machine

2. State Diagrams - All State

We will see how to use jSpin to generate the state diagrams for example-10.pml.

Open example-10.pml in jSpin, then click “SpinSpidei”, in the appeared dialog box, select No trail option, also include the variable names under the “Variables” section.

Figure 4 shows the generated state diagram

C. iSpin

Following examples will guide you to use iSpin as a GUI for Spin.

1. Finite State Machine

We will see how to use iSpin to generate the finite state machine for example-7.pml.

Open example-7.pml through “Open” tab, then click “Automata View” on the right display panel which will generate FSM for each process. You need to select which FSM to render from the options given.

Click “p_Sender” and it will render the automata diagram for the p_Sender process as shown in Figure 5(b).




Figure 4: State Diagram




Figure 5: Finite State Machine

2. Simulation Run

We will see how to use iSpin to run a simulation without using command line instructions for example-1.pml.

Open example-1.pml through “Open” tab, then Click on “Simulate/Replay” tab and click the “Run” button for simulation

As shown in Figure 6, there are several outputs.

1. Log Window: At the upper right of the iSpin display shows which commands are being generated by iSpin and executed by Spin
2. Data Window: Lower left windows display the current values of variables
3. Channel Window: Lower right window display the values used in message passing
4. Simulation Output: Lower middle window shows the simulation log

3. Message Sequence Chart

We will see how to use iSpin to generate a message sequence chart without using command line instructions for example-6.pml.

Open example-6.pml through “Open” tab, then Click on “Simulate/Replay” tab and click the “Run” button for simulation, Click on “Stop” button to terminate the program.




Figure 6: Simulation Run for example-1.pml

As shown in the Figure 7, the display at middle right of the iSpin window generates the message sequence chart for the simulation we ran. You can save the diagram in PS format (which can be later used to produce png or pdf) by clicking the button “Save in: msc.ps”




Figure 7: Message Sequence Chart for example-6.pml