Status	Finished
Started	Wednesday, 28 October 2026, 3:59 PM
Completed	Wednesday, 28 October 2026, 4:29 PM
Duration	30 mins 11 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 2.00 out of 2.00

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.

Suppose the following input is supplied to the program:

9

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

For example:

Test	Result
print(Summation(8))	9872

Answer: (penalty regime: 0 %)

Reset answer

```
import sys

def Summation(a):
    s = str(a)
    n1 = int(s * 1)
    n2 = int(s * 2)
    n3 = int(s * 3)
    n4 = int(s * 4)
    return n1 + n2 + n3 + n4

if __name__ == "__main__":
    user_input = sys.stdin.read().strip()

    if user_input:
        digit = int(user_input)
        result = Summation(digit)
        print(result)

```

	Test	Expected	Got	
✓	print(Summation(8))	9872	9872	✓
✓	print(Summation(10))	10203040	10203040	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **2**

Correct

Mark 2.00 out of 2.00

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

Example 1:

Input:

69

Output:

true

Example 2:

Input:

88

Output:

true

Example 3:

Input:

962

Output:

false

Example 4:

Input:

1

Output:

true

For example:

Test	Result
`print(Strobogrammatic(69))`	`True`
`print(Strobogrammatic(962))`	`False`

Answer: (penalty regime: 0 %)

Reset answer

```
def Strobogrammatic(num) -> bool:
    num_str = str(num).strip()

    maps = {
        '0': '0',
        '1': '1',
        '6': '9',
        '8': '8',
        '9': '6'
    }

    if not num_str:
        return False

    left, right = 0, len(num_str) - 1
    while left <= right:
        if num_str[left] not in maps or maps[num_str[left]] != num_str[right]:
            return False
        left += 1
        right -= 1
```

```
21
22      return True
23  try:
24      user_input = input("")
25      print(Strobogrammatic(user_input))
26  except (EOFError, KeyboardInterrupt):
27      pass
28
```

	Test	Expected	Got	
✓	print(Strobogrammatic(69))	True	True	✓
✓	print(Strobogrammatic(88))	True	True	✓
✓	print(Strobogrammatic(962))	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **3**

Correct

Mark 2.00 out of 2.00

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all

the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
print(christmasDiscount(578))	12

Answer: (penalty regime: 0 %)

Reset answer

```
def christmasDiscount(orderValue):
    bill_str = str(orderValue)
    prime_digits = {'2', '3', '5', '7'}
    return sum(int(digit) for digit in bill_str if digit in prime_digits)
if __name__ == "__main__":
    try:
        user_input = input().strip()
        if user_input:
            print(christmasDiscount(user_input))
    except EOFError:
        pass

```

	Test	Expected	Got	
✓	print(christmasDiscount(578))	12	12	✓
✓	print(christmasDiscount(57))	12	12	✓
✓	print(christmasDiscount(222))	6	6	✓
✓	print(christmasDiscount(77777))	35	35	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **4**

Correct

Mark 2.00 out of 2.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: U = 2^a * 3^b * 5^c, where a, b and c are nonnegative integers.

For example:

Test	Result
`print(checkUgly(6))`	`ugly`
`print(checkUgly(21))`	`not ugly`

Answer: (penalty regime: 0 %)

Reset answer

```
import sys


def checkUgly(n: int) -> str:
    if n <= 0:
        return "not ugly"
    for factor in (2, 3, 5):
        while n % factor == 0:
            n //= factor
    return "ugly" if n == 1 else "not ugly"


def main():
    input_data = sys.stdin.read().split()

    for item in input_data:
        try:
            num = int(item)
            print(checkUgly(num))
        except ValueError:
            continue


if __name__ == "__main__":
    main()
```

	Test	Expected	Got	
✓	`print(checkUgly(6))`	`ugly`	`ugly`	✓
✓	`print(checkUgly(21))`	`not ugly`	`not ugly`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **5**

Correct

Mark 2.00 out of 2.00

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
import sys


def coinChange(amount: int) -> int:
    if amount <= 0:
        return 0

    coins = amount // 4
    remainder = amount % 4

    if remainder > 0:
        coins += 1

    return coins
coin_change = coinChange

if __name__ == "__main__":
    input_data = sys.stdin.read().split()
    if input_data:
        for token in input_data:
            try:
                n = int(token)
                print(coinChange(n))
            except ValueError:
                continue
```

	Test	Expected	Got	
✓	print(coinChange(16))	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.