Status	Finished
Started	Thursday, 29 October 2026, 6:37 PM
Completed	Thursday, 29 October 2026, 6:43 PM
Duration	6 mins 51 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

a. tupl.sort()

b. tupl.append(2)

c. tupl[1]=2

d. tupl1=tupl+tupl ✓

Question **2**

Correct

Mark 1.00 out of 1.00

Which of the following options will produce the same output?

```
t = (15, 83, 21, 49, 60,45,52,85,100)
# options i, ii, iii, or iv
print(t[:-1])
print(t[0:5])
print(t[0:8])
print(t[-7:])
```

a. ii,iv

b. iii,iv

c. i,iii ✓

d. i,ii

Question **3**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

```
t1=(55,12,78,64,25)
t1.pop(12)
print(tuple1)
```

a. 12

b. (55,78,64,25)

c. Error ✓

d. (12)

Question **4**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (55, 44, 33, 22, 11)
x = [t1[i] for i in range(0, len(t1), 2)]
print(x)
```

a. [(55,33,11)]

b. (55,33,11)

c. [55, 33, 11] ✓

d. ([55,33,11])

Question **5**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. {0,9} ✓

b. It will throw an error as there are two 0 while creating the set.

c. {0,0,9}

d. {9}

Question **6**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. False

b. True ✓

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {2,5,1}

b. {2,5,3,1}

c. {}

d. {3} ✓

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

a. (36, 25, 14) ✓

b. (58,47,36,25)

c. Error

d. (3,14,25)

Question **9**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

- a. (16,17,18,19) ✓
- b. (25,19,18,17)
- c. (16,17,18)
- d. Error

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

- a. True ✓
  True
- b. False
  False
- c. False
  True
- d. True
  False

Question **11**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. Computer
b. (Computer)
c. Error
d. () ✓

Question **12**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

my_t1 = (1, 2, 3, 4)

my_t1.append((5, 6, 7))

print(len(my_t1))

a. 5
b. 1
c. Error ✓
d. 2

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. Name Error
b. TypeError: update() doesn't allow list as a argument.
c. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓
d. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

Question **14**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t = (11, 3)

x = 3 * t

print(x)

a. (11,3,11,11,3,11,11,11,3)

b. [11,11,11,3,3,3]

c. (11, 3, 11, 3, 11, 3) ✓

d. (11,3)(11,3)(11,3)

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. SynatxError: Different types cannot be used with sets

b. {40, 10, 50, 20, 60, 30}

c. {40, 10, '10', 50, 20, 60, 30} ✓

d. {40, '10', 50, 20, 60, 30}