

Configuration

CRM/ERP Platform Documentation

Configuration Reference

All configuration is via environment variables. Never commit `.env` or `.env.local`.

Backend: `backend/.env`

Required

Variable	Example	Description
<code>DATABASE_URL</code>	<code>mysql://root:@127.0.0.1:3306/enterprise_crm</code>	Prisma connection string
<code>JWT_SECRET</code>	<code>change-me-32-chars-minimum</code>	Signs access tokens (24h expiry)
<code>JWT_REFRESH_SECRET</code>	<code>another-secret</code>	Signs refresh tokens (7d expiry)
<code>FRONTEND_URL</code>	<code>http://localhost:3000</code>	CORS allowed origin(s), comma-separated
<code>PORT</code>	<code>4000</code>	HTTP port for NestJS
<code>NODE_ENV</code>	<code>development</code> or <code>production</code>	Controls logging verbosity

Optional — Queue

Variable	Default	Description
<code>REDIS_URL</code>	<code>redis://localhost:6379</code>	BullMQ job queue connection

Without Redis, workflow execution and bulk import jobs will fail. The rest of the app works.

Optional — AI/OCR

Variable	Description
<code>ANTHROPIC_API_KEY</code>	Anthropic API key. Required for OCR document extraction in forms. Get one at console.anthropic.com

Optional — Google Calendar / Sheets

Variable	Description
<code>GOOGLE_CLIENT_ID</code>	OAuth2 client ID from Google Cloud Console
<code>GOOGLE_CLIENT_SECRET</code>	OAuth2 client secret
<code>GOOGLE_REDIRECT_URI</code>	Must match the authorized redirect URI in Google Console. Production: <code>https://your-domain.com/api/v1/calendar-sync/auth/callback</code>

Optional — SMTP

SMTP is configured **per-organization** inside the app (Settings → Email). There is no global SMTP env variable — organizations bring their own credentials.

Frontend: `mycrm/.env.local`

Variable	Example	Description
<code>NEXT_PUBLIC_API_URL</code>	<code>http://localhost:3000</code>	Base URL for the frontend itself (used for absolute URLs in emails, etc.)
<code>ANTHROPIC_API_KEY</code>	<code>sk-ant-api03-...</code>	Only if any server-side Next.js routes call Claude directly

The Next.js proxy rewrites `/api/v1/*` → `http://localhost:4000/api/v1/*` , so the frontend never needs to know the backend URL directly.

Production Overrides

On Railway / VPS, set these additional values:

```
NODE_ENV=production
DATABASE_URL=mysql://user:password@host:3306/dbname
FRONTEND_URL=https://app.yourdomain.com
GOOGLE_REDIRECT_URI=https://api.yourdomain.com/api/v1/calendar-sync/auth/callback
```

On Netlify (frontend), set:

```
NEXT_PUBLIC_API_URL=https://app.yourdomain.com
```

And update `mycrm/next.config.ts` proxy destination:

```
destination: 'https://api.yourdomain.com/api/v1/:path*'
```

Security Notes

- `JWT_SECRET` must be at least 32 characters. Use `openssl rand -hex 32` to generate.
- Rotate `JWT_SECRET` causes all existing sessions to invalidate — users must log in again.
- `ANTHROPIC_API_KEY` carries billing liability. Restrict it to the backend only; never expose in frontend bundles.
- Store production secrets in your hosting provider's secret manager, not in files checked into git.