

Deployment

CRM/ERP Platform Documentation

Deployment

The recommended stack is **Railway** (backend + database) + **Netlify** (frontend).

Backend on Railway

1. Create a Railway project

```
npm install -g @railway/cli  
railway login  
railway init
```

2. Add services

In the Railway dashboard, add:

- **MySQL** service (Railway managed)
- **Redis** service (Railway managed)
- **Node.js** service pointed at `backend/`

3. Set environment variables

In the Railway Node.js service settings, add:

```
DATABASE_URL=<copied from Railway MySQL service>  
REDIS_URL=<copied from Railway Redis service>  
JWT_SECRET=<generate with openssl rand -hex 32>  
JWT_REFRESH_SECRET=<generate with openssl rand -hex 32>  
FRONTEND_URL=https://your-app.netlify.app
```

```
PORT=4000  
NODE_ENV=production  
ANTHROPIC_API_KEY=<your key>  
GOOGLE_CLIENT_ID=<optional>  
GOOGLE_CLIENT_SECRET=<optional>  
GOOGLE_REDIRECT_URI=https://<railway-domain>/api/v1/calendar-sync/auth/callback
```

4. Configure root directory

In Railway service settings, set **Root Directory** to `backend` .

5. Build and start commands

Railway auto-detects Node.js. Ensure `backend/package.json` has:

```
{  
  "scripts": {  
    "build": "nest build",  
    "start:prod": "node dist/main"  
  }  
}
```

Railway runs `npm run build` then `npm run start:prod` .

6. Run migrations on deploy

Add a pre-deploy command or a one-off command after deploy:

```
npx prisma migrate deploy
```

Frontend on Netlify

1. Connect repository

In Netlify dashboard → New site → import from Git.

2. Configure build settings

Setting	Value
Base directory	<code>mycrm</code>
Build command	<code>npm run build</code>
Publish directory	<code>mycrm/.next</code>

3. Environment variables

In Netlify → Site settings → Environment variables:

```
NEXT_PUBLIC_API_URL=https://your-app.netlify.app
```

4. Update backend proxy URL

In `mycrm/next.config.ts`, change the proxy destination for production:

```
{
  source: '/api/v1/:path*',
  destination: `${process.env.BACKEND_URL ?? 'http://localhost:4000'}/api/v1/:path*`,
}
```

Add `BACKEND_URL=https://<railway-domain>` to Netlify env vars.

Docker (Self-hosted)

A minimal `docker-compose.yml` for self-hosting:

```
version: '3.9'
services:
  db:
    image: mysql:8.0
    environment:
      MYSQL_ROOT_PASSWORD: rootpass
```

```

    MYSQL_DATABASE: enterprise_crm

volumes:
  - db_data:/var/lib/mysql

ports:
  - "3306:3306"

redis:
  image: redis:7-alpine
  ports:
    - "6379:6379"

backend:
  build: ./backend
  environment:
    DATABASE_URL: mysql://root:rootpass@db:3306/enterprise_crm
    REDIS_URL: redis://redis:6379
    JWT_SECRET: change-me
    JWT_REFRESH_SECRET: change-me-too
    FRONTEND_URL: http://localhost:3000
    PORT: 4000
    NODE_ENV: production
  ports:
    - "4000:4000"
  depends_on:
    - db
    - redis
  command: sh -c "npm run prisma migrate deploy && node dist/main"

frontend:
  build: ./mycrm
  environment:
    NEXT_PUBLIC_API_URL: http://localhost:3000
    BACKEND_URL: http://backend:4000
  ports:
    - "3000:3000"
  depends_on:
    - backend

volumes:
  db_data:

```

```
docker-compose up -d
```

Post-Deployment Checklist

- ☐ Backend health: `GET https://api.yourdomain.com/api/v1/auth/check-email`
- ☐ Frontend loads and shows login
- ☐ Database migrations ran successfully
- ☐ First user registration works
- ☐ File uploads work (check `uploads/` volume is writable)
- ☐ WebSocket connects (check browser console for Socket.io errors)
- ☐ Email settings configured in org Settings → Email