N-Channel 75-V (D-S) MOSFET

PRODUCT SUMMARY			
$V_{(BR)DSS}$ (V)	$r_{DS(on)}$ (Ω)	I_D (A)	Q_g (Typ)
75	0.0048 at V_{GS} = 10 V	90[d]	105
	0.006 at V_{GS} = 8 V	90[d]	

FEATURES

- TrenchFET® Power MOSFET
- 175 °C Junction Temperature
- 100 % UIS Tested

RoHS
COMPLIANT

APPLICATIONS

- Power Supply
  - Half-Bridge
  - Secondary Synchronous Rectification
- Industrial

TO-263



Top View

Ordering Information: SUM90N08-4m8P-E3 (Lead (Pb)-free)



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T_C = 25 °C, unless otherwise noted				
Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	75	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current (T_J = 175 °C)	T_C = 25 °C	I_D	90[d]	A
	T_C = 70 °C		90[d]	
Pulsed Drain Current		I_{DM}	240	
Avalanche Current		I_{AS}	70	
Single Pulse Avalanche Energy[a]	L = 0.1 mH	E_{AS}	245	mJ
Maximum Power Dissipation[a]	T_C = 25 °C	P_D	300[b]	W
	T_A = 25 °C[c]		3.75	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	- 55 to 175	°C

THERMAL RESISTANCE RATINGS			
Parameter	Symbol	Limit	Unit
Junction-to-Ambient (PCB Mount)[c]	R_{thJA}	40	°C/W
Junction-to-Case (Drain)	R_{thJC}	0.5	

Notes:
a. Duty cycle ≤ 1 %.
b. See SOA curve for voltage derating.
c. When Mounted on 1" square PCB (FR-4 material).
d. Package limited.

SPECIFICATIONS T_J = 25 °C, unless otherwise noted						
Parameter	**Symbol**	**Test Conditions**	**Min**	**Typ**	**Max**	**Unit**
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{DS} = 0 V, I_D = 250 µA	75			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$, I_D = 250 µA	2		4	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ± 20 V			± 250	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 75 V, V_{GS} = 0 V			1	µA
		V_{DS} = 75 V, V_{GS} = 0 V, T_J = 125 °C			50	
		V_{DS} = 75 V, V_{GS} = 0 V, T_J = 150 °C			250	
On-State Drain Current[a]	$I_{D(on)}$	$V_{DS} \geq$ 10 V, V_{GS} = 10 V	70			A
Drain-Source On-State Resistance[a]	$r_{DS(on)}$	V_{GS} = 10 V, I_D = 20 A		0.004	0.0048	Ω
		V_{GS} = 10 V, I_D = 20 A, T_J = 125 °C			0.0096	
		V_{GS} = 8 V, I_D = 20 A, T_J = 150 °C			0.0106	
		V_{GS} = 8 V, I_D = 20 A		0.0046	0.006	
Forward Transconductance[a]	g_{fs}	V_{DS} = 15 V, I_D = 20 A		58		S
Dynamic[b]						
Input Capacitance	C_{iss}	V_{GS} = 0 V, V_{DS} = 40 V, f = 1 MHz		6460		pF
Output Capacitance	C_{oss}			571		
Reverse Transfer Capacitance	C_{rss}			275		
Total Gate Charge[c]	Q_g	V_{DS} = 30 V, V_{GS} = 10 V, I_D = 85 A		105	160	nC
Gate-Source Charge[c]	Q_{gs}			32		
Gate-Drain Charge[c]	Q_{gd}			28		
Gate Resistance	R_g	f = 1 MHz		1.3	2.6	Ω
Turn-On Delay Time[c]	$t_{d(on)}$	V_{DD} = 30 V, R_L = 0.4 Ω $I_D \cong$ 85 A, V_{GEN} = 10 V, R_g = 1 Ω		23	35	ns
Rise Time[c]	t_r			17	26	
Turn-Off Delay Time[c]	$t_{d(off)}$			34	52	
Fall Time[c]	t_f			8	15	
Source-Drain Diode Ratings and Characteristics (T_C = 25 °C)[b]						
Continuous Current	I_S				85	A
Pulsed Current	I_{SM}				240	
Forward Voltage[a]	V_{SD}	I_F = 30 A, V_{GS} = 0 V		0.85	1.5	V
Reverse Recovery Time	t_{rr}	I_F = 75 A, di/dt = 100 A/µs		68	100	ns
Peak Reverse Recovery Current	$I_{RM(REC)}$			2.6	4	A
Reverse Recovery Charge	Q_{rr}			88	132	µC

Notes:
a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2 %.
b. Guaranteed by design, not subject to production testing.
c. Independent of operating temperature.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Output Characteristics



Transfer Characteristics



Transconductance



On-Resistance vs. Drain Current



On-resistance vs. Gate-to-Source Voltage



Capacitance

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Gate Charge



On-Resistance vs. Junction Temperature



Source-Drain Diode Forward Voltage



Threshold Voltage



Drain Source Breakdown vs. Junction Temperature



Single Pulse Avalanche Current Capability vs. Time

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Maximum Drain Current vs. Case Temperature



*V_{GS} > minimum V_{GS} at which $r_{DS(on)}$ is specified

Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Case

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see http://www.vishay.com/ppg?74458.

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.