

# Competitive Programming Notes

Raul Almeida

## Contents

1	Tables	1
2	Algorithms	1
2.1	Graph	1
2.1.1	Articulations and Bridges	1
2.1.2	Edmond Karp MaxFlow	2
2.1.3	Euler Tour	2
2.1.4	Floyd Warshall	2
2.1.5	Kahn's Topological Sort	2
2.1.6	Kruskal	2
2.1.7	Lowest Common Ancestor	2
2.1.8	Max Cardinality Bipartite Matching	2
2.1.9	Prim's Algorithm	2
2.1.10	Tarjan	2
2.2	Math	2
2.2.1	Floyd	2
2.3	Paradigm	2
2.3.1	Coordinate Compression	2
2.3.2	128 Bit Integers	2
2.4	String	2
2.4.1	Prefix Function (KMP)	2

## 1 Tables

$n$	not-TLE	Example
$\leq [10..11]$	$\mathcal{O}(n!), \mathcal{O}(n^6)$	Enumerate permutations
$\leq [15..18]$	$\mathcal{O}(2^n n^2)$	TSP with DP
$\leq [18..22]$	$\mathcal{O}(2^n n)$	Bitmask DP
$\leq 100$	$\mathcal{O}(n^4)$	3D DP with $\mathcal{O}(n)$ loop
$\leq 400$	$\mathcal{O}(n^3)$	Floyd-Warshall
$\leq 2 \cdot 10^3$	$\mathcal{O}(n^2 \log n)$	2 nested loops + tree query
$\leq 5 \cdot 10^4$	$\mathcal{O}(n^2)$	Bubble/Selection/Insertion Sort
$\leq 10^5$	$\mathcal{O}(n \log^2 n)$	Build suffix array
$\leq 10^6$	$\mathcal{O}(n \log n)$	Merge Sort
$\leq 10^7$	$\mathcal{O}(n \log \log n)$	Totient function
$\leq 10^8$	$\mathcal{O}(n)$	Mathy solution often with IO bottleneck ( $n \leq 10^9$ )

$10^8$  operations per second

Sign	Type	Bits	Max	Digits
$\pm$	char	8	127	2
+	char	8	255	2
$\pm$	short	16	32 767	4
+	short	16	65 535	4
$\pm$	int/long	32	$2 \cdot 10^9$	9
+	int/long	32	$4 \cdot 10^9$	9
$\pm$	long long	64	$9 \cdot 10^{18}$	18
+	long long	64	$18 \cdot 10^{18}$	19
$\pm$	__int128	128	$17 \cdot 10^{37}$	38
+	__int128	128	$3 \cdot 10^{38}$	38

## 2 Algorithms

Algorithm	Time	Space
Articulations and Bridges	$\mathcal{O}(V + E)$	$\mathcal{O}(V + E)$
Bellman-Ford	$\mathcal{O}(VE)$	$\mathcal{O}(V + E)$
Dijkstra	$\mathcal{O}((V + E) \log V)$	$\mathcal{O}(V^2)$
Edmond Karp	$\mathcal{O}(VE^2)$	$\mathcal{O}(V + E)$
Euler Tour	$\mathcal{O}(E^2)$	
Floyd Warshall	$\mathcal{O}(V^3 + E)$	$\mathcal{O}(V^2 + E)$
Graph Check	$\mathcal{O}(V + E)$	$\mathcal{O}(V + E)$
Kahn	$\mathcal{O}(VE)$	$\mathcal{O}(V + E)$
Kruskal	$\mathcal{O}(E \log V)$	$\mathcal{O}(V + E)$
LCA	$\mathcal{O}(N \log N)$	$\mathcal{O}(N \log N)$
MCBM	$\mathcal{O}(VE)$	
Prim	$\mathcal{O}(E \log V)$	$\mathcal{O}(V + E)$
Tarjan	$\mathcal{O}(V + E)$	$\mathcal{O}(V + E)$
Extended Euclid	$\mathcal{O}(\log \min(a, b))$	$\mathcal{O}(1)$
Floyd (cycle)	$\mathcal{O}(V)$	$\mathcal{O}(1)$
Prime Fac. w/ Opt. Trial Div.	$\mathcal{O}(\pi(\sqrt{n}))$	$\mathcal{O}(n)$
Sieve of Eratosthenes	$\mathcal{O}(n \log \log n)$	$\mathcal{O}(n)$
Binary Search	$\mathcal{O}(\log N)$	
Coordinate Compression	$\mathcal{O}(N \log N)$	
KMP	$\mathcal{O}(N)$	
MUF	$\mathcal{O}(AM)$	$\mathcal{O}(N)$
Bottom-Up SegTree	$\mathcal{O}(\log N)$	$\mathcal{O}(N)$

A: Ackermann function

### 2.1 Graph

#### 2.1.1 Articulations and Bridges

If vertex  $v$  is an **articulation point** and you remove it, the connected component to which it belongs becomes disconnected

If edge  $u, v$  is a **bridge** and you remove it, you can't reach  $v$  from  $u$

#### 2.1.2 Edmond Karp MaxFlow

Ford-Fulkerson's method with BFS  $\rightarrow \mathcal{O}(VE)$  BFS calls,  $\mathcal{O}(E)$  per BFS

**Vertex weights:** if vertex  $V$  has a weight, create  $V_{in}$  (receives all in-edges of  $V$  and has an edge to  $V_{out}$ ) and  $V_{out}$  (receives an edge from  $V_{in}$  and has all out-edges of  $V$ ); edge  $\{V_{in}, V_{out}\}$  has the weight from  $V$

**MinCut:** run EdmondKarp;  $S - T$  sets are: all  $V$  that you can reach from the source with edges of positive residual capacity and all other  $V$

**MultiSource/MultiSink:** create a super source with infinite capacity pointing to all sources, analogous for sinks

**Max Cardinality Bipartite Matching:** use capacity 1 on all edges and apply the multi-source and multi-sink strategies

### 2.1.3 Euler Tour

Find the closest neighbor that has a path back to the current vertex to build an euler tour

**Euler path:** visits each edge once

**Tour/cycle/circuit** euler path that starts and ends at same node

**Undirected and has path:** every vertex has even degree or two have odd degree

**Undirected and has circuit:** every vertex has even degree

**Directed and has path:**  $\delta^+(v) - \delta^-(v) = 1$  for at most one  $v$ ,  $= -1$  for at most one  $v$ ,  $= 0$  for all other  $v$

**Directed and has circuit:**  $\delta^+(v) = \delta^-(v) \forall v \in V$

### 2.1.4 Floyd Warshall

Also works for SSSP ( $V \leq 400$ )

**Printing path:**  $p[i][j]$  set to  $i$  (last node that appears before  $j$  on the path), then  $p[i][j] = p[k][j]$  on update.

**Transitive Closure:** weight is boolean (init as 1 if there's an edge), update with bitwise OR

**Minimax/Maximin:**  $w[i][j]$  will be  $\min(w[i][j], \max(w[i][k], w[k][j]))$

**Finding negative/cheapest cycle:** init  $w[i][i] = \text{inf}$ ;  $\text{run}()$ ; any  $w[i][i] \neq \text{inf}$  is a cycle and the smallest is the cheapest; any  $w[i][i] < 0$  is negative cycle

This can also be used for finding SCCs (check with transitive closure)

### 2.1.5 Kahn's Topological Sort

Particular order (alphabetical)

### 2.1.6 Kruskal

Order edges by increasing weight, then use a MUF to know if each edge is useful (if it connects two previously disconnected vertices)

**Min Span Subgraph:** previously process fixed edges

**Min Span Forest:** count number of sets on the MUF

**2nd Best MST:** run kruskal; for each chosen edge, flag it as unavailable and run it without using that edge ( $O(VE)$ )

**Minimax:** max edge weight on the MST (maximin: min)

### 2.1.7 Lowest Common Ancestor

Binary lift to binary search the LCA or Euler Path

### 2.1.8 Max Cardinality Bipartite Matching

Jump from free to matched edges until you've used them all

### 2.1.9 Prim's Algorithm

Take smallest edge that leads to vertex  $v$

### 2.1.10 Tarjan

A node can reach any other node in its own SCC (DFS + stack)

## 2.2 Math

### 2.2.1 Floyd

Slow and fast (tortoise and hare)

## 2.3 Paradigm

### 2.3.1 Coordinate Compression

Normalize vector access; can also be done with map/set but high constant

### 2.3.2 128 Bit Integers

GCC extension;  $2^{127} 10^{38}$

## 2.4 String

### 2.4.1 Prefix Function (KMP)

To find occurrences of  $s$  in  $t$ , use the string  $s\%+t$ , then look for  $pi[i] = s.length()$  on the " $t$  side"