


# KM 211 S

MANUAL END MILLING MACHINE  
MANUEL ORTA KAYIT ALIŞTIRMA MAKİNESİ



|                                                                                       |                                                                                       |                                                                                       |                                                                                       |              |                                                                                       |                                                                                       |
|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |              |  |  |
|                                                                                       |                                                                                       |                                                                                       | Bar                                                                                   | Air Cons.    |                                                                                       |                                                                                       |
| 1200W 400V AC<br>3P PE 50-60 Hz,                                                      | DMax: Ø170 mm<br>d: Ø30 mm                                                            | 3.000<br>RPM                                                                          | 6-8<br>Bar                                                                            | 14<br>L/min. | WxLxH cm<br>44x74x116                                                                 | 63<br>61                                                                              |

## GENERAL FEATURES

- High quality end-milling operations by the manual operation
- Safety operations with top guard
- Practical cutter adjustment thanks to the gap parts
- Fixing the workpiece firmly thanks to the pneumatic vertical and horizontal clamps
- Robust machine stand
- Profile clamping capacity: H: 160 x W: 150 mm
- Max. end-milling capacity: H: 90 x W: 70 mm
- Max. cutter diameter(D x d): Ø170 x Ø30 mm

## STANDARD ACCESSORIES

- 1x pneumatic vertical clamp
- 1x pneumatic horizontal clamp
- Spray tool lubrication system
- Air gun

## OPTIONAL ACCESSORIES

- Milling cutter set
- MKN 100 roller conveyor (1m)

## GENEL ÖZELLİKLER

- Manuel freze hareketi ile kaliteli kertme operasyonları
- Koruma kapağı ile güvenli çalışma
- Farklı kalınlıktaki şim ve pullar vasıtası ile pratik kesme derinliği ayarlama
- Pnömatik mengener ile iş parçası güvenli olarak bağlanır
- Sağlam makine şasesi
- Mengene profil bağlama kapasitesi: H: 160 x W: 150 mm
- Maksimum kertme kapasitesi: H: 90 x W: 70 mm
- Maksimum testere çapı(D x d): Ø170 x Ø30 mm

## STANDART AKSESUARLAR

- 1x pnömatik dikey mengene
- 1x pnömatik yatay mengene
- Püskürtmeli testere soğutma sistemi
- Hava tabancası

## OPSİYONEL AKSESUARLAR

- Bıçak seti
- MKN 100 konveyör (1m)

