

```

[> # Атака угадыванием значения функции Эйлера
[> with(numtheory) :
[> with(RandomTools) :
[> q1 := nextprime(Generate(integer(range=2..10^5))); # Начальное условие
                                q1 := 19391 (1)
[> q2 := nextprime(Generate(integer(range=2..10^5))); # Начальное условие
                                q2 := 2351 (2)
[> rB := q1·q2; # Известно взломщику
                                rB := 45588241 (3)
[> phi_rB := (q1 - 1)·(q2 - 1);
                                phi_rB := 45566500 (4)
[> Q1 :=  $\frac{(rB - \text{phi\_rB} + 1 + ((rB - \text{phi\_rB} + 1)^2 - 4 \cdot rB)^{(0.5)})}{2}$ ;
                                Q1 := 19391.000000 (5)
[> Q2 :=  $\frac{(rB - \text{phi\_rB} + 1 - ((rB - \text{phi\_rB} + 1)^2 - 4 \cdot rB)^{(0.5)})}{2}$ ;
                                Q2 := 2351.000000 (6)
[> a := ((q1 - Q1 = 0) or (q2 - Q1 = 0)); # Проверка
                                a := true (7)
[> b := ((q1 - Q2 = 0) or (q2 - Q2 = 0)); # Проверка
                                b := true (8)
[>

```