

Exercise 8

Task 1: Virtual Machine (VM) vs. Docker

Virtual Machine (VM)	Docker Container
<p>Definition: A VM is a complete virtual computer running on top of a physical machine. It uses a hypervisor (like VMware or Hyper-V) to emulate hardware and run a full guest operating system separately from the host.</p> <p>Structure:</p> <ul style="list-style-type: none">- Physical hardware- Host operating system- Hypervisor- Guest operating system (with its own kernel)- Applications inside the VM <p>Resource consumption: High, each VM includes its own OS, so it uses more CPU, memory, and storage.</p> <p>Isolation level: Very strong; VMs are fully separated from each other and from the host at the hardware level.</p> <p>Startup time: Slow, usually takes minutes to boot up.</p> <p>Best suited for: Running different operating systems on the same machine or when strict isolation is required, like running Linux and Windows side by side.</p>	<p>Definition: Containers are lightweight, isolated environments that run applications using the host system's kernel. They package an app with its dependencies but don't include a full OS.</p> <p>Structure:</p> <ul style="list-style-type: none">- Physical hardware- Host operating system + container engine (e.g., Docker)- Containers (each with its own libraries and configuration, but sharing the host kernel)- Applications inside the containers <p>Resource consumption: Low, since containers don't bundle an entire OS.</p> <p>Isolation level: Good, but not as complete as VMs, because they separate processes using kernel features instead of full hardware emulation.</p> <p>Startup time: Very fast, typically seconds or less.</p> <p>Best suited for: Quickly deploying applications, running many isolated services on one server, and implementing microservices architectures.</p>

Task 2:

The correct answer is: c) frequently integrate code into a shared repository and run automated tests

The main purpose of Continuous Integration (CI) is to help developers merge their changes into a shared codebase frequently (often multiple times a day). Each integration is verified by automated builds and tests, which helps detect errors early, reduce integration problems, and improve code quality.

Task 3: in IntelliJ

Task 4:

The correct answer is: b) Jenkins

Jenkins is one of the most widely used tools for orchestrating CI/CD pipelines. It automates building, testing, and deploying applications, and supports plugins for integrating with many

Task 5:

1.Parallelize tests: Split your test suite across multiple executors or runners to run tests simultaneously.

2. Run only impacted tests (test selection): Use tools or plugins to run tests related only to the code changes (e.g., Jest's `--changedSince` or Bazel's test selection).

3.Optimize and refactor tests: Identify and fix slow or flaky tests. Mock expensive external dependencies (like databases, APIs).

4.Use faster test frameworks: Some frameworks have faster startup or execution times.

5. Use build/test caching: Tools like Gradle, Bazel, or GitHub Actions' caching can reuse results from unchanged parts of your codebase.