

Problem Set 6

Due Date March 8
Name Alex Ojemann
Student ID 109722375
Collaborators

Contents

Instructions	1
1 Standard 17: Balanced versus unbalanced partitioning.	2
1.1 Problem 1	2
2 Standard 18: Quicksort.	5
2.1 Problem 2	5
2.2 Problem 3	6

Instructions


- The solutions **must be typed**, using proper mathematical notation. We cannot accept hand-written solutions. Useful links and references on \LaTeX can be found here on Canvas.
- You should submit your work through the **class Canvas page** only. Please submit one PDF file, compiled using this \LaTeX template.
- You may not need a full page for your solutions; pagebreaks are there to help Gradescope automatically find where each problem is. Even if you do not attempt every problem, please submit this document with no fewer pages than the blank template (or Gradescope has issues with it).
- You are welcome and encouraged to collaborate with your classmates, as well as consult outside resources. You must **cite your sources in this document**. **Copying from any source is an Honor Code violation. Furthermore, all submissions must be in your own words and reflect your understanding of the material.** If there is any confusion about this policy, it is your responsibility to clarify before the due date.
- Posting to **any** service including, but not limited to Chegg, Reddit, StackExchange, etc., for help on an assignment is a violation of the Honor Code.

1 Standard 17: Balanced versus unbalanced partitioning.

1.1 Problem 1

Problem 1. (a) Consider a modified Merge-Sort algorithm that at each recursion splits an array of size n into two subarrays of sizes 4 and $n - 4$, respectively. Write down a recurrence relation for this modified Merge-Sort algorithm and give its asymptotic solution.

Answer. $T(n) = T(4) + T(n - 4) + \Theta(n)$.



Number of levels:

$$n - 4k = 4$$

$$n - 4 = 4k$$


$$(n - 4)/4 = k$$

Thus, $T(n) = n((n - 4)/4) \in \Theta(n^2)$

□

- (b) Consider a modified Merge-Sort algorithm that at each recursion splits an array of size n into two subarrays of sizes $\frac{1}{5}n$ and $\frac{4}{5}n$, respectively. Write down a recurrence relation for this modified Merge-Sort algorithm and give its asymptotic solution.

Answer. $T(n) = T(n/5) + T(4n/5) + \Theta(n)$.



Number of levels:


$$\begin{aligned} n * (4/5)^k &= 1 \\ n &= (5/4)^k \\ \log_{5/4} n &= k \end{aligned}$$

Thus, $T(n) = n(\log_{5/4} n) \in \Theta(n(\log_{5/4} n))$

□

- (c) Suppose that we modify the Merge-Sort algorithm in such a way that on alternating levels of the recursion, the partitioning is either a $(2, n - 2)$ split or a $(n/2, n/2)$ split. Write down a recurrence relation for this modified Merge-Sort algorithm and give its asymptotic solution. Then, give a verbal explanation of how this Merge-Sort algorithm changes the running time of Merge-Sort.

Answer. $T(n) = T(2) + T(n - 2) + \Theta(n)$ if odd level, $T(n) = T(n/2) + T(n/2) + \Theta(n)$ if even level.



Number of levels:

$$\begin{aligned}
 (n - 2) * (1/2)^{k/2} &= 1 \\
 n - 2 &= (1/2)^{k/2} \\
 \log_{1/2}(n - 2) &= k/2 \\
 2 \log_{1/2}(n - 2) &= k
 \end{aligned}$$

Thus, $T(n) = n(2 \log_{1/2}(n - 2)) \in \Theta(n(\log_{1/2} n))$

□

2 Standard 18: Quicksort.

2.1 Problem 2

Problem 2. Given an input array $\{3, 7, 1, 8, 2, 6, 5, 4\}$. Consider the deterministic QuickSort algorithm and show the input array, the output array, and the global array at every partition as in the example in Section 2.1.1 of the course notes for week 8 (see Week 8 under “Modules” of the course canvas).

Answer. Start: Input: $[3, 7, 1, 8, 2, 6, 5, 4]$ Output: $[3, 1, 2 — 4 — 7, 8, 6, 5]$ Global Array: $[3, 1, 2, 4, 7, 8, 6, 5]$

Input: $[3, 1, 2]$ Output: $[1 — 2 — 3]$ Global Array: $[1, 2, 3, 4, 7, 8, 6, 5]$

Input: $[7, 8, 6, 5]$ Output: $[— 5 — 7, 8, 6]$ Global Array: $[1, 2, 3, 4, 5, 7, 8, 6]$

Input: $[7, 8, 6]$ Output: $[— 6 — 7, 8]$ Global Array: $[1, 2, 3, 4, 5, 6, 7, 8]$

Input: $[7, 8]$ Output: $[7 — 8 —]$ Global Array: $[1, 2, 3, 4, 5, 6, 7, 8]$

□


2.2 Problem 3

Problem 3. Suppose that we modify PARTITION(A, s, e) so that it chooses the median element of $A[s..e]$ in calls that occur in nodes of even depth of the recursion tree of a call QUICKSORT($A[1, \dots, n], 1, n$), and it chooses the minimum element of $A[s..e]$ in calls that occur in nodes of odd depth of this recursion tree.

Assume that the running time of this modified PARTITION is still $\Theta(n)$ on any subarray of length n . You may assume that the root of a recursion tree starts at level 0 (which is an even number), its children are at level 1, etc.

Write down a recurrence relation for the running time of this version of QUICKSORT given an array n distinct elements and solve it asymptotically, i.e. give your answer as $\Theta(f(n))$ for some function $f(n)$. Show your work.

Answer. $T(n) = T(1) + T(n - 1) + \Theta(n)$ if odd depth, $T(n) = T(n/2) + T(n/2) + \Theta(n)$ if even depth.



Number of levels:

$$\begin{aligned}
 (n - 1) * (1/2)^{k/2} &= 1 \\
 n - 1 &= (1/2)^{k/2} \\
 \log_{1/2}(n - 1) &= k/2 \\
 2 \log_{1/2}(n - 1) &= k
 \end{aligned}$$

Thus, $T(n) = n(2 \log_{1/2}(n - 1)) \in \Theta(n(\log_{1/2} n))$

□