① srcML of the loop nest (lines 10–15)

```
<for>e for <control><expr><name>layer</name></expr><range>in <expr><call><name>range</name><argument_list>(
    ↪ <argument><expr><name>layers f</name></expr></argument>)</argument_list></call></expr></range></control><block>:
    ↪ <block_content>
    <for>e for <control><expr><name>qubit</name></expr><range>in <expr><call><name>range</name><argument_list>(
        ↪ <argument><expr><name>n f</name></expr></argument>)</argument_list></call></expr></range></control><block>:
        ↪ <block_content>
        <expr_stmt><expr><call><name><name>qc</name><operator>.</operator><name>ry b</name></name><argument_list>(
            ↪ <argument>angle . . . </argument>, <argument><expr><name>qubit c</name></expr></argument>)</argument_list></call>
            ↪ </expr></expr_stmt>
        <expr_stmt><expr><call><name><name>qc</name><operator>.</operator><name>rz b</name></name><argument_list>(
            ↪ <argument>angle . . . </argument>, <argument><expr><name>qubit c</name></expr></argument>)</argument_list></call>
            ↪ </expr></expr_stmt>
</block_content></block></for><for>e for <control><expr><name>qubit</name></expr><range>in <expr><call><name>
    ↪ range</name><argument_list>(<argument><expr><name>n f</name><operator>-</operator><literal type="number">1
    ↪ </literal></expr></argument>)</argument_list></call></expr></range></control><block>:<block_content>
        <expr_stmt><expr><call><name><name>qc</name><operator>.</operator><name>cx b</name></name><argument_list>(
            ↪ <argument><expr><name>qubit c</name></expr></argument>, <argument><expr><name>qubit c</name><operator>+
            ↪ </operator><literal type="number">1 c</literal></expr></argument>)</argument_list></call></expr>
            ↪ </expr_stmt>
</block_content></block></for></block_content></block></for>
```

e `for` → unrolled **f** range → iteration count, from lines 4–5 **b** gate **c** qubit argument → a qubit per iteration *angle . . .* elided, kept symbolic

② Unrolled operations in the slice of q_0

line 12, `ry`	line 13, `rz`	line 15, `cx`
5 of 6	**5** of 6	**3** of 4



Filled squares are in the QDG slice of q_0, 13 of 16 operations. The lines are the same in every iteration, but in the second layer the rotations of q_2 and its `cx` *are not dependences of q_0; a line-level slice keeps lines 12, 13 and 15 anyway.*