

Práctica 4 – Vulnerabilidades

Report generated by Tenable Nessus™ Thu, 12 Mar 2026 04:31:53 CST

TABLE OF CONTENTS

Vulnerabilities by Host

- 192.168.1.160 4

Vulnerabilities by Host

192.168.1.160

CRITICAL	HIGH	MEDIUM	LOW	INFO
0	8	10	3	128

Host Information

IP:	192.168.1.160
MAC Address:	C0:3E:BA:28:51:67 5C:3A:45:A7:71:CF
OS:	Linux Kernel 6.8.9-100.fc38.x86_64 on Fedora release 38 (Thirty Eight)

Vulnerabilities

197900 - Intel Media SDK Multiple Vulnerabilities (INTEL-SA-00935)

Synopsis

The version of Intel Media SDK installed on the remote host is affected by multiple vulnerabilities.

Description

The version of Intel Media SDK installed on the remote host is affected by multiple vulnerabilities:

- Improper input validation in Intel Media SDK software all versions may allow an authenticated user to potentially enable denial of service via local access. (CVE-2023-48368)

- Improper buffer restrictions in Intel Media SDK all versions may allow an authenticated user to potentially enable escalation of privilege via local access. (CVE-2023-45221)

- Out-of-bounds read in Intel Media SDK and some Intel oneVPL software before version 23.3.5 may allow an authenticated user to potentially enable escalation of privilege via local access. (CVE-2023-22656)

- Out-of-bounds write in Intel Media SDK all versions and some Intel oneVPL software before version 23.3.5 may allow an authenticated user to potentially enable escalation of privilege via local access. (CVE-2023-47282)

- Improper buffer restrictions in Intel Media SDK software all versions may allow an authenticated user to potentially enable denial of service via local access. (CVE-2023-47169)

Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

http://www.nessus.org/u?c8710b2e

Solution

Intel has issued a Product Discontinuation notice for Intel Media SDK software and recommends that users of the Intel Media SDK software uninstall it or discontinue use at their earliest convenience.

Risk Factor

Medium

CVSS v3.0 Base Score

7.8 (CVSS:3.0/AV:L/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.8 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.0005

CVSS v2.0 Base Score

6.8 (CVSS2#AV:L/AC:L/Au:S/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

II

References

CVE	CVE-2023-48368
CVE	CVE-2023-45221
CVE	CVE-2023-22656
CVE	CVE-2023-47282
CVE	CVE-2023-47169
XREF	IAVB:2024-B-0064

Plugin Information

Published: 2024/05/24, Modified: 2025/08/28

Plugin Output

tcp/0

201194 - OpenSSH < 9.8 RCE

Synopsis

The SSH server running on the remote host is affected by a vulnerability.

Description

The version of OpenSSH installed on the remote host is prior to 9.8. It is, therefore, affected by a vulnerability as referenced in the release-9.8 advisory.

- This release contains fixes for two security problems, one critical and one minor. 1) Race condition in sshd(8) A critical vulnerability in sshd(8) was present in Portable OpenSSH versions between 8.5p1 and 9.7p1 (inclusive) that may allow arbitrary code execution with root privileges. Successful exploitation has been demonstrated on 32-bit Linux/glibc systems with ASLR. Under lab conditions, the attack requires on average 6-8 hours of continuous connections up to the maximum the server will accept. Exploitation on 64-bit systems is believed to be possible but has not been demonstrated at this time. It's likely that these attacks will be improved upon. Exploitation on non-glibc systems is conceivable but has not been examined. Systems that lack ASLR or users of downstream Linux distributions that have modified OpenSSH to disable per-connection ASLR re-randomisation (yes - this is a thing, no - we don't understand why) may potentially have an easier path to exploitation. OpenBSD is not vulnerable. We thank the Qualys Security Advisory Team for discovering, reporting and demonstrating exploitability of this problem, and for providing detailed feedback on additional mitigation measures. 2) Logic error in ssh(1) ObscureKeystrokeTiming In OpenSSH version 9.5 through 9.7 (inclusive), when connected to an OpenSSH server version 9.5 or later, a logic error in the ssh(1) ObscureKeystrokeTiming feature (on by default) rendered this feature ineffective - a passive observer could still detect which network packets contained real keystrokes when the countermeasure was active because both fake and real keystroke packets were being sent unconditionally. This bug was Daniel Hugenroth and Alastair Beresford of the University of Cambridge Computer Lab. Worse, the unconditional sending of both fake and real keystroke packets broke another long- standing timing attack mitigation. Since OpenSSH 2.9.9 sshd(8) has sent fake keystoke echo packets for traffic received on TTYs in echo-off mode, such as when entering a password into su(8) or sudo(8). This bug rendered these fake keystroke echoes ineffective and could allow a passive observer of a SSH session to once again detect when echo was off and obtain fairly limited timing information about keystrokes in this situation (20ms granularity by default). This additional implication of the bug was identified by Jacky Wei En Kung, Daniel Hugenroth and Alastair Beresford and we thank them for their detailed analysis.

This bug does not affect connections when ObscureKeystrokeTiming was disabled or sessions where no TTY was requested. (openssh-9.8-1)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://www.openssh.com/txt/release-9.8

Solution

Upgrade to OpenSSH version 9.8 or later.

Risk Factor

High

CVSS v3.0 Base Score

8.1 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.3 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

9.2

EPSS Score

0.3595

CVSS v2.0 Base Score

7.6 (CVSS2#AV:N/AC:H/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

6.0 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2024-6387
CVE	CVE-2024-39894
XREF	IAVA:2024-A-0375-S

Plugin Information

Published: 2024/07/01, Modified: 2025/03/11

Plugin Output

tcp/22/ssh

299758 - PostgreSQL 14.x < 14.21 / 15.x < 15.16 / 16.x < 16.12 / 17.x < 17.8 / 18.x < 18.2 Multiple Vulnerabilities

Synopsis

The remote database server is affected by multiple vulnerabilities.

Description

The version of PostgreSQL installed on the remote host is 14 prior to 14.21, 15 prior to 15.16, 16 prior to 16.12, 17 prior to 17.8, or 18 prior to 18.2. As such, it is potentially affected by multiple vulnerabilities:

- Missing validation of multibyte character length in PostgreSQL text manipulation allows a database user to issue crafted queries that achieve a buffer overrun. That suffices to execute arbitrary code as the operating system user running the database. Versions before PostgreSQL 18.2, 17.8, 16.12, 15.16, and 14.21 are affected. (CVE-2026-2006)

- Heap buffer overflow in PostgreSQL pgcrypto allows a ciphertext provider to execute arbitrary code as the operating system user running the database. Versions before PostgreSQL 18.2, 17.8, 16.12, 15.16, and 14.21 are affected. (CVE-2026-2005)

- Missing validation of type of input in PostgreSQL intarray extension selectivity estimator function allows an object creator to execute arbitrary code as the operating system user running the database. Versions before PostgreSQL 18.2, 17.8, 16.12, 15.16, and 14.21 are affected. (CVE-2026-2004)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

http://www.nessus.org/u?fbf9397e

https://www.postgresql.org/support/security/CVE-2026-2003/

https://www.postgresql.org/support/security/CVE-2026-2004/

https://www.postgresql.org/support/security/CVE-2026-2005/

https://www.postgresql.org/support/security/CVE-2026-2006/

Solution

Upgrade to PostgreSQL 14.21 / 15.16 / 16.12 / 17.8 / 18.2 or later.

Risk Factor

High

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

7.4

EPSS Score

0.0009

CVSS v2.0 Base Score

9.0 (CVSS2#AV:N/AC:L/Au:S/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

6.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2026-2003
CVE	CVE-2026-2004
CVE	CVE-2026-2005
CVE	CVE-2026-2006
XREF	IAVB:2026-B-0047

Plugin Information

Published: 2026/02/23, Modified: 2026/02/24

Plugin Output

tcp/0

299757 - PostgreSQL 18.x < 18.2 Heap Buffer Overflow (CVE-2026-2007)

Synopsis

The remote database server is affected by a heap buffer overflow vulnerability.

Description

The version of PostgreSQL installed on the remote host is 18 prior to 18.2. As such, it is potentially affected by a vulnerability:

- Heap buffer overflow in PostgreSQL pg_trgm allows a database user to achieve unknown impacts via a crafted input string. The attacker has limited control over the byte patterns to be written, but we have not ruled out the viability of attacks that lead to privilege escalation. PostgreSQL 18.1 and 18.0 are affected.

(CVE-2026-2007)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

http://www.nessus.org/u?fbf9397e

https://www.postgresql.org/support/security/CVE-2026-2007/

Solution

Upgrade to PostgreSQL 18.2 or later.

Risk Factor

High

CVSS v3.0 Base Score

8.2 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:H)

CVSS v3.0 Temporal Score

7.1 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.0

EPSS Score

0.0004

CVSS v2.0 Base Score

8.5 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:C)

CVSS v2.0 Temporal Score

6.3 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2026-2007
XREF	IAVB:2026-B-0047

Plugin Information

Published: 2026/02/23, Modified: 2026/02/24

Plugin Output

tcp/0

274433 - Python Library Brotli <= 1.1.0 DoS

Synopsis

A Python library installed on the remote host is affected by a denial of service vulnerability.

Description

The detected version of the Brotli Python package, Brotli, is prior or equal to 1.1.0. It is, therefore, affected by a denial of service (DoS) vulnerability due to decompression.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://github.com/advisories/GHSA-2qfp-q593-8484

Solution

Upgrade to Brotli version 1.2.0 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

VPR Score

3.6

EPSS Score

0.0004

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

STIG Severity

I

References

CVE	CVE-2025-6176

XREF IAVA:2025-A-0813

Plugin Information

Published: 2025/11/07, Modified: 2025/11/07

Plugin Output

tcp/0

195217 - R Programming Language 1.4.0 < 4.4.0 Insecure Deserialization

Synopsis

An application installed on the remote host is affected by an insecure deserialization vulnerability.

Description

The version of the R Programming Language running on the remote host is 1.4.0 or later, before 4.4.0. It is, therefore, affected by an insecure deserialization vulnerability. Deserialization of untrusted data can occur, enabling a maliciously crafted RDS (R Data Serialization) formatted file or R package to run arbitrary code on an end user's system when interacted with.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://hiddenlayer.com/research/r-bitrary-code-execution/

https://www.openwall.com/lists/oss-security/2024/04/29/3

https://www.kb.cert.org/vuls/id/238194

Solution

Upgrade to R version 4.4.0 or later.

Risk Factor

High

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:R/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.0132

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2024-27322
XREF	IAVA:2024-A-0268

Plugin Information

Published: 2024/05/09, Modified: 2025/08/25

Plugin Output

tcp/0

283875 - Security Update for Azure Core shared client library for Python < 1.38.0 (January 2026)

Synopsis

The Azure Core shared client library for Python installation on the remote host is affected by an elevation of privilege vulnerability.

Description

The Azure Core shared client library for Python installation on the remote host is missing a security update. It is, therefore, affected by an elevation of privilege vulnerability (CVE-2026-21226).

- An attacker who successfully exploited this vulnerability could gain elevated privileges by manipulating how the library handles credential caching or environment variable processing in certain configurations.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://msrc.microsoft.com/update-guide/vulnerability/CVE-2026-21226

Solution

Update the 'azure-core' Python package to version 1.38.0 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:H/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0045

CVSS v2.0 Base Score

7.1 (CVSS2#AV:N/AC:H/Au:S/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:U/RL:OF/RC:C)

References

CVE	CVE-2026-21226

Plugin Information

Published: 2026/01/14, Modified: 2026/02/12

Plugin Output

tcp/0

282519 - Apache Log4j 2.0-beta9 < 2.25.3 MitM

Synopsis

A logging library installed on the remote host is affected by a man in the middle vulnerability.

Description

The version of Apache Log4j on the remote host is 2.0-beta9 through 2.25.2. The Socket Appender in Apache Log4j Core versions 2.0-beta9 through 2.25.2 does not perform TLS hostname verification of the peer certificate, even when the verifyHostName https://logging.apache.org/log4j/2.x/manual/appenders/network.html#SslConfiguration-attr-verifyHostName configuration attribute or the log4j2.sslVerifyHostName https://logging.apache.org/log4j/2.x/manual/systemproperties.html#log4j2.sslVerifyHostName system property is set to true. This issue may allow a man-in-the-middle attacker to intercept or redirect log traffic under the following conditions:

- The attacker is able to intercept or redirect network traffic between the client and the log receiver.

- The attacker can present a server certificate issued by a certification authority trusted by the Socket Appender's configured trust store (or by the default Java trust store if no custom trust store is configured).

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://lists.apache.org/thread/xr33kyxq3sl67lwb61ggvm1fzc8k7dvx

Solution

Upgrade to Apache Log4j version 2.25.3 or later.

Risk Factor

Medium

CVSS v4.0 Base Score

6.3 (CVSS:4.0/AV:N/AC:H/AT:N/PR:N/UI:N/VC:L/VI:N/VA:N/SC:N/SI:L/SA:N)

CVSS v3.0 Base Score

4.8 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v3.0 Temporal Score

4.3 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

3.3

EPSS Score

0.0003

CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

3.1 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2025-68161
XREF	IAVA:2026-A-0001

Plugin Information

Published: 2026/01/09, Modified: 2026/02/17

Plugin Output

tcp/0

187201 - OpenSSH < 9.6 Multiple Vulnerabilities

Synopsis

The SSH server running on the remote host is affected by multiple vulnerabilities.

Description

The version of OpenSSH installed on the remote host is prior to 9.6. It is, therefore, affected by multiple vulnerabilities as referenced in the release-9.6 advisory.

- ssh(1), sshd(8): implement protocol extensions to thwart the so-called Terrapin attack discovered by Fabian Bumer, Marcus Brinkmann and Jrg Schwenk. This attack allows a MITM to effect a limited break of the integrity of the early encrypted SSH transport protocol by sending extra messages prior to the commencement of encryption, and deleting an equal number of consecutive messages immediately after encryption starts. A peer SSH client/server would not be able to detect that messages were deleted. While cryptographically novel, the security impact of this attack is fortunately very limited as it only allows deletion of consecutive messages, and deleting most messages at this stage of the protocol prevents user user authentication from proceeding and results in a stuck connection. The most serious identified impact is that it lets a MITM to delete the SSH2_MSG_EXT_INFO message sent before authentication starts, allowing the attacker to disable a subset of the keystroke timing obfuscation features introduced in OpenSSH 9.5.

There is no other discernable impact to session secrecy or session integrity. OpenSSH 9.6 addresses this protocol weakness through a new strict KEX protocol extension that will be automatically enabled when both the client and server support it. This extension makes two changes to the SSH transport protocol to improve the integrity of the initial key exchange. Firstly, it requires endpoints to terminate the connection if any unnecessary or unexpected message is received during key exchange (including messages that were previously legal but not strictly required like SSH2_MSG_DEBUG). This removes most malleability from the early protocol. Secondly, it resets the Message Authentication Code counter at the conclusion of each key exchange, preventing previously inserted messages from being able to make persistent changes to the sequence number across completion of a key exchange. Either of these changes should be sufficient to thwart the Terrapin Attack. More details of these changes are in the PROTOCOL file in the OpenSSH source distribition. (CVE-2023-48795)

- ssh-agent(1): when adding PKCS#11-hosted private keys while specifying destination constraints, if the PKCS#11 token returned multiple keys then only the first key had the constraints applied. Use of regular private keys, FIDO tokens and unconstrained keys are unaffected. (CVE-2023-51384)

- ssh(1): if an invalid user or hostname that contained shell metacharacters was passed to ssh(1), and a ProxyCommand, LocalCommand directive or match exec predicate referenced the user or hostname via %u, %h or similar expansion token, then an attacker who could supply arbitrary user/hostnames to ssh(1) could potentially perform command injection depending on what quoting was present in the user-supplied ssh_config(5) directive. This situation could arise in the case of git submodules, where a repository could contain a submodule with shell characters in its user/hostname. Git does not ban shell metacharacters in user or host names when checking out repositories from untrusted sources. Although we believe it is the user's responsibility to ensure validity of arguments passed to ssh(1), especially across a security boundary such as the git example above, OpenSSH 9.6 now bans most shell metacharacters from user and hostnames supplied via the command-line. This countermeasure is not guaranteed to be effective in all situations, as it is infeasible for ssh(1) to universally filter shell metacharacters potentially relevant to user-supplied commands. User/hostnames provided via ssh_config(5) are not subject to these restrictions, allowing configurations that use strange names to continue to be used, under the assumption that the user knows what they are doing in their own configuration files. (CVE-2023-51385)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://www.openssh.com/txt/release-9.6

Solution

Upgrade to OpenSSH version 9.6 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v3.0 Temporal Score

5.9 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.5786

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-48795
CVE	CVE-2023-51384
CVE	CVE-2023-51385
XREF	IAVA:2023-A-0701-S

Plugin Information

Published: 2023/12/22, Modified: 2025/02/28

Plugin Output

tcp/22/ssh

275842 - PostgreSQL 13.x < 13.23 / 14.x < 14.20 / 15.x < 15.15 / 16.x < 16.11 / 17.x < 17.7 / 18.x < 18.1 Multiple Vulnerabilities

Synopsis

The remote database server is affected by multiple vulnerabilities

Description

The version of PostgreSQL installed on the remote host is 13 prior to 13.23, 14 prior to 14.20, 15 prior to 15.15, 16 prior to 16.11, 17 prior to 17.7, or 18 prior to 18.1. As such, it is potentially affected by multiple vulnerabilities:

- Integer wraparound in multiple PostgreSQL libpq client library functions allows an application input provider or network peer to cause libpq to undersize an allocation and write out-of-bounds by hundreds of megabytes. This results in a segmentation fault for the application using libpq. Versions before PostgreSQL 18.1, 17.7, 16.11, 15.15, 14.20, and 13.23 are affected. (CVE-2025-12818)

- Missing authorization in PostgreSQL CREATE STATISTICS command allows a table owner to achieve denial of service against other CREATE STATISTICS users by creating in any schema. A later CREATE STATISTICS for the same name, from a user having the CREATE privilege, would then fail. Versions before PostgreSQL 18.1, 17.7, 16.11, 15.15, 14.20, and 13.23 are affected. (CVE-2025-12817)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

http://www.nessus.org/u?eb23efca

Solution

Upgrade to PostgreSQL 13.23 / 14.20 / 15.15 / 16.11 / 17.7 / 18.1 or later

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.0004

CVSS v2.0 Base Score

5.4 (CVSS2#AV:N/AC:H/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

4.0 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2025-12817
CVE	CVE-2025-12818
XREF	IAVB:2025-B-0192-S

Plugin Information

Published: 2025/11/20, Modified: 2026/02/24

Plugin Output

tcp/0

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.

- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.

- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

https://www.itu.int/rec/T-REC-X.509/en

https://en.wikipedia.org/wiki/X.509

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/8834/www

200807 - urllib3 Python Library < 1.26.19, < 2.2.2 (CVE-2024-37891)

Synopsis

A Python library installed on the remote host is affected by a vulnerability.

Description

urllib3 is a user-friendly HTTP client library for Python. When using urllib3's proxy support with 'ProxyManager', the 'Proxy-Authorization' header is only sent to the configured proxy, as expected. However, when sending HTTP requests without using urllib3's proxy support, it's possible to accidentally configure the 'Proxy-Authorization' header even though it won't have any effect as the request is not using a forwarding proxy or a tunneling proxy. In those cases, urllib3 doesn't treat the 'Proxy-Authorization' HTTP header as one carrying authentication material and thus doesn't strip the header on cross-origin redirects.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

http://www.nessus.org/u?7b44847c

Solution

Upgrade to urllib3 version 1.26.19, 2.2.2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.9 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.0021

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:L/Au:S/C:C/I:N/A:N)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

II

References

CVE	CVE-2024-37891
XREF	IAVA:2024-A-0363-S

Plugin Information

Published: 2024/06/21, Modified: 2026/01/21

Plugin Output

tcp/0

201358 - Fedoraproject Fedora SEoL (38.x)

Synopsis

An unsupported version of Fedoraproject Fedora is installed on the remote host.

Description

According to its version, Fedoraproject Fedora is 38.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

https://docs.fedoraproject.org/en-US/releases/eol/

Solution

Upgrade to a version of Fedoraproject Fedora that is currently supported.

Risk Factor

Low

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/0

234554 - OpenSSH < 10.0 DisableForwarding

Synopsis

The SSH server running on the remote host is affected by a vulnerability.

Description

The version of OpenSSH installed on the remote host is prior to 10.0. It is, therefore, affected by a vulnerability. In sshd in OpenSSH the DisableForwarding directive does not adhere to the documentation stating that it disables X11 and agent forwarding.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://www.openssh.com/txt/release-10.0

Solution

Upgrade to OpenSSH version 10.0 or later.

Risk Factor

Low

CVSS v3.0 Base Score

3.8 (CVSS:3.0/AV:L/AC:L/PR:L/UI:N/S:C/C:N/I:L/A:N)

VPR Score

2.4

EPSS Score

0.0001

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:N/I:P/A:N)

STIG Severity

I

References

CVE	CVE-2025-32728
XREF	IAVA:2025-A-0258-S

Plugin Information

Published: 2025/04/17, Modified: 2025/10/29

Plugin Output

tcp/22/ssh

269984 - OpenSSH < 10.1 / 10.1p1 Multiple Vulnerabilities

Synopsis

The SSH server running on the remote host is affected by multiple vulnerabilities.

Description

The version of OpenSSH installed on the remote host is prior to 10.1. It is, therefore, affected by multiple vulnerabilities:

- ssh in OpenSSH before 10.1 allows control characters in usernames that originate from certain possibly untrusted sources, potentially leading to code execution when a ProxyCommand is used. The untrusted sources are the command line and %-sequence expansion of a configuration file. (A configuration file that provides a complete literal username is not categorized as an untrusted source.) (CVE-2025-61984)

- ssh in OpenSSH before 10.1 allows the '\0' character in an ssh:// URI, potentially leading to code execution when a ProxyCommand is used. (CVE-2025-61985)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://www.openssh.com/releasenotes.html#10.1p1

Solution

Upgrade to OpenSSH version 10.1/10.1p1 or later.

Risk Factor

Low

CVSS v3.0 Base Score

3.6 (CVSS:3.0/AV:L/AC:H/PR:L/UI:N/S:U/C:L/I:L/A:N)

VPR Score

5.0

EPSS Score

0.0001

CVSS v2.0 Base Score

2.4 (CVSS2#AV:L/AC:H/Au:S/C:P/I:P/A:N)

STIG Severity

II

References

CVE	CVE-2025-61984
CVE	CVE-2025-61985
XREF	IAVA:2025-A-0806
XREF	IAVA:2025-A-0729-S

Plugin Information

Published: 2025/10/10, Modified: 2025/11/18

Plugin Output

tcp/22/ssh

196906 - AI/LLM Software Report

Synopsis

Reports a summary of AI/LLM software detected on the remote host.

Description

This plugin utilizes various Nessus detection methods and reports software identified by to Nessus and known to utilize "Artificial Intelligence" (AI) and Large Language Model (LLM) technology.

Note that this plugin uses several detection methods. The products reported by this plugin will grow as more detections and methods are added.

See Also

https://www.tenable.com/plugins/nessus/196906/dependencies

Solution

Remove any applications that are not compliant with your organization's acceptable use and security policies.

Risk Factor

None

Plugin Information

Published: 2024/05/29, Modified: 2026/03/09

Plugin Output

tcp/0

46180 - Additional DNS Hostnames

Synopsis

Nessus has detected potential virtual hosts.

Description

Hostnames different from the current hostname have been collected by miscellaneous plugins. Nessus has generated a list of hostnames that point to the remote host. Note that these are only the alternate hostnames for vhosts discovered on a web server.

Different web servers may be hosted on name-based virtual hosts.

See Also

https://en.wikipedia.org/wiki/Virtual_hosting

Solution

If you want to test them, re-scan using the special vhost syntax, such as :

www.example.com[192.0.32.10]

Risk Factor

None

Plugin Information

Published: 2010/04/29, Modified: 2022/08/15

Plugin Output

tcp/0

```
The following hostnames point to the remote host :
  - alonso
```

189973 - AnyDesk Installed (Linux)

Synopsis

AnyDesk is installed on the remote Linux host.

Description

AnyDesk is installed on the remote Linux host.

Note that more paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.

See Also

https://anydesk.com/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/02/03, Modified: 2026/02/03

Plugin Output

tcp/0

141394 - Apache HTTP Server Installed (Linux)

Synopsis

The remote host has Apache HTTP Server software installed.

Description

Apache HTTP Server is installed on the remote Linux host.

See Also

https://httpd.apache.org/

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0530

Plugin Information

Published: 2020/10/12, Modified: 2026/03/09

Plugin Output

tcp/0

156000 - Apache Log4j Installed (Linux / Unix)

Synopsis

Apache Log4j, a logging API, is installed on the remote Linux / Unix host.

Description

One or more instances of Apache Log4j, a logging API, are installed on the remote Linux / Unix Host.

The plugin timeout can be set to a custom value other than the plugin's default of 45 minutes via the 'timeout.156000' scanner setting in Nessus 8.15.1 or later.

Note, this plugin runs certain commands differently if the scan is configured to use the 'Attempt Least Privilege' option. If enabled, scan times are expected to increase, especially on hosts with many files.

Please see https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom for more information.

See Also

https://logging.apache.org/log4j/2.x/

Solution

n/a

Risk Factor

None

References

XREF	IAVA:0001-A-0650
XREF	IAVT:0001-T-0941

Plugin Information

Published: 2021/12/10, Modified: 2026/02/03

Plugin Output

tcp/0

133766 - Apache Maven Installed (Linux / Unix)

Synopsis

Apache Maven is installed on the remote Linux / Unix host.

Description

Apache Maven, a software project management and comprehension tool, is installed on the remote Linux / Unix host.

See Also

https://maven.apache.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/02/18, Modified: 2026/02/03

Plugin Output

tcp/0

34098 - BIOS Info (SSH)

Synopsis

BIOS info could be read.

Description

Using SMBIOS and UEFI, it was possible to get BIOS info.

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2008/09/08, Modified: 2024/02/12

Plugin Output

tcp/0

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

http://cpe.mitre.org/

https://nvd.nist.gov/products/cpe

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

tcp/0

```
The remote operating system matched the following CPE :

  cpe:/o:fedoraproject:fedora:38::~~workstation~~x86_64~ -> Fedora

Following application CPE's matched on the remote system :

  cpe:/a:anydesk:anydesk:6.3.0 -> Anydesk Anydesk for Windows
  cpe:/a:apache:http_server:2.4.59 -> Apache Software Foundation Apache HTTP Server
  cpe:/a:apache:log4j -> Apache Software Foundation log4j
  cpe:/a:apache:log4j:2.17.2 -> Apache Software Foundation log4j
  cpe:/a:apache:log4j:2.22.1 -> Apache Software Foundation log4j
  cpe:/a:apache:log4j:2.24.1 -> Apache Software Foundation log4j
  cpe:/a:apache:maven:3.8.6 -> Apache Software Foundation Maven
  cpe:/a:exiv2:exiv2:0.27.6 -> Exiv2
  cpe:/a:exiv2:libexiv2:0.27.6
  cpe:/a:gnome:gnome-shell:44.10 -> GNOME gnome-shell -
  cpe:/a:gnupg:libgcrypt:1.10.2 -> GnuPG Libgcrypt
  cpe:/a:haxx:curl:8.0.1 -> Haxx Curl
```

```
cpe:/a:haxx:libcurl:8.0.1 -> Haxx libcurl
cpe:/a:imagemagick:imagemagick:7.1.1.26 -> ImageMagick
cpe:/a:intel:onevpl_gpu_runtime:24.1.3 -> Intel oneVPL GPU Runtime
cpe:/a:jmcnamara:spreadsheet%3a%3aparseexcel:0.66 -> John McNamara Spreadsheet::ParseExcel
cpe:/a:linuxfoundation:containerd:1.6.33 -> The Linux Foundation containerd
cpe:/a:numpy:numpy:1.24.4 -> NumPy
cpe:/a:openbsd:openssh:9.0 -> OpenBSD OpenSSH
cpe:/a:openssl:openssl:3.0.19 -> OpenSSL Project OpenSSL
cpe:/a:openssl:openssl:3.0.9 -> OpenSSL Project OpenSSL
cpe:/a:openvpn:openvpn:2.6.9 -> OpenVPN
cpe:/a:oracle:openjdk:11.0.23 -> Oracle OpenJDK -
cpe:/a:oracle:openjdk:17.0.11 -> Oracle OpenJDK -
cpe:/a:oracle:openjdk:17.0.4 -> Oracle OpenJDK -
cpe:/a:oracle:openjdk:22.0.1 -> Oracle OpenJDK -
cpe:/a:oracle:openjdk:8.0.412 -> Oracle OpenJDK -
cpe:/a:php:php:8.2.18 -> PHP PHP
cpe:/a:podman_project:podman:4.9.4 -> Podman Project Podman
cpe:/a:postgresql:postgresql:13.23 -> PostgreSQL
cpe:/a:postgresql:postgresql:14.20 -> PostgreSQL
cpe:/a:postgresql:postgresql:15.15 -> PostgreSQL
cpe:/a:postgresql:postgresql:15.4 -> PostgreSQL
cpe:/a:postgresql:postgresql:16.11 -> Po [...]
```

237414 - Containerd Installed (Linux)

Synopsis

containerd was detected on the remote host.

Description

containerd, a container runtime which can manage the complete container lifecycle of its host system is installed on the target host.

See Also

https://github.com/containerd/containerd/tree/main

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/05/28, Modified: 2026/02/03

Plugin Output

tcp/0

182774 - Curl Installed (Linux / Unix)

Synopsis

Curl is installed on the remote Linux / Unix host.

Description

Curl (also known as curl and cURL) is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.

- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.182774' scanner setting in Nessus 8.15.1 or later.

Please see https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom for more information.

See Also

https://curl.se/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/10/09, Modified: 2026/03/09

Plugin Output

tcp/0

55472 - Device Hostname

Synopsis

It was possible to determine the remote system hostname.

Description

This plugin reports a device's hostname collected via SSH or WMI.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/06/30, Modified: 2026/02/23

Plugin Output

tcp/0

```
Hostname : Alonso
  Alonso (hostname command)
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose
Confidence level : 100
```

159273 - Dockerfile Detection for Linux/UNIX

Synopsis

Detected Dockerfiles on the host.

Description

The host contains Dockerfiles, text files containing instructions to build Docker images.

See Also

https://docs.docker.com/engine/reference/builder/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/03/29, Modified: 2026/02/03

Plugin Output

tcp/0

25203 - Enumerate IPv4 Interfaces via SSH

Synopsis

Nessus was able to enumerate the IPv4 interfaces on the remote host.

Description

Nessus was able to enumerate the network interfaces configured with IPv4 addresses by connecting to the remote host via SSH using the supplied credentials.

Solution

Disable any unused IPv4 interfaces.

Risk Factor

None

Plugin Information

Published: 2007/05/11, Modified: 2025/09/24

Plugin Output

tcp/0

```
The following IPv4 addresses are set on the remote host :

 - 127.0.0.1 (on interface lo)
 - 192.168.1.160 (on interface wlp3s0)
```

25202 - Enumerate IPv6 Interfaces via SSH

Synopsis

Nessus was able to enumerate the IPv6 interfaces on the remote host.

Description

Nessus was able to enumerate the network interfaces configured with IPv6 addresses by connecting to the remote host via SSH using the supplied credentials.

Solution

Disable IPv6 if you are not actually using it. Otherwise, disable any unused IPv6 interfaces.

Risk Factor

None

Plugin Information

Published: 2007/05/11, Modified: 2025/09/24

Plugin Output

tcp/0

```
The following IPv6 interfaces are set on the remote host :

 - ::1 (on interface lo)
 - 2806:106e:1f:741a:d334:38ad:a3a5:62bb (on interface wlp3s0)
 - fe80::b9b0:4c87:fec2:6086 (on interface wlp3s0)
```

33276 - Enumerate MAC Addresses via SSH

Synopsis

Nessus was able to enumerate MAC addresses on the remote host.

Description

Nessus was able to enumerate MAC addresses by connecting to the remote host via SSH with the supplied credentials.

Solution

Disable any unused interfaces.

Risk Factor

None

Plugin Information

Published: 2008/06/30, Modified: 2022/12/20

Plugin Output

tcp/0

170170 - Enumerate the Network Interface configuration via SSH

Synopsis

Nessus was able to parse the Network Interface data on the remote host.

Description

Nessus was able to parse the Network Interface data on the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/01/19, Modified: 2025/02/11

Plugin Output

tcp/0

179200 - Enumerate the Network Routing configuration via SSH

Synopsis

Nessus was able to retrieve network routing information from the remote host.

Description

Nessus was able to retrieve network routing information the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/08/02, Modified: 2023/08/02

Plugin Output

tcp/0

168980 - Enumerate the PATH Variables

Synopsis

Enumerates the PATH variable of the current scan user.

Description

Enumerates the PATH variables of the current scan user.

Solution

Ensure that directories listed here are in line with corporate policy.

Risk Factor

None

Plugin Information

Published: 2022/12/21, Modified: 2026/02/23

Plugin Output

tcp/0

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

https://standards.ieee.org/faqs/regauth.html

http://www.nessus.org/u?794673b4

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :

C0:3E:BA:28:51:67 : Dell Inc.
5C:3A:45:A7:71:CF : CHONGQING FUGUI ELECTRONICS CO.,LTD.
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

204827 - Exiv2 Installed (Linux / Unix)

Synopsis

Exiv2 is installed on the remote Linux / Unix host.

Description

Exiv2 is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.

- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.204827' scanner setting in Nessus 8.15.1 or later.

Please see https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom for more information.

See Also

https://exiv2.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/07/29, Modified: 2026/02/03

Plugin Output

tcp/0

168982 - Filepaths contain Dangerous characters (Linux)

Synopsis

This Tenable product detected files or paths on the scanned Unix-like system which contain characters with command injection or privilege escalation potential.

Description

This Tenable product detected files or paths on the scanned Unix-like system which contain characters with command injection or privilege escalation potential. Although almost any character is valid for an entry in this kind of filesystem, such as semicolons, use of some of them may lead to problems or security compromise when used in further commands.

This product has chosen in certain plugins to avoid digging within those files and directories for security reasons.

These should be renamed to avoid security compromise.

Solution

Rename these files or folders to not include dangerous characters.

Risk Factor

None

Plugin Information

Published: 2022/12/21, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/8834/www

```
The remote web server type is :

NessusWWW
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
192.168.1.160 resolves as Alonso.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/8834/www

```
Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : yes
Keep-Alive : no
Options allowed : (Not implemented)
Headers :

  Cache-Control: must-revalidate
  X-Frame-Options: DENY
  Content-Type: text/html
  ETag: 531992e39b9ad5468479cbb87d5736ea
  Connection: close
  X-XSS-Protection: 1; mode=block
  Server: NessusWWW
  Date: Thu, 12 Mar 2026 10:30:37 GMT
  X-Content-Type-Options: nosniff
  Content-Length: 1629
  Content-Security-Policy: upgrade-insecure-requests; block-all-mixed-content; form-action
 'self'; frame-ancestors 'none'; frame-src https://store.tenable.com www.youtube.com; default-src
 'self'; connect-src 'self' data.nessus-telemetry.tenable.com content.nessus-telemetry.tenable.com
 api.tenable.com www.tenable.com; script-src 'self' content.nessus-telemetry.tenable.com
 www.tenable.com; img-src 'self' data: content.nessus-telemetry.tenable.com data.nessus-
telemetry.tenable.com pendo-static-5689996938182656.storage.googleapis.com s.ytimg.com i.ytimg.com;
```

```
 style-src 'self' content.nessus-telemetry.tenable.com data.nessus-telemetry.tenable.com pendo-
static-5689996938182656.storage.googleapis.com www.tenable.com; object-src 'none'; base-uri 'self';
  Strict-Transport-Security: max-age=31536000; includeSubDomains
  Expect-CT: max-age=0

Response Body :

<!doctype html>
<html lang="en">
    <head>
        <meta http-equiv="X-UA-Compatible" content="IE=edge,chrome=1" />
        <meta http-equiv="Content-Security-Policy" content="upgrade-insecure-requests; block-all-
mixed-content; form-action 'self'; frame-src https://store.tenable.com www.youtube.com; default-src
 'self'; connect-src 'self' data.nessus-telemetry.tenable.com content.nessus-telemetry.tenable.com
 api.tenable.com www.tenable.com; script-src 'self' content.nessus-telemetry.tenable.com
 www.tenable.com; img-src 'self' data: data.nessus-telemetry.tenable.com content.nessus-
telemetry.tenable.com pendo-static-5689996938182656.storage.googleapis.com s.ytimg.com i.ytimg.com;
 style-src 'self' c [...]
```

171410 - IP Assignment Method Detection

Synopsis

Enumerates the IP address assignment method(static/dynamic).

Description

Enumerates the IP address assignment method(static/dynamic).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/02/14, Modified: 2026/02/23

Plugin Output

tcp/0

278763 - ImageMagick Installed (Linux)

Synopsis

ImageMagick is installed on the remote Linux host.

Description

ImageMagick Tool is installed on the remote Linux host.

Additional information:

- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.182774' scanner setting in Nessus 8.15.1 or later.

Please see https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom for more information.

See Also

https://ImageMagick.org

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/16, Modified: 2026/02/03

Plugin Output

tcp/0

197894 - Intel Media SDK Installed (Linux)

Synopsis

Intel Media SDK is installed on the remote Linux host.

Description

Intel Media SDK is installed on the remote Linux host.

See Also

https://github.com/Intel-Media-SDK/MediaSDK

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/05/24, Modified: 2026/02/03

Plugin Output

tcp/0

200434 - Intel oneVPL GPU Runtime Installed (Linux)

Synopsis

Intel oneVPL GPU Runtime is installed on the remote Linux host.

Description

Intel oneVPL GPU Runtime is installed on the remote Linux host.

See Also

https://github.com/intel/vpl-gpu-rt

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/06/12, Modified: 2026/02/03

Plugin Output

tcp/0

147817 - Java Detection and Identification (Linux / Unix)

Synopsis

Java is installed on the remote Linux / Unix host.

Description

One or more instances of Java are installed on the remote Linux / Unix host. This may include private JREs bundled with the Java Development Kit (JDK).

Notes:

- This plugin attempts to detect Oracle and non-Oracle JRE instances such as Zulu Java, Amazon Corretto, AdoptOpenJDK, IBM Java, etc

- To discover instances of JRE that are not in PATH, or installed via a package manager, 'Perform thorough tests' setting must be enabled.

See Also

https://en.wikipedia.org/wiki/Java_(software_platform)

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0690

Plugin Information

Published: 2021/03/16, Modified: 2026/02/09

Plugin Output

tcp/0

189990 - Jmcnamara Spreadsheet-ParseExcel Installed (Unix)

Synopsis

Jmcnamara Spreadsheet-ParseExcel is installed on the remote Unix host.

Description

Jmcnamara Spreadsheet-ParseExcel is installed on the remote Unix host.

See Also

https://github.com/jmcnamara/spreadsheet-parseexcel

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/02/05, Modified: 2026/02/03

Plugin Output

tcp/0

151883 - Libgcrypt Installed (Linux/UNIX)

Synopsis

Libgcrypt is installed on this host.

Description

Libgcrypt, a cryptography library, was found on the remote host.

See Also

https://gnupg.org/download/index.html

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/07/21, Modified: 2026/02/03

Plugin Output

tcp/0

157358 - Linux Mounted Devices

Synopsis

Use system commands to obtain the list of mounted devices on the target machine at scan time.

Description

Report the mounted devices information on the target machine at scan time using the following commands.

/bin/df -h /bin/lsblk /bin/mount -l

This plugin only reports on the tools available on the system and omits any tool that did not return information when the command was ran.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/02/03, Modified: 2023/11/27

Plugin Output

tcp/0

193143 - Linux Time Zone Information

Synopsis

Nessus was able to collect and report time zone information from the remote host.

Description

Nessus was able to collect time zone information from the remote Linux host.

Solution

None

Risk Factor

None

Plugin Information

Published: 2024/04/10, Modified: 2024/04/10

Plugin Output

tcp/0

95928 - Linux User List Enumeration

Synopsis

Nessus was able to enumerate local users and groups on the remote Linux host.

Description

Using the supplied credentials, Nessus was able to enumerate the local users and groups on the remote Linux host.

Solution

None

Risk Factor

None

Plugin Information

Published: 2016/12/19, Modified: 2025/03/26

Plugin Output

tcp/0

45433 - Memory Information (via DMI)

Synopsis

Information about the remote system's memory devices can be read.

Description

Using the SMBIOS (aka DMI) interface, it was possible to retrieve information about the remote system's memory devices, such as the total amount of installed memory.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/06, Modified: 2018/03/29

Plugin Output

tcp/0

```
Total memory : 12288 MB
```

129056 - Microsoft Visual Studio Code Installed (Linux)

Synopsis

A code editor is installed on the remote host.

Description

Microsoft Visual Studio Code, an integrated development environment software application, is installed on the remote Linux host.

Note: If thorough tests is enabled, this plugin will check for snap installs.

See Also

https://code.visualstudio.com/

https://github.com/Microsoft/vscode

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2019/09/19, Modified: 2026/02/03

Plugin Output

tcp/0

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

```
Information about this scan :

Nessus version : 10.11.3
Nessus build : 20047
Plugin feed version : 202603102249
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : fc38-x86-64
Scan type : Normal
Scan name : Práctica 4 - Vulnerabilidades
```

```
Scan policy used : Basic Network Scan
Scanner IP : 192.168.1.160
Ping RTT : Unavailable
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 0
Safe checks : yes
Optimize the test : yes
Credentialed checks : yes (on the localhost)
Attempt Least Privilege : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : No
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/3/12 4:09 CST (UTC -06:00)
Scan duration : 1365 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no (not licensed)
```

10147 - Nessus Server Detection

Synopsis

A Nessus daemon is listening on the remote port.

Description

A Nessus daemon is listening on the remote port.

See Also

https://www.tenable.com/products/nessus/nessus-professional

Solution

Ensure that the remote Nessus installation has been authorized.

Risk Factor

None

References

XREF	IAVT:0001-T-0673

Plugin Information

Published: 1999/10/12, Modified: 2025/11/03

Plugin Output

tcp/8834/www

64582 - Netstat Connection Information

Synopsis

Nessus was able to parse the results of the 'netstat' command on the remote host.

Description

The remote host has listening ports or established connections that Nessus was able to extract from the results of the 'netstat' command.

Note: The output for this plugin can be very long, and is not shown by default. To display it, enable verbose reporting in scan settings.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/02/13, Modified: 2023/05/23

Plugin Output

tcp/0

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/546

```
Port 546/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/5353/mdns

```
Port 5353/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/5355

```
Port 5355/tcp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/5355

```
Port 5355/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/7070

```
Port 7070/tcp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

tcp/8834/www

```
Port 8834/tcp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/21119

```
Port 21119/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/34738

```
Port 34738/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/43697

```
Port 43697/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/50001

```
Port 50001/udp was found to be open
```

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

https://en.wikipedia.org/wiki/Netstat

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

udp/59146

```
Port 59146/udp was found to be open
```

201190 - NumPy Detection

Synopsis

A NumPy Python library is installed on the remote host.

Description

A NumPy Python library is installed on the remote host.

Note that Nessus has relied upon on the application's self-reported version number.

See Also

https://github.com/NumPy/NumPy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/07/01, Modified: 2026/03/09

Plugin Output

tcp/0

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, “OS Identification”, the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

```
Following OS Fingerprints were found

Remote operating system : Linux Kernel 6.8.9-100.fc38.x86_64
Confidence level : 99
Method : uname
Type : general-purpose
Fingerprint : uname:Linux Alonso 6.8.9-100.fc38.x86_64 #1 SMP PREEMPT_DYNAMIC Thu May  2 18:50:49
 UTC 2024 x86_64 GNU/Linux


Remote operating system : Linux Kernel 6.8.9-100.fc38.x86_64 on Fedora release 38 (Thirty Eight)
Confidence level : 100
Method : LinuxDistribution
Type : general-purpose
Fingerprint : unknown

Following fingerprints could not be used to determine OS :
 SSH:!:SSH-2.0-OpenSSH_9.0
HTTP:!:Server: NessusWWW

SSLcert:!:i/CN:Nessus Certification Authorityi/O:Nessus Users Unitedi/OU:Nessus Certification
 Authoritys/CN:Alonsos/O:Nessus Users Uniteds/OU:Nessus Server
0804cc0fa834afd52ee397062ba7749c7fce863e
```

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 6.8.9-100.fc38.x86_64 on Fedora release 38 (Thirty Eight)
Confidence level : 100
Method : LinuxDistribution


The remote host is running Linux Kernel 6.8.9-100.fc38.x86_64 on Fedora release 38 (Thirty Eight)
```

97993 - OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH Library)

Synopsis

Information about the remote host can be disclosed via an authenticated session.

Description

Nessus was able to login to the remote host using SSH or local commands and extract the list of installed packages.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/05/30, Modified: 2025/02/11

Plugin Output

tcp/0

```
Nessus can run commands on localhost to check if patches are applied.

The output of "uname -a" is :
Linux Alonso 6.8.9-100.fc38.x86_64 #1 SMP PREEMPT_DYNAMIC Thu May  2 18:50:49 UTC 2024 x86_64 GNU/
Linux

Local checks have been enabled for this host.
The remote Fedora system is :
Fedora release 38 (Thirty Eight)

OS Security Patch Assessment is available for this host.
Runtime : 4.650436 seconds
```

117887 - OS Security Patch Assessment Available

Synopsis

Nessus was able to log in to the remote host using the provided credentials and enumerate OS security patch levels.

Description

Nessus was able to determine OS security patch levels by logging into the remote host and running commands to determine the version of the operating system and its components. The remote host was identified as an operating system or device that Nessus supports for patch and update assessment. The necessary information was obtained to perform these checks.

Solution

n/a

Risk Factor

None

References

XREF	IAVB:0001-B-0516

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

148373 - OpenJDK Java Detection (Linux / Unix)

Synopsis

A distribution of Java is installed on the remote Linux / Unix host.

Description

One or more instances of OpenJDK Java are installed on the remote host. This may include private JREs bundled with the Java Development Kit (JDK).

Notes:

- Addition information provided in plugin Java Detection and Identification (Unix)

- Additional instances of Java may be discovered by enabling thorough tests

See Also

https://openjdk.java.net/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/04/07, Modified: 2025/09/29

Plugin Output

tcp/0

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

https://www.openssh.com/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/02/03

Plugin Output

tcp/22/ssh

168007 - OpenSSL Installed (Linux)

Synopsis

OpenSSL was detected on the remote Linux host.

Description

OpenSSL was detected on the remote Linux host.

The plugin timeout can be set to a custom value other than the plugin's default of 15 minutes via the 'timeout.168007' scanner setting in Nessus 8.15.1 or later.

Please see https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom for more information.

Note: This plugin leverages the '-maxdepth' find command option, which is a feature implemented by the GNU find binary. If the target does not support this option, such as HP-UX and AIX devices, users will need to enable 'thorough tests' in their scan policy to run the find command without using a '-maxdepth' argument.

See Also

https://openssl.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/11/21, Modified: 2026/03/09

Plugin Output

tcp/0

232856 - OpenVPN Installed (Linux)

Synopsis

OpenVPN is installed on the remote Linux host.

Description

OpenVPN is installed on the remote Linux host.

Note: Enabling the 'Perform thorough tests' setting will search the file system more broadly.

See Also

https://openvpn.net/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/03/19, Modified: 2026/02/03

Plugin Output

tcp/0

216936 - PHP Scripting Language Installed (Unix)

Synopsis

The PHP scripting language is installed on the remote Unix host.

Description

The PHP scripting language is installed on the remote Unix host.

Note: Enabling the 'Perform thorough tests' setting will search the file system much more broadly. Thorough test is required to get results on hosts running MacOS.

See Also

https://www.php.net

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/06/13, Modified: 2026/03/09

Plugin Output

tcp/0

179139 - Package Manager Packages Report (nix)

Synopsis

Reports details about packages installed via package managers.

Description

Reports details about packages installed via package managers

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/08/01, Modified: 2025/05/07

Plugin Output

tcp/0

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/03/10

Plugin Output

tcp/0

233359 - Podman Installed (Linux)

Synopsis

Podman was detected on the remote host.

Description

Podman, a daemonless, open source, Linux native tool designed to make it easy to find, run, build, share and deploy applications using Open Containers Initiative (OCI) Containers and Container Images, is installed on the remote host.

See Also

https://docs.podman.io/en/latest/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/03/26, Modified: 2026/02/03

Plugin Output

tcp/0

130024 - PostgreSQL Client/Server Installed (Linux)

Synopsis

One or more PostgreSQL server or client versions are available on the remote Linux host.

Description

One or more PostgreSQL server or client versions have been detected on the remote Linux host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2019/10/18, Modified: 2026/02/03

Plugin Output

tcp/0

45432 - Processor Information (via DMI)

Synopsis

Nessus was able to read information about the remote system's processor.

Description

Nessus was able to retrieve information about the remote system's hardware, such as its processor type, by using the SMBIOS (aka DMI) interface.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/06, Modified: 2016/02/25

Plugin Output

tcp/0

119602 - Python Flask Installed (Linux)

Synopsis

Python Flask is installed on the remote host.

Description

Flask, a micro web framework written in Python, is installed on the remote Linux host.

See Also

http://flask.pocoo.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/12/12, Modified: 2026/02/03

Plugin Output

tcp/0

299596 - Qemu Installed (Linux)

Synopsis

Qemu is installed on the remote Linux host.

Description

Qemu is installed on the remote Linux host.

See Also

https://www.qemu.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2026/02/19, Modified: 2026/02/19

Plugin Output

tcp/0

254438 - R Programming Language Installed (Linux)

Synopsis

The R Programming Language is installed on the remote Linux host.

Description

The R Programming Language is installed on the remote Linux host.

See Also

https://www.r-project.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/08/25, Modified: 2026/03/09

Plugin Output

tcp/0

45405 - Reachable IPv6 address

Synopsis

The remote host may be reachable from the Internet.

Description

Although this host was scanned through a private IPv4 or local scope IPv6 address, some network interfaces are configured with global scope IPv6 addresses. Depending on the configuration of the firewalls and routers, this host may be reachable from Internet.

Solution

Disable IPv6 if you do not actually using it.

Otherwise, disable any unused IPv6 interfaces and implement IP filtering if needed.

Risk Factor

None

Plugin Information

Published: 2010/04/02, Modified: 2024/07/24

Plugin Output

tcp/0

```
The following global address was gathered :

  - 2806:106e:1f:741a:d334:38ad:a3a5:62bb
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

http://www.nessus.org/u?7a390f87

http://www.nessus.org/u?ad7d6b3b

http://www.nessus.org/u?1c0c61e0

http://www.nessus.org/u?5eec4b28

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

http://www.nessus.org/u?7a390f87

http://www.nessus.org/u?ad7d6b3b

http://www.nessus.org/u?1c0c61e0

http://www.nessus.org/u?5eec4b28

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/8834/www

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

tcp/22/ssh

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

udp/5353/mdns

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

tcp/5355

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

udp/5355

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

tcp/7070

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

tcp/8834/www

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

udp/21119

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

udp/34738

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

udp/43697

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

udp/50001

25221 - Remote listeners enumeration (Linux / AIX)

Synopsis

Using the supplied credentials, it was possible to identify the process listening on the remote port.

Description

By logging into the remote host with the supplied credentials, Nessus was able to obtain the name of the process listening on the remote port.

Note that the method used by this plugin only works for hosts running Linux or AIX.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2024/07/05

Plugin Output

udp/59146

207584 - Ruby Gem Modules Installed (Linux)

Synopsis

Nessus was able to enumerate one or more Ruby Gem modules installed on the remote host.

Description

Nessus was able to enumerate one or more Ruby Gem modules installed on the remote host.
Note that 'Perform thorough tests' may be required for an in-depth search of all Ruby Gem modules.

See Also

http://www.nessus.org/u?26bc7c8b

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/09/23, Modified: 2026/02/23

Plugin Output

tcp/0

202184 - Ruby Programming Language Installed (Linux)

Synopsis

The Ruby programming language is installed on the remote Linux host.

Description

The Ruby programming language is installed on the remote Linux host.

See Also

https://ruby.org/en/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/07/11, Modified: 2026/02/03

Plugin Output

tcp/0

233288 - RustDesk Installed (Linux)

Synopsis

RustDesk is installed on the remote Linux host.

Description

RustDesk is installed on the remote Linux host.

See Also

https://rustdesk.com/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/03/24, Modified: 2026/02/03

Plugin Output

tcp/0

133964 - SELinux Status Check

Synopsis

SELinux is available on the host and plugin was able to check if it is enabled.

Description

SELinux is available on the host and plugin was able to check if it is enabled.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/02/25, Modified: 2026/02/03

Plugin Output

tcp/0

174788 - SQLite Local Detection (Linux / Unix)

Synopsis

The remote Linux host has SQLite Database software installed.

Description

Version information for SQLite was retrieved from the remote host. SQLite is an embedded database written in C.

- To discover instances of SQLite that are not in PATH, 'Perform thorough tests' setting must be enabled.

See Also

https://www.sqlite.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/04/26, Modified: 2026/03/09

Plugin Output

tcp/0

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

https://tools.ietf.org/html/rfc4252#section-8

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the
SSH protocol :

  - 1.99
  - 2.0
```

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_9.0
SSH supported authentication : publickey,gssapi-keyex,gssapi-with-mic,password
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/8834/www

```
This port supports TLSv1.3/TLSv1.2.
```

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/8834/www

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

https://www.openssl.org/docs/man1.0.2/man1/ciphers.html

http://www.nessus.org/u?e17ffced

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2024/09/11

Plugin Output

tcp/8834/www

```
Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv13
  High Strength Ciphers (>= 112-bit key)

    Name                         Code             KEX           Auth     Encryption             MAC
    ----------------------       ----------       ---           ----     --------------------   ---
    TLS_AES_256_GCM_SHA384       0x13, 0x02       -             -        AES-GCM(256)
 SHA384


SSL Version : TLSv12
  High Strength Ciphers (>= 112-bit key)

    Name                         Code             KEX           Auth     Encryption             MAC
    ----------------------       ----------       ---           ----     --------------------   ---
    ECDHE-RSA-AES128-SHA256      0xC0, 0x2F       ECDHE         RSA      AES-GCM(128)
 SHA256
    ECDHE-RSA-AES256-SHA384      0xC0, 0x30       ECDHE         RSA      AES-GCM(256)
 SHA384

The fields above are :
```

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

https://www.openssl.org/docs/manmaster/man1/ciphers.html

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/8834/www

```
Here is the list of SSL PFS ciphers supported by the remote server :

  High Strength Ciphers (>= 112-bit key)

    Name                         Code             KEX           Auth     Encryption             MAC
    ----------------------       ----------       ---           ----     ---------------------  ---
    ECDHE-RSA-AES128-SHA256      0xC0, 0x2F       ECDHE         RSA      AES-GCM(128)
 SHA256
    ECDHE-RSA-AES256-SHA384      0xC0, 0x30       ECDHE         RSA      AES-GCM(256)
 SHA384

The fields above are :

  {Tenable ciphername}
  {Cipher ID code}
  Kex={key exchange}
  Auth={authentication}
```

```
    Encrypt={symmetric encryption method}
    MAC={message authentication code}
    {export flag}
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/02/02

Plugin Output

tcp/8834/www

```
A TLSv1.3 server answered on this port.
```

tcp/8834/www

```
A web server is running on this port through TLSv1.3.
```

11153 - Service Detection (HELP Request)

Synopsis

The remote service could be identified.

Description

It was possible to identify the remote service by its banner or by looking at the error message it sends when it receives a 'HELP'

request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/11/18, Modified: 2024/11/19

Plugin Output

tcp/22/ssh

```
An SSH server seems to be running on this port.
```

298387 - Shor's Harvest Now Decrypt Later

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

http://www.nessus.org/u?54fba2c1

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None

Plugin Information

Published: 2026/02/09, Modified: 2026/02/09

Plugin Output

tcp/0

22869 - Software Enumeration (SSH)

Synopsis

It was possible to enumerate installed software on the remote host via SSH.

Description

Nessus was able to list the software installed on the remote host by calling the appropriate command (e.g., 'rpm -qa' on RPM-based Linux distributions, qpkg, dpkg, etc.).

Solution

Remove any software that is not in compliance with your organization's acceptable use and security policies.

Risk Factor

None

References

XREF	IAVT:0001-T-0502

Plugin Information

Published: 2006/10/15, Modified: 2025/03/26

Plugin Output

tcp/0

42822 - Strict Transport Security (STS) Detection

Synopsis

The remote web server implements Strict Transport Security.

Description

The remote web server implements Strict Transport Security (STS).

The goal of STS is to make sure that a user does not accidentally downgrade the security of his or her browser.

All unencrypted HTTP connections are redirected to HTTPS. The browser is expected to treat all cookies as 'secure' and to close the connection in the event of potentially insecure situations.

See Also

http://www.nessus.org/u?2fb3aca6

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/11/16, Modified: 2019/11/22

Plugin Output

tcp/8834/www

```
The STS header line is :

Strict-Transport-Security: max-age=31536000; includeSubDomains
```

35351 - System Information Enumeration (via DMI)

Synopsis

Information about the remote system's hardware can be read.

Description

Using the SMBIOS (aka DMI) interface, it was possible to retrieve information about the remote system's hardware, such as its product name and serial number.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/01/12, Modified: 2025/03/18

Plugin Output

tcp/0

```
Chassis Information
  Serial Number : GWFMB53
  Version       : Not Specified
  Manufacturer  : Dell Inc.
  Lock          : Not Present
  Type          : Notebook

System Information
  Serial Number : GWFMB53
  Version       : Not Specified
  Manufacturer  : Dell Inc.
  Product Name  : Inspiron 5593
  Family        : Inspiron
```

277654 - TLS Supported Groups

Synopsis

The remote service negotiates TLS supported curve groups.

Description

This plugin detects which TLS supported groups entries are supported by the remote service.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2026/01/20

Plugin Output

tcp/8834/www

136318 - TLS Version 1.2 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

https://tools.ietf.org/html/rfc5246

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/05/04, Modified: 2020/05/04

Plugin Output

tcp/8834/www

138330 - TLS Version 1.3 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.3.

See Also

https://tools.ietf.org/html/rfc8446

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/07/09, Modified: 2023/12/13

Plugin Output

tcp/8834/www

110095 - Target Credential Issues by Authentication Protocol - No Issues Found

Synopsis

Nessus was able to log in to the remote host using the provided credentials. No issues were reported with access, privilege, or intermittent failure.

Description

Valid credentials were provided for an authentication protocol on the remote target and Nessus did not log any subsequent errors or failures for the authentication protocol.

When possible, Nessus tracks errors or failures related to otherwise valid credentials in order to highlight issues that may result in incomplete scan results or limited scan coverage. The types of issues that are tracked include errors that indicate that the account used for scanning did not have sufficient permissions for a particular check, intermittent protocol failures which are unexpected after the protocol has been negotiated successfully earlier in the scan, and intermittent authentication failures which are unexpected after a credential set has been accepted as valid earlier in the scan. This plugin reports when none of the above issues have been logged during the course of the scan for at least one authenticated protocol. See plugin output for details, including protocol, port, and account.

Please note the following :

- This plugin reports per protocol, so it is possible for issues to be encountered for one protocol and not another.

For example, authentication to the SSH service on the remote target may have consistently succeeded with no privilege errors encountered, while connections to the SMB service on the remote target may have failed intermittently.

- Resolving logged issues for all available authentication protocols may improve scan coverage, but the value of resolving each issue for a particular protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol and what particular check failed. For example, consistently successful checks via SSH are more critical for Linux targets than for Windows targets, and likewise consistently successful checks via SMB are more critical for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF	IAVB:0001-B-0520

Plugin Information

Published: 2018/05/24, Modified: 2025/08/28

Plugin Output

tcp/0

141118 - Target Credential Status by Authentication Protocol - Valid Credentials Provided

Synopsis

Valid credentials were provided for an available authentication protocol.

Description

Nessus was able to determine that valid credentials were provided for an authentication protocol available on the remote target because it was able to successfully authenticate directly to the remote target using that authentication protocol at least once. Authentication was successful because the authentication protocol service was available remotely, the service was able to be identified, the authentication protocol was able to be negotiated successfully, and a set of credentials provided in the scan policy for that authentication protocol was accepted by the remote service. See plugin output for details, including protocol, port, and account.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.

- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/10/15, Modified: 2024/03/25

Plugin Output

tcp/0

163326 - Tenable Nessus Installed (Linux)

Synopsis

Tenable Nessus is installed on the remote Linux host.

Description

Tenable Nessus is installed on the remote Linux host.

See Also

https://www.tenable.com/products/nessus

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/07/21, Modified: 2026/02/03

Plugin Output

tcp/0

56468 - Time of Last System Startup

Synopsis

The system has been started.

Description

Using the supplied credentials, Nessus was able to determine when the host was last started.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/10/12, Modified: 2018/06/19

Plugin Output

tcp/0

192709 - Tukaani XZ Utils Installed (Linux / Unix)

Synopsis

Tukaani XZ Utils is installed on the remote Linux / Unix host.

Description

Tukaani XZ Utils is installed on the remote Linux / Unix host.

XZ Utils consists of several components, including:

- liblzma

- xz

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.

- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.192709' scanner setting in Nessus 8.15.1 or later.

Please see https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom for more information.

See Also

https://xz.tukaani.org/xz-utils/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/03/29, Modified: 2026/02/03

Plugin Output

tcp/0

83303 - Unix / Linux - Local Users Information : Passwords Never Expire

Synopsis

At least one local user has a password that never expires.

Description

Using the supplied credentials, Nessus was able to list local users that are enabled and whose passwords never expire.

Solution

Allow or require users to change their passwords regularly.

Risk Factor

None

Plugin Information

Published: 2015/05/10, Modified: 2023/11/27

Plugin Output

tcp/0

110483 - Unix / Linux Running Processes Information

Synopsis

Uses /bin/ps auxww command to obtain the list of running processes on the target machine at scan time.

Description

Generated report details the running processes on the target machine at scan time.

This plugin is informative only and could be used for forensic investigation, malware detection, and to confirm that your system processes conform to your system policies.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/06/12, Modified: 2023/11/27

Plugin Output

tcp/0

152742 - Unix Software Discovery Commands Available

Synopsis

Nessus was able to log in to the remote host using the provided credentials and is able to execute all commands used to find unmanaged software.

Description

Nessus was able to determine that it is possible for plugins to find and identify versions of software on the target host. Software that is not managed by the operating system is typically found and characterized using these commands. This was measured by running commands used by unmanaged software plugins and validating their output against expected results.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/08/23, Modified: 2021/08/23

Plugin Output

tcp/0

186361 - VMWare Tools or Open VM Tools Installed (Linux)

Synopsis

VMWare Tools or Open VM Tools were detected on the remote Linux host.

Description

VMWare Tools or Open VM Tools were detected on the remote Linux host.

See Also

https://kb.vmware.com/s/article/340

http://www.nessus.org/u?c0628155

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/11/28, Modified: 2026/02/03

Plugin Output

tcp/0

159182 - Zoom Installed (Linux)

Synopsis

Zoom was detected on the remote Linux host.

Description

Zoom was detected on the remote Linux host.

Note that enabling the 'Perform thorough tests' setting will search the file system for the product.

See Also

https://zoom.us/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/03/23, Modified: 2026/02/03

Plugin Output

tcp/0

198234 - gnome-shell Installed (Linux / UNIX)

Synopsis

gnome-shell is installed on the remote Linux / UNIX host.

Description

gnome-shell is installed on the remote Linux / UNIX host.

See Also

https://gitlab.gnome.org/GNOME/gnome-shell/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/05/31, Modified: 2026/02/03

Plugin Output

tcp/0

182848 - libcurl Installed (Linux / Unix)

Synopsis

libcurl is installed on the remote Linux / Unix host.

Description

libcurl is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.

- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.182848' scanner setting in Nessus 8.15.1 or later.

Please see https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom for more information.

See Also

https://curl.se/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/10/10, Modified: 2026/03/09

Plugin Output

tcp/0

204828 - libexiv2 Installed (Linux / Unix)

Synopsis

libexiv2 is installed on the remote Linux / Unix host.

Description

libexiv2 is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.

- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.204828' scanner setting in Nessus 8.15.1 or later.

Please see https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom for more information.

See Also

https://exiv2.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/07/29, Modified: 2026/02/03

Plugin Output

tcp/0

66717 - mDNS Detection (Local Network)

Synopsis

It is possible to obtain information about the remote host.

Description

The remote service understands the Bonjour (also known as ZeroConf or mDNS) protocol, which allows anyone to uncover information from the remote host such as its operating system type and exact version, its hostname, and the list of services it is running.

This plugin attempts to discover mDNS used by hosts residing on the same network segment as Nessus.

Solution

Filter incoming traffic to UDP port 5353, if desired.

Risk Factor

None

Plugin Information

Published: 2013/05/31, Modified: 2013/05/31

Plugin Output

udp/5353/mdns